FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No. F6/DFS/MS/CGHS/SZ/2024/ 57

Dated: 24/01/2024

FIRE SAFETY CERTIFICATE

Certified that the building of True Friends CGHS Ltd. Located at Plot no 29, Sector -06, Dwarka, New Delhi -110075 having 04 blocks comprised of Basement + Ground / Stilt +07/08 Upper floors was issued Fire Safety Certificate by this department vide letter No. F6/DFS/MS /CGHS/2004/2672 Dated 03/11/2004. The premise was re inspected by the officer concerned of this department on 08/01/2024 in the presence of. Sh. Aklesh Kumar (Manager) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Residential Building" Group A-4 with effect from $\frac{24}{01/2024}$ for a period of five years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 24/01/2024 at New Delhi by.

(Atul Garg)
Director

Delhi Fire Service

Copy to:

- 1. The President, True Friends CGHS Ltd. Plot no 29, Sector 06, Dwarka, New Delhi 75.
- 2. The Joint Director (Building) DDA, Vikas Sadan, INA, Delhi-110023.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management. •
- The trained staff should be available round the clock.
- Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per building bye laws.
- The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. www.dfs.delhigovt.nic.in.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

TION REPORT

 Name & address of the building: True Friends CGHS Ltd. Located at Plot no 29, Sector - 06, Dwarka, New Delhi - 110075.

2. Type of Occupancy : Residential Building "A"

3. Type of Case: Renewal (Basement + G / Stilt + 07 / 08 Upper floors (04 Blocks)

4. Details of previous NOC: F6/DFS/MS/CGHS/2004/2672 Dated 03/11/2004

Fire Safety directives L. No.: F6/DFS/MS/BP/CGHS/99/686 dated 04/08/99

6. Date of inspection

: 08/01/2024

7. Name of the Inspecting Officer: ADO (DWK)

8. Name and designation of Officer

from the building side

: Sh. Aklesh Kumar (Manager)

9. Year of Construction

: 2000

10. Applicant's letter No.

: Email Dated-26/12/2023

0	Minimum standards on fire prevention and fire safety U/R 33	NBC Requirement	P	rovided at site	100	Remarks MR/NMR		
	Access of building							
	Road width	30 mtrs		Provided	1	MR		
14	Gate width	06mtrs		06mtrs		MR		
	Width of internal road	Required		5.5m to 6m	MR (I	Being old o	ase)	
2.	Number, width, Type & Arranger	nents of exits			- Lo			
	a. Number of staircases							
	Upper floors	1 no each blk	1(Interconnected	at terr	ace level)	MR	
	Basements	8 nos	8 Provided			MR		
	b. Width of staircases	V						
	Upper floors	1.25 m Prov.			M			
	Basements	1.25 mtr	4X 90	cm & 4X 135 c	m	MR		
	c. Protection of exits			1				
	Fire check door	NA		NA		NA ·		
	Pressurization	NA		. NA		NA		
۸.	d. No of continuous	Required		Provide	d	MR		
	staircase to terrace	Required		Provide	d	MR		
17	e. Width Of Corridor	Required		Provide		MR		
-	f. Door Size		_					
3.	Compartmentation	NA		NA		NA		
	Fire check door	The second of th		PARE	4		_	
	Sealing of electrical shafts	Required		Provide	a	MR		
	Fire Rating of shaft door	NA		NA		NA		
V	Water Curtain	NA		NA		NA		
	Fire Dampers	NA		NA		NA		
4.								
7.	Basements	30 a/c per ho		Provided		MR		
-	Upper floors	12 a/c per ho	Natural ven	Natural ventilation				

N/16

	Fire Extinguishers				4				_
\neg	 Total numbers 	02	nos a	t each floo	r	Provided	N	/IR	
-[Types 	C	02 &1	WCO2		CO2 &WCC	2 N	ИR	
	IS marking	IS	I marl	ked		ISI marked	N	/IR	
	First - Aid Hose Reels								
\neg	Total numbers on each	ch floor	01 r	10		Provided	N	1R	
	 Length of hose reel h 		30 ı	W-47-51		Provided	I N	1R	
	Nozzle diameter	.000	05 1			Provided	N	⁄IR	
	Automatic fire detection and	10 SVS							
	Type of detectors		-	NA -		NA		NA	
	Location of Main Pa	nel	-	NA		NA		NA	
	Location of Repeater			NA		NA		NA	1
	Alternate source of p		_	NA		NA		NA	
	Hooters' Location	OWCI	-	NA .	\neg	NA		NA	
	MOEFA					Provided		MR	+-
	Public Address System		_	Required		Provided			\vdash
0.	Automatic Sprinkler System	1		Required		Frovided	_	MR	1
٠.	Basements		-	Required	Dros	vided		MR	
	Upper Floor			NA	NA	rideu		NA	
	Sprinkler above fals	e ceiling	.	NA	NA			NA	
1.	Internal Hydrants:	c cennig		1144	1121			IVA	-
	Size of riser/down-	omer.		Required		Provided	MR		
	Number of hydrants			1		Provided	MR		
	Hose Box	per moo		01	Prov		IVII	MR	
12.	Yard Hydrants			UI.	1101	lucu		MIK	-
	Total number of hyd	Irante		Required		Provided	MR	-	
	Hose Box	Turity.		Required	_	Provided	MR		
13.	Pumping Arrangements:			1,5	_	11011404	IVIIC		
	Ground Level								
	Discharge of main p	ump	NA		. IN	NA	NA	-	
	➤ Head of main pump		NA	,		NA .	NA		
	➤ Number of main pur	mps	NA		_	NA .	NA		
	Jockey pump out pu	t i	NA			NA.	NA		
	Jockey pump head		NA		_	NA .	NA		
	Standby Pump out p	ut	NA			NA.	NA		
	> Standby Pump Head		NA	51"		NA ·	NA		
	➤ Auto Staring/Manua stopping	ıl [NA			NA .	NA	-	
	➤ Pump House Access	. }	NA	- V	×	NA .	37.		
	Terrace level	1	*17.	8	I P	1A	NA		
	➤ Discharge of pump		450 1	pm each bl	ook	Decret	1 75		
	Head of the pump	+	30 m			Provided rovided	MR		
	Power supply	ł			_	of extra position and the second	MR		
	Auto starting of pump						MR I		
14.	Captive water Storage for fire fighting:								
	 Under ground tank capacity 			200000 ltr		Provided		MR	
	Draw off connection	1		Required		Provided		MR	
	Fire service inlet		*0	Required		Provided		MR	
	Access to tank			Required		Provided		MR	
	Overhead Tank capacity			20000 ltr		Provided		MR	
15	Exit Signage					ti			
	EAR DIGHAGE			Required		Provided		MR	

No m

Y	Provision of Lifts Pressurization of Lift Shaft	l NA		NA			NA	
ľ	> Pressurization of lift lobby	NA						
1	aiostion in IIA Can	Required		NA Provided			NA	
							MR	
	Fireman's Grounding Swit	1100	Required Required		Provided Provided			
	▶ Lift Signage	Requi						
7.	Standby power supply	Requi	Required		Provided		MR	
8.	Refuge Area				990			
	➤ .Total area	NA NA				NA	NA NA	
	> Location							
19.	Fire control room							
		NA	NA			NA		
	Flow Switch Panel	NA	NA Provided at ground level Provided at ground level				NA MR MR	
	PA System Panel	Required						
	▶ Battery backup	Required						
	➢ Building Floor Plans	Required		Provided at ground level				
20.	Special Fire Protection Systems	Required	CC	CO2 5			MR MR	
	for Protection of special Risks, if any;	Required			CO2 fire extinguisher provided near electric panel			

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Ir view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter No. F6/DFS/MS /CGHS/2004/2672, dated 03/11/2004 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer
Name Volv North

Designation

ADOPOWA

W, 171, 12

17/04/2024

Director

ADD DWV

step 99 -10

Secriptiva

HIM