GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001



No. F.6/DFS/MS/WZ/2024/ JNDL 91

Dated:- 13/02/2024

FIRE SAFETY CERTIFICATE

Certified that the M/s. Asian Paints Ltd., Located at Khasra No. 111/6, & 111/15, Phirni Road, Mundka, New Delhi-110041, comprised of Ground Floor only owned/occupied by M/s. Asian Paints Ltd., was issued Fire Safety Certificate by this department vide letter No. F.6/DFS/MS/WZ/2021/88 dated 03/02/2021. The said premises was re inspected by the officer concerned of this department on 23/01/2024 in the presence of Sh. Jagjit, Supervisor and found that the premises have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rule, 2010 and that the building/premises is fit for occupancy class "Storage" Group-H with effect from 13 02 202 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010, printed below.

Issued on 13 02 2024. at New Delhi by.

Tel No. 011-23414000

Copy to: -

 The Authorized Signatory, M/s. Asian Paints Ltd., Khasra No. 111/6 & 111/15, Phirni Road, Mundka, New Delhi-110041.

Following Fire Safety Directive must be adhered to :-

1. All the means of escape shall be kept free of all type of obstruction all the time.

All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

 All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be responsible.

Any deviation, with regards to construction, ventilation, occupation, electric installation etc.
may be got verified from the concerned authorities. In case of deviation the NOC be treated
as Null & Void.

The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.

6. All comments / directions of licensing Department shall always be permitted and followed.

 The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

 The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry. 10-0

INSPECTION REPORT

1. Name & address of the building :

: M/s. Asian Paints Located at Kh. No. 111/6,

111/15, Phirni Road, Mundka, New Delhi-

110041

2. Type of Occupancy

: Storage (Group-II)

3. Type of Case

: Renewal (Ground Floor only)

4. Details of previous NOC

: F6/DFS/MS/WZ/2021/88 dated 03/02/2021

5. Fire Safety directives Letter No.

: NBC (Part-IV)

6. Date of inspection

: 23/01/2024

7. Name of the Inspecting Officer

: Aman Kumar Lathar, ADO (JWP)

8. Name and designation of Officer

from the building side

: Sh. Jagjit, Supervisor

9. Year of Construction

: 2011

10. Applicant's letter no.

: email dated 11/01/2024

S No	Minimum standards on fire prevention and fire safety U/R 33	BBL/NBC (Part-IV Requirements/ as p FSC dated 03/02/20	er site	Remarks MR/NMR				
1.	Access of building							
	 Road width 	06 m	12 m	MR				
	 Gate width 	05 m	Provided	MR				
	 Width of internal road 	03 m	Provided	MR				
2.	Number, width, Type & Arrangements of exits							
	a. Number of staircases							
	 Upper floors 	NΛ	NΛ	NΛ				
	 Basements 	NΛ	NΛ	NA				
	b. Width of staircases							
	 Upper floors 	NΛ	NΛ	NΛ				
	 Basements 	NA	NΛ	NΛ				
	c. Protection of exits							
	 Fire check door 	NΛ	NΛ	NΛ				
	 Pressurization 	NA	NΛ	NΛ				
	d. No of continuous staircase to terrace	NA	NΛ	NA				
	c. Width Of Corridor	NΛ	NA	NΛ				
	f. Door Size	1.50 m	3.0 m	MR				
	Compartmentation		3.0 III	IVIX				
	 Fire check door Scaling of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers 	NΛ	NΛ	NΛ				
		NΛ	NΛ	NA				
		NΛ	NΛ	NA				
		NΛ	NΛ	NΛ				
	a no istampera	NΛ	NΛ	NΛ				
	Smoke managements System Basements							
		NΛ	NΛ	NΛ				
	Upper floors Fire Extinguish	Required	Provided (Hall)	MR				
+	Fire Extinguishers		(,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	TATIC				
	Total numbersTypesIS marking	12 nos. ABC & CO ₂	25 nos. Provided	MR MR				
- 1	To marking	ISI marked	Provided	MR				

N-16

	N. Lo						
6.	First Aid Hose Reels	03	Provided	MR			
	Total numbers on each	03	* **********				
	floor	30 m	Provided	MR			
	Length of hose reel hose	5 mm	Provided	MR			
	Nozzle diameter	1372 539053919					
7.	DEATH						
	 Type of detectors 	Ground Floor		I MR			
	 Location of Main Panel 			100000000000000000000000000000000000000			
	 Location of Repeater Panel 	Ground Floor	Provided				
	 Alternate source of power 	Required	Provided				
1	 Hooters' Location 	Ground Floor		NΛ			
8.	MOEFA	NΛ	NΛ				
9.	Public Address System	Required	Provided	IVIK			
10.	Automatic Sprinkler System						
	Basements	NA	NΛ	NA NA			
	Upper Floor	Required	Provided				
	Sprinkler above false ceiling	ÑΛ	NΛ	NΛ			
11	- 1 0 y - 10 y -		•				
11.	Size of riser/down-comer	150 mm	Provided	MR			
	The state of the s	05	Provided	MR			
	Number of hydrants per						
	floor	05	Provided	MR			
	Hose Box						
12.		05	10	MR			
	Total number of hydrants	05	10	MR			
S. S.	Hose Box						
13.							
	Ground Level	2280 lpm	Provided	MR			
	Discharge of main pump	65 m	Provided	MR			
	➤ Head of main pump	01	Provided	. MR			
	Number of main pumps		Provided	MR			
	> Jockey pump out put	220 lpm 65 m	Provided	MR			
	➤ Jockey pump head		Provided	MR			
	> Standby Pump out put	2280 lpm	Provided	MR			
	> Standby Pump Head	65 m	Provided	MR			
	➤ Auto Staring/Manual . stopping	Required	Provided	IVIIC			
	➤ Pump House Access	Required	Provided	MR			
	Terrace level			1 214			
	> Discharge of pump '	NΛ	· NA	NA NA			
	> Head of the pump	NΛ	NΛ	NA NA			
	> Power supply	NΛ	NΛ	NA NA			
	> Auto starting of pump	NΛ	NΛ	NΛ			
14.	Captive water Storage for firefighting:	50,000 1	السال السال	MR			
	 Underground tank capacity 	50,000 ltrs.	Provided	- I CONSTRUCT			
	> Draw off connection	NΛ	NΛ	NA			
	> Fire service inlet	NA	NA Danidad	NA			
	> Access to tank	Required	Provided	MR			
	 Overhead Tank capacity 	10,000 ltrs.	Provided	MR			
15	Exit Signage	Required	Provided	MR			
16.	Provision of Lifts						
	> Pressurization of Lift Shaft	NΛ	NΛ	NΛ			
	> Pressurization of lift lobby	NΛ	NA	NΛ			
	Communication in lift Car	NΛ	NΛ	NΛ			
	> Fireman's Grounding	NΛ	NΛ	NΛ			
	Switch	NA	NΛ	NΛ			
	➤ Lift Signage	Danis	D) Am			
17.	Standby power supply	Required	Provided	MR			
18.	Refuge Area			1 1 1 1 1 1 1 1			
	> Total area	NA NA	NΛ	NΛ			
	> Location	NΛ	NΛ	NΛ			
	(Je						