Directo

Delhi Fire Service

FORM 'H' FORM FOR ISSUING FIRE SAFETY CERTIFICATE [Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No.F6/DFS/MS/2024/3chool 113

Dated: 15/02/2024

FIRE SAFETY CERTIFICATE

Certified that the building of J.D Tytler School, Located at R- Block, New Rajender Nagar, New Delhi - 110060 comprised of Basement + Ground +3 Upper Floors was issued FSC vide Letter No. F6/DFS/MS/School/2020/SZ/539, dated 07/12/2020. The premises was re inspected by the officer concerned of this department on 08/02/2024 in the presence of Mr. J D Babar (Account officer) and found that premises have deemed complied with the fire prevention and fire safety requirements in accordance with DOE Circular 3298-3398 Dated 01/03/2011 issued by Directorate of Education, Govt. of NCT of Delhi and that the building is fit for occupancy class B "Educational building" with effect from 15/02/2029 for a period of three years. In accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 15 02 2024 at New Delhi by.

Copy to:

1. The Principal, J.D Tytler School, at R- Block, New Rajender Nagar, New Delhi - 60.

2. Directorate of Education Old Secretariat Delhi - 110054

Following fire safety directives must be adhered to:-

- 1 All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2 Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3 The trained staff should be available round the clock.
- 4 Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5 The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6 The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. www.dfs.delhigovt.nic.in.
- 7 Basement shall be used strictly as per building bye laws.
- 8 The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

INSPECTION REPORT

Name & address of the building: J.D Tytler School, Located at R- Block, New Rajender Nagar, New Delhi - 110060.

Type of Occupancy : Educational (Basement + Ground +03 Upper floor)

Type of Case : Renewal

Details of previous NOC: F6/DFS/MS/School/2020/SZ/539, dated 07/12/2020

Fire Safety directives Letter No.:. NA

Date of inspection : 08/02/2024

Name of the Inspecting Officer: ADO (DWK)

No. of Students=1994 No. of class rooms=64 Plot area=3.06 acre

Covered area=10324 sqmtr

Name and designation of Officer

from the building side : Mr. J D Babar (Account officer)

Year of Construction

: 1985-86

10. Applicant's letter No.

: JDTS/letter/2023-24/409, dated - 19/01/2024

S No	Minimum standards on fire prevention and fire safety U/R 33	As per N/18, N/19 & N/20					Remarks MR/NMR			
1.	Access of building				1 A	160				
	Road width	06 mtrs			Provided M			IR		
	Gate width	4.5mtrs Provided						MR		
1	Width of internal road	Required	P	rovide	d from tw	o sides		MR		
2.	Number, width, Type & Arrangements of exits									
	a. Number of staircases				3		11			
	Upper floors	04 Nos.			Provided			MR		
	Basements	03 Nos.			Provided	1]	MR			
П	b. Width of staircases									
	 Upper floors 	1.5 mtr or 2.47			7m, 1.5m, 1.47,			MR Old		
\parallel	Basements	less & 0.75m						case		
11				1.48	48m, 1.47m & 1.5m			MR Old		
	= - 11	less & 0.75m								
П	c. Protection of exits									
	 Fire check door 	NA			NA			NA		
Π	 Pressurization 	NA 1			NA			NA		
	d. No of continuous staircase to terrace	1 No.			Provided			ΛR		
	e. Width Of Corridor	1.5 mtr			Provided			MR		
	f. Door Size	01 mtr	Prov	vided		MR				
	Compartmentation				15%					
П	Fire check door	NA		1	NA			NA		
	 Sealing of electrical shafts 	NA		1	NA			NΑ		
П	 Fire Rating of shaft door 	NA			NA			NA		
П	Water Curtain	NA			NA			NA		
П	Fire Dampers	NA		1	NA			NΑ		

M	12	6

4.	Smoke managements System Basements			20 -/ bour		Exhaust Fans		-	MR MR	
) PERSONAL PROPERTY OF THE PRO			30 a/c per hour						
5.	Upper floors Fire Extinguishers		12 8	12 a/c per hour		Natural ventilation				
•				ă		ببل			100	
		numbers	24	nos.			Provided		MR	
	• Type:		I	SC & CO2			Provided		MR	
-		rking .	ISI	marke	d		ISI marked		MR	
6.	First - Aid H	2.5-22-5.10-53-05-7.4-12-1								
-6	 Total 	numbers on each floor	03 Nos. Provid		led			MR		
6	• Lengt	th of hose reel hose	30 1	30 mtr 30 mtr					MR	
_	Nozzle diameter		5 m	5 mm 5 mm						
7.	Automatic fi	re detection and alarmin	g sys	tem				•		
	 Type 	of detectors	_	NA	7		NA	NA		
	 Locat 	ion of Main Panel	-	NA	NA			NA	_	
	• Locat	tion of Repeater Panel	8	NA	1111		NA	NA NA		
	• Alter	nate source of power	ω.	NA			NA.	INA	-	
	Hoote	ers' Location	-	NA	_	_	TORKS.	1374	NA	
8.	MOEFA			NA			NA	NA	_	
9.	Public Addre	ess System		A SAME TO			NA	NA	_	
10.	Automatic S	prinkler System .		Requi	rea		Provided	MR		
		ments		D	10					
		r Floor		Requ	ured		Provided	MR		
	Sprinkler above false ceiling			NA		_			A	
11.	Internal Hyd			NA			NA	NA		
		-	Tyre			1				
	Numi	of riser/down- comer ber of hydrants per floor	.	NA		_	NA	NA		
-	Hose	Box		NA		_	NA	NA		
12.	Yard Hydran	te		NA			NA	NA		
	Hose	number of hydrants		NA		_	NA	NA		
13.		24.14. O.C.		NA			NA	NA		
15.	. Pumping Arrangements:									
	• Grow	nd Level								
	San Santan	narge of main pump		NA		A	NA	NA		
	> Head	of main pump	_	NA NA		1	NA	NA		
	> Numl	ber of main pumps	_				NA	NA	1	
-	Jocke	y pump out put	_	AV	2		NA	NA		
	> Jocke	y pump head	_	NA			NA	NA		
	> Stand	by Pump out put	_	NA		1	NA	· NA		
	> Stand	by Pump Head	1	NA)	NA	NA		
	> Pumr	Staring/Manual stopping House Access	g	NA]	NA NA			
		110000 1100000	1	NA		1	NA	NA		
	Terrace level			-						
6		arge of pump	900 lpm		Provided MI					
	Head	of the pump	30 mtr				40 mtr	MR		
11		r supply		Required		_	Provided	MR		
	> Auto	starting of pump	_	Required			rovided			
)			200	-	-51464	MR	e S	
h		ě								
	-									

to	aptive water Storage for fire fighting: Under ground tank capacity	NA	1	NA .	NA		
VI	Draw off connection	NA	1	NA	NA		
Y	ru- service inlet	NA	1	NA	NA		
	Access to tank	NA		NA	NA		
	Overhead Tank capacity	15,000 ltr Provid		d	MR	MR	
1		Required Prov			MR	MR	
5 E	dt Signage						
6. Pi	vovision of Lifts	NA	NA	NA			
-11-	> Pressurization of Lift Shaft	NA NA		NA.	NA		
- 11	 Pressurization of lift lobby Communication in lift Car 	No. of the last of		NA	NA		
- 11	 Communication in fitt Car Fireman's Grounding Switch 	NA		NA	NA		
П	> Lift Signage	NA		NA	NA		
- 11) Ditt organization	NA		NA	NA		
17.1	Standby power supply	NA					
	Refuge Area	NA	-	NA '	NA		
	> Total area	NA NA		NA	NA		
П	> Location	NA					
19	Fire control room	NA		NA	NA		
	> Detector system panel	NA		NA	NA		
1 1	> Flow Switch Panel > PA System Panel > Battery backup > Building Floor Plans	NA NA		NA	NA NA		
1 1				NA			
1 1		NA		NA	NA MI		
20.	Special Fire Protection Systems for Protection of special Risks, if any;	Paguired CO2		re extinguis ed near elec	nguisher electric panel		

The fire protection systems provided in the building were test checked and found

functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the FSC issued vide letter No. F6/DFS/MS/School/2020/SZ/539, dated 07/12/2020 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended

Signature of the Inspecting Officer Udas Vir Name Designation