

FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE [Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE **NEW DELHI**

No.F6/DFS/MS/School/2024/ 110

Dated: |5 / 02/2024

FIRE SAFETY CERTIFICATE

Certified that the building of Prudence School, Located at Dwarka, Phase-II, HAF Pocket-A, Sector-16B, New Delhi-110075. comprised of Basement + Stilt/ Ground + 4 Upper Floor was issued FSC vide Letter No. F6/DFS/MS/School/2021/SZ/70 Dated 29/01/2021 (Issued for Basement + Stilt/ Ground + 4 Upper Floors). The premises was re inspected by the officers concerned of this department on 08-02-2024 in the presence of Mr. Anil Banbah (School Representative) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class-B "Educational" with effect from 15 02 2024 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on .1.5.192.1.202.4. at New Delhi by.

Delhi Fire Service

Copy to:

1. The Assistant Director(Building)DDA, Vikas SadanINA, Delhi-23

2. The Principal, Prudence School, Dwarka, Phase-II, HAF Pocket-A, Sector-16B, New Delhi-

3. Directorate of Education Old Secretariat Delhi - 110054

Following fire safety directives must be adhered to:-

The lift shall run from ground floor to upper floors.

- All the fire safety arrangements provided therein shall be maintained in good working
- 3 Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

The trained staff should be available round the clock.

5 Any deviations w.r.t. construction shall be verified by the concerned building sanctioning

6 The certificate may not be treated in any case for the regularization of the unauthorized

7 The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its

8 Basement shall be used strictly as per building bye laws.

9 The owner/occupier shall submit a declaration every year in the form 'K' provided in the first

INSPECTION REPORT

N-35

1. Name & address of the building: Prudence School, located at Dwarka, Phase-II, HAF Pocket-A, Sector-16B, New Delhi-110075.

2. Type of Occupancy : Educational (Basement + Stilt / Ground+ 4 UFs)

Type of Case

: Renewal

: F6/DFS/MS/School/2021/SZ/70 Dated 4. Details of previous NOC 29/01/2021 (Issued for Basement + Stilt / Ground+ 4 Upper Floors issued to Presidium School)

5. Fire Safety directives Letter No.: F6/DFS/MS/BP/2008/1088 Dated 15/04/08

6. Date of inspection

: 08/02/2024

No. of Students=1276 No. of class rooms=36

7. Name of the Inspecting Officer: ADO (DWK)

Plot area=3999 m² Covered area=2358m²

8. Name and designation of Officer

from the building side

: Mr. Anil Banbah (School Representative)

9. Year of Construction

: 2007

10. Applicant's l. No.: PRU/DW16B/DDE/SWB/2024/JAN/843 Dated 28/01/24

| S No | Minimum standards on fire prevention and fire safety U/R 33 | As per N/27 | | Provid site | | Remarks MR/NMR | | |
|---------|---|--------------|-------|----------------|-----------------|---------------------|--|--|
| 1. | Access of building | 10 | Prov | ided | MR | | | |
| | Road width | 10 1111 | | vided MR | | | | |
| | Gate width | OJ MILL | | | | R (being old case) | | |
| | Width of internal road | 06 mtr | | 0 0 III | IVII C | (0011.8 | | |
| 2. | Number width, Type & Arra | ngements of | exits | 1 | | | | |
| <u></u> | a. Number of staircases | 1//2 | | 2 Non | | MR | | |
| 38 | Upper floors | 2 Nos. | | 211001 | | MR | | |
| | Basements | 2 Nos. | | 2 Nos | • | IVIIC | | |
| | b. Width of staircases .Upper floors | 142 cm | 142 | cm & 1 | 32cm | MR (being old case) | | |
| | • Basements , | 158 cms & | | | ms & n & Ram | MR (being old | | |
| | a Protection of exits | | | | | | | |
| | Fire check door | Required | Pr | ovided | | MR | | |
| | Pressurization | NA | | NA | | NA | | |
| | d. No of continuous staircase to terrace | 02 Nos. | | 02 N | os. , | MR | | |
| | e. Width Of Corridor | 1.5m | | Prov | ided | MR | | |
| | f. Door Size | 109 X 205 cm | | 109 X 205 cm | | cm MR | | |
| 3. · | Compartmentation | | | Ι | T.C. | MR | | |
| | Fire check door | Required | | rovideo | | | | |
| | Sealing of electrical shafts | Required | | Provided | | MR | | |
| | Fire Rating of shaft door | .NA | | NA | | NA | | |
| | Water Curtain | NA | | NA | | NA | | |
| | Fire Dampers | NA | | NA | | NA . | | |



4-2 Smoke managements System Exhaust fans provided MR **Basements** 30 a/c charge MR Natural ventilation 12 a/c charge Upper floors Fire Extinguishers 5. 28 Nos. Provided MR Total numbers 25 nos. ABC, CO₂ & WCO₂ MR ABC, CO₂ & WCO₂ Types MR ISI marked ISI marked IS marking First - Aid Hose Reels 6. MR Provided 02 Total numbers on each floor MR Provided 30 Length of hose reel hose MR Provided 05 mm Nozzle diameter Automatic fire detection and alarming system 7. NA NA NA Type of detectors NA Near Reception NA Location of Main Panel NA NA Location of Repeater MR Provided Required Alternate source of power MR Near Staircase Appropriate place Hooters' Location MR Provided Required MOEFA MR Provided Required Public Address System Automatic Sprinkler System MR Provided Required **Basements** NA NA NA Upper Floor NA NA NA Sprinkler above false ceiling 11. Internal Hydrants: NA NA 100 mm Size of riser/down-comer NA NA 01 Number of hydrants per floor MR Provided Required Hose Box Yard Hydrants Total number of NA NA NA NA NA NA hydrants Hose Box 13. Pumping Arrangements: •

| • | Ground Level | | | |
|----------|------------------------------|----------------------|----------------------|------|
| | Discharge of main pump | NA . | NA | NA |
| > | | . NA | NA | NA |
| > | Number of main pumps . | NA | NA | NA |
| > | Jockey pump out put | NA | NA | NA |
| A | Jockey pump head | NA | NA | NA |
| A | Standby Pump out put | NA | NA | NA |
| A | Standby Pump Head | NA | NA | NA . |
| A | Auto staring/Manual stopping | NA | NA - | NA |
| | Pump House Access | NA | NA | NA |
| • | Terrace level | | 1.112. | IVA |
| A | | 900 lpm & 180 lpm | 900 lpm & 180 lpm | MR |
| 1 | Head of the pump | 30 mtr | NA | MR |
| 1 | Power supply | Required | Provided | MR |
| <i>P</i> | Auto starting of pump | Required | Provided | MR |

| 14 | Captive water Storage for fire f | ughtin | g: | | | | 45.24 | |
|-----|--|-----------------|-----------|-------------------|---|-------------|----------|--|
| 1 | capacity | | ltrs | Provided Provided | | | MR | |
| | | NA | 50 | Pro | ovided ovided ovided | | MR | |
| | | NA | 1000 | | | | MR MR | |
| - | | NA | 7.6 | Pro | | | | |
| | Access to tank Overhead Tank capacity | 50000 | ltrs | Pro | ovided | | MR | |
| 15 | Exit Signage | Requi | red | Pro | ovided | | MR | |
| 16. | Provision of Lifts (Lift Shall run from Ground to Upper Floors) | | | | | | | |
| | Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch | | NA | NA | | | NA | |
| - 1 | | | NA | | NA | | NA | |
| - 1 | | | Required | Required | | Provided | | |
| | | | Required | | Provided | | MR | |
| ١ | | | Required | Required | | Provided | | |
| 17: | Standby power supply | | Required | | DG set 125 & 62.5 KVA | | MR | |
| 18. | Refuge Area | | | | | 4) | | |
| | > Total area | | NA | | NA NA | | | |
| | > Location | | NA | | NA | NA | ν | |
| 19. | | | | | | | | |
| - | Detector system panel | | NA | _ | NA | | NA NA | |
| | Flow Switch Panel | | NA | | | NA | | |
| | PA System Panel Battery backup Building Floor Plans | | Required | d | Provided | | MR | |
| | | | Require | | Provided | | MR | |
| | | | Require | d | Provided | | MR | |
| 20. | Special Fire Protection Syste Protection of special Risks, | ms fo if any | r Require | d | ABC, Fire extinguish provided electric p | her near | MR | |

The fire protection systems provided in the building were test checked and

found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter F6/DFS/MS/School/2021/SZ/70 Dated 29/01/2021 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Name Udai Vir Singh

Designation ADO/DWK

sola of all

CPO (SZ) Vmg8

Inector /1/17/3

As John ON