

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No.F.6/DFS/MS/2024/SZ/ 109

Dated: 90 / 02 /2024

FIRE SAFETY CERTIFICATE

Certified that the Community Hall in the Name & Style of M/s Chittaranjan Park Bangiya Samaj (Regd.) located at C-405, C. R Park, New Delhi – 110019 Comprised of Basement, Ground + 03 Upper Floors was issued FSC by this department vide letter No. F.6/DFS/MS/2021/SZ/156 dated 05/03/2021. The premises re-inspected by officers concerned of this department on 09/02/2024 in the presence of M. Parveen Kumar and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of Delhi Fire Service Rules, 2010 and that building is fit for occupancy "Assembly Building, Group-D" (Community Hall) as above with effect from 20/02/2024 for period of Three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 20/02/2024 at New Delhi by

DIRECTOR FIRE SERVICE

Copy to: -

- 1. The Executive Engineer, (Bldg) Central Zone, Jal Vihar, Lajpat Nagar, New Delhi 110024.
- Mr. G.M Bhattacharya, (General Secretary) Chittaranjan Park Bangiya Samaj (Regd.) C-405, C. R Park, New Delhi – 110019

Conditions for the validity of Fire Safety Certificate: -

- All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to nonfunctional fire safety measures shall be at the responsibility of the management.
- All the staff members must know the correct method of operation of fire fighting system.
- 3. The basement shall be used strictly as per the provision of Building Bye Laws.
- The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.
- "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry."
- 7. This Fire Safety Certificate is valid for Front Portion (older Part of Building only).



	INSPECTI	ON REPORT	the self-on the con-		
V.1	Name & Address of the Building	Chittaranjan Parl R Park, New De	c Bangiya Samaj (Regd.)	at C-405, C.	
2	Type of Occupancy	Group "D" Com	munity Hall		
3	Building Comprised of	Basement, Ground + 03 upper floors.			
4	Type of Case	Renewal			
5	Details of Previous NOC	F.6/DFS/MS/202	21/SZ/156 dated 05/03/20	021	
6	Fire Safety Directives Letter No	F6/DFS/MS/BP/	97/396 dated 10.04.1997	,21	
7	Date of Inspection	09/02/2024	e igligani se salasi igi		
8	Name of the Inspecting Officers	DO (South) & A	DO (BCP)		
9	Name & Designation of Officers from the building side	Mr. Parveen Kumar			
10	Year of construction	1997 & 2014			
11	Applicant letter No.		12569 dated 02-02-202	4	
S. No.	Minimum standards on Fire Prevention and Fire Safety U/R 33	NBC requirements	Provided at Site	Remarks MR/NMR	
1	Access to Building.	· · · · · · · · · · · · · · · · · · ·			
==1	Road width	9 mtr	Provided	MR	
200	Gate width	4.5 mtr	Provided	MR	
1,48	Width of internal road	-NA-	-NA-	-NA-	
	I are in the second of the sec	****	A CONTRACTOR OF THE PARTY	A	
2	Number, width, type & arrangement of exits.		+ Parelles		
10	a) Number of Staircase	02 Nos	02 Nos	MR	
12-1	> Upper floors.	02 Nos	02 Nos	MR	
	> Basement floor.	02 1405	02 1103	IVIK	
R-	b) Width of Staircase			MR	
	> Upper floors	1.25 mtr	1.23 mtr & 0.75 mtr	(old case)	
	> Basement floor	1.25 mtr	1.23 mtr, 1.65 mtr & 4.25 mtr	MR (old case)	
	c) Protection of exits	Thriddries Initial	marketing to some a		
1	> Fire check door	Required	Provided	MR	
	> Pressurization	-NA-	-NA-	-NA-	
W	d) No. of continuous staircase to terrace	Required	01 Nos	MR	
mi i	e) Width of corridor	-NA-	-NA-	-NA-	
HC I	f) Door size (Exits in hall)	-NA-	-NA-	-NA-	
3	Compartmentation.		THE WATER WORLD	1 514	
	Fire check door.	-NA-	-NA-	-NA-	
100	 Sealing of electrical shafts. 	-NA-	-NA-	-NA-	
-	Fire rating of shaft door.	-NA-	-NA-	-NA-	
the 1	Water curtain	-NA-	-NA-	-NA-	
	Fire dampers.	-NA-	-NA-	-NA-	
4.	Smoke Management system.			1 37	
30	Basement	30 ACPH	Provided	MR	
Ø.	Upper floors	12 ACPH	Natural	MR	
5.	Fire Extinguishers.	entio fill	1737	MR	
	Total numbers	Required	15 Nos	71 2	
		ISI marked	Co2, ABC & DCP	MR	
M -	Iypes ISI Marking	ISI marked	Provided	MR	
		56-5	dazeller VesserNupulg		
6.	First Aid Hose Reels.	01 Nos	Provided	MR	
4	Total numbers on each floor.		Provided	MR	
APC ALC ALC ALC ALC ALC ALC ALC ALC ALC AL	 Length of hose-reel hose. 	30m	== -== - (-E-20-20-20-20-11	MR	
	Nozzle Diameter	5mm	Provided	IVII	



7	Automatic fire detection & alarming system.	70	G,-įc.	нысч
No.	Type of detectors	XIII III		
	Location of Main Panel	-NA-	-NA-	-NA-
	Location of Main Panel Location of Panel	-NA-	-NA-	-NA-
	Location of Repeater Panel Alternate and Alternat	-NA-	-NA-	-NA-
	Alternate source of power	-NA-	-NA-	-NA-
8.	Hooter's location MOEFA	-NA-	-NA-	-NA-
9,		Required	Provided	MR
10.	Public Address System	-NA-	-NA-	-NA-
	Automatic Sprinkler System			
	Basement	Required	Provided	MR
	• Upper floors.	-NA-	-NA-	-NA-
11.	Sprinkler above false ceiling	-NA-	-NA-	-NA-
***	Internal Hydrants.			
	 Size of Riser/Down-comer 	-NA-	-NA-	-NA-
	 Number of Hydrant per floor 	-NA-	-NA-	-NA-
10	Hose box.	-NA-	-NA-	-NA-
12.	Yard Hydrants.			1
	 Total number of hydrants. 	-NA-	-NA-	-NA-
	Hose box.	-NA-	-NA-	-NA-
13.	Pumping arrangements.	TAA*	-INA-	-11/12-
	Ground Level	Control of the Control		
	Discharge of main pump.	-NA-		
	➤ Head of main pump.	-NA-	-NA-	-NA-
	Number of main pumps.	-NA-	-NA-	-NA-
	A Jackey Property	-NA-	-NA-	-NA-
177	> Jockey Pump output.	-NA-	-NA-	-NA-
	Jockey Pump head.	-NA-	-NA-	-NA-
	Standby Pump output.	-NA-	-NA- -NA-	-NA-
	Standby Pump head.	-NA-		-NA-
	Auto Starting/Manual Stopping.		-NA-	-NA-
	Pump house access.	-NA-	-NA-	-NA-
	Terrace Level			†
	Discharge of pump.	900 LPM	Provided	MD
	➤ Head of pump.	40 m	Provided	MR
	➤ Power supply.	Required	Provided	MR
	Auto starting of pump.	Required	Provided	MR
14.	Captive water storage for fire fighting.	1,	TIOVIGE	MR
	 Underground tank capacity. 	25,000 Ltr	Provided	100
	Draw-off connection.	Required	Provided	MR
	➤ Fire Service Inlet.	Required	Provided	MR
	➤ Access to tank.	Required	Provided	MR
	Overhead tank capacity.	12,500 Ltr	Provided	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.		TIOVIDED	MR
N. I.V.	Pressurization of lift shaft.	-NA-	-NA-	
	 Pressurization of lift lobby. 	-NA-		-NA
	Communication in lift car.		-NA-	-NA
	Fireman's switch.	-NA-	-NA-	-NA
	Lift signage.	Required	Provided	MR
		Required	Provided	MR
17.	Standby Power Supply	Required	Provided (DG Set)	MR
18.	Refuge Area	0.0011.20		IATI
	Total area	-NA-	-NA-	-NA

3)



19.	Fire Control Room.			
	Detector system panel.	-NA-	-NA-	-NA-
	 Flow switch panel. 	-NA-	-NA-	-NA-
	 PA system panel. 	-NA-	-NA-	-NA-
	 Battery backup. 	-NA-	-NA-	-NA-
	 Building floor plan. 	-NA-	-NA-	-NA-
20.	Special Fire Protection System for the Protection of special Risk, if any.	-NA-	-NA-	-NA-

The fire protection system provided in the building were randomly checked and found functional at the time of inspection and the renewal of FSC is for Front Portion (older Part only).

Keeping in view of the deemed compliance of the minimum standard on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no F.6/DFS/MS/2021/SZ/156 dated 05/03/2021, renewal under rule 35(6) of the Delhi Fire Service rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspection Officer Name: Sh. Manoj Kumar Sharma

Design: DO (South)

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar

Design: ADO (BCP)

CFO (HQ)

to approved, F.J. lettel is putup or your signature Pl. 1/19/2/1000