FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35] GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F6/DFS/MS/2024/ GH 39

Dated: 20 /02/2024

Delhi Fire Serv

FIRE SAFETY CERTIFICATE

Certified that the M/s Hotel Pablas International Located at Ground, 1st, 2nd & 3rd floors, 12A/22, WEA, Karol Bagh, New Delhi-110005 comprised of Basement (hall + 03 rooms for staff) + Ground floor (reception, office & 03 guest rooms + first floor (08 guest rooms) + second floor (08 guest rooms) + third floor (08 guest rooms) + fourth floor (Vacant / not in use as per affidavit given by the owner) (Total=27Rooms) was issued FSC vide Letter No F6/DFS/MS/GH/SZ/2021/05, dated 06/01/2021. The premises was re inspected by the officer concerned of this department on 06/02/2024 in the presence of Sh. Sandeep Sharma (Manager) and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential" (guest house) with effect from 20 02 2024 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 20/02/2024.... at New Delhi by.

Copy to:

 The Joint. Commissioner of Police (Lic), 1st Floor, Licensing Unit, Police Station, Defence Colony, New Delhi.

2. The Manager, M/s Hotel Pablas International at Ground, 1st, 2nd & 3rd floors, 12A/22, WEA, Karol Bagh, New Delhi-110005.

Following fire safety directives must be adhered to:-

- 1. The 4th Floor shall not be used, stair at terrace level shall be kept open & free from lock and key & all the exit shall be clear from any obstruction otherwise the FSC shall be null & void.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- The trained staff should be available round the clock.
- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 7. Basement strictly shall be kept vacant as seen during inspection.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 9. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

1.100

INSPECTION REPORT

 Name & address of the building: M/s Hotel Pablas International Located at Ground, 1st, 2nd & 3rd floors, 12A/22, WEA, Karol Bagh, New Delhi-110005.

2. Type of Occupancy

:Lodging or rooming "A-1"

3. Type of Case : Renewal (Basement + Ground + 4 Upper Floor)
The Hotel is running at Ground, 1st, 2nd, & 3rd floor only 4rth floor laying vacant)

4. Details of previous NOC: F6/DFS/MS/GH/SZ/2021/05, dated 06/01/2021

5. Fire Safety directives Letter No.: Nil

6. Date of inspection

:06/02/2024

7. Name of the Inspecting Officer: ADO (DWK)

8. Name and designation of Officer

from the building side

: Sh. Sandeep Sharma (Manager)

9. Year of Construction

: 2004-05

10. Applicant's letter No.

:2024013101046, dated 01/02/2024

S No	Minimum standards on fire prevention and fire safety U/R		As per N/26, P: 33 N/27 & N/28 si		rovided at Rem		arks NMR	
1.	Access of building							200//10/5
	 Road width 	06	mtr	Prov	rided			MR
	Gate width	4.:	5m	Direct Accessible From			Road	NA
	 Width of internal road 	N.	A	NA				NA
2.	Number, width, Type & Arrang	gem	ents of	exits			1	a//
V:	 a. Number of staircases 							
	Upper floors	01		41.1	01		MR	
-	Basements	01	No.		01 No		MR	
	 b. Width of staircases 							
	Upper floors	1.2	25 mtr	Pro	ovided		MR	
	 Basements 	1.2	25 mtr	Pr	ovided		M	IR.
	c. Protection of exits					1	7.	
	Fire check door	N.	A			NA		NA
	Pressurization	N	4		4	NA .		NA
	d. No of continuous , staircase to terrace	01				01		MR
-	e. Width Of Corridor	1.2	25 mtr		11/4	Provided	M	R
	f. Door Size		d case		0.89m	MR (Be	eing old	l case)
3.	Compartmentation							
	Fire check door	Re	quired			Provided		MR
	Sealing of electrical shafts	Re	quired			Sealed		MR
	Fire Rating of shaft door	N	Α .			NA .		NA
	Water Curtain	N	A			NA		NA
	Fire Dampers	N	A			NA		NA
	(4 m)		G/X					

			19	1//3	3			
1.	Smales management Control		113	1:10				
٠.	Smoke managements System	12 a/c per hour			Exhaust Fan	MF		
	Basements	12 a/	c per n		Natural ventilation	MF		
	Upper floors	12 a/						
5.	Fire Extinguishers	20.31	22		Provided	MI		
	 Total numbers 	20 N	os. & CO	i.	CO ₂ & ABC	MI		
	• Types			2	Provided	MI		
	 IS marking 	Required			Provided			
6	First – Aid Hose Reels	0.1			Provided	MR		
	Total numbers on	01			Tiovided			
	each floor	20 m	tr	- 5	30 mtr			
	Length of hose reel	30 111	30 mtr 5 MM		30 1114	390		
	hose	5 MN			Provided	M		
7	Nozzle diameter Automatic fire detection and al	TO THE REAL PROPERTY OF THE PARTY OF THE PAR			Descriptions			
7.		CO	detecto	ors.	complied	M		
	Type of detectorsLocation of Main	Requ	34.57		Near reception	M		
	Panel	Kequ	med		Trout toophon			
	Location of Repeater	NA		NA		N/		
	Panel	1471		9.33				
	Alternate source of	Regu	ired	Provi	ided	M		
	power							
	 Hooters' Location 	Requ	ired		Provided	M		
8.	MOEFA	Required		Provided		M		
9.	Public Address System	Requ		Provi	ided	M		
10.	Automatic Sprinkler System		8	8.2		H		
	Basements	Requ	uired		Provided	MR		
	Upper Floor	NA		8	NA	NA		
	Sprinkler above false	NA			NA	NA		
	ceiling							
11.	Internal Hydrants:	76		1274				
	Size of riser/down- cor	prosect to		7	NA	NA		
	 Number of hydrants pe 	r floor	N/	1	NA	NA		
	Hose Box	NA		1	NA	NA		
12.	Yard Hydrants					NA		
	Total number of	NA.	P 1		NA			
	hydrants							
r	Hose Box	NA .			NA	NA		
13.								
	Ground Level				1374	[57.		
	Discharge of main pun	-P _	NA		NA	NA NA		
	> Head of main pump	-	NA		NA NA	NA NA		
	Number of main pump	-		•	NA NA	NA NA		
	> Jockey pump out put	_	NA NA NA NA NA		NA NA	NA NA		
	Jockey pump headStandby Pump out put				NA NA	NA NA		
	Standby Pump Head Standby Pump Head	4			NA NA	NA NA		
	> Auto Staring/Manual	3.00			NA NA	NA NA		
	stopping	NA NA			NA NA	NA NA		
	> Pump House Access		NA NA			INF		
	Terrace level	450 lpm Provided			Provided	M		
	Discharge of pump		30 mt		Provided	M		
	➤ Head of the pump	-	Required		Provided	M		
	Power supply	-	Required		Provided	M		
	> Auto starting of pump	10	110001		1 TO VIGOU	I IVII		

we by

to	aptive water Storage for fire fig	ghting:		
: 10	Under ground tank capacity	NA	NA I	A
	[[[[[[[[[[[[[[[[[[[NA	NA ·	NA
		NA	1 3 7 4	NA
	> Access to tank	NA	NTA .	NA
Ì	Overhead Tank capacity	5,000 ltr	Provided	MR
E	Exit Signage	Required	Provided	MR
	Provision of Lifts	•		
-	 Pressurization of Lift Shaft 	NA	NA ·	NA
	 Pressurization of lift lobby 	NA	NA	NA
э	 Communication in lift Car 	Required	Provided	MR
	> Fireman's Grounding Switch	Required	Provided	MR
> Lift Signage		Required	Provided	MR
17.	Standby power supply	Required	Provided	MR
18.	Refuge Area .			
10.	> Total area	NA	NA	NA
	> Location	NA	NA	NA
19.	70 - 1000		1.00	NA
17.	> Detector system panel	NA	NA	NA NA
	Flow Switch Panel	NA	NA .	NA NA
	> PA System Panel	NA	NA Provided	MR
	> Battery backup	Required		NA
-	Building Floor Plans	NA	NA Langue suringuisher	MR
20	The second secon	Required	ABC fire extinguisher provided near electric panel	T00010000

The fire protection systems provided in the building were test checked and found

functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter no. F6/DFS/MS/GH/SZ/2021/05, dated 06/01/2021 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Name: Sh. Udaivir Singh Designation: ADO (DWK)