GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2024/37

Dated: 20/92/2024

FIRE SAFETY CERTIFICATE

Certified that the Step Inn Gold Guest House located at 2/3, D.B.G. Road, Pahar Ganj, New Delhi in a building comprised of ground +mezzanine and 02 upper floors, Ground floor (Bank of Baroda), mezzanine (other portion), 1st floor (03 guest rooms), 2nd (07 guest rooms), total 10 guest rooms owned/occupied by Step Inn Gold Guest House. The FSC was earlier granted by this department vide letter No.F6/DFS/MS/GH/NDZ/2021/435 dated 29/09/21 for 10 guest room only. Now, the premise was re-inspected by the officers concerned of this department on 09/02/24 in the presence of Manager and found that the said guest have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 first (03 guest rooms) & second floor (07 rooms) total 10 guest rooms only and valid up to 31.03.2027 from the date of issue in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 20/02/2024 New Delhi by.

DIRECTOR Delhi Fire Service

Copy to:-

- 1. The Commissioner, North MCD, Civic Centre, New Delhi: To ensure the occupancy in the building as detailed above
- The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. 2024020301171 dated 03/02/24.
- 3. The Manager, Step Inn Gold Guest House at 2/3, D.B.G. Road, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

- 4. Any deviation w.r.t. construction, use of occupancy, height of building, electric installation, set back area etc. shall be checked & verified by the concerned authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 9. Any flammable material for interior decoration shall be strictly prohibited.

M12/3 INSPECTION REPORT 1. Name & address of the building Step Inn Gold Guest House 2/3, D.B.G. Road, Pahar Ganj, New Delhi Residential, Sub Division-A-1 2. Type of occupancy:-Gr.+ mez.+ 02 Upper floors (total 10 Guest rooms) Ground floor (bank of Baroda), mez.(other portion)

Ist floor (03 guest rooms), 2nd (07guest rooms) Renewal 3. Type of case:-No. F6/DFS/MS/GH/NDZ/2021/435 dated 4. Details of previous FSC:-29/09/21. N/A Fire safety directives No.-09/02/24 6. Date of inspection:-Sh. Ravinder Singh (ADO/CC) 7. Name of the inspecting officer:-8. Name & designation of officer Manager From the building side:-9. Year of construction:-Online id no. 2024020301171 dated 03/02/24. 10. Applicant's letter No:-Old Case Provided at site Remarks Requirement/ Minimum Standards on fire S.No. Existing fire safety MR/NMR Prevention and fire safety U/R 33 arrangements Access to Building 1. N/A 18 mtr. N/A 1) Road width N/A N/A N/A 2) Gate width N/A N/A N/A 3) Width of internal road Number, Width Type & Arrangement of Exits 2. A. Number of staircases MR 02 Nos. 01 Nos. 1. Upper floors N/A N/A 2. Basements N/A B. Width of staircase 0.87 & 1.50mtr. MR 0.80 mtr. 1. Upper floors N/A N/A N/A 2. Basements C. Protection of exits MR Provided Required 1. Fire check door N/A N/A N/A 2. Pressurization N/A N/A N/A D. No. of continuous staircase to terrace N/A 1.20 to 1.4 mtr 01 E. Width of corridor MR 01 mtr. 01 mtr. F. Door size Compartmentation 3. N/A N/A N/A 1) Fire check door

12 ACPH Natural/Exhaust MR 2) Upper floors fan Fire Extinguishers 5. MR 06 Nos. 08 Nos. 1) Total numbers ABC & CO2 ABC & CO2 MR 2) Types MR Provided Required 3) ISI marking First-Aid Hose Reel 6.

30 ACPH

N/A

N/A

N/A

N/A

2) Sealing of electrical shafts

Smoke Management System

3) Fire rating of shaft door

4) Water curtain

5) Fire Dampers

1) Basements

4.

N/A

10

-111	1) Total number of eachfloor	01	1.0	
	2) Length of hose reel hose	01	01	MR
	3) Nozzle diameter	30 mtr.	30 mtr.	MR
7.	Automatic Fire Detection & Ala	05 mm	05 mm	MR
No.	1) Type of detectors Co type	pe Required Provided		
	2) Location of main panel	Ground flo	or Provided	MR MR
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	Required	Provided	MR
	5) Hooter's Location	Ground flo		MR
8.	MOEFA	Required	Provided	MR
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System	required	Flovided	IVIX
	1) Basement	N/A N/A		N/A
	2) Upper floors	N/A N/A		N/A
	3) Sprinkler above false ceiling	N/A	N/A	N/A
11.	Internal Hydrants	11/21	IVA	IWA
	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per floor	N/A	N/A	N/A
	3) Hose box	N/A	N/A	N/A
12.	Yard Hydrants	ANA	A.364.B	13/44
	1) Total number of hydrants	N/A N/A		N/A
	2) Hose box	N/A	N/A	N/A
13.	Pumping Arrangement	W - L-	7.37.5.5	
	1) Ground level	N/A N/A		N/A
	a) Discharge of main pump	N/A N/A		N/A
	b) Head of main pump	N/A N/A		N/A
	c) Number of main pump	N/A	N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual	N/A	N/A	N/A
	stopping			
	2) Terrace level			
	a) Discharge of pump	450 LPM	450 LPM	MR
	b) Head of pump	30 mtr.	30 mtr.	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of pump	Required Provided		MR
14.	Captive Water Storage for Fire	Fighting	Estra	INT/A
	 Under ground tank 	N/A	N/A	N/A
	capacity	27/4	NIA	N/A
	a) Draw-off connection	N/A	N/A	N/A N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A / 5,000 ltr.	MR
	d) Over head tank capacity	5,000 ltr.	Provided	MR
15.	Exit Signage.	Required	Provided	IVIIC
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A

do \

	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System Risk, if any: One ABC type fire e	MR		

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if approved, we may renew the FSC issued vide letter no. F6/DFS/MS/GH/NDZ/2021/435 dated 29/09/21 under rule 35 of the Delhi Fire Service rules 2010. Accordingly, DFA is put up for kind perusal and signature please.

Signature of the Inspecting Officer

Name: - Ravinder Singh Designation: - ADO (CC

As atopor us son putup for Ican pormed and Cy

Acase My 9/1 m

11/00/24 J