GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001

Dated:

FIRE SAFETY CERTIFICATE

Certified that the Delhi Public School located at Mathura Road, New Delhi, comprised of Senior block - Ground + 3 upper floors, Junior block - Ground + 3 upper floors & Work & Experience block - Ground + 1 upper floor + Pota cabin on 2nd floor, was granted Fire Safety Certificate by this department vide letter no. F6/DFS/MS/School/2020/SZ/482 dated 05.11.2020. The school building was re-inspected by Assistant Divisional Officer (M. Road) from this department on 15.02.2023 in the presence of Mr. Rajeev Sharma (School Engineer) and found that the building has deemed complied with the fire prevention and fire safety requirements in accordance with the circular no. 3298 to 3398 dated 01.03.2011 issued by the Directorate of Education and the building/premises is fit for occupancy of Group B "Educational Building" with effect from 21 02 2 renewed for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to conditions under Rule 38 of Delhi Fire Service Rules, 2010 printed below.

Issued on....21.02 ... at New Delhi by.

Atul Garg) Director

Delhi Fire Service

Copy to:-.

1. The Directorate of Education, Govt. of NCT of Delhi, Old Secretariat, Delhi.

2. The Principal, Delhi Public School located at Mathura Road, New Delhi.

Conditions for the validity of Fire Safety Certificate:-

1. The owner /occupier shall apply for renewal of this fire safety certificate to the Director in form J' [sub rule(1) of rule 37] along with a copy of this certificate, six months prior to its expiry

2. All the means of escape shall be kept free of all the type of obstruction all the time.

3. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

4. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.

5. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc .may be got verified from the authorities

6. This Fire Safety Certificate cannot be treated in any case for regularizations of unauthorized construction

7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.

| | | | nd address of the | PECTION REPORT Delhi Public School | located at Mathema D | and N | | |
|-------|---|-----|--|--|---|---------------------|--|--|
| | build | in | g: | Delhi Public School located at Mathura Road, New Delhi. | | | | |
| | Building is comprised of | | | Comprised of five blo | ocks:- | | | |
| | | | | Senior block – Ground + 3 upper floors | | | | |
| | | | | Junior block - Groun | d + 3 upper floors | | | |
| | | | | Work & Experience block – Ground + 1 upper floor + Pota cabin on 2 nd floor Hostel block – Ground + 3 upper floor (Not in Purview of Rule 27) Nursery block – Already issued separate FSC | | | | |
| | | | | | | | | |
| | | | | | | | | |
| - 1 | | | | | | | | |
| | Typ | e c | foccupancy | Educational Building Group -B | | | | |
| | Type of occupancy Type of case: | | | Renewal | | | | |
| | | | s of previous FSC: | F6/DFS/MS/School/2020/SZ/482 dated 05.11.2020 | | | | |
| | Date of inspection: Name of the inspecting officer: Name and designation of the | | | F.16/Estate/CC/Fire Safety/2011/3298to 3398 date 01/03/2011 | | | | |
| | | | | | | | | |
| 1 | | | | 15.02.2024 ADO Rajesh Kumar Shukla (M. Road) | | | | |
| 3 | | | | | | | | |
|) | | | | Mr. Rajeev Sharma (School Engineer) | | | | |
| | | | r from the building side: | 1000 1005 | | | | |
| 10 | Year of construction: | | | 1968 to 1997 | | | | |
| 11 | | | ence letter no.: | Outdoor diary no. 10700 dated 11.12.2023 | | Remarks | | |
| S,No | Minimum Standards on fire Prevention and fire safety requirements U/R 33 | | | Requirements | Provide at site | MR/NMR | | |
| | | | | | | | | |
| _ | | • | | | | 10.00 | | |
| 1 | - | | ss to Building | Annancible | 12.0 mtrs. | MR | | |
| | A | - | Road width | Accessible NA | 5 Gates (2 nos. of 6.7 | NA | | |
| | В | 1 | Gate width | INA | m, 5 m, 4.9 m & 4.8 m) | 1111 | | |
| | C | 1 | Width of internal roads | NA | NA | NA | | |
| 1217 | | | | 20000000 | | | | |
| 2 | _ | | ber, Width, Type & Arran | ngement of Exits | | | | |
| | A | + | No. of staircase: | | Control Control |) (D | | |
| | | 8 | a) Upper floor | Senior block - 5 nos. Junior block - 2 nos. | Senior block – 5 nos. Junior block – 2 nos. | MR | | |
| | A. | 1 | | Work & Experience | Work & Experience | | | |
| | | | | block - 2 nos. | block - 2 nos. | | | |
| | | T | b) Basements | NA | NA | NA | | |
| | В | | Width of the staircase: | AH III W | | T . | | |
| | | | a) Upper floor | 1 staircase of 1.5 mtrs or if main staircase | Senior block – 1.23 m, 1.25 m, 1.30 m & 1.50 m | MR | | |
| - | | ١ | | width is < 1.5 mtrs an | Junior block – 1.22 m & | | | |
| | | | | additional staircase of | 1.07 m | | | |
| | | | | 0.75 mtrrs width is | Work & Experience | | | |
| 1 - | 115 | | | required. | block - 1.30 m & 0.87 m | NTA | | |
| 1 | _ | | b) Basements | NA | NA | NA | | |
| 1 | (| ; | Protection of exits | Lyn | Lyva | 1274 | | |
| | | | a) Fire check door | NA | NA | NA | | |
| | | | b) Pressurization | NA | NA | NA | | |
| | I |) | No. of continuous staircase | 1 no. | Senior block - 5 nos. | MR | | |
| | | | to terrace: | LL 15 | Junior block - 2 nos. Work & Experience | | | |
| 1 | | | THE PART OF THE PA | | block - 2 nos. | | | |
| | 1 | F | Width of the corridor | NA | NA | NA | | |
| | | E | Door size | 1.0 mtrs. | 1.18 mtrs | MR | | |
| | 3 Compartmentation: | | | | | L | | |
| | | A | Fire check doors | NA | NA | NA | | |
| | | В | Sealing of electrical shafts | NA | NA | NA | | |
| | | C | Fire rating of shaft doors | NA | NA | NA | | |
| 24 - | | D | Water curtain | NA | NA | NA , | | |
| 3 | | E | Fire dampers | NA | NA | NA | | |
| 4 | | Sr | noke Management System: | | JAN ET I T | | | |
| | | A | Upper floors | NA | NA | NA | | |
| | | В | | NA | NA | NA | | |
| | 5 | Fi | re Extinguishers | | | Trace of the second | | |
| | - 76 | A | | 60 nos. | 90 nos. | MR | | |
| | 1 | В | 9503 Area St. Constant Page | CO ₂ & ABC | CO ₂ & ABC | MR | | |
| e III | 1 | C | | Required | Provided | MR | | |

NIH

| 0 | A | Total no. at each floor | Senior block – 8 nos. Junior block – 3 nos. Work & Experience block – 1 nos. | Provided | MR |
|--------|------|--|--|---|--------|
| | _ | I th of hose mal | 30 mtrs. | 30 mtrs. | MR |
| | B | | 5 mm | 5 mm | MR |
| | C | Nozzle diameter | | | |
| 7 | - | utomatic Fire Detection and Ala | NA | NA | NA |
| | A | Type of detectors | NA NA | NA | NA |
| | В | | NA NA | NA | NA |
| | C | | NA NA | NA | NA |
| | D | | NA NA | NA | NA |
| - | E | in the state of th | NA NA | NA | NA |
| 8 | I.V. | IOEFA Sourtem | NA | Provided | NA |
| 9 | P | ublic Address System | 1,441 | | |
| 10 | _ | utomatic Sprinkler System Basement | NA | NA | NA |
| | A | Upper floor | NA | NA | NA |
| | R | Sprinklers above false ceiling | NA | NA | NA |
| 11 | | iternal Hydrants | | | 102.00 |
| 11 | A | | NA | NA | NA |
| | B | | NA | NA | NA_ |
| | C | | NA | NA | NA |
| 12 | | ard Hydrants | | | 13.4 |
| | A | | NA | NA | NA |
| | B | | NA | NA | NA |
| 13 | | imping Arrangements | | | |
| | A | Ground Level | | | |
| | | a) Discharge of main pump | NA | NA | NA |
| | | b) Head of main pump | NA | NA | NA |
| | | c) Number of main pump | NA | NA | NA |
| М | | d) Discharge of jockey pump | NA | NA | NA |
| | | e) Head of jockey pump | NA | NA | NA |
| J | | f) Discharge of standby pump | NA | NA | NA |
| _ // | | g) Head of standby pump | NA | NA | NA |
| | | h) Auto starting/ manual stopping | NA | NA | NA |
| \neg | В | Terrace Level | | | |
| | = | a) Discharge of terrace pump | 450 LPM | 3 nos. of 450 LPM | MR |
| | | b) Head of terrace pump | 40 m | Provided | MR |
| | ĺ | c) Alternate power supply | Required | Provided | MR |
| | | d) Auto starting of pump | | Provided | MR |
| 4 | Ca | ptive Water Storage for Fire Figl | | | 4 |
| | A | Underground tank capacity | THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS NA | NA | NA |
| - | В | Draw off connection | | NA | NA |
| - | | Fire service inlet | 2.50 | NA | NA |
| | E | Access to tank | *** | NA | NA |
| | D | Overhead tank capacity | 10,000 Ltrs | 15,000 Ltrs (common for three blocks) | MR |
| | | Signage | Required | Provided | MR |
| _ | _ | vision of lift | | | IVIK |
| _ | | Pressurization of lift shaft | NA | NA | NIA |
|] | 3 | Pressurization of lift lobby | ATA | NA | NA |
| (| | Communication in lift car | NIA . | NA | NA |
| _ | | Fireman switch | NA | NA NA | NA |
| 100 | | Lift signage | NIA | NA NA | NA |
| S | tan | dby Power Supply | NIA | | NA |
| | | | | NA | NA |

Delhi Public School located at Mathura Road, New Delhi



Delhi Public School located at Mathura Road, New Delhi

| 18 8 | Refuge Area | | | | | |
|---------------|---|----|------|-----|--|--|
| | \ location | NA | NA | NA | | |
| 1 | 3 Total area | NA | NA | NA | | |
| 19 F | Fire Control Room | | | | | |
| | Fire detection system panel | NA | NA | NA | | |
| - 2 | Flow switch panel | NA | NA | NA | | |
| | P A system panel | NA | NA | NA | | |
| $\overline{}$ | 1 | NA | NA | NA | | |
| D | Battery backup | NA | NA | NA. | | |
| E | Building floor plan | | 1.00 | NA | | |
| 0 8 | Special Fire Protection for special risk if any | | | | | |

Meeting requirement (MR), Not meeting requirement (NMR), Not applicable (NA), Provided but not functional (PNF).

The fire protection systems provided in the building were tested, checked at random and found functional at the time of inspections.

Keeping In view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required under the Rules, the FSC issued vide letter no. F6/DFS/MS/School/2020/SZ/482 dated 05.11.2020 is recommended to be renewed under Rule 37 of the Delhi Fire Service Rules 2010.

Signature of the Inspecting Officer

Name Rajesh Kumar Shukla

Designation ADO (M. Road)

Medle Tolym

Denector My XX

FT PS

Director (Dole) hy 12/24

Sylvaly 9