

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE **NEW DELHI** 

No.F6/DFS/MS/2024/ School 125

Dated: 22/02/2024

## FIRE SAFETY CERTIFICATE

Certified that the building of Sulabh International Centre for Action Sociology Located at Sulabh Bhawan, RZ-83, Mahavir Enclave, New Delhi-110045 having two blocks namely old & new block old block comprised of comprised of G+2 Upper floors was issued Fire Safety Certificate vide letter No. F.6/DFS/MS/School/2020/SZ/538, dated 23/12/2020. The premises was re inspected by the officer concerned of this department on 12/02/2023 in the presence of Sh. Anil Kumar (Secretary) and found that premises have deemed complied with the fire prevention and fire safety requirements in accordance with DOE Circular 3298-3398 Dated 01/03/2011 issued by Directorate of Education, Govt. of NCT of Delhi and that the building is fit for occupancy class B "Educational building" with effect from 22 02 2024 for a period of three years. In accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 22 02 2024 at New Delhi by.

Director

Delhi Fire Service.

Note; - Newly constructed rooms at 2nd floor shall not be used for any purpost

Copy to:

1. The Principal, Sulabh International Centre for Action Sociology Located at Sulabh Bhawan, RZ-83, Mahavir Enclave, New Delhi-110045.

2. Directorate of Education Old Secretariat Delhi - 110054

## Following fire safety directives must be adhered to:-

- 1 All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2 Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

3 The trained staff should be available round the clock.

- 4 Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5 The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6 The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry, www.dfs.delhigovt.nic.in.

7 Basement shall be used strictly as per building bye laws.

8 The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

## INSPECTION REPORT

 Name & address of the building: Sulabh International Centre for Action Sociology Located at Sulabh Bhawan, RZ-83, Mahavir Enclave, New Delhi-110045.

2. Type of Occupancy : Ground +02 Upper floor)

3. Type of Case : Renewal

4. Details of previous NOC: F.6/DFS/MS/School/2020/SZ/538, dated 23/12/2020

5. Fire Safety directives Letter No.: . DOE Circular. Dated 01/03/2011

6. Date of inspection : 12/02/2024

7. Name of the Inspecting Officer: ADO (DWK)

8. Name and designation of Officer

No. of Students=440 No. of class rooms=44 Plot area=2530sq.mtr Covered area=1418 sq.mtr

from the building side : Sh. Anil Kumar (Secretary)

9. Year of Construction

: 2000

10. Applicant's letter No.

: Email dated - 27/01/2024

| S<br>No | Minimum standards on fire pre<br>and fire safety U/R 33  |                |         | As per N/10,<br>N/11 & N/12 |  | Provided at site  |    | Remarks<br>MR/NMR   |  |
|---------|--|----------------|---------|-----------------------------|--|---|----|---------------------|--|
| 1.      | Access of building   |                |         |                             |  |   |    |                     |  |
|         | Road width     Gate width     Width of internal road   |                | 06 mtrs |                             | Control of the contro | ******  |    | MR .                |  |
|         |  |                |         |                             |  | accessible from roa   |    | ad MR               |  |
|         |  |                | NA      |                             | NA   |   | NA | ¥                   |  |
| 2.      | Number, width, Type & Arran  | gements        | of exi  | ts                          |  | •   | 1  |                     |  |
|         | a. Number of staircases  | 04 Nos.        |         |                             | Pro  | Provided  |    | MR                  |  |
|         | Upper floors   | NA             |         |                             | NA   |   |    | X                   |  |
|         | Basements  | IVA            |         |                             |  |   |    | 7.                  |  |
|         | <ul><li>b. Width of staircases</li><li>Upper floors</li></ul>                                    | 1.5m d<br>75cm |         |                             |  | X104cm & 90cm<br>9cm & 105cm  |    | MR (Being old case) |  |
|         | Dominanto  | NA             |         |                             |  | NA N  |    | ١A                  |  |
|         | Basements  Description of exits  | 112.2          |         |                             |  |   |    |                     |  |
|         | c. Protection of exits   | NA: NA         |         |                             |  |   | NA |                     |  |
|         | Fire check door  | 1121           |         |                             | The Control of the Co | NA  |    | NA                  |  |
|         | Pressurization     No of continuous     staircase to terrace     Width Of Corridor     Door Size | NA .           |         |                             |  | 1 No each block   |    | MR                  |  |
|         |  | Required       |         |                             |  |   |    | 1.50                |  |
|         |  | 1.25m          |         |                             | 1.25 to 1.8 m  |   | MR |                     |  |
|         |  | 01 mt          | ı       | Prov                        | ided   | MR  |    |                     |  |
| 3.      | Compartmentation   |                |         | The second                  | NTA  |   |    | NA                  |  |
|         | Fire check door  | NA             | NA .    |                             | NA   |   |    | NACONTROL           |  |
|         | Sealing of electrical shafts     Fire Rating of shaft door                                       | NA             |         | NA                          | NA   |   | NA |                     |  |
|         |  | NA             | NA      |                             | NA   | NA  |    | NA                  |  |
|         | Water Curtain     Fire Dampers   |                | A       |                             | NA   | NA .  |    | NA                  |  |
|         |  |                | 1-40111 |                             | NA   | HILL STATE OF THE |    | NA                  |  |
|         |  | *              |         |                             |  |   |    |                     |  |

1110

| +   | Smoke managements System     Basements   | NA                     |  | NA         |              | N    | IA   |  |
|-----|--|------------------------|--|------------|--------------|------|------|--|
|     | Upper floors   | 12 a/c                 | c per hour   | Natural v  | entilation   | N    | 1R   |  |
|     | Fire Extinguishers   | 0.500.05.0             |  | 1          |              |      | 20   |  |
|     | Total numbers  | ABC & CO <sub>2</sub>  | 30 P   | rovided    | N            | 1R   |      |  |
| - 1 | Types  | date in the second     | every 300sq.m  | 100        | Provided     |      | 1R   |  |
|     | IS marking   |                        | narked   |            | ISI marked   |      | MR   |  |
| j.  | First - Aid Hose Reels   | 1 31/05/99 24 7        |  | 1          |              |      |      |  |
| -   | Total numbers on each  | 01 No. for new b       | lock   | Provided   | ı N          | /IR  |      |  |
|     | floor  |                        | Ç1 110. 101 11 <b>0</b> 11 0   | TOOK       |              |      | 77.7 |  |
|     | The state of the s |                        | 30 mtr Provi   | ded        |              |      | /IR  |  |
|     | Nozzle diameter  |                        | 5 mm   | ILe it es  | 5 mm         | N    | 1R   |  |
| 7.  | Automatic fire detection and al  |                        |  |            | er converse  |      |      |  |
|     | Type of detectors  | NA NA                  | NA   | 13-        | NA.          |      |      |  |
|     | <ul> <li>Location of Main Pane</li> </ul>  | NA                     | 10000000   | NA 1       |              |      |      |  |
|     | Location of Repeater P   | NA                     |  | NA :       |              |      |      |  |
|     | Alternate source of pov  | NA                     |  | NA I       |              | -    |      |  |
|     | Hooters' Location  | NA                     |  | NA 1       |              | -    |      |  |
| 8.  | MOEFA  |                        | NA   | NA NA      | 7770.000.000 |      |      |  |
| 9.  | Public Address System  |                        | NA ·   | NA<br>NA   |              |      | -    |  |
| 10. | Automatic Sprinkler System   |                        | I AVEL   | INA        |              | NA   | -    |  |
|     | Basements  | NA .                   | NA   |            | NA           | +    |      |  |
|     | Upper Floor  |                        | NA   |            | NA NA        |      | +    |  |
|     | Sprinkler above false contains a second con      |                        |  |            |              | -    |      |  |
| 11. | Internal Hydrants:   |                        |  | 1/6/6/5    |              | NA   | _    |  |
|     | <ul> <li>Size of riser/down- cor</li> </ul>  | NA                     | NA NA N  |            | NA           |      |      |  |
|     | <ul> <li>Number of hydrants per</li> </ul>   |                        |  | 7000000000 |              | NA   |      |  |
|     | Hose Box   | NA                     | 1,000,000,000  | NA N       |              |      |      |  |
| 12. | Yard Hydrants  |                        |  | 3.00       |              | 1474 |      |  |
| П   | <ul> <li>Total number of hydra</li> </ul>  | nts                    | NA   | NA         |              | NA   | -    |  |
|     | Hose Box   | NA                     |  |            |              | -    |      |  |
| 13. | Pumping Arrangements:  |                        |  |            |              | NA   | -    |  |
|     | Ground Level   |                        |  |            |              |      | -+   |  |
|     | Discharge of main pur  | np                     | NA   | NA         | NA           |      |      |  |
|     | > Head of main pump  | > Head of main pump    |  |            | NA           |      | +    |  |
|     | Number of main pump  | os                     | NA   |            | NA NA        |      | +    |  |
|     | Jockey pump out put  |                        | NA ·   |            | NA N         |      | _    |  |
|     | Jockey pump head   | NA                     |  | NA N       |              | -    |      |  |
|     | Standby Pump out put   | . NA                   |  | NA N       |              |      |      |  |
|     | Standby Pump Head  | NA                     |  | NA NA      |              |      |      |  |
|     | > Auto Staring/Manual  |                        | NA.  | 1          | NA           |      |      |  |
| 1   | <ul> <li>Pump House Access</li> <li>Terrace level</li> </ul>   |                        | NA   | NA.        | NA I         |      |      |  |
|     | <ul> <li>Discharge of pump</li> </ul>  | 11 1                   | 7  |            | T            |      |      |  |
| 14  | > Head of the pump   | 450 lpm                | MINISTER STATE OF THE PROPERTY |            | MR           |      |      |  |
|     | > Power supply   | 40 mtr                 |  | 40 mtr     |              |      |      |  |
|     | Auto starting of pump  | Required               |  | Provided N |              |      |      |  |
|     | 4. Captive water Storage for fire fighting:  |                        |  |            |              |      |      |  |
| Ė   | Under ground tank ca   | ing:                   | *  |            | 112.200      |      |      |  |
|     | > Draw off connection  | ****                   | N/   |            | NA           |      |      |  |
| 1   | > Fire service inlet   |                        | NA ·   | N/         |              | NA   | -    |  |
|     | > Access to tank   | NA .                   | NA<br>NA   |            | NA           | -    |      |  |
|     | Overhead Tank capacitank   | Overhead Tank capacity |  | Provided   | 1            | NA   | NAD  |  |
| 1.3 | 5 Exit Signage   |                        | 10,000 ltr<br>Required F   | Provided   |              |      | MR   |  |

no de

|     | Requ   | ired P   | rovided  |          | MR   |  |  |
|-----|--|----------|--|----------|------|--|--|
| 15  | Callia Cionago   |          |  |          |      |  |  |
| 16. | Provision of Lifts  Pressurization of Lift Shaft                         | NA.      | NA   | NA NA    |      |  |  |
| 10- | > Pressurization of Lift Share > Pressurization of lift lobby            | NA       | NA   | NA       | 7    |  |  |
|     | > Pressurization of Int loosy<br>> Communication in lift Car             | NA       | NA   | NA NA    |      |  |  |
|     | Fireman's Grounding Switch   | NA       | NA   |          |      |  |  |
| - 1 |  | NA NA    |  | NA       |      |  |  |
|     | > Lift Signage   | NA NA    | 1/1  |          | NA ' |  |  |
|     | Standby power supply   | INA      |  |          |      |  |  |
| 18. | Refuge Area  | NA       | NA   | NA       |      |  |  |
|     | <ul><li>Total area</li><li>Location</li></ul>                            | NA NA    | NA ·   | NA       |      |  |  |
| 19. | Fire control room  |          |  |          |      |  |  |
| 17. | > Detector system panel  | NA       | NA   |          |      |  |  |
| - 1 | > Flow Switch Panel  | NA       | NA   | NA       |      |  |  |
|     | > PA System Panel  | NA       | NA   | NA<br>NA |      |  |  |
|     | > Battery backup > Building Floor Plans                                  | NA       | NA   |          |      |  |  |
|     |  | NA       | NA   | NA L CO  |      |  |  |
| 20. | Special Fire Protection Systems for Protection of special Risks, if any; | Required | CO2 fire extinguisher provided near electric panel |          | MR   |  |  |

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the FSC issued vide letter No.

safety as required under the rules the FSC issued vide letter No. F.6/DFS/MS/School/2020/SZ/538, dated 23/12/2020 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended

Note;- School management has submitted an undertaking stated that the newly constructed rooms at 2<sup>nd</sup> floor has been abandoned.

Signature of the Inspecting Officer
Name Udoy Var Simph

Designation Aboluwy

Q4)16/21

Directer My 2/2/8/

for not do took so settle for self

DRECTOR MA ML

Ta Ta