GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/EH/SZ/2024/63

Dated- 29 .03.2024

FIRE SAFETY CERTIFICATE

Certified that the eating house situated at third floor, Plot No- 07, Block No- 34, Kh. No. 865/767, Pusa Road, WEA, Karol Bagh, New Delhi- 110005, in a building comprised of basement, stilt, ground plus three upper floors but restaurant is running at third floor only, owned/occupied by Resaca (A Unit of Nuanced Hospitality LLP), was inspected by the officer concerned of this department on 23.02.2024 in the presence of Sh. Ashwani Sharma, Liaison Officer and found that the management have complied with the fire prevention and fire safety requirements in accordance with Rule 33 of Delhi Fire Service Rules 2010 and that the building/premises is fit for occupancy class Group-D Restaurant with effect from 2 9.03.2024 for a period upto 31.03.2027 in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010 subject to conditions printed below.

Issued on 29 .09,2024 at New Delhi by.

Delhi Fire Service

Copy to: -

Owner, M/s Resaca (A Unit of Nuanced Hospitality LLP)Plot No- 07, Block No- 34, Pusa Road, Karol Bagh, New Delhi-110005.

Conditions for the validity of Fire Safety Certificate

- All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- The means of escape arrangements shall be kept unlocked & unobstructed for speedy evacuation of occupants in case of an emergency.
- Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 4. The trained staff should be available round the clock.
- Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 6. Basement shall be used as per the building bye laws.
- The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

N/1

INSPECTION REPORT

1. Name & address of the building

: Third Floor, Plot No. 7, Block No- 34, Kh. No.

865/767Pusa Road, Karol Bagh, New Delhi- 110005.

2. Type of Occupancy

: Eating House

3. Building Composition

:Said building is comprised of basement, stilt, ground, plus three upper floors but restaurant is running at 3rd

floor only.

4. Type of Case

: New Case

Details of previous NOC

: F6/DFS/MS/SZ/2024/79, dated 07.02.2024 for whole

building for completion.

6. Fire Safety directives letter No

: F6/DFS/MS/BP/2018/384 dated 5.12.2018 for whole

building.

7. Date of inspection

: 23.02.2024

8. Name of the Inspecting Officers

: Vedpal Chhikara, DO(SW)

9. Name and designation of officers

from the building side

: Sh. Ashwani Sharma, Liaison Officer.

9. Year of Construction

: 2023-24

10. Applicant's letter No.

: Online ID No. 2024021501707 & 2024021301607.

Sr. No.	Minimum Standards on fire prevention and fire safety U/R 33	Requirement as per NBC-IV	Provided at site	Remarks MR/NMR
1	Access to building			
	Road width	06 mts	30m Provided	MR
	Gate width	05 mts	Provided	MR
	Width of internal road	N/A	N/A	N/A
2	Number, Width, Type & Arrangemen	t of Exits		
	a. Number of staircases		-	·
	Upper Floors	02 Nos.	02 Nos.	MR
	Basements	02 Nos.	02 Nos.	MR
	b. Width of staircases			
	Upper Floors	2m &1.5 mts	2m & 1.5 m	ts. MR
	Basements	2m2 1.5 mts №0	1.5 & 1.5 mi	ts. MR
	c. Protection of exits		~	
	Fire check door	Required	Provided	MR
	Pressurization	N/A	N/A	N/A
	e. No. of continuous staircases to terrace	02	02	MR
	g. Width of Corridor	N/A	N/A	N/A
	h. Door Size	2m & 1.50 mts	2m & 1.50 m	nts MR

h

_	A ***	170		
3	Compartmentation.			1
(d	Fire check door	Required	Provided	1
	Sealing of electrical shafts	Required	Not Provided	M
	Fire Rating of shaft door	N/A	N/A	- NV
	Water Curtain	N/A	N/A	-N
	Fire Dampers	N/A	N/A	N N
4	Smoke Management System.		Fraggings.	N
	Basements	30 a/c per hour	Provided	
	Upper floors	12 a/c per hour	Natural Ventilation	n N
5	Fire Extinguishers	1750ma Ris 134 ∎ sales reseguence	1 Turburus 1 January	n N
	Total numbers	04	Provided	MF
	 Types 	ABC & CO ₂ type	ABC & CO ₂ type	MF
	IS marking	ISI marked	Provided	MF
6	First-Aid Hose Reels.		-	
	Total numbers on each floor	01 no.	01 Nos. Provided	MR
	Length of hose reel hose	30 mts.	Provided	MR
	Nozzle diameter	5 mm	Provided	MR
7	Automatic fire detection and alarming	g system.		
	Type of detectors	Smoke/heat	Provided	MR
	Location of Main Panel	Required	Provided	MR
	Location of Repeater Panel	N/A	N/A	N/A
	Alternate source of power	Required	Provided	MR
	Hooters' Location	Entire building	Provided	MR
3	MOEFA	Required	Provided	MR
)	Public Address System.	N/A	N/A	N/A
0	Automatic Sprinkler System.			
	Basement	Required	Provided	MR
	Upper Floor / Ground Floor	N/A	Provided	N/A
	Sprinkler above false ceiling	N/A	N/A	N/A
1	Internal Hydrants			
	Size of riser/down-comer	100 mm	Provided	MR
1	Number of hydrants per floor	01	0	MR
1	Hose Box	01	01	MR
2	Yard Hydrants.			
	Y			>1/A
	Total number of hydrants	N/A	N/A	N/A
-)	Hose Box	N/A	N/A	N/A

-	Ground Level Discharge of main P				
ŀ	Discharge of main Pump	2280 LPM	Provided	MR	
}	> Head of Main pump	70 mts	Provided	MR	
1	Number of main pumps	01 No.	Provided	MR	
}	> Jockey Pump out put	180 LPM	Provided	MR	
	Jockey pump head	40 mts	Provided	MR	
	Standby Pump out put	2280 LPM	Provided	MR	
	Standby Pump Head	70 mts	Provided	MR	
	Auto Starting/ Manual stopping	g Required	Provided	MR	
	➤ Pump House Access	Required	Provided	MR	
	Terrace level		********		
	➢ Discharge of pump	N/A	900LPM	N/A	
	► Head of the pump	N/A	40m	N/A	
	➤ Power Supply	N/A	Provided	N/A	
	➤ Auto Starting of pump	N/A	Provided	N/A	
l	Captive Water Storage for fire fighting. (Fire fighting system is common for whole building)				
	Underground tank capacity	2,00,000	Provided	MR	
	> Draw-off connection	Required	Provided	MR	
	➤ Fire service inlet	Required	Provided	MR	
	> Access to tank	Required	Provided	MR	
N	Overhead Tank capacity	30,000 lts	30,000 lts	MR	
5	Exit Signage.	Required	Provided	MR	
5	Provision of Lifts.		. h		
	Pressurization of Lift Shaft	N/A	N/A	N/A	
	Pressurization of Lift lobby	N/A	N/A	N/A	
	Communication In lift Car	Required	Provided		
	Fireman's Grounding Switch	Required	red Provided		
	Lift Signage	Required	quired Provided		
7	Standby power supply	Required	Provided	MR	
3	Refuge Area.				
	> Total Area	N/A	N/A	N/A	
	> Location	N/A	N/A	N/A	
i y	Location	N/A	N/A	N/A	

36	ı	
	и	~
1	,	~

19	Fire Control Room			
	Detector System Panel	N/A	N/A	
	Flow Switch Panel	N/A	N/A	
	PA System Panel	N/A	N/A	
	Batter backup	N/A	N/A	
	Building Floor Plans	N/A	N/A	
20	Special Fire Protection Systems for Protection of special Risks, if any:	Required	Fire Extinguishers are provided near electric panel.	

The Electric meters are installed in stilt floor away from escape routes.

The fire protection systems provided in the building were test checked randomly and found functional at the time of inspection. In view of the above substantial compliance of the minimum standards on fire prevention and fire safety measures as required under the Rules, it is recommended to grant Fire Safety Certificate under Rule 35 of Delhi Fire Service Act - 2007 & Rules 2010.

Accordingly, DFA is put up for approval & signature please.

Signature of the Inspecting Officer

Name- Vedpal Chhikara

Divisional Officer (SW)

Clarify point no 26 basement.

1thus
27/24/2011

Dolan Sie necessay correction has been made. Regret for mistake. Resulmitted following 27/1/14