FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No.F6/DFS/MS/SZ/2024/EH 62

Dated: 29/02/2024

FIRE SAFETY CERTIFICATE

Certified that the building Foodlink, F and B Holdings India Pvt. Ltd. Located at 2nd Floor ECC, Sector-25, Dwarka, Delhi, in a building comprised of 4 tier Basement + Ground + 08 Upper Floors, (Fire Safety Certificate issued to the ECC vide letter No. F6/DFS/MS/SZ/2023/428 dated 06/09/2023) owned/ occupied by Foodlink F and B Holdings India Pvt. Ltd have complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rule, 2010 and verified by the officers concerned from this department on 20/02/2024 in the presence of Sh. Rakesh Awaste (Foodlink Representative) and found that the said premises is fit for occupancy class "Assembly" Group D (Second Floor) with effect from 29 02 224 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on .29 22. 2.4. at New Delhi by.

Delhi Fire Service

Copy to:

1. The Joint Commissioner Police, Licensing, 1st Floor, PS, Defence Colony, N Delhi.

2. The Manager, Foodlink F and B Holdings India Pvt. Ltd. at 2nd Floor Exhibition Cum Convention Centre (ECC) located at, Sector-25, Dwarka, Delhi.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction,
- Basement shall be used as per building bye laws.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 8. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.

11/2

INSPECTION REPORT

1. Name & address of the building: Foodlink, F and B Holdings India Pvt. Ltd. Located at 2nd Floor, ECC, Sector-25, Dwarka, Delhi.

2. Type of Occupancy : Assembly at 2nd Floor (At ECC building comprised of 2B+G+8 UFs)

3. Type of Case

: Nil (F6/DFS/MS/SZ/2023/428, dated 4. Details of previous NOC 06/09/2023, Issued to ECC building) (Whole building)

5. Fire Safety directives L. No.: F6/DFS/MS/BP/2018/194, dated 18/06/2018

6. Date of inspection

: 20/02/2024

7. Name of the Inspecting Officer: DO/SW &ADO (DWK)

8. Name and designation of Officer

from the building side :Sh. Rakesh Awaste (Foodlink Representative)

9. Year of Construction

: 2019 to 2023

10. Applicant's letter No. : 2024012000661 dated 07/02/2024

S No	Minimum standards on fire prevention and fire safety U	As per l Require	NBC/UBBI ments	Provide site		Remarks MR/NMR			
1.	Access of building								
	Road width	12 mtr	Provide			MR			
	Gate width	6 mtr	ntr Provided MR						
	Width of internal ro	ad 9	m	Provided		MR			
2.	Number, width, Type & Ar	mber, width, Type & Arrangements of exits							
4=	a. Number of staircases ,	glén							
	Upper floors	2 Nos	3.		Provided		MR		
	Basements	NA			Provided		NA .		
	b. Width of staircases								
	Upper floors	2 mtr		Provided			MR		
B-	Basements	NA		Provided .			NA		
	c. Protection of exits	1							
	Fire check door	Requ	ired Pr	ovided			MR		
	Pressurization	Required Provided					MR		
	d. No of continuous staircase to terrace	Requ	ired Pr	ovided			MR		
	e. Width Of Corridor	2 mtr	Pr	ovided			MR		
	f. Door Size	2x2 n	ntr Pr	ovided		MR	3,445		
3.	Compartmentation		rtx Au	orided		IVIK			
	Fire check door		Re	quired	Provided		MR		
	Sealing of electrical shafts			quired	Provided		MR		
	Fire Rating of shaft door		02	hrs rating	Provide	Provided			
	Water Curtain			quired	Provide	55/	MR ·		
	Fire Dampers			quired Provided		20	MR		



						T				
4.	Smoke managements System	1	2 -1 -1		TXT	riniga.			7	
	Basements	NA		Pro	vided		h 1 HH	1	NA	
	Upper floors	Requi	ired			Provided		MR	37.5	
5.	Fire Extinguishers	•	-00							
	Total numbers	As pe	r IS 219	90/19	92	Provided		MR	MR	
	Types		& ABC			CO ₂ & ABC		MR	204420	
	IS marking	ISI m				Provided		MR		
5.	First - Aid Hose Reels		nmon with EC					1,111	-	
	Total numbers on each floor	Required Provide					MF	2		
ž	Length of hose reel hose	30 m		30	30 m		MR	MR		
	 Nozzle diameter 	5 mm		¥X	5 1	mm		MR		
7	Automatic fire detection and			em				IVIIC		
	Type of detectors		Smok		Teat		Provided	MR	-	
	Location of Main Pa	nel								
	Location of Repeater		Ground floor		330 230	-2,700 (10 to 10 t		MR		
	Panel Panel			All floors Provi					MR	
	Alternate source of power			Required		Provided		MR		
3.	Hooters' Location		Appropriate p		e place	s N	ear staircase	es	MR	
) <u>. </u>	MOEFA			Required		Provided		MR	MR	
0.	Public Address System		Required Prov		ovide	ided		MR		
U.	Automatic Sprinkler System							•		
	Basements				Provi	rovided		N/	NA	
	Upper Floor				Provi	rovided		M	MR	
	Sprinkler above false ceiling		Requi	7	Provi	Provided			MR	
1.	Internal Hydrants (Comm	on with	ECC)					F	
	 Size of riser/down-comer 		150 mm		115	150 mm		MR		
	Number of hydrants per floor					Provided		IVIK	M	
	Hose Box		Required I		· D	Provided		1.0		
2.	Yard Hydrants	, required Flovide			<u>a</u>	MR				
	Total number of hydrants		13 Nos.		-	D		1.00		
	Hose Box		Required		_	Provided		MR		
3.	Pumping Arrangements (Common		with ECC				Provided	MR		
	Ground Level	шшон	WILLI	cc)						
	Discharge of main p	ume	2050	1	02		2050			
	➤ Head of main pump		2850 lpm(03 85 m		OJ NOS	_	2850 lpm	MR ·		
	➤ Number of main pumps		2 Nos			85 m		MR		
	> Jockey pump out put				137	2 Nos		MR		
	> Jockey pump head		280 lpm (4 N		Nos.)		30 lpm (4 N	os.)	MR	
	Standby Pump out put		85 m		0) :	85 m		MR	MR	
	Standby Pump Head		2850 lpm(2Nos		2Nos)			MR	MR .	
	➤ Auto Staring/Manua	1	85 m			Provided		MR ·		
	stopping		Required		1-1	Provided M				
		Pump House Access		ired			Drovid. 1	-		
							Provided	MR		
	 Pump House Access Terrace level 				N/A				I Sec.	
	 Pump House Access Terrace level Discharge of pump 		N/A	TLX:			N1/4			
	 Pump House Access Terrace level Discharge of pump 		N/A N/A	in al		1	N/A	N/A		
	 Pump House Access Terrace level 		N/A N/A N/A				N/A N/A N/A	N/A N/A	Α	

		14		1	ì					
14.	Captive water Storage for fire fighting (Common with ECC))									
	Under ground tank capacity	800,000 litre	Provided	d						
	Draw of connection	Required	Pro	vided	MR					
	➤ Fire service inlet ·	Required Required		Pro	Provided Provided					
	➤ Access to tank.			Pro						
	 Overhead Tank capacity 	20,000 ltr	Pro	Provided Provided						
15	Exit Signage	Required	Pro	Provided						
16.	Provision of Lifts									
	Pressurization of Lift Shaft	Required		Provided		MR				
	 Pressurization of lift lobby 	Required	Pro	Provided		MR				
	> Communication in lift Car	Required	Pro	Provided		MR				
b	➤ Fireman's Grounding Switch	Required	Pro	Provided		MR				
	➤ Lift Signage	Required	Pro	Provided						
17.	Standby power supply	Required Provided		1		MR				
18.	Refuge Area			71. No est	24/74 IV	5				
	> Total area	N/A	N/A	N/A		N/A				
	> Location	N/A	N/A	N/A		N/A				
19.	Fire control room (Common with ECC)									
	> Detector system panel	Required	Required		MR	MR				
	➤ Flow Switch Panel	Required		Provided		MR				
	▶ PA System Panel	Required		Provided		MR				
	> Battery backup	Required		Provided MR						
	➤ Building Floor Plans	Required		Provided MR						
20.	Special Fire Protection Systems for Protection of special Risks, if any;					MR				

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under Rule 35 of the Delhi Fire Service Rules 2010.

- Foodlink, F and B Holdings India Pvt. Ltd. Located at 2nd Floor ECC, Sector-25, Dwarka, Delhi..
- 2. As per letter/ plan submitted by the applicant the area of the restaurant is 538 m^2
- 3. As per part IV, NBC-2016, table no 4.3 under clause 4.4.2.1 the occupant load for dining area and restaurant is 1.8. Accordingly the number of seats come out to be 299 (538/1.8=299) for whole restaurant.

4. The thtal seating capacity comes out be 299.

Signature of the Inspecting Officer

Name: Sh. Vedpal Designation: DO/SW Signature of the Inspecting Officer

Name: Udai Vir Singh Designation: ADO/DWK

down 2m fcc 31 +418