



GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F.6/DFS/MS/CNG/SZ/2024/ /45

Dated: 08 / 63 /2024

FIRE SAFETY CERTIFICATE

Certified that M/s Indraprastha Gas Limited Retail Outlet (CNG Pump) located at San Martin, Chanakyapuri, New Delhi, comprised of ground floor only was issued Fire Safety Certificate by this department vide letter No. F.6/DFS/MS/2021/CNG/231 dated 22/04/2021. The premises was re-inspected by the officer concerned of this department on 02/03/2024 in the presence of Sh. Rahul Kirar (Dy. Manager–F&S) and observed that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/premises is fit for occupancy class Hazardous (CNG Pump) with effect from ____OS_02/2024 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 of Delhi Fire Service Rules, 2010 and subject to compliance of the conditions mentioned below.

Issued on 08/03/2024 at New Delhi by

(AFULCARG)
DIRECTOR
DELHI FIRE SERVICE

Copy to: -

- Sh. Ajay Khatri, General Manager (Fire & Safety), IGL Bhawan, Plot No. 4, Community Centre, R.K. Puram, Sector-9, New Delhi-110022
- 2. The Addl. Comm. of Police (Lic.), First floor, P.S. Defence Colony, New Delhi-110049

Conditions for the validity of Fire Safety Certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of firefighting system.
- The owner/occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

1	Name & Address of the Building	TION REPOR				
2		M/S Indraprastha Gas Ltd. Retail Outlet (CNO Pump), San Martin, Chanakyapuri, New Delh				
3	Type of Occupancy	Hazardous (CNG Pump)				
	Building Comprised of	Ground floor only (02 Cascades at roof of office bldg. 01 Compressor units & 05nos dispensing units)				
4	Type of Case	Renewal				
5	Details of Previous NOC		/2021/CNG/231 dat	ed 22/04/202		
6	Fire Safety Directives Letter No	F.6/DFS/MS/2021/CNG/231 dated 22/04/202 F.5/DFS/3A/2000/BP/103 dated 23/03/2000				
7	Date of Inspection	02/03/2024				
8	Name of the Inspecting Officers	Santosh Kumar, ADO (SJ)				
9	Name & Designation of Officers from the building side	Sh. Rahul Kirar (Dy. Manager-F&S)				
10	Year of construction	2000				
11	Applicant letter No.	Outdoor Diary No. 13125 dated 14/02/2024				
S. No.	Minimum standards on Fire Prevention and Fire Safety U/R 33	Requirements/ Existing Fire Protection System Requirements/ Existing Fire Protection System				
1	Access to Building.					
	Road width	9m	12m	MR		
	Gate width	NA	NA	NA		
	Width of internal road	NA	NA	NA		
2	Number, width, type & arrangeme	ent of exits.		+		
	a) Number of Staircase					
	> Upper floors.	Required	01	MR		
	➤ Basement.	NA	NA	NA		
	b) Width of Staircase					
	> Upper floors	Required	0.67m	MR		
	➢ Basement	NA	NA	NA		
	c) Protection of exits		2895.2			
	> Fire check door	NA	NA	NA		
	> Pressurization	NA	NA	NA		
	d) No. of continuous staircase to terrace	NA	NA	NA		
	e) Width of corridor	NA	NA	NA		
	f) Door size	1m	1m	MR		
3	Compartmentation.					
100	Fire check door.	NA	NA	NA		
	Sealing of electrical shafts.	NA	NA	NA		
	Fire rating of shaft door.	NA	NA	NA		
	Water curtain	NA	NA	NA		
	Fire dampers.	NA	NA	NA		
4.	Smoke Management system.					
	Basement	NA	NA	NA		
	Upper floors	NA	NA	NA		
5.	Fire Extinguishers.	1,77	*11.2			
3.	State (1974) - And Control of the Control of the Anti-	20000	22nos	MR		
	Total numbersTypes	20nos CO ₂ & DCP	CO ₂ (4.5kg)-04 & Do (75kg)-3, DCP (10kg)	CP MR		
	ISI Marking	ISI marked	Provided	MR		
6.	First Aid Hose Reels.		2,000,000,000,000			
	Total numbers on each floor.	NA	NA	NA		
	Length of hose-reel hose.	NA	NA	NA		
- 0	• Length of hose-real hose					



7.	Automatic fire detection & alarming sy Type of detectors	Gas & Flame	Provided in compressors & portable gas detector	MR
	Location of Main Panel	NA	with staff NA	NA
	Location of Repeater Panel	NA NA	NA NA NA Technician room NA	NA NA MR NA
	Alternate source of power	NA NA		
	Hooter's location	Required		
		NA		
8.	MOEFA	NA NA	NA	NA
9.	Public Address System	INA		
10.	Automatic Sprinkler System	274	NA	NA
	Basement	NA NA	NA NA	NA
	Ground floor.	NA	NA NA	NA
	 Sprinkler above false ceiling 	NA	INA	
11.	Internal Hydrants.			NA
	Size of Riser/Down-comer	NA	NA	
	Number of Hydrant per floor	NA	NA	NA
	Hose box.	NA	NA	NA
12.	Yard Hydrants.		السيدية	U
14.	Total number of hydrants.	NA	NA	NA
	Hose box.	NA	NA	NA
	5.903 INTO TATO CONTRACT AND CO	Calumati		
13.	Pumping arrangements.			18
	Ground Level Discharge of main pump.	NA	NA	NA
	And the state of t	NA	NA	NA
		NA	NA	NA
	Number of main pumps.Jockey Pump output.	NA	NA	NA
	> Jockey Pump head.	NA	NA	NA
	Standby Pump output.	NA	NA	NA
	> Standby Pump head.	NA	NA	NA
	> Auto Starting/Manual Stopping.	NA	NA	NA
	Pump house access.	NA	NA	NA
	Terrace Level			1
	> Discharge of pump.	NA	NA	NA
	> Head of pump.	NA	NA	NA
	> Power supply.	NA	NA	NΑ
	> Auto starting of pump.	NA	NA	NΑ
1407	740 SEE 40 CONTRACTOR - CONTRAC		1 1 1	12 (1752)
14.	Captive water storage for Fire Fighting Underground tank capacity.	NA	NA	NA
	 Underground tank capacity. Draw-off connection. 	NA	NA	NA
	Fire Service Inlet.	NA	NA	NA
	> Access to tank.	NA	NA	NA
	Overhead tank capacity.	NA	NA	ΝA
15.	No Smoking Signage (Hindi & English)	Required	Provided	MR
16.	Provision of Lifts.			1
10.	Pressurization of lift shaft.	NA	NA	NA
	Pressurization of lift lobby.	NA	NA	NA
	Communication in lift car.	NA	NA	NA
	Fireman's switch.	NA	NA	NA
	 Lift signage. 	NA	NA	NA
17.	Standby Power Supply	NA	Provided	NA
18.	Refuge Area			
	Total area	NA	NA	NA
	 Location 	NA	NA	NA

W.

19.	Fire Control Room.			
	Detector system panel.	NA	NA	NA
	 Flow switch panel. 	NA	NA	NA
	PA system panel.	NA	NA	NA
	Battery backup.	NA	NA	NA
	Building floor plan.	NA	NA	NA
20.	Special Fire Protection System for the Protection of special Risk, if any.	NA	Provided CO ₂ flooding system connected through detectors in each compressor	NA

The fire protection systems provided in the building/premises were checked, tested at random and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter No. F.6/DFS/MS/2021/CNG/231 dated 22/04/2021, renewal under rule 37 of the Delhi Fire Service Rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name: Santosh Kumar Designation: ADO (SJ)