



GOVERNMENT OF NATIONAL CAPITAL TERRITOTY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE **NEW DELHI- 110001**

F.6/DFS/MS/CNG/2024/SZ/ [68 No.

Dated: 1.4./.03/2024

FIRE SAFETY CERTIFICATE

Certified that CNG Dispensing Station located at Pushpa Bhawan, New Delhi comprised of Single story building owned/occupied by M/s Indraprastha Gas Limited, was issued FSC by this department vide letter no. F6/MS/DFS/CNG/2021/SZ/242 Dated 28/04/2021. The premise was re-inspected by the officer concerned of this department on 06/03/2024 in the presence of Mr. Sunchit Sehrawat of the said filling station and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Hazardous (CNG Pump) with effect from 14/03/2024 for a period of three years in accordance with rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject/ to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010

Issued on 14 / 63 / 2024 at New Delhi by

ELHI FIRE SERV

Copy to: -

1. The Joint C.P (Lic.) First Floor, PS Defence Colony, New Delhi 110049.

2. Sh. Ajay Khatri, DGM-(Fire & Safety) (IGL) LGL Bhawan, Plot No 4, Community Centre, R. K Puram, Sector- 09, New Delhi 110049

Conditions for the validity of Fire Safety Certificate: -

1. All the means of escape/entry/exit shall be kept free from any obstruction.

2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the

3. All the staff members must know the correct method of operation of fire fighting

4. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on

5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of

6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.



		ION REPORT	Automotic from Thirteenia			
1	Name & Address of the Building	CNG Dispensing station, Pushpa Bhawan, New Delhi				
2	Type of Occupancy	Hazardous "Group –J (CNG Pump)				
3	Building Comprised of	Ground floor only				
4	Type of Case	Renewal ASTINIA A				
5	Details of Previous NOC	F6/MS/DFS/CNG/2021/SZ/242 Dated 28/04/2021				
6	Fire Safety Directives Letter No	Nil				
7	Date of Inspection	06-03-2024				
8	Name of the Inspecting Officers	Mr. Rajesh Kumar (ADO BCP)				
9	Name & Designation of Officers from the building side	Mr. Sunchit Sehrawat				
10	Year of construction	2002 sammered lamental 1 111 1				
11	Applicant letter No.	IGL/F&S/2024/	15/69/1 Dated 19-02-2024			
. No	Minimum standards on Fire Prevention and Fire Safety U/R 33	Old NOC Requirement	Provided at Site	Remarks MR/NMF		
1	Access to Building.					
	Road width	09 mtr	Provided	MR		
2-	Gate width Width of internal mod	-NA-	-NA-	-NA-		
2	Width of internal road Number, width, type and arrangements		-INA-	-11/4-		
-	a. Number of Staircase	or cans.	Managara digital	- 11		
	AND THE STATE OF T	-NA-	-NA-	-NA-		
}	Upper floors Basement floor	-NA-	-NA-	-NA-		
-	b. Width of Staircase	HVA	in malificialism.	-1474		
Н		NA NA	-NA-	-NA-		
-	Upper floors Resement floor	-NA-	-NA-	-NA-		
- #	• Baschielli 11001	-NA-	-NA-	-NA-		
	c. Protection of exits		I was bland a			
	Fire check door	-NA-	-NA-	-NA-		
	Pressurization	-NA-	-NA-	-NA-		
	d. No. of continuous staircase to terrace	-NA-	-NA-	-NA-		
	e. Width of corridor	-NA-	-NA-	-NA-		
1	f. Door size	-NA-	-NA-	-NA-		
3	Compartmentation.	Stronders y	ma instrumental +			
-	Fire check door.	-NA-	-NA-	-NA-		
	Sealing of electrical shafts.	-NA-	-NA-	-NA-		
	Fire rating of shaft door.	-NA-	-NA-	-NA-		
	Water curtain	-NA-	-NA-	-NA-		
	Fire dampers.	-NA-	-NA-	-NA-		
1.	Smoke Management system.	-	20 De galacier I	.01		
	Basement	-NA-	-NA-	-NA-		
	Upper floors	-NA-	-NA-	-NA-		
. I	Fire Extinguishers.		In the second of			
	Total numbers	Required	24 Nos	MR		
	• Types	ISI Marked	DCP/75 kg- 4, DCP/10kg - 15 & CO ₂ - 05	MR		
	ISI Marking		Provided	MR		
. F	First Aid Hose Reels.		Gover Appro	le le		
-	 Total numbers on each floor. 	-NA-	-NA-	-NA-		
- -	Length of hose-reel hose.	-NA ₅	-NA-	-NA-		
	Nozzle Diameter	-NA-	-NA-	-NA-		

7	Automatic Fire Detection and Alarming system.				
		554			
	Type of detectors	Gas & Flame	Provided in compressors	M	
	 Location of Main Panel 	Required	Ground floor	M	
	 Location of Repeater Panel 	-NA-	-NA-	-N	
	Alternate source of power	Required	Provided	M	
	Hooter's location	Required	Technician room	M	
8.	MOEFA	-NA-	-NA-	-N	
9.	Public Address System	-NA-	-NA-	-NA	
10.	Automatic Sprinkler System	and Fag			
	Basement	-NA-	-NA-	-NA	
	Upper floors	S(S) 11		1,500	
	Sprinkler above false ceiling	-NA-	-NA-	-NA	
	opinion doors mad doning	-NA-	-NA-marra	-NA	
11.	Internal Hydrants.		Language and A	101	
	Size of Riser / Down-comer	-NA-	-NA-	-NA	
	Number of Hydrant per floor	-NA-	u this be -NA- mumbe	-NA	
RIVIES.	Hose box.	-NA-	-NA-	-NA	
12.	Yard Hydrants.		otlow duo?		
-71	Total number of hydrants.	-NA-	-NA-	-NA	
	Hose box.	-NA-	-NA-	-NA-	
13,	Pumping arrangements.	composite Steen by		TVA	
	Ground Level				
		NTA	Codd rough) b		
	Discharge of main pump.	-NA-	-NA-	-NA-	
	> Head of main pump.	-NA-	-NA-	-NA-	
	Number of main pumps.	-NA-	-NA-	-NA-	
	 Jockey Pump output. Jockey Pump head. 	-NA-	ADDII -NA- =	-NA-	
1000	> Standby Pump nead.	-NA-	s of top -NA- a	-NA-	
	> Standby Pump head.	-NA-	-NA-	-NA-	
	> Auto Starting/Manual Stopping.	-NA-	-NA-	-NA-	
	To Provide the Constant	-11/1-	marinstragesri •	-NA-	
		NA		NIA	
WALL.	Discharge of pump. Head of pump.	-NA-	-NA-	-NA-	
	Head of pump.Power supply.	-NA-	-NA-	-NA-	
-X X	> Auto starting of pump.	-NA-	-NA-	-NA-	
14.	Captive water storage for fire-fighting.	-IVA-	-NA-	-NA-	
	Underground tank capacity.	-NA-	.norst-NA-uguai)	-NA-	
	> Draw-off connection.	-NA-	-NA-	-NA-	
4 %	> Fire Service Inlet.	-NA-	965 4.9 -NA-	-NA-	
	> Access to tank.	-NA-	-NA-	-NA-	
14.15	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	-NA-	-NA-	-NA-	
15.	Overhead tank capacity. No Smoking signage	Required	Provided in Hindi &	MR	
16.	Provision of Lifts.	The first	English		
	Pressurization of lift shaft.	-NA-	-NA-	-NA-	
	Pressurization of lift lobby.	-NA-	-NA-	-NA-	
	Communication in lift car.	-NA-	-NA-	-NA-	
-il×	Fireman's switch.	-NA-	indio -NA- 4	-NA-	
-16	The second state of the second	-NA-	-NA-	-NA-	
17	Lift signage. Standby Power Supply	-NA- NA	Provided (DG Set)	-NA-	
		, MA	Torida (DO Set)	NA.	
18.	Refuge Area		erenant i		
	Total area	-NA-	-NA-	-NA-	
	Location	-NA-	-NA-	-NA-	

NIIG

आज़ादी मा अमृत महोत्सद

19.	Fire Control Room.					
	Detector System Panel.	-NA-	-NA-	-NA-		
	 Flow Switch Panel. PA system Panel. Battery backup Building floor plan 	-NA-	-NA-	-NA-		
		-NA-	-NA-	-NA-		
		-NA-	-NA-	-NA-		
		-NA-	-NA-	-NA-		
20.	Special Fire Protection System for the Protection of special Risk, if any.	NA	Co2 flooding system connected through detectors provided in each compressor unit	MR		

"No Smoking" Sign boards were found displayed both in Hindi & English at conspicuous places. No loose electric wiring was seen in the premises.

The fire protection systems provided in the building were test checked at random and found functional at the time of inspection. In view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under rules, renewal of the FSC issued vide letter No F6/MS/DFS/CNG/2021/SZ/242 Dated 28/04/2021, under rules 37 of the Delhi Fire Service Rules 2010 is recommended.

Accordingly, DFA is put up for perusal and signature please.

Signature of the Inspecting Officer Name: Mr. Rajesh Kumar

Designation: ADO (BCP)

DO (SD)

Myry

11 31 Sory

Director

Any pol n

ou smaker of tetter is pritup

you synature of

1119