GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/NDZ/2024/ | \$ 3

Dated 20,03,2024

FIRE SAFETY CERTIFICATE

Certified that the Videsh Sanchar Bhawan located at Bangla Sahib Road, New Delhi comprised of Basement + Ground + 7 Upper floors owned/occupied by Videsh Sanchar Bhawan was earlier granted FSC by this department vide letter No.F6/DFS/MS/NDZ/2021/375 dated 04/08/21. Now, the premises was re-inspected by the officers concerned of this department on 11.03.24 in the presence of Sh. Rajeev Kumar and found that the said building has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Business, Sub Division-E with effect from . 20.03. 2024..... for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued. 20 03 2024 at New Delhi by.

Copy to: -

1. The Chief Architect, NDMC, Palika Kendra, New Delhi.

2. The General Manager, Videsh Sanchar Bhawan, Bangla Sahib Road, New Delhi.

Conditions for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

- 4. The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 9. The flammable material use for interior decoration, if any, shall strictly be prohibited.

NI

INSPECTION REPORT

1. Name & address of the building : Videsh Sanchar Bhawan, Bangla Sahib Road,

New Delhi.

2. Type of occupancy : Business Building

(B + Gr. + 07 Upper floors)

3. Type of case:- : Renewal 12 point

4. Details of previous FSC : F6/DFS/MS/NDZ/2021/375 dated 04/08/21.

5. Fire safety directives No. : NA6. Date of inspection: 11/03/24

7. Name of the inspecting officer : Sh. Ravinder Singh ADO/CC Sh. Rajinder Atwal, DO (CD)

Name & designation of officer From the building side

: Sh. Rajeev Kumar

9. Year of construction : 1976

10. Applicant's letter No :e-mail < sunil.jha@contractor.tatacommunication.com>

dated 19/02/2024.

			Old	Case
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing fire safety arrangements	Provided at site	Remarks MR/NMF
1.	Approach to Building			
	1) Road width	06 mtr.	06 mtr.	MR
	2) Gate width	05 mtr.	05 mtr.	MR
	3)Width of internal road	N/A	06 mtr.(two side)	N/A
	Number, Width Type & Arra	angement of Exit	ts	
	A. Number of staircases			
	1. Upper floors	02 No.	02 No.	MR
	2. Basements	02 No	02 No.& 01 Ramp	MR
	B. Width of staircase			
	1. Upper floors	1.25 & 0.80 mtr.	1.35 & C	MR
	2. Basements	1.25 mtr.	1.35 & 1.15 mtr. 01 ramp 3.5 mtr.	MR
	C. Protection of exits	T V M - T T		
	Fire check door (fire escape)	Required	Provided	MR
	2. Pressurization	N/A	N/A	N/A
	D. No. of continuous staircase to terrace	01 No	01 No	MR
	E. Width of corridor	N/A	N/A	N/A
	F. Door size	1 Mtr.	1 Mtr.	MR
3 4	Compartmentation			IVIIC
	1) Fire check door	Required	Provided	MR
	2) Sealing of electrical shafts	Required	Provided	MR
	3) Fire rating of shaft door	Required	Provided	MR
	4) Water curtain	N/A	N/A	N/A
) Fire Dampers	N/A	N/A	N/A
1	Smoke Management System			IVA
) Basements	12 ACPH	Provided/ exhaust fan	MR
1	Upper floors	12 ACPH	Provided	MD
1	Fire Extinguishers		- To Flacu	MR
) Total numbers	54 Nos.	60 Nos.	MR

N/55

11 411

	2) Types	ABC & CO2	ABC, CO2 & W.CO2	MR		
	3) ISI marking	Required	Provided	MR		
6.	First-Aid Hose Reel		013/5	100		
	1)Total number of each floor	01 No.	01 No. /	MR		
	2) Length of hose reel hose	30 m	30 m	MR		
	3) Nozzle diameter	5 mm	5 mm	MR		
7.	Automatic Fire Detection & Alarming System					
	1) Type of detectors	Required	Provided	MR		
	2) Location of main panel	Gr. Floor	Provided	MR		
	3) Location of repeater panel	Required	Provided 4th floor	MR		
	4) Alternate source of power	Required	Provided	MR		
	5) Hooter's Location	Required	Provided Every / floor Near S/case	MR		
8.	MOEFA	Required	Provided	MR		
9.	Public Address System	Required	Provided	MR		
10.	Automatic Sprinkler System			MR		
	1) Basement	Required	Provided	N/A		
	2) Upper floors	N/A	Provided	NA NA		
	Sprinkler above false ceiling	NA	NA	INA		
11.	Internal Hydrants			100		
11.	1) Size of riser/down-comer	150 MM	150 MM	MR		
	2) Number of hydrants per	01	01	MR		
	floor	01	01	MR		
	3) Hose box each floor Yard Hydrants					
12.	1) Total number of hydrants	04	04	MR		
	2) Hose box	04	04	MR		
1	Pumping Arrangement					
13.	1) Ground level					
	a) Discharge of main	2850 LPM '-	2850 LPM	MR		
	b) Head of main pump	80 mtr.	80 mtr.	MR		
	c) Number of main	01	01	MR		
	d) Jockey pump out put	220 LPM (220 LPM	MR		
	(2 Nos.)	80 mtr.	80 mtr. (MIR		
	e) Jockey pump head f) Stand by pump	2800 LPM .	2800 LPM	MR		
	output hand	80 mtr.	80 mtr.	MIR		
	g) Stand by pump head		Provided	MR		
	h) Auto starting/Manual stopping	Required	Tiovided	IMIX		
	2) Terrace level	SVET	-			
	a) Discharge of pump	N/A	N/A	NA		
	b) Head of pump	N/A	N/A	N/A		
	c) Power supply	N/A	N/A	NA		
	d) Auto starting of pump	N/A	N/A	N/A		

14.	Captive Water Storage for Fi	re Fighting		
	1) Under ground tank capacity	1,00,000 ltr.	1,00,000 ltr.	MR
	a) Draw-off connection	Required	Provided	MR
	 b) Fire service inlet 	Required	Provided	MR
	c) Access to tank	Required	Provided	MR
	d) Over head tank capacity	20,000 Ltrs.	20,000 Ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.	1/1/2	1 7 7 7 7	
and the	 a) Pressurization of lift shaft 	N/A	N/A	N/A
	 b) Pressurization of lift lobby 	N/A	N/A	N/A
	 c) Communication in lift car 	Required	Provided	MR
	d) Fireman's switch	Required	Provided	MR
	e) Lift signage	Required	Provided	MR
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	Required	Provided	MR
	a) Detector system panel	Required	Provided	MR
	b) Flow switch panel	Required	Provided	MR
	c) PA system panel	Required	Provided	MR
	d) Battery backup	Required	Provided	MR
	e) Building floor plan	NA	NA	NA
20.	Special Fire Protection System if any: Total flooding system is	MR		

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection. Further, requirements of fire extinguishers as per IS 2190 is 5-6 extinguishers at each floor. Accordingly, inspection note has been amended from previous report.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if approved, we may renew the FSC issued vide letter no. F6/DFS/MS/NDZ/2021/375 dated 04/08/21, under rule 35 of the Delhi Fire Service rules 2010. Accordingly, DFA is put up for kind perusal and signature please.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name: - Sh. Rajinder Atwal

Designation: - DO (CD)

Name: - Sh. Ravinder Singh

Designation: ADO (CC)