# FORM 'H' FORM FOR ISSUING FIRE SAFETY CERTIFICATE [Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE, NEW DELHI

No. F6/DFS/MS/2024/School 215
FIRE SAFE

Dated: 20/03/2024

#### **FIRE SAFETY CERTIFICATE**

Certified that the building of St. Thomas School, Located at Goyala Vihar, Near Sector-19, Dwarka, New Delhi-110074, comprised of basement, Ground + 03 Upper Floors owned/occupied by St. Thomas School was issued FSC vide Letter No. F6/DFS/MS/2021/SZ/49, dated 20-01-2021. The premises was re inspected by the officer concerned of this department on 05/03/2024 in the presence of Sh. Naresh Sharma and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Educational" Group B with effect from 20/03/2024 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on .20/03/2024. at New Delhi by.

Director Delhi Fire Service

Copy to: -

1. The Principal, St. Thomas School, Goyala Vihar, Near Sector-19, Dwarka, New Delhi-

2. Director of Education Govt. of NCT of Delhi, Old Secretariat, New Delhi-110054.

#### Following fire safety directives must be adhered to:-

- 1. A temporary structure / rooms created at terrace shall not be used for school activity.
- All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 4. The trained staff should be available round the clock.
- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 7. Basement shall be used as per building by laws.
- The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expired.

### N/15-

## INSPECTION REPORT

 Name & address of the building: St. Thomas School, Goyala Vihar, Near Sector-19, Dwarka, New Delhi-110074.

2. Type of Occupancy : Educational (Basement + Ground + 3 Upper Floor)

3. Type of Case : Renewal

4. Details of previous NOC : F6/DFS/MS/2021/SZ/49, dated 20-01-2021

5. Fire Safety directives Letter No.: N/A

6. Date of inspection : 05-03-2024

7. Name of the Inspecting Officer: ADO (DWK)

8. Name and designation of Officer

from the building side : Sh. Naresh Sharma

9. Year of Construction : 2005

10. Applicant's letter No. : STS/2024, dated 20-01-2024

S No	Minimum standards on fire prevention and fire safety U/R 33	Requirement a N/11, N/12 &		Provided at site	Remarks MR/NM		
1	Access of building	N.A.			1100		
	Road width	Accessible 06 mtr			MR		
	Gate width	4.5mtr	5.		MR	10.71	
1	Width of internal road	NA	N	A	NA		
2	Number, width, Type & Arrangeme	ents of exits					
_	a. Number of staircases  • Upper floors				1.00		
-		03 No's		4 No's	MR		
	Basements	03 No's	0	4 No's	MR		
	b. Width of staircases			77.4	L) (D)	-	
	Upper floors     Basements	150 cms		50 cmsX4	MR	-	
		150 cms	1	50 cmsX4	MK ·	MR .	
	c. Protection of exits		7.5		1271		
	Fire check door     Pressurization	NA NA			NA		
		NA		JA	NA		
	d. No of continuous staircase to terrace	Required	arron, T	Γwό MR			
		150 cms		200 91110		MR	
-	e. Width Of Corridor  f. Door Size	100 cms	110 c	ms (single)	MR		
3 .	Compartmentation			JA	NA		
-	<ul> <li>Fire check door</li> <li>Sealing of electrical shafts</li> <li>Fire Rating of shaft door</li> <li>Water Curtain</li> </ul>	NA		(9)	NA NA		
		NA		AND DESCRIPTION			
		NA .		NA NA			
		NA		NA NA			
	Fire Dampers	NA	1	IA	NA		
4	Smoke managements System		- <u>                                     </u>	xhaust fans are provided		MR	
7	Basements						
	Upper floors	Required 1	Natural	ventilation p	TOVIDED	IVIIC	
5.	Fire Extinguishers	20	T	rovided	MR	-	
	Total numbers	30 nos. ABC & CO <sub>2</sub>		rovided	MR		
	Types     IS marking	ISI marked	1	SI marked	MR		



N	16
	10

27	D' ALLTE DI.	•	190			
6.	First – Aid Hose Reels	02 no's	Provided	M	R	
	<ul> <li>Total numbers on each floor</li> </ul>	30mtr	Provided	M		
		5m	Provided	M		
	<ul> <li>Length of hose reel hose</li> <li>Nozzle diameter</li> </ul>	m	1 To vided			
7.	Automatic fire detection and alarming system					
	Type of detectors	NA NA NA				
	Location of Main Panel	NA	NA	NA		
	Location of Repeater     Panel	NA	NA	. NA		
	Alternate source of power	NA	NA	NA		
	Hooters' Location	NA	NA	NA		
8.	MOEFA	NA	Provided	NA		
9.	Public Address System	NA	Provided	NA.	_	
10.	Automatic Sprinkler System	Section in	Tiovided	1 112 1	-	
	Basements	Required	Provided ·	MR		
	Upper Floor	NA	NA	NA		
	Sprinkler above false	NA ·	NA	NA		
	ceiling	PA (RE)	(containment)		$\mathbb{R}^r$	
11.	Internal Hydrants:	čić 270				
	Size of riser/down-comer	NA ·	100mm	NA		
	Number of hydrants per floor	NA	02	NA		
	Hose Box	NA	02	NA.	11	
12.	Yard Hydrants	NAMES OF TAXABLE PARTY.	-	1		
	Total number of hydrants	NA	NA	NA		
	Hose Box	NA	NA	NA		
13.	Pumping Arrangements:	-111	1474	IVA	_	
	Ground Level					
	Discharge of main pump	NA	NA	NA		
: 4	Head of main pump	NA	NA ·	NA NA		
	> Number of main pumps	NA	NA	NA NA		
	> Jockey pump out put	NA ·	NA	NA NA		
	> Jockey pump head	NA	NA		_	
	Standby Pump out put	NA	NA	NA NA		
	> Standby Pump Head	NA	NA			
	➤ Auto Staring/Manual	NA NA	NA	NA		
	stopping	AAA	INA	NA	P. F.	
	<ul> <li>Pump House Access</li> <li>Terrace level</li> </ul>	NA	NA	NA.		
	Discharge of pump	450 lpm &180lpm	Provided	MD		
	➤ Head of the pump	40Mtr	Provided	MR		
	➤ Power supply	Required	Provided	MR		
	<ul><li>Auto starting of pump</li></ul>	Required	Provided	MR	1	
14.	Captive water Storage for fire figh	ting	riovided	MR		
V	Under ground tank     capacity	50,000ltrs	Provided ·	MR		
	Draw off connection	NA ·	NA	NY A		
	Fire service inlet	NA	Section of	NA		
	Access to tank	NA	Provided NA	NA		
	Overhead Tank capacity	15,000Ltr	Provided	NA		
15	Exit Signage	Required	Provided	MR MR		
	40 25 25	10	K I			

6.	Provision of Lifts	*			
	Pressurization of Lift Shaft	NA	NA	NA	
	<ul> <li>Pressurization of lift lobby</li> </ul>	NA	NA	NA.	
	Communication in lift Car	NA	NA	NA	
	➤ Fireman's Grounding Switch	Required	Provided	MR	
	➤ Lift Signage	Required	Provided	MR	
17.	Standby power supply	NA	Provided	NA	
18.	Refuge Area	4.1			
	> Total area	NA	NA ·	NA	
	> Location	NA	NA	NA	
19.	Fire control room				
	Detector system panel	NA	, NA	NA	
	> Flow Switch Panel	NA	NA .	NA	
	> PA System Panel	NA	NA	NA	
	> Battery backup	NA	NA	NA	
	> Building Floor Plans	NA	NA	NA	
20.	Special Fire Protection Systems for Protection of special Risks, if any;	NA	NA	NA ·	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the FSC issued vide letter No. F6/DFS/MS/2021/SZ/49, dated 20-01-2021 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Note; - The temporary structure / rooms created at terrace shall not be used for school activity. This makes the beau sines to school management.

Signature of the Inspecting Officer Name Uday Vir Sayh Designation ADO 115W

CF0 (\$2)

AM Son So

Aculan