GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/EH/NDZ/2024/101

Dated: 04. 04/2024

FIRE SAFETY CERTIFICATE

Certified that the M/s Caffe Tonino (A Unit of Pyraminds) located at 9, H-Block, Mezzanine floor, Plaza Cinema Building, Connaught Place, New Delhi in a building comprised of Ground + Mezzanine + 02 Upper floor and Restaurant running at Mezzanine floor only owned /occupied by M/s Caffe Tonino (A Unit of Pyraminds), was earlier issued fire safety certificate vide letter No. F6/DFS/MS/EH/2018/NDZ/2021/143 dated 20/07/21. Now, the premises has been reinspected by the officers concerned of this department in presence of Manager on dated 22/03/24 and found that the said restaurant has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and the said building / premises, is fit for occupancy class Assembly Building (Group-D) of Sub-Division D-5, Restaurant at Mezzanine floor only and valid up to 31.03.2027 from the date of issue in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on ... 2.4. 24... at New Delhi by.

DIRECTOR elhi Fire Officer

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. ID No 2024021801815 dated 14/03/24.
- 2. The Chief Medical Officer (Lic-II), NDMC, Palika Kendra, New Delhi 110001.
- 3. The Manager, M/s Caffe Tonino 9, H-Block, Mezzanine floor, Plaza Cinema Building, Connaught Place, New Delhi

Condition for the validity of Fire Safety Certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times. This FSC is valid for restaurant at mezzanine floor only.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its
- 8. The means of escape shall be kept unobstructed / unlocked & remain available to the occupants for uninterrupted evacuation in case of an emergency.
- 9. Any flammable material for interior decoration shall strictly prohibited.

INSPECTION REPORT 1. Name & address of the building M/S Caffe Tonino (A Unit of Pyraminds) at

9, H- Block, Mezzanine floor, Plaza Cinema Building, Connaught Place, New Delhi.

Gr. + Mezzanine + 02 Upper floors

2. Type of occupancy:-Assembly Building Group-D

, Restaurant is running at Mezzanine/first floor only

3. Type of case:-

4. Details of previous FSC:-F6/DFS/MS/EH/2018/NDZ/2021/143 dated

20/07/21

5. Fire safety directives No.-N/A 6. Date of inspection:-22/03/24

7. Name of the inspecting officer:-Sh. Ravinder Singh (ADO/CC) Sh. Rajinder Atwal, DO/CD

8. Name & designation of officer from the building side:-

(Manager) 9. Year of construction:-Old Heritage

ID No 2024021801815 dated 14/03/24. 10. Applicant's letter No:-

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR
1.	Access to Building			
	1) Road width	N/A	06 mtr.	MR
	2) Gate width	N/A	N/A	N/A
	3)Width of internal road	N/A	N/A	N/A
2.	Number, Width Type & Ari	angement of Ex	cits	
	A. Number of staircases			
	1. Upper floors	03	03	MR
	2. Basements	N/A	N/A	N/A
	B. Width of staircase	114	- i	
	1. Upper floors	0.80, 1.25 mtr.	1.80, 1.09 & 0.90 mtr.	MR
	2. Basements	N/A	N/A	N/A
	C. Protection of exits	N/A	N/A	N/A
1=	1. Fire check door	N/A	N/A	N/A
	2. Pressurization	N/A	N/A	N/A
	D. No. of continuous staircase to terrace	N/A	N/A	N/A
	E. Width of corridor	N/A	N/A	N/A
	F. Door size	02 mtr.	02 mtr. /	MR
3.	Compartmentation	Bright .		_
34-3	1) Fire check door	N/A	N/A	N/A
1	2) Sealing of electrical shafts	N/A	N/A	N/A
	3) Fire rating of shaft door	N/A	N/A	N/A
	4) Water curtain	N/A	N/A	N/A
	5) Fire Dampers	N/A	N/A	N/A
4.	Smoke Management System	THE THE IT		•
	1) Basements	30 ACPH	N/A	N/A
	2) Upper floors	12 ACPH	Natural	MR
	Fire Extinguishers			
	1) Total numbers	09 Nos.	10 Nos.	MR
	2) Types	ABC & CO2	ABC & CO2	MR
	3) ISI marking	Required	Provided	MR
i.	First-Aid Hose Reel			17700

2) Length of hose reel hose 30 mtr. 30 mtr. No.	-			Lat				
3) Nozzle diameter 05 mm 05 mm No 7. Automatic Fire Detection & Alarming System 1) Type of detectors Required Provided No 2) Location of main panel Gr. Floor Provided No 4) Alternate source of power Required Provided No 10 Noter's Location Office main provided No 10 Noter's Location No 10 Noter's Location No 10 Noter's Location No 10 Noter's Location No 10					MR			
1) Type of detectors					MR			
1) Type of detectors Required Provided No. 2) Location of main panel Gr. Floor Provided No. 3) Location of repeater panel Gr. Floor Provided No. 4) Alternate source of power Required Provided No. 5) Hooter's Location Office main lobby Provided No. 4 No. 5 No				- COMMISSION CONTRACTOR	MR			
2) Location of main panel Gr. Floor Provided N 3) Location of repeater panel Gr. Floor Provided N 4) Alternate source of power Required Provided N 5) Hooter's Location Office main lobby 8. MOEFA Required Provided N 9. Public Address System N/A Provided N 10. Automatic Sprinkler System Mezz. Floor Provided N 11) Basement N/A N/A N/A N/A 2) Upper floors N/A N/A N/A N/A 3) Sprinkler above false ceiling N/A N/A N/A N/A N/A 11. Internal Hydrants 1) Size of riser/down-comer System N/A	7.							
3) Location of repeater panel Gr. Floor Provided M 4) Alternate source of power Required Provided M 5) Hooter's Location Office main lobby 8. MOEFA Required Provided M 9. Public Address System N/A Provided M 10. Automatic Sprinkler System M/A Provided M 11. Match Basement N/A N/A N/A N/A 12. Upper floors N/A N/A N/A N/A 13. Sprinkler above false Ceiling N/A N/A N/A N/A 14. Internal Hydrants O1 O1 M 15. Internal Hydrants O1 O1 M 16. Automatic Sprinkler System N/A N/A N/A N/A N/A 17. Internal Hydrants O1 O1 M 18. Internal Hydrants O1 O1 M 19. Size of riser/down-comer 150 mm 150 mm M 19. Automatic Sprinkler System O1 O1 M 19. Automatic Sprinkler System O1 O1 M 19. Automatic Sprinkler System O1 O1 M 19. Automatic Sprinkler System O2 O2 M 19. Automatic Sprinkler System O2 O2 M 19. Automatic Sprinkler System O2 O2 M 10. Automatic Sprinkler System O1 O1 M 11. Automatic Sprinkler System O1 O1 M 12. Automatic Sprinkler System O1 O1 M 13. Pumping Arrangement F/F System exiting with Plaza Cine 19. Ground level a Discharge of main pump B9 mtr. 89 mtr. M 19. Head of main pump B9 mtr. 89 mtr. M 10. Auto starting/Manual Sent. S9 mtr. M 11. Automatic Sprinkler System N/A N/A N/A 12. Automatic Sprinkler System N/A N/A N/A 19. Stand by pump 40 mtr. 40 mtr. M 19. Stand by pump 40 mtr. 40 mtr. M 10. Captive Water Storage for Fire Fighting N/A N/A N/A 10. Automatic Sprinkler System N/A N/A N/A 10. Automatic Sprinkler System N/A N/A N/A 10. Automatic Sprinkler System N/A N/A N/A 10. Captive Water Storage for Fire Fighting N/A N/A N/A 10. Over head tank capacity N/A N/A N/A 10. Over head tank capacity N/A N/A N/A 10. Over head tank capacity N/				#UPLEMI-25070000	MIR			
4) Alternate source of power S) Hooter's Location Office main provided N S) Hooter's Location Office main provided N Required Provided M Public Address System N/A Provided N 10. Automatic Sprinkler System Mezz. Floor Provided M 1) Basement N/A N/A N/A N/A N/A 2) Upper floors N/A		2) Location of main panel	Gr. Floor	Provided	MR			
S Hooter's Location		3) Location of repeater panel	Gr. Floor	Provided	MR			
Sample S		4) Alternate source of power	Required	Provided	MR			
9. Public Address System N/A Provided N 10. Automatic Sprinkler System Mezz. Floor Provided M 1) Basement N/A N/A N/A N/A N/A 2) Upper floors N/A N/A N/A N/A N/A 3) Sprinkler above false ceiling 11. Internal Hydrants 1) Size of riser/down-comer 150 mm 150 mm M 2) Number of hydrants per floor 3) Hose box 01 01 M 12. Yard Hydrants 1) Total number of hydrants 02 02 M 13. Pumping Arrangement F/F System exiting with Plaza Cine 1) Ground level a) Discharge of main pump 89 mtr. 89 mtr. M b) Head of main pump 89 mtr. 89 mtr. M c) Number of main 01 01 M Discharge of main 2800 LPM 2800 LPM M e) Jockey pump head 89 mtr. 89 mtr. M f) Stand by pump 2800 LPM 2800 LPM M e) Jockey pump head 89 mtr. 89 mtr. M f) Stand by pump 2800 LPM 2800 LPM M e) Jockey pump head 89 mtr. 89 mtr. M f) Stand by pump head 89 mtr. 89 mtr. M f) Stand by pump head 89 mtr. 89 mtr. M f) Stand by pump head 89 mtr. 89 mtr. M f) Stand by pump head 89 mtr. 89 mtr. M h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump 450 LPM M b) Head of pump 40 mtr. 40 mtr. M h) Head of pump 40 mtr. 40 mtr. M h) Head of pump 40 mtr. 40 mtr. M h) Head of pump 40 mtr. 40 mtr. M h) Head of pump 40 mtr. 40 mtr. M h) Head of pump 40 mtr. 40 mtr. M h) Head of pump 40 mtr. 40 mtr. M h) Head of pump 40 mtr. 40 mtr. M h) Head of pump 40 mtr. 40 mtr. M h) Head of pump 40 mtr. 40 mtr. M h) Head of pump 40 mtr. 40 mtr. M h) Head of pump 40 mtr. 40 mtr. M h) Head of pump 40 mtr. 40 mtr. M h) Head of pump 40 mtr. 40 mtr. M h) Head of pump 40 mtr. Ho more tended M h) Head of pump 40 mtr. Ho more tended M h) Head of pump 40 mtr. Ho more tended M h) Head of pump 40 mtr. Ho more tended M h) Head of pump 40 mtr. Ho more tended M h) Head of pump 40 mtr. Ho more tended M h) Head of pump 40 mtr. Ho more tended M h) Head of pump 40 mtr. Ho more tended M h) Head of pump 40 mtr. Ho more tended M h) Head of pump 40 mtr. Ho more tended M h) Head of pump 40 mtr. Ho more tended M h) Head of pump 40 mtr. Ho more tended M h) Head of pump 40 mtr. Ho more tended M h) Head of pump 40			Office main	Provided	MR			
10. Automatic Sprinkler System Mezz. Floor Provided M	4 A.M. A.D.I	MOEFA	Required	Provided	MR			
10. Automatic Sprinkler System Mezz. Floor Provided M		Public Address System	N/A	Provided	N/A			
1) Basement	10.		Mezz, Floor	Provided	MR			
2) Upper floors				Participation of the Control of the	N/A			
3) Sprinkler above false ceiling 11. Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per floor 3) Hose box 10. Vard Hydrants 1) Total number of hydrants 2) Hose box 11. Total number of hydrants 1) Ground level 1) Discharge of main pump 2800 LPM 2800 LPM 10. Number of main pump 2800 LPM 2800 L		2) Upper floors	The state of the s	0.5774555.00	N/A			
11. Internal Hydrants 1 Size of riser/down-comer 150 mm 150 mm M 2 Number of hydrants per floor 3 Hose box 01 01 01 M M M M M M M M M		3) Sprinkler above false			N/A			
1) Size of riser/down-comer 150 mm 150 mm M	11.	Internal Hydrants						
2) Number of hydrants per floor 3) Hose box 01 01 01 M 12. Yard Hydrants 1) Total number of hydrants 2) Hose box 02 02 03 M 13. Pumping Arrangement 1) Ground level a) Discharge of main pump b) Head of main pump b) Head of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump 40 Minum c) Number of main pump 40 Jockey pump head 89 mtr. 89 mtr. Minum Minu		1) Size of riser/down-comer	150 mm	150 mm	MR			
12. Yard Hydrants 1) Total number of hydrants 2) Hose box 1) Ground level a) Discharge of main pump b) Head of main pump c) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head stopping 2) Terrace level a) Discharge of pump b) Head of pump 40 Auto starting of pump b) Head of pump c) Required c) Power supply d) Auto starting of pump d) Discharge of pump head stopping 2) Terrace level a) Discharge of pump b) Head of main pump c) Required c) Power supply d) Required c) Provided d) Auto starting of pump head stopping d) Required d) Auto starting of pump head of pump		2) Number of hydrants per		C PRESIDENCE CONTRACTOR	MR			
12. Yard Hydrants 1) Total number of hydrants 2) Hose box 1) Ground level a) Discharge of main pump b) Head of main pump c) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head stopping 2) Terrace level a) Discharge of pump b) Head of pump 40 Auto starting of pump b) Head of pump c) Required c) Power supply d) Auto starting of pump d) Discharge of pump head stopping 2) Terrace level a) Discharge of pump b) Head of main pump c) Required c) Power supply d) Required c) Provided d) Auto starting of pump head stopping d) Required d) Auto starting of pump head of pump		3) Hose box	01	01	MD			
1) Total number of hydrants 02 02 M	12.							
2) Hose box Pumping Arrangement 1) Ground level a) Discharge of main pump b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump d) Jockey pump head f) Required f) Auto starting of pump f) Head of pump f) Required f) Auto starting of pump f) Head of pump f) Required f) Required f) Required f) Auto starting of pump f) Au			02	102	LACO			
13. Pumping Arrangement 1) Ground level a) Discharge of main pump b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump d) Auto star			0.000					
1) Ground level a) Discharge of main pump b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head stopping 2) Terrace level a) Discharge of pump b) Head of pump d) Auto starting of pump f) Auto starting of pump f) Head of pum	13.							
a) Discharge of main pump b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump d) Auto starting of pump f) Required f) Required f) Required f) Required f) Required f) Provided f) Auto starting of pump f) Required f) Required f) Provided f) Auto starting of Required f) Required f) N/A f) N/A f) N/A f) Draw-off connection f) N/A f) N/A f) N/A f) Over head tank capacity f) 10 000 ltr f] 10 000 ltr								
b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump f) Starting of pump li Head of pump f) Auto starting of pump f) Head of pump f) Required f) Required f) Provided f) Auto starting of pump f) Required f) Provided f) Auto starting of pump f) Required f) Provided f) Auto starting of pump f) Required f) Provided f) Auto starting of pump f) Required f) Provided f) Auto starting of pump f) Required f) Provided f) Auto starting of pump f) Required f) Provided f) Auto starting of pump f) Required f) Provided f) Auto starting of pump f) Required f) Provided f) Auto starting of pump f) Required f) Provided f) Auto starting of pump f) Required f) Provided f) Auto starting of pump f) Required f) Provided f) Auto starting of pump f) Required f) Provided f) Auto starting of pump f) Required f) Requir		a) Discharge of main	2800 LPM	2800 LPM	MR			
c) Number of main pump d) Jockey pump out put 280 LPM 280 LPM M e) Jockey pump head 89 mtr. 89 mtr. M f) Stand by pump 2800 LPM 2800 LPM M output g) Stand by pump head 89 mtr. 89 mtr. M h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump 450 LPM 450 LPM M b) Head of pump 40 mtr. 40 mtr. M c) Power supply Required Provided M d) Auto starting of Required Provided M d) Auto starting of Required Provided M 14. Captive Water Storage for Fire Fighting 1) Under ground tank capacity 10 000 ltr 10 000 ltr c) Access to tank N/A N/A			89 mtr.	89 mtr	MD			
e) Jockey pump head 89 mtr. 89 mtr. MI f) Stand by pump 2800 LPM 2800 LPM MI g) Stand by pump head 89 mtr. 89 mtr. MI h) Auto starting/Manual Required Provided MI stopping 2) Terrace level a) Discharge of pump 450 LPM 450 LPM MI b) Head of pump 40 mtr. 40 mtr. MI c) Power supply Required Provided MI d) Auto starting of pump Required Provided MI 14. Captive Water Storage for Fire Fighting 1) Under ground tank capacity a) Draw-off connection N/A N/A b) Fire service inlet N/A N/A c) Access to tank N/A N/A d) Over head tank capacity 10 000 ltr 10 000 ltr					MR			
e) Jockey pump head 89 mtr. 89 mtr. MI f) Stand by pump 2800 LPM 2800 LPM MI g) Stand by pump head 89 mtr. 89 mtr. MI h) Auto starting/Manual Required Provided MI stopping 2) Terrace level a) Discharge of pump 450 LPM 450 LPM MI b) Head of pump 40 mtr. 40 mtr. MI c) Power supply Required Provided MI d) Auto starting of pump Required Provided MI 14. Captive Water Storage for Fire Fighting 1) Under ground tank capacity a) Draw-off connection N/A N/A b) Fire service inlet N/A N/A c) Access to tank N/A N/A d) Over head tank capacity 10 000 ltr 10 000 ltr		d) Jockey pump out put	280 LPM	280 I PM	MD			
f) Stand by pump output g) Stand by pump head 89 mtr. 89 mtr. MI h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump 450 LPM 450 LPM MI b) Head of pump 40 mtr. 40 mtr. MI c) Power supply Required Provided MI d) Auto starting of pump Required Provided MI 11. Captive Water Storage for Fire Fighting 1 Under ground tank capacity a) Draw-off connection N/A N/A b) Fire service inlet N/A N/A c) Access to tank N/A N/A d) Over head tank capacity 10 000 ltr 10 000 ltr		e) Jockey pump head			200000000000000000000000000000000000000			
h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump		f) Stand by pump output		A CONTRACTOR OF THE CONTRACTOR	MR			
h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump 450 LPM 450 LPM MF b) Head of pump 40 mtr. 40 mtr. MF c) Power supply Required Provided MF d) Auto starting of Required Provided MF pump 14. Captive Water Storage for Fire Fighting 1) Under ground tank capacity a) Draw-off connection N/A N/A b) Fire service inlet N/A N/A N/A c) Access to tank N/A N/A N/A d) Over head tank capacity 10 000 ftr 10 000 ftr		g) Stand by pump head	89 mtr.	89 mtr.	MR			
a) Discharge of pump 450 LPM 450 LPM MF b) Head of pump 40 mtr. 40 mtr. MF c) Power supply Required Provided MF d) Auto starting of Required Provided MF pump 14. Captive Water Storage for Fire Fighting 1) Under ground tank N/A N/A capacity a) Draw-off connection N/A N/A N/A b) Fire service inlet N/A N/A N/A c) Access to tank N/A N/A N/A d) Over head tank capacity 10 000 ftr 10 000 ftr		stopping	Required		MR			
b) Head of pump 40 mtr. 40 mtr. MI c) Power supply Required Provided MI d) Auto starting of Required Provided MI pump 14. Captive Water Storage for Fire Fighting 1) Under ground tank capacity a) Draw-off connection N/A N/A b) Fire service inlet N/A N/A c) Access to tank N/A N/A d) Over head tank capacity 10 000 ftr 10 000 ftr			alla Saran	4.1 1				
b) Head of pump 40 mtr. 40 mtr. MI c) Power supply Required Provided MI d) Auto starting of pump Required Provided MI 14. Captive Water Storage for Fire Fighting 1) Under ground tank capacity a) Draw-off connection N/A N/A b) Fire service inlet N/A N/A c) Access to tank N/A N/A d) Over head tank capacity 10 000 ftr 10 000 ftr			450 LPM	450 LPM	MR			
c) Power supply Required Provided MF d) Auto starting of Provided MF pump 14. Captive Water Storage for Fire Fighting 1) Under ground tank Capacity a) Draw-off connection N/A N/A b) Fire service inlet N/A N/A c) Access to tank N/A N/A d) Over head tank capacity 10 000 ftr 10 000 ftr			40 mtr.		MR			
d) Auto starting of pump 14. Captive Water Storage for Fire Fighting 1) Under ground tank capacity a) Draw-off connection N/A N/A b) Fire service inlet N/A N/A c) Access to tank N/A N/A d) Over head tank capacity 10 000 ftr 10 000 ftr			Required	The second secon	MR			
1) Under ground tank		pump			MR			
1) Under ground tank	14.	Captive Water Storage for Fire Fighting						
b) Fire service inlet N/A N/A 1 c) Access to tank N/A N/A 1 d) Over head tank capacity 10 000 ftr 10 000 ftr		1) Under ground tank capacity	N/A	N/A	N/			
b) Fire service inlet N/A N/A c) Access to tank N/A N/A N/A d) Over head tank capacity 10 000 ftr 10 000 ftr			N/A	N/A	N/			
c) Access to tank N/A N/A d) Over head tank capacity 10 000 ltr 10 000 ltr		h) Dies seemile in the	N/A		N/			
d) Over head tank capacity 10 000 ltr 10 000 ltr								
15. Exit Signage. Required Provided		c) Access to tank	N/A		N/			

6.	Provision of Lifts.				
	a) Pressurization of lift shaft	N/A	N/A	N/A	
	b) Pressurization of lift lobby	N/A	N/A	N/A	
	c) Communication in lift car	Required	Provided	MR	
	d) Fireman's switch	Required	Provided	MR	
	e) Lift signage	Required	Provided	MR	
17.	Stand by Power Supply	Required	Provided	MR	
18.	Refuge Area	N/A	N/A	N/A	
	Total area location	N/A	N/A	N/A	
19.	Fire Control Room	N/A	N/A	N/A	
	a) Detector system panel	N/A	N/A	N/A	
	b) Flow switch panel	N/A	N/A	N/A	
	c) PA system panel	N/A	N/A	N/A	
	d) Battery backup	N/A	N/A	N/A	
	e) Building floor plan	N/A	N/A	N/A	
20.	Special Fire Protection System for Protection of special Risk, if any:				

The fire protection systems provided in the building were randomly tested, checked and

found functional at the time of inspection. In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/EH/2018/NDZ/2021/143 dated 20/07/21, renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended for approval.

Signature of the Inspecting Officer

Name :- Rajinder Atwal

Designation :- DO (CD)

Signature of the Inspecting Officer

Name :- Ravinder Singh Designation :- ADO (CC)

Director