GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/EH/NDZ/2024/ 83

Dated: 10/04/2024

FIRE SAFETY CERTIFICATE

Certified that the M/S Hotel Kabir Palace located at T-2345, Ashok Nagar Faiz Road, Karol Bagh, New Delhi comprises of B+ stilt +Gr. + 03 Upper floors (total 20 Guest rooms), basement (storage), stilt -parking, Ground to 3rd floor (05 guest rooms at each floor) total 20 guest rooms up to third floor only, was earlier granted FSC by this department vide letter No. F6/DFS/MS/GH/NDZ/2021/143 dated 16/03/21 for 20 guest rooms up to third floor only. Now, the premise was inspected by the officer concerned of this department on 26/03/2024 in the presence of Manager and found that the said guest house building has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 basement – storage, stilt-parking, ground- to 3rd floor (5 guest rooms at each floor) Total – 20 guest rooms up to third floor, and valid up to 31.03.2027 from the date of issue in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

DIRECTOR Delhi Fire Service

Copy to:-

- 1. The Commissioner, MCD, Civic Centre, New Delhi: to kindly ensure the occupancy as detailed above and deviation if any.
- The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi ID no. 2024031703124 dated 17.03.2024.
- 3. The Manager, M/S Hotel Kabir Palace located at T-2345, Ashok Nagar Faiz Road, karol Bagh, New Delhi.

Conditions for the validity of fire safety certificate.

- All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained firefighting staff should be available round the clock.
- 4. The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned.
- This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

		N/8					
INSPECTION REPORT							
1.	Name & address of the building	M/S Hotel Kabir Palace located at T-2345, Ashok Nagar, Faiz Road, karol Bagh, New Delhi, Basement +Stilt +Ground and Three upper floor.					
2.	Type of occupancy: -	Residential Group A-1 Basement – storage, stilt -parking, ground floor to 3 rd floor 05 guest rooms & 09 beds at each floor, Total 20 room& 36 beds					
3	Type of case: -	Renewal					
4	Details of previous FSC: -	F6/DFS/MS/GH/NDZ/2021/143 dated 16/03/21					
5	Fire safety directives No	N/A					
6	Date of inspection: -	26.03.2024					
7	Name of the inspecting officer: -	Sh. Ravinder Singh (ADO/CC) Sh. Rajinder Atwal (DO /CD)					

Manager

2020

Name & designation of officer From the building side: -Year of construction: -

Applicant's letter No: -

10

old case

Online id no. 2024031703124 dated 17.03.2024.

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement as per BBL-1983 /NBC part-4	Provided at site	Remarks MR/NMR
1.	Access to Building			
	1) Road width	06 mtr	15mtr	MR
	2) Gate width	N/A	N/A	N/A
	3)Width of internal road	N/A	N/A	N/A
2.	Number, Width Type & Arran	gement of Exits		
2.	A. Number of staircases			
	1. Upper floors	02 Nos.	02 Nos.	MR
	2. Basements	02 Nos.	02 Nos.	MR
	B. Width of staircase			
	1. Upper floors	1.50mtr	1.50 mtr.	MR
	2. Basements	1.50mtr	1.50 mtr.	MR
	C. Protection of exits			
	Fire check door(required in basement)	Required	provided	MR
	2. Pressurization	N/A	N/A	N/A
	D. No. of continuous staircase to terrace	02 Nos	Provided	MR
	E. Width of corridor	1.50m	1.50m	MR
	F. Door size(room)	01 mtr.	01 mtr.	MR
3.	Compartmentation			
	1) Fire check door	N/A	N/A	N/A
	2) Sealing of electrical shafts	N/A	N/A	N/A
	3) Fire rating of shaft door	N/A	N/A	N/A
	4) Water curtain	N/A	N/A	N/A

N19

4	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System	110 4 000	The second second	A COLUMN	
	1) Basements	12 ACPH	Exhaust fan	MR	
-	2) Upper floors	12 ACPH	Exhaust fan	MR	
5.	Fire Extinguishers	T 22-2-2		_ 1	
	1) Total numbers	12 Nos.	12 Nos.	MR	
	2) Types	ABC & CO2	ABC & CO2	MR	
_	3) ISI marking	Required	Provided	MR	
6.	First-Aid Hose Reel				
	1) Total number at each floor	01	Provided	MR	
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR	
	3) Nozzle diameter	05 mm	05 mm	MR	
7.	Automatic Fire Detection & Alarming System				
	1) Type of detectors CO type	Required	Provided	MR	
	2) Location of main panel	Stilt floor	Provided	MR	
	3) Location of repeater panel	N/A	N/A	N/A	
	4) Alternate source of power	Required	Provided	MR	
	5) Hooter's Location	At each floor	Provided	MR	
8.	MOEFA	N/A	Provided	N/A	
9.	Public Address System	Required	Provided	MR	
10.	Automatic Sprinkler System		Tiovided	IVIK	
	1) Basement	N/A	N/A	N/A	
	2) Upper floors	N/A	Provided	N/A	
	3) Sprinkler above false ceiling	N/A	N/A	N/A	
11.	Internal Hydrants	35.00		11//	
	1) Size of riser/down-comer	N/A	N/A	N/A	
	2) Number of hydrants per floor	N/A	N/A	N/A	
	3) Hose box	N/A	N/A	N/A	
12.	Yard Hydrants		1.071	110/7	
	1) Total number of hydrants	N/A	N/A	N/A	
	2) Hose box	N/A	N/A	N/A	
13.	Pumping Arrangement			10/1	
	1) Ground level	N/A	N/A	NI/A	
	a) Discharge of main	N/A	N/A	N/A	
	pump	***************************************	INE	IN/A	
	b) Head of main pump	N/A	N/A	N/A	
	c) Number of main pump	N/A	N/A	N/A	
	d) Jockey pump out put	N/A	N/A	N/A	
	e) Jockey pump head	N/A	N/A	N/A	
	f) Stand by pump output	N/A	N/A		
	g) Stand by pump head	N/A	N/A	N/A	
	h) Auto starting/Manual	N/A	N/A	N/A	
	stopping	-37.5	IVA	N/A	
	2) Terrace level			+	
	a) Discharge of pump	450LPM	450 LPM	NO	
	b) Head of pump	30 mtr.	30 mtr.	MR	
	c) Power supply	N/A	Provided	N/A	
	d) Auto starting of pump	N/A		N/A	
14.	Captive Water Storage for Fire Fighting				
	capacity	IN/A	N/A	N/A	

	a) Draw-off connection	N/A	N/A	N/A
		N/A	N/A	N/A
	b) Fire service inlet	Required	Provided	MR
	c) Access to tank	5.000	5,000 ltr.	MR
	d) Over head tank capacity	Required	Provided	MR
5.	Exit Signage.	Kequireu	100	400
16.	Provision of Lifts.	Sec. 35	M. C. I.	N/A
. 4	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift	N/A	N/A	
	c) Communication in lift car	Required	Provided	MR
	d) Fireman's switch	Required	Provided	MR
		Required	Provided	MR
126	e) Lift signage	Required	Provided	MR
17.	Stand by Power Supply	N/A	N/A	N/A
18.	Refuge Area			N/A
	Total area location	N/A	N/A	
cos le		N/A	N/A	N/A
19.	a) Detector system panel	N/A	N/A	N/A
	a) Death symmetry		N/A	N/A
	b) Flow switch panel	N/A		N/A
	c) PA system panel	N/A	N/A	
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
	Special Fire Protection System for		Consist Dick if	N/A

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if approved, we may renew the PSC issued vide letter no. F6/DFS/MS/GH/NDZ/2021/143 dated 16/03/21, under rule 35(6) of the Delhi Fire Service rules 2010 Accordingly, DFA is put up for kind perusal and signature

Signature of the Inspecting Officer

what 13 run to aldry Bed to the aldry Me don to the