

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001



No F 6 / DFS / MS / 2024 / School/WZ/ 307

Dated 12 04 2024

FIRE SAFETY CERTIFICATE

Certified that the MCD Primary School located at AK-Block, Shalimar Bagh, Delhi-110088 comprised of Ground and First floor owned/occupied by MCD Primary School was issued FSC by this department vide letter No F6 /DFS/MS/School/WZ/2021/261 dated 26.03.2021. The premises was re-inspected by the officer concerned of this department on 04.04.2024 in the presence of Smt. Shail Gupta (In-charge), and observed that all the fire prevention and fire safety arrangements as provided in the premises found in good working condition. The premises have deemed complied with requirements of circular issued by Director of Education letter no 3298-3398 dated 01.03.2011 and the building/ premise is fit for occupancy, Group B Educational with effect from 12/04/224 for a period of three years, subject 16 compliance of the conditions mentioned below:

Issued on .. 12 04 2024.. at New Delhi by

Director Ph. 011-23414000

Copy to:-

1. The Director, Education, MCD, Civic Center, New Delhi.

2. The Principal, MCD Primary School, AK- Block, Shalimar Bagh, Delhi-110088.

Conditions for the validity of Fire Safety Certificate:

1. All the fire safety arrangement provided there-in shall be maintained in good working

2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.

5. This certificate cannot be treated in any case for regularizations of unauthorized

6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to

7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on WWW.dfs.Delhigovt.nic.in

8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.

9. Electric meter under the staircase must be removed within a period of three months from the date of issuance of the Fire Safety Certificate. Failing to do so the Fire

INSPECTION REPORT

Name & address of the building : MCD Primary School, AK- Block, Shalimar Bagh, Delhi- 110088.

Educational

 Type of Occupancy
 Building Comprised of Ground plus First floor

Renewal 4. Type of Case

F6/DFS/MS/School/WZ/2021/261 dated 26/03/2021 5. Details of Previous NOC 6. Fire Safety directives letter No DOE circular No. 3298-3398 dated 01/03/2011

7. Date of inspection 04/04/2024

R.K.Sinha, ADO (BW) 8. Name of Inspecting Officer

9. Name and designation of officers

From the building side Smt. Shail Gupta (In-charge)

10. Year of Construction 2012

| S. No. | Minimum Standards on fire prevention and fire safety U/R 33 | DOE Requirement | Provided at site | Remarks MR/NMR | | |
|-----------|--|--------------------|----------------------|-------------------|--|--|
| | Access to building | Requirement | | | | |
| 1. | Road width | 6 m | Provided | MR | | |
| | Gate width | 4.5 m | 3.70 m | MR(old case | | |
| | Width of internal road | NA | NA | NA | | |
| 2. | Number, Width, Type & Arrangeme | | | | | |
| | a. Number of staircases | | | | | |
| | Upper Floors | 02 | 02 | MR | | |
| | Basements | NA | NA | NA | | |
| | b. Width of staircases | | | * U | | |
| | Upper Floor | 1.50 m each | Provided | MR | | |
| | Basements | NA | NA | NA | | |
| | c. Protection of exits | | | | | |
| | | NA | NA | NA | | |
| | Fire check door | NA NA | NA NA | NA | | |
| | Pressurization | INA | III | 1111 | | |
| | d. No. of continuous staircases to terrace | 01 | Provided | MR | | |
| | e. Width of Corridor | 1.5 m | Provided | MR | | |
| it. | f. Door Size | 1 m | Provided | MR | | |
| 3. | Compartmentation | 1 | r | | | |
| ٥. | CALLET THE COLUMN TO A CALLET | NA I | NA | NA | | |
| | Fire check door | ATEMOTICS | NA NA | NA | | |
| | Sealing of electrical shafts | NA | | | | |
| | Fire Rating of shaft door | NA | NA | NA | | |
| | Water Curtain | NA | NA | NA | | |
| | Fire Dampers | NA | NA | NA | | |
| 4. | Smoke Management System | | | | | |
| | Basements | NA | NA | NA | | |
| | Upper floors | Required | Naturally Ventilated | MR | | |
| 5. | Fire Extinguishers | | | | | |
| | Total numbers | 07 | 07 | MR | | |
| | Types | ABC/CO2 Type | Provided | MR | | |
| | IS marking | Required | Provided | MR | | |
| j | First-Aid Hose Reels | | | | | |
| | Total numbers on each floor | NA | NA | NA | | |
| | Length of hose reel hose | NA | NA | NA | | |
| | Nozzle diameter | NA | NA | NA | | |
| 7. | Automatic fire detection and alarming system | | | | | |
| | Type of detectors | NA | NA | NA | | |
| | Location of Main Panel | NA | NA | NA | | |
| | The second secon | NA NA | NA | NA | | |
| | Location of Repeater Panel Alternate source of power | NA NA | NA | NA | | |
| | Alternate source of power | | 200 | | | |
| | Hooters' Location | NA | NA | NA | | |

a

N-14

| | | N-14 | | | | |
|-----|---|----------------|--------------------|----------|--|--|
| 8. | MOEFA | NA | NA | NA NA | | |
| 9. | Public Address System | NA | NA | NA | | |
| 10. | Automatic Sprinkler System | | | | | |
| | Basement | NA | NA | NA | | |
| | Ground Floor | NA | NA | NA | | |
| | 2 | NA | NA | NA | | |
| 11. | Sprinkler above false ceiling Internal Hydrants | | | | | |
| | order of the state of the stat | l NA | NA NA | NA NA | | |
| | Size of riser/down-comer | NA NA | NA NA | NA | | |
| | Number of hydrants per floor Hose Box | NA NA | NA | NA | | |
| 12. | Hose Box Yard Hydrants | | | | | |
| 12. | Taid Hydrand | | | NA NA | | |
| | Total number of hydrants | NA NA | NA NA | NA NA | | |
| | Hose Box | NA | IVA | | | |
| 13. | Pumping Arrangements | l' | part in the second | | | |
| | Ground Level | · | | NA | | |
| | Discharge of main Pump | NA | NA NA | NA NA | | |
| | > Head of Main pump | NA | NA | | | |
| | ➤ Number of main pumps | NA | NA | NA | | |
| | > Jockey Pump out put | NA | NA | NA NA | | |
| | > Jockey pump head | NA | NA | NA NA | | |
| | > Standby Pump out put | NA | NA | NA NA | | |
| | > Standby Pump Head | NA | NA | NA NA | | |
| | ➤ Auto Starting/Manual Stopping | NA | NA | NA | | |
| | > Pump House Access | NA | NA | NA | | |
| | Terrace level | | | | | |
| | ➢ Discharge of pump | NA | NA | NA | | |
| | > Head of the pump | NA | NA | NA | | |
| | > Power Supply | NA | NA | NA | | |
| | > Auto Starting of pump | NA | NA | NA | | |
| 14. | Captive Water Storage for fire fighting | 3 | | | | |
| | Underground tank capacity | NA | NA | NA | | |
| | > Draw-off connection | NA | NA | NA | | |
| | > Fire service inlet | NA | NA | NA NA | | |
| | > Access to tank | NA | NA | NA NA | | |
| 15. | Overhead Tank capacity Exit Signage. | NA Required | NA Provided | MR | | |
| | | | | 1 | | |
| 16. | Provision of Lifts. | | LL N | | | |
| | Pressurization of Lift Shaft | NA | NA | NA NA | | |
| | Pressurization of Lift lobby | NA NA | NA NA | NA NA | | |
| | Communication In lift Car | NA NA | NA NA | 1 | | |
| | Fireman's Grounding Switch | NA NA | NA | NA NA | | |
| | Lift Signage | NA NA | NA NA | NA NA | | |
| 17. | Standby power supply | NA | NA | NA | | |
| 18. | Refuge Area. | | | | | |
| | > Total Area | NA | NA | NA | | |
| | > Location | NA | NA | NA | | |

×

| NA | N-15 | | | | |
|-----|---|----------------|----|----|----------|
| | Detector Syst | em Panel | NA | NA | 7 |
| 1 | Flow Switch | Panel | NA | NA | NA NA |
| 1 | PA System P | anel | ŇA | NA | NA NA |
| | Battery backs | ıp - | NA | NA | NA |
| × | Building Flor | or Plans | NA | NA | NA NA |
| 20. | Special Fire Protect Protection of special | ion System for | NA | NA | NA NA |

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

Note: Electric meter found installed under the staircase which have to be removed to a safer place.

Keeping in view of deemed compliance of the minimum standards of fire prevention and fire safety measures as required under DOE circular no. 3298-3398 dated 01/03/2011, it is recommended to renew the Fire Safety Certificate issued vide letter number F6/DFS/MS/2021/School/WZ/370 dated 10/05/2021.

Mention that no file is

Dycfolory pendery.

Abo (Bourana)

Signature of Inspecting Officer Name: Rajeev Kumar Sinha Designation: ADO/B.W.

In. No Poerrovi file in Pender cart one

Dectors

Jan 1914

Any SW fr. FT lette in pure forsonthe Rule.

DOFO!....7.85.....