GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F.6/DFS/MS/Industrial/2024/SZ/ 234

Dated: 18./04./2024

FIRE SAFETY CERTIFICATE

Certified that the M/s Ramayana Handicrafts located at E-40/5, Okhla Industrial Area, Phase-II, New Delhi - 110020 comprised of Basement, ground, Mezzanine, 1st Floor & ½2nd Floor was issued Fire Safety Certificate by this department vide letter No. F6/DFS/MS/SZ/Industrial/2021/216 dated 08/04/2021. The building was re-inspected by the officer concerned of this department on 09/04/2024 in the presence of Mr. Kawaljeet Singh and found to have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy Class - G, Industrial Building with effect from 1.8./.9.4 /2024 for a period of Three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued 18 04 /2024 at New Delhi by

DIRECTOR

Copy to: -

- 1. M/s Ramayana Handicrafts at E-40/5, Okhla Industrial Area, Phase-II, New Delhi 110020
- 2. The Executive Engineer (Bldg.) SDMC, Jal Vihar, Lajpat Nagar, New Delhi 110024

Conditions for the validity of Fire Safety Certificate:

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. The basement shall be used as per the provisions of UBBL-2016 /NBC Part- IV.
- 4. All the staff members must know the correct method of operation of fire fighting system.
- The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL- 2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.
- 7. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (l) of rule 37] along with a copy of this Certificate, six month prior to its expiry."

MA

1	Name & Address of the Building	M/s Ramayar	a Handicrafts E4	0-5, Okhl	
1	hat emily hadayak	M/s Ramayana Handicrafts, E 40-5, Okhla Industrial Area Phase- II, New Delhi 110020.			
2	Type of Occupancy	Industrial (Group - G)			
3	Building Comprised of	Basements, Ground, Mezzanine, First Floor & ½ 2 nd floor			
4	Type of Case	Donovvol			
5	Details of Previous NOC	F6/DFS/MS/SZ/Industrial/2021/216 dated 08/04/202			
6	Fire Safety Directives Letter No	Nil never tradition for period 101			
7	Date of Inspection	09/04/2024			
8	Name of the Inspecting Officers	DO (South) & A			
9	Name & Designation of Officers from the building side	Mr. Kawaljeet Si			
10	Year of construction	1982			
	VENEZI ESTATE DE COMPANION,	Outdoor diary no 14546 dated 22-03-2024			
11	Applicant letter No.			Remarks	
S. No.	Minimum standards on Fire Prevention and Fire Safety U/R 33	NBC / BBL requirement	Figvided in San	MR/NMF	
1	Access to Building.		The state of the state of the	MR	
		9 mtr	Provided	MR (old case	
	Road width	5 mtr	4.5 mtr	-NA-	
	Gate width	-NA-	-NA-	-NA-	
	Width of internal road				
2	Number, width, type & arrangement of exits		A STATE OF THE STA		
	a. Number of Staircase	mesus unitali	sepulgad 3	MR	
	570 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	2 Nos	Provided		
	Upper floors	2 Nos	Provided	MR	
	Basement floor	21100	Traducat 4		
	b. Width of Staircase	Indino d	7 0 0 0 0 mtm	MR (old case	
	Upper floors	1.2 mtr	1.20 & 0.94 mtr	> CD (ald age	
	Basement floor	1.2 mtr	1.20 & 1.1 mtr	MR (old cas	
	c. Protection of exits	Required	Provided	MR	
	Fire check door		have less-NA-	-NA-	
	Pressurization	-NA-		MR	
	d. No. of continuous staircase to terrace	02 Nos	The state of the s	1874	
		-NA-	eq to Dest-NA-	-NA-	
	e. Width of corridor	NA	1 mtr (Final Exit)	NA	
	f. Door size	PHILAG TO B	HERE CHILA		
	Compartmentation.	age for her light	Capthol water stor	MR	
3	Fire check door.	Required	Provided	-NA-	
	Fire check door. Sealing of electrical shafts.	-NA-	-NA-	-NA-	
	Sealing of electrical states. Fire rating of shaft door.	-NA-	-NA-	-NA-	
	Water curtain	-NA-	-NA-	-NA-	
	Fire dampers.	-NA-	-NA-	-147	
	Smoke Management system.	i i i i i i i i i i i i i i i i i i i	nonemit vist	1,1	
4.	La contract of the second of t	30 ACPH	Ex. Fan Provided	MR	
	Basement	12 ACPH	Natural ventilation	MR	
	Upper floors	175.00 H 1 10 HO	desamente »		
5.	Fire Extinguishers.	and the first of	30 Nos	MR	
	Total numbers	Required	THE RESERVE OF THE PARTY OF THE	MR	
1		ABC / Co2	ABC/ Co2 type	THE PROPERTY.	
	Types ISI Marking	ISI Marked	Provided	MR	
	First Aid Hose Reels.	5040		Tit	
6.	FIRST AND LINES ON each floor	01 at each floor	Provided	MR	
	Total numbers on each floor.	30 m	Provided	MR	
	 Length of hose-reel hose. 	5 mm	Provided	MR	
	Nozzle Diameter	3 11111	11011000	14114	
7	Automatic fire detection & alarming system.		HOLD THE SECTION		
- 16-	Type of detectors	Required	Smoke/Heat	MR	
	A LADO OI GOLOGIA				

4//9

		Required	Ground floor	M
	Location of Main Panel	-NA-	-NA-	-N
	Location of Repeater Panel	Required	Provided	M
	Alternate source of power	All Area	Provided	M
	Hooter's location	•	Provided	М
8.	MOEFA	Required	-NA-	-N
9.	Public Address System	-NA-	-NA-	-10/
10.	Automatic Sprinkler System	i ivila	Company (to	
+	Basement	Required	Provided	M
	Upper floors	Required	Provided	M
	Sprinkler above false ceiling	-NA-	-NA-	-NA
11.	Internal Hydrants.	-		100
	Size of Riser / Down-comer	100 mm	Provided	M
	Number of Hydrant per floor	01 Nos.	Provided	MI
6	Hose box.	01 Nos.	Provided	MI
12.	Yard Hydrants.			
	Total number of hydrants.	02 Nos	Provided	MR
	Hose box.	02 Nos	Provided	MF
13.	Pumping arrangements.	Lippi Milli	and diling referen	
	Ground Level	0000 Y 70 4	Provided	MR
	Discharge of main pump.	2280 LPM	Provided	MR
	➤ Head of main pump.	60 M 01 No	Provided	MR
	Number of main pumps.	-NA-	-NA-	-NA
	> Jockey Pump output.	-NA-	Online in -NA-W	-NA
	> Jockey Pump head.	-NA-	mod sor-NA-*	-NA-
	Standby Pump output.	-NA-	-NA-	-NA-
=	 Standby Pump head. Auto Starting/Manual Stopping. 	Required	Provided	MR
- =	> Pump House Access	Required	Provided	MR
-1	Terrace Level		district will a	
	> Discharge of pump.	900 LPM	450 & 900 LPM	MR
	> Head of pump.	40 mtr	30 & 40 m respectively	MR
	> Power supply.	Required	Provided	MR
	> Auto starting of pump.	Required	Provided	MR
14.	Captive water storage for fire fighting.		out the district of the second	
	Underground tank capacity.	1,00,000 Ltrs	1,00,000 Ltrs	MR
	> Draw-off connection.	Required	Provided Provided	MR MR
-	➤ Fire Service Inlet.	Required	Provided	MR
1	> Access to tank.	Required 20,000 Ltrs	20,000 Ltrs.	MR
15.	Overhead tank capacity. E-it Signage	JEAU 73.32	Provided	MR
16.	Exit Signage. Provision of Lifts.	Required	11011000	
10.	Pressurization of lift shaft.	-NA-	-NA-	-NA-
	Pressurization of lift lobby.	-NA-	-NA-	-NA-
	Communication in lift car.	Required	Provided	MR
	Fireman's switch.	Required	Provided	MR
	Lift signage.	Required	Provided	MR
17		Required	Provided (DG Set)	MR
18.	Refuge Area	700 141-34-14	ole of least	
	Total area	-NA-	-NA-	-NA-
	Location	-NA-	-NA-	-NA-
19				
	Detection System Panel	Required	Provided	MR

	V 1/4				
:	 Flow Switch Panel PA System Panel 	Required -NA-	Provided -NA-	MR -NA-	
20.	Battery backup. Building Floor plans Special Fire Protection Systems for Protection of Special Risks, if any. The Green Protection Systems for Protection of Special Risks, if any.	-NA-	-NA-	-NA-	
		-NA-	-NA- 02 ABC type fire	-NA-	
		Required	Extinguisher Near LT Panel	MR	

The fire protection system provided in the building were randomly checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standard on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no F6/DF\$/MS/SZ/Industrial/2021/216 dated 08/04/2021, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature pleas

re of the Inspection Of

Signature of the Inspection Officer Name Sh. Manoj Kumar Sharma

Design: DO (South)

Signature of the Inspecting Officer

Name: Sh. Rajesh Kumar

Design: ADO (BCP)

СГО (НО)

15 41 Som

Director

As approved, F

1. retter in

ontup for

Hord

synature p

18/4/224

Director 101