

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELIII- 110001



No. F6/DFS/MS/School/NDZ/2024/328

Dated: 19/04/2024

#### **FIRE SAFETY CERTIFICATE**

Certified that the Rajkiya Pratibha Vikas Vidyalaya, Located at Surajmal Vihar, Delhi110092, building comprised of ground plus three upper floors owned/occupied by Rajkiya
Pratibha Vikas Vidyalaya, was issued FSC vide letter No. F6/DFS/MS/School/2020/NDZ//122
dated 17/03/2020. The School building was re-inspected by the officer concerned of this department
on 05/04/2024 in presence of Mr. Hariom Sharma (Principal) of the school and found that the
school building have deemed complied with the fire prevention and fire safety requirements in
accordance with Circular no. F.16/Estate/CC/Firesafety/2011/3298 to 3398 dated 01/03/2011 issued
by Director of Education and the school building is fit for occupancy class "Educational Building"
(Group-B) with effect from 10/04/2024 for a period of three years, in accordance with rule 36
unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the
conditions under Rule 38 of the Delhi Fire Service Rules 2010, printed below

Issued on 19 04 2014 at New Delhi by.

(ATUL GARG) DIRECTOR DELHI FIRE SERVICE

### Copy to:-

- 1. The Director of Education, Government of NCT Delhi, Old Sectt., Delhi-110054.
- 2. The Principal, Rajkiya Pratibha Vikas Vidyalaya, Located at Surajmal Vihar, Delhi-110092.

#### Conditions for the validity of Fire Safety Certificate

- 1. The owner /occupier shall apply for renewal of this fire safety certificate to the Director in form J' [sub rule(1) of rule 37] along with a copy of this certificate, six months prior to its expiry
- 2. All the means of escape shall be kept free of all the type of obstruction all the time.
- 3. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 4. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc .may be got verified from the authorities concerned.
- 6. This Fire Safety Certificate cannot be treated in any case for regularizations of unauthorized construction unauthorized use of land if any..
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.

|             |   | INSPI                                   | ECTION REPORT                                |                      |            |  |  |  |  |
|-------------|---|---|--|----------------------|------------|--|--|--|--|
| 01.         | Rajkiya Pratibha Vikas Vidyalaya, Loca        |   |  |                      |            |  |  |  |  |
| Ψ.          |   | A.A.                                    | Ground plus Thre                             | e upper floors       |            |  |  |  |  |
| 02.         |   | ailding is comprised of                 | Educational Build                            |                      |            |  |  |  |  |
| 03.         | Ty  | pe of occupancy                         |  | B                    |            |  |  |  |  |
| 04.         | T   | pe of case                              | Renewal F6/DFS/MS/School/2020/ NDZ/122 dated |                      |            |  |  |  |  |
| 05.         | D   | etails of previous FSC                  | 6 95   | 001/2020/ NDZ/122    | dated      |  |  |  |  |
| φ.          | "   | , man 0 - F                             | 17/03/2020.                                  | - 100111000          | 2209       |  |  |  |  |
|             | E   | re safety directives letter no.         |  | ire safety/2011/329  | 08 to 3398 |  |  |  |  |
| 06.         | FI  | e safety directives                     | dated 01/03/2011.                            |                      |            |  |  |  |  |
|             | _   | C:tion                                  | 05/04/2024                                   |                      |            |  |  |  |  |
| 07.         | Da  | te of inspection                        | Vashwant Singh I                             | Meena ADO (L.N)      |            |  |  |  |  |
| <b>d8</b> . | Na  | me of the inspecting officers           | Mr. Hariom Sharma (Principal)                |                      |            |  |  |  |  |
| 09.         | Na  | me of the designation of                | IVII. Harlom Gian                            | ACCRECANE A S        |            |  |  |  |  |
|             | of  | ficer from the building side            |  |                      |            |  |  |  |  |
| 10.         |   | ear of construction                     | 1995   | 1.4.6.4.9 dated 27/0 | 3/2024     |  |  |  |  |
| 11.         | Aı  | pplicant's letter no.                   |  | .14648 dated 27/03   | Remarks    |  |  |  |  |
| 5.N         |   | Minimum standard of fire                | Requirement                                  | Provided at site     | MR/NMR     |  |  |  |  |
| 0           | p   | revention and fire safety U/R 33        |  | Site                 | a/ana      |  |  |  |  |
| 41          | Δ,  | cess to Building:                       |  | 11                   |            |  |  |  |  |
| 01.         | A   | Road width                              | 6.0 mtrs.                                    | 30 mtrs.             | MR         |  |  |  |  |
| 1           | B   | Gate width                              | NA   | NA                   | NA         |  |  |  |  |
| 1           | C   | Width of internal road                  | NA   | NA                   | NA         |  |  |  |  |
| 02.         | Number, Width, Type and Arrangement of Exits: |   |  |                      |            |  |  |  |  |
| 12.         | A   | Number of staircases                    |  |                      |            |  |  |  |  |
| 1           | A   | 1                                       | 02 nos.                                      | 02 nos.              | MR         |  |  |  |  |
|             | $\vdash$                                      | DEL ICA CAMADOM PRESENTA                | NA   | NA                   | NA         |  |  |  |  |
|             | D   | b Basement Width of staircases          | 17/2   |                      |            |  |  |  |  |
|             | В   | NAARROW 20                              | 1.50 mtrs                                    | 1.50 mtrs, each      | MR         |  |  |  |  |
|             |   | a Upper floor                           |  |                      | antessa.   |  |  |  |  |
|             |   | b Basement                              | NA   | NA                   | NA         |  |  |  |  |
|             | C   | Protection of exits                     |  |                      |            |  |  |  |  |
|             |   | a Fire check door                       | NA   | NA                   | NA         |  |  |  |  |
|             |   | b Pressurization                        | NA .   | NA                   | NA         |  |  |  |  |
|             | D   | No. of continuous staircases to terrace | NA   | NA                   | NA         |  |  |  |  |
|             | E   | Width of corridor                       | 1.50 mtrs.                                   | 1.50 mtrs.           | MR         |  |  |  |  |
| ŀ           | F   | Door size                               | 01 mtrs                                      | 01 mtrs              | MR         |  |  |  |  |
| 3.          |   | npartmentation:                         | or mas                                       | Or mus               | 1 WILC     |  |  |  |  |
|             | A   | Fire check door                         | NA   | N/A                  | NT A       |  |  |  |  |
| ŀ           | B   | Sealing of electrical shafts            | NA<br>NA                                     | NA<br>NA             | NA         |  |  |  |  |
| 1           | C   | Fire rating of shaft door               | NA<br>NA                                     |                      | NA         |  |  |  |  |
| 1           | D   | Water curtain                           |  | NA<br>NA             | NA<br>NA   |  |  |  |  |
| 1           | E   | Fire dampers                            | NA<br>NA                                     | NA<br>NA             | NA         |  |  |  |  |
| 4.          |   | oke Management System:                  | NA   | NA                   | NA         |  |  |  |  |
| 26          | A   | Basement                                | X74 T  |                      |            |  |  |  |  |
|             | B   | Upper floor                             | NA   | NA                   | NA         |  |  |  |  |
|             |   | opport tioot                            | NA   | NA                   | NA         |  |  |  |  |

N/20

# Rajkiya Pratibha Vikas Vidyalaya, Located at Surajmal Vihar, Delhi-110092.

| 05. | A                     | re Extinguisher:  Total numbers           | 13 nos.             | 15 nos.             | / MR        |  |  |  |
|-----|-----------------------|---|---------------------|---------------------|-------------|--|--|--|
|     | B                     | Types                                     | ABC/CO <sub>2</sub> | ABC/CO <sub>2</sub> | MR          |  |  |  |
|     | C                     | ISI marking                               | ISI marked          | ISI marked          | MR          |  |  |  |
| ^   | C ISI marking         |   |                     |                     |             |  |  |  |
| 06. | -                     | Total numbers of each floor               | 01 nos              | 01 nos              | MR          |  |  |  |
|     | A                     | Length of hose reel hose                  | 30 mtrs             | 30 mtrs             | MR          |  |  |  |
|     | B                     | Nozzle diameter                           | 05 mm               | 05 mm               | MR          |  |  |  |
|     | 10.7                  | tomatic Fire Detection and Ala            | 1 24 25 25          |                     |             |  |  |  |
| 07. |                       |   | N/A                 | N/A                 | N/A         |  |  |  |
|     | A                     | Type of detectors  Location of main panel | N/A                 | N/A                 | N/A         |  |  |  |
|     | B                     | Location of main panel                    | N/A                 | N/A                 | N/A         |  |  |  |
|     | C                     | Alternate source of power                 | N/A                 | N/A                 | N/A         |  |  |  |
|     | D                     |   | N/A                 | N/A                 | N/A         |  |  |  |
| 00  | E                     | Hooters                                   | N/A                 | Provided            | MR          |  |  |  |
| 08. | 100                   | OEFA:                                     | N/A                 | Provided            | MR          |  |  |  |
| 09  |                       | blic Address System:                      | IV/A                | Tioridea            |             |  |  |  |
| 10. | Au                    | tomatic Sprinkler System:                 | 1 222               | 27/4                | N/A         |  |  |  |
|     | A                     | Basement                                  | N/A                 | N/A                 | 43/3//34/34 |  |  |  |
|     | В                     | Upper floor                               | N/A                 | N/A                 | N/A         |  |  |  |
|     | C                     | Sprinkler above false ceiling             | N/A                 | N/A                 | N/A         |  |  |  |
| 11. | Internal Hydrants:    |   |                     |                     |             |  |  |  |
|     | A                     | Size of riser/down-comer                  | N/A                 | 100 mm              | MR          |  |  |  |
|     | В                     | Number of hydrants per floor              | N/A                 | 01 nos              | MR          |  |  |  |
|     | C                     | Hose box                                  | N/A                 | 01 nos              | MR          |  |  |  |
| 12. | Vard Hydrants:        |   |                     |                     |             |  |  |  |
|     | A                     | Total number of hydrants                  | N/A                 | N/A                 | N/A         |  |  |  |
|     |                       | Hose box                                  | N/A                 | N/A                 | N/A         |  |  |  |
|     | Pumping Arrangements: |   |                     |                     |             |  |  |  |
| 13. | Cround level          |   |                     |                     |             |  |  |  |
| 1   |                       | Discharge of main pump                    | N/A                 | N/A                 | N/A         |  |  |  |
|     | A<br>B                | Head of main pump                         | N/A                 | N/A                 | N/A         |  |  |  |
|     | C                     | Number of main pumps                      | N/A                 | N/A                 | N/A         |  |  |  |
|     | D                     | Jockey pump out put                       | N/A                 | N/A                 | N/A         |  |  |  |
|     | E                     | Jockey pump head                          | N/A                 | N/A                 | N/A         |  |  |  |
|     | F                     | Standby pump out put                      | N/A                 | N/A                 | N/A         |  |  |  |
|     | G                     | Standby pump head                         | N/A                 | N/A                 | N/A         |  |  |  |
|     | Н                     | Auto starting /manual stopping            | N/A                 | N/A                 | N/A         |  |  |  |
|     | I                     | Pump house access                         | N/A                 | N/A                 | N/A         |  |  |  |
|     |                       |   |                     |                     |             |  |  |  |
| 2   | Ter                   | race Level                                | 450 7 70 4          | 450 T DN4           | / MR        |  |  |  |
|     | A                     | Discharge of pump                         | 450 LPM             | 450 LPM<br>40 m     | MR          |  |  |  |
|     | В                     | Head of the pump                          | 40 m<br>Required    | Provided            | MR          |  |  |  |
|     | C                     | Power supply                              | N/A                 | N/A                 | N/A         |  |  |  |
| t   | D                     | Auto starting of pump                     | IN/A                | IVA                 |             |  |  |  |

Rajkiya Pratibha Vikas Vidyalaya, Located at Surajmal Vihar, Delhi-110092. Captive Water Storage for Fire Fighting: Underground tank capacity N/A N/A N/A Draw-off connection N/A N/A N/A C Fire service inlet N/A N/A N/A Access to tank D N/A N/A N/A Overhead tank capacity 10,000 liters 10,000 liters MR Exit Signage: Required Provided MR 16. Provision of Lifts: Pressurization of lift shaft N/A N/A N/A Pressurization of lift lobby N/A N/A N/A C Communication in lift car N/A N/A N/A Firemen's grounding switch N/A N/A N/A Lift signage N/A N/A N/A Standby Power Supply: N/A N/A N/A Refuge Area: Total area N/A N/A N/A Location N/A N/A N/A Fire Control Room: Detector system panel N/A N/A N/A N/A N/A B | Flow switch panel N/A N/A C | PA system panel N/A N/A N/A N/A N/A D Battery backup N/A N/A Building floor plans N/A N/A N/A Special Fire Protection systems for NA protection of special Risks, if any:

The fire protection systems provided in the school building were tested, checked at random and found functional at the time of inspections.

Keeping in view of the compliance of minimum standards of fire prevention and fire safety measures required as per Circular No. F16/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01/03/2011, under the rules the FSC issued vide letter no. F6/DFS/MS/School/2020/NDZ/122 dated 17/03/2020, renewal under Rule 35 of the Delhi Fire Service Rules 2010, is recommended to be renewed.

No file is pending with me before disposal of this case.

0/4/2024

Signature of the Inspecting Officer Yashwant Singh Meena Name: -

Designation: -

ADO (L.N)

DY. CFOANDZ

up for sign. Aleany