

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110 001

No.F6/DFS/MS/School/NDZ/2024/ 332

Dated: 19 / 04 /2024

FIRE SAFETY CERTIFICATE

Certified that the Sardarni Sada Kaur Khalsa Girls Sr. Sec. School located at Daryaganj, New Delhi, comprised of ground plus + 01 upper floor was granted Fire Safety Certificate by this department vide letter No.- F6/DFS/MS/School/NDZ/2021/188 dated 05.03.2021. The school building was reinspected by the officer concerned from this department on 05.04.2024 in the presence of Mrs. Haritima (Principal) and found that the school building have deemed complied with the fire prevention and fire safety requirements in accordance with the circular No. 262-362 dated 17.01.2005 issued by the Director of Education and the building (Ground floor + 01 upper floor only) is fit for occupancy of Group B "Educational Building" with effect from 19 04 2024 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to conditions under rule 38 of Delhi Fire service Rules, 2010 printed below.

> Delhi Fire Service Tel: 011-234140

Copy to:-

1. The Principal Sardarni Sada Kaur Khalsa Girls Sr. Sec. School at Daryaganj, New Delhi.

2. The Director of Education, Govt. of NCT of Delhi, Old Secretariat, Delhi

Condition for the validity of fire safety certificate

1. The owner /occupier shall apply for renewal of this fire safety certificate to the Director in form J' [sub rule(1) of rule 37] along with a copy of this certificate, six months prior to its expiry

2. All the means of escape shall be kept free of all the type of obstruction all the time.

3. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

4. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.

- 5. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc .may be got verified from the authorities
- 6. This Fire Safety Certificate cannot be treated in any case for regularizations of unauthorized construction
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

	INSPE	CTION REPORT				
		Sardarni Sada Kaur Khalsa Girls Sr. Sec. School located at Daryaganj, New Delhi.				
	Building is comprised of	Ground + 1 upper floor				
	T CO	Group B –Educational Building				
	Tyma of C	Renewal	Building			
	D. 1. 05	P1-12-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-				
	Pi- C C . H	F6/DFS/MS/School/NDZ/2021/188 dated 05.03.2021				
/		Directorate of Education Circular no. 262-362 dated 17.01.2005				
	Date of Inspection	05.04.2024				
3	Name of the Inspecting Officers	Sumit Kumar, ADO (SPM)				
9	Name of the designation of Officer from the building side	Mrs. Haritima (Principal)				
10	Year of Construction	2008				
11 S.No	Applicant's letter No	2008				
	o Minimum Standards on fire	Email dated 27.03.2024				
	safety requirements as per circular no. 262-362 dated 17.01.2005	Requirement	Provided at Site	Remark s MR/N		
1	Access to building			MR		
	Road width	Accessible	06 m			
1	Gate width	Accessible	VACENTAL STATE	MR .		
_	Width of internal road	NA	Provided	MR		
7	Number, Width, Type and Arran	gement of Exits	NA	NA		
	A. Number of Staircases	B				
	Upper Floor	02 no.	-			
-	Basement	NA NA	02 no.	MR		
	B. Width of Staircases		NA	NA		
	Upper Floor	1.20 & 0.90 m	Gr. to terrace – 1.20 m	MR		
	Basement	NA	Gr. to 1st floor- 0.90 m			
	C. Protection of exits	NA	NA NA	NA		
	Fire check door	NA	NA	NA		
	Pressurization D. No. of continuous	NA	NA NA	NA		
	D. No. of continuous staircases to terrace	01 no.	01 no.	NA		
	E. Width of Corridor			MR		
	G. Door size	NA	NA	NA		
3		1 m	1m	200.5		
	Compartmentation			MR		
	Fire check door	NA	NA			
	Sealing of electrical shafts	NA	NA NA	NA		
	Fire rating of shaft door	NA	NA NA	NA		
	Water curtain	NA		NA		
4	Fire Dampers	NA	NA NA	NA		
-	Smoke Management System.		NA	NA		
	Basement	30a/c per hour	NIA			
NA.	1 1 1	Por Hour	NA	X 1 4		
-	Upper floor	12 a/c per hour	NA	NA		

(Su

	Fire Extinguisher	04 no.	06 no.	M			
	Total numbers	N1501	CO ₂ & ABC	M			
	types	CO ₂ & ABC	Provided	MI			
	IS marking	Required	Provided	.,,,,,			
į.	First-aid-Hose Reels.						
	Total numbers of each floor	03 nos.	2 no. at Gr. floor 1 no. at 1 st floor	MF			
	Length of hose reel hose	30 m	30 m	MF			
	Nozzle diameter	05 mm	05 mm	MF			
	Automatic fire detection and alarming system.						
	Type of detectors	NA	NA	NA			
	Location of main panel	NA	NA	NA			
	Location of repeater panel	NA NA	NA NA	NA			
	Alternate source of power	NA NA	NA NA	NA			
	Hooters	NA NA	NA NA	NA			
3	MOEFA	Required	Provided	MR			
9	Public address System.	NA	NA	NA			
10	Automatic Sprinkler System.	1.44	1 1 1	1 11 2			
	basement	NA	NA	NA			
	upper floor	NA	NA NA	NA			
	Sprinkler above false ceiling	NA	NA NA	NA			
11	Internal Hydrants						
	size of riser/down-comer	NA	NA	NA			
	Number of hydrants per floor	NA NA	NA NA	NA			
	Hose Box	NA	NA NA	***************************************			
12	Yard Hydrants.		INA	NA			
10/4/01	Total number of hydrants	NA	NA				
	Hose Box	NA NA		NA			
13	Pumping Arrangements.	INA	NA	NA			
10	Ground Level						
	➤ Discharge of main Pump	NA	5.0				
	➤ Head of Main Pump	Section 1	NA	NA			
	> Number of main pumps	NA	NA	NA			
	> Jockey pump out put	NA	NA	NA			
	> Jockey pump head	NA	NA	NA			
	 Standby pump out put 	NA NA	NA	NA			
	> Standby pump Head	NA NA	NA	NA			
	> Auto Starting /Manual	NA NA	NA	NA			
	stopping	INA.	NA	NA			
	> Pump House Access	NA	NA	NTA			
	Terrace Level Discharge			NA			
	Discharge of pump	225 LPM	225 LPM	MD			
	➢ Head of the Pump➢ Power supply	40 m	40 m	MR MR			
	> Auto Starting of pump	Required	D 11 1	MR			
	Auto Starting of pump	Required	Provided	TATE			

W.

	Underground tank capacity	NA	NA	NA
[Draw-off connection	NA	NA	NA
	Fire service inlet	NA	NA	NA
	Access to tank	NA	NA	NA
	Overhead Tank capacity	3,000 liters	3,000 liters	MR
15	Exit Signage.	Required	Provided	MR
16	Provision of Lifts.			
	Pressurization of Lift Shaft	NA	NA	NA
	Pressurization of Lift lobby	NA	NA	NA
	Communication in lift car	NA	NA	NA
	Firemen's grounding switch	NA	NA	NA
	Lift Signage	NA	NA	NA
17	Standby power supply	NA	NA	NA
18	Refuge Area.			
	Total area	NA	NA	NA
	Location	NA	NA	NA
19	Fire Control Room			
	Detector system panel	NA	NA	NA
	Flow switch panel	NA	NA	NA
	PA system panel	NA	NA	NA
	Batter backup	NA	NA _	NA
	Building Floor Plans	NA	l NA	NA

There are two building blocks and 10 temporary sheds inside the school premise out of which eastern block is abandoned and western block is used for school. The sheds are used as classroom however only the western block is being considered for FSC in this inspection. This building block comprises of ground plus one upper floor + one room vacant room on the terrace (previously used as generator room).

The fire protection systems provided in the building were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required in Directorate of Education Circular no. 262-362 dated 17.01.2005, the FSC issued vide letter No. F6/DFS/MS/School/NDZ/2021/188 dated 05.03.2021, renewal under Rule 35 of Delhi Fire Service Rules 2010, is recommended.

sir, no file is bending with me, before disposal of this file.

Signature of the Inspecting Officer

Name

Sumit Kumar

Designation ADO (SPM)

DO (CD)

84/24

Dice (2005)

15 41 (204

Director Miles

Anysonn