FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE, NEW DELHI

No. F6/DFS/MS/School/2024/SW 330

Dated: (9/04/2024

ethi Fire Service

FIRE SAFETY CERTIFICATE

Certified that the building of St. Mary's Sr. Secondary School Located at Sector – 19, Dwarka, New Delhi – 110075, comprised of Basement + Ground + 02 Upper Floor was issued Fire Safety Certificate vide letter No. F6/DFS/MS/School/2019/SZ/290, dated 05/02/2019. The premises was re inspected by the officer concerned of this department on 08/04/2024 in the presence of Ms. Seema Bali (V.Pricipal) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Educational" with effect from 19 04 10 11 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ... 19/04/2024 at New Delhi by.

Copy to: -

1. The Principal, St. Mary's Sr. Secondary School at Sector - 19, Dwarka, New Delhi - 110075.

The Finicipal, St. Iviary Sol. Secondary States of NCT of Delhi, Old Secretariat, New Delhi-110054.
 The Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi-110054.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

3. The trained staff should be available round the clock.

- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

6. Basement shall be used as per building by laws.

7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

8. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expired.

INSPECTION REPORT

 Name & address of the building: St. Mary's Sr. Secondary School Located at Sector – 19, Dwarka, New Delhi – 110075.

2. Type of Occupancy: Educational (Basement + Ground+ 2 Upper Floors)

3. Type of Case : Renewal

4. Details of previous NOC: F6/DFS/MS/School/2019/SZ/290, dated 05/02/19

5. Fire Safety directives Letter No.: F6/DFS/MS/BP/97/56, dated 15/01/1997

6. Date of inspection : 08/04/2024

7. Name of the Inspecting Officer :Sh. Udai vir singh, ADO (DWK)

8. Name and designation of Officer

from the building side: Ms. Seema Bali (V.Pricipal)

9. Year of Construction :2003

10. Applicant's letter No. : Nil dated 22/03/2024

	Minimum standards on fire prevention and fire safety U/R			As per N/6, N/7 & N/8		Provided at site		Remarks MR/NMR			
110.7	ccess of building						8				
· ·		09 mtr	mtr Provided			MR					
			mtr Provided		ded	MR					
	Width of internal road	06 mt	r	Provi		506	MR				
. 1	Number, width, Type & Ar	ranger	nents	of exit	S	*					
	a. Number of staircaseUpper floors	es	04 Nos. Provide			:d			MR		
	Basementsb. Width of staircases		4 Nos	_		Provided			MR		
-			F	anah	Dro	vided	T.			MR	
- 1	Upper floorsBasements		1.0			ovided			MR		
	c. Protection of exits	11	The state of the s								
3	 Fire check door Pressurization d. No of continuous staircase to terrace e. Width Of Corridor f. Door Size 		NA			NA			NA NA		
			NA			NA				IA_	
1			04 Nos.			Provided			1	ИR	
			1.5 m Provid			ded			MR		
						Provided N			MR.		
	The second secon	•		W					NTA	_	
3.	Fire check door Sealing of electrical shafts Fire Rating of shaft do Water Curtain Fire Dampers		: NA			NA			NA		
			NA			NA			NA		
			oor NA			NA			NA		
			NA NA			NA			NA		
			NA NA			NA			NA		
	Smoke managements Sys	stem				- 1				MR	
4.	Basements Upper floors	- 1	Required Required			Provided Natural ventilation				MR	
5.	Fire Extinguishers	1 50		y.			e.	. 1		-	



MILY

	Fire Exting	uishers		_		114	١				Ų	_
		al numbers	04 n	06 4	angh f	loor	I p.	-ovided		MR		-
		oes						Provided ABC & CO ₂ ISI marked		MR MR		_
	• IS 1	marking	ISI	narl	narked							
	First - Aid	Hose Reels		-141			10	oi illaik	cu	17110		-
1	The state of the s	tal numbers on ea	ch	02	Nos.		T	Provide	d	MR	-	
1	flo			_	mtr		_	Provide	0.5	MR		+
4.7	• Le	ngth of hose reel l	hose		mm			Provide	CV.	MR		4
	• No	zzle diameter	nosc	0.5	1111111		1	riovide	u	IVIK		
7.	Automatic	fire detection and	d alarmi	nos	zveten	,						_
	• Ty	pe of detectors	- 41441111		NA		IN	JA.		NA	_	2
	Location of Main Panel				NA.			NA		NA NA		
		cation of Repeate			NA			NA.		NA		
	• Al	ternate source of	power		NA	1796		NA.		NA		-
	. • Ho	oters' Location			NÁ		_	NA.		NA		_
8.	MOEFA	_		-	NA	NA	11 165	22.0		NA		_
9.	Public Ad	dress System		_	NA NA				NA NA		_	
10.	Automatic	c Sprinkler Syster	n		1111	TALX				INA		
		asements	Require	ed	P	rovide	ed			MR	()	
	Upper Floor NA				NA NA			A G		NA .		-
		orinkler above	NA			· N	0.16760			NA		
	fa	lse ceiling	and the same of th				and the second			1 12 1		-
11.	Internal F	lydrants:		¥.					-	_		
	• Si	ze of riser/down-	comer		NA			NA			N	A
	• N	umber of hydrant	s per		NA			NA		-	N	
	fle	oor									872	11 T
		ose Box			NA.	01		NA			N.	A
12.	Yard Hyd	Irants							-		8,470	10.000
2	• T	N	NA NA			NA						
		ose Box		N	A			NA		NA		
13.	Pumping	Arrangements:				*						_
		round Level									.4	
	• D	ischarge of main	pump	NA				N.	A			NA
		ead of main pum		NA				N.	A		_	NA
		umber of main pu		NA	2.04			N.	A		_	NA
		ockey pump out p		NA		()		N.	A			NA
		ockey pump head		NA				N.	A	_	_	NA
		tandby Pump out		NA				N	A		_	NA
		tandby Pump Hea		N/	and the same of th			N	A		_	NA
		uto staring/Manu	iai	'NA	1			· N	A	- 17	_	NA
		topping										00
		ump House Acce	SS	N/	4			N	Α			NA
		errace level			4							
(9)		Discharge of pump			900 lj	om:	Pro	vided			M	R
		lead of the pump			mtr		Pro	Provided				R
		ower supply			quire		Pro	vided			M	
		uto starting of pu		Re	equire	d	Pro	vided			M	
14.		water Storage for					9					2007
	Under ground tank			50,000 ltr				Provided			MR	
	capacity			NA				NA	NA			
		Draw off connecti	on	NA ·				NA	NA NA			
		ire service inlet		1	NA			NA			N/	
	> A	access to tank		35,000 ltr				Provided			M	
			2									

15	Exit Signage	Required Pro		rovided		MR		
16.	Provision of Lifts							
1	 Pressurization of Lift Shaft 			NA		NA		
	> Pressurization of lift lobby			NA	NA			
ai i	Communication in lift Car			Provided	MR MR MR			
	➤ Fireman's Grounding Switch			Provided Provided				
	➤ Lift Signage							
7.	Standby power supply	Required		DG Set		MR		
8.	Refuge Area							
	➤ Total area	NA		NA NA				
¥	Location	NA		NA NA				
9.	Fire control room	18		5.53	K			
6	Detector system panel	NA		NA		NA		
	> Flow Switch Panel	NA NA NA NA		ŅA	NA .			
	> PA System Panel			NA	NA NA			
	➤ Battery backup			NA				
	➤ Building Floor Plans			NA	NA			
20.	Special Fire Protection Systems for Protection of special Risks, if any;	Required C		2 & ABC, F nguisher pro electric par	MR			

The fire protection systems provided in the building were test checked and found

functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire issued vide letter No. the FSC the rules under required safety F6/DF\$/MS/School/2019/SZ/290, dated 05/02/2019 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended. If approved FSC may be issued.

Sign of Inspecting Officer Name Designation Apolowy