

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001



No. F6/DFS/MS/EH/WZ/2024 | 14

Dated: 19 / 04 /2024

FIRE SAFETY CERTIFICATE

Certified that the M/s. Haldiram Products Pvt. Ltd. located at C-4, Rajouri Garden, New Delhi-110027, is running at Ground floor in a building comprised of Basement, Ground & three upper floors owned/occupied by M/s. Haldiram Products Pvt. Ltd., was issued Fire Safety Certificate vide Letter No. F6/DFS/MS/EH/WZ/2021/185 dated 16/08/2021, The premises was re-inspected by officer concerned of this department on 12/04/2024 in the presence of Sh. Sudhir Sharma and found that the said building/Premises have deemed complied with the fire prevention & fire safety requirements in accordance with Rule 33 of Delhi Fire Service Rule 2010 & the said premises is fit for occupancy class "Assembly" Group - D (Ground Floor Only) and valid upto 31/03/2027 in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010 condition mentioned below.

Issued on 19104 2024 at New Delhi by.

Copy to:

- 1. The Owner/occupier Haldiram Products Pvt. Ltd. located at C-4, Rajouri Garden, New Delhi-110027.
- 2. The Joint Commissioner of Police, Licensing Unit, 1st floor, Police Station, Defence Colony, New Delhi. (addlcp.lic-dl@nic.in.
- 3. The Dy. Health Officer, MCD, West Zone, Vishal Enclave, Rajouri Garden, New Delhi 110027. (dhowest zone@gmail.com)

Following Fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

	_		N	5				
		<u>II</u>		CTION REPORT				
1.	Nam	e & address of the building	Haldiram Products Pvt. Ltd. located at C-4, Rajouri Garden, New Delhi-110027.					
2.	Туре	of Occupancy	Assembly					
-			Rene	ewal				
Type of Case Details of previous NOC				F6/DFS/MS/EH/WZ/2021/185 dated 16/08/2021				
			Nil					
		Safety directives letter No						
3-5		of inspection		4/2024	40	N		
	Nam	te of the Inspecting Officers te and designation of ters from the building side	Sarabjeet Singh ADO (MN) Sh. Sudhir Sharma					
9.	Year	of Construction	2010	(As per MHA Po	rtal)			
10	. Appl	icant's letter No.	Onli	ne Application ID	No.	2024032903764 date	ed 29/03/2024	
* T	The Se	id Restaurant is running at	gralit	nd floor in a build	ding	comprised of Basen	nent +	
S.	Fround M	d + 03 upper floors. Iinimum Standards on fire	I	Required as per Ri 5(6) of DFS Rule 2	ule	Provided at site	Remarks MR/NMR	
No.		ention and fire safety U/R 3	3 3.	3(0) 01 D1 3 14410 =				
1	Acce	ss to building	11.	06m		Provided	MR	
	•	Road width Gate width		05m		Provided	MR	
-		Width of internal road		NA NA		Provided	MR	
•	N	ber, Width, Type & Arrang	remen					
2	a Nu	mber of staircases	,cmen				371	
	•	Upper Floors		NA		NA (G.F.)	NA	
				NA		NA	NA	
	b. W	idth of staircases		NA		NA (CE)	NA	
	•	Upper Floors		NA NA		NA (G.F.)	NA	
		Basements		INA		NA	IM	
	c. Pro	otection of exits		. NA		NA	NA	
	•	Fire check door		NA		NA	NA	
	•	Pressurization		NA		NA	NA	
	130000000000000000000000000000000000000	of continuous staircases to ter	rrace	NA		NA	NA	
	1:50%	idth of Corridor oor Size		2m & 1.5 m	Pro	ovided (2m & 1.60m)	MR	
•	-							
3	Com	partmentation.		NA		NA	NA NA	
	•	Fire check door		NA		NA	NA	
	•	Sealing of electrical shafts		NA		NA	NA	
		Fire Rating of shaft door		NA		NA	NA	
		Water Curtain Fire Dampers		NA		NA	NA	
1	-			7 - 7	_	Section 1. Property		
4	эшо	ke Management System. Basements		NA		NA	NA	
	•	Upper floors		Required		Provided	MR	
5	Di-							
5		Extinguishers Total numbers		05 Nos.		Provided	MR	
	•			THE STATE OF THE S		Provided	7	
	, •	->		CO ₂ , ABC type ISI marked	-		MR	
	•	IS marking		131 marked		Provided	MR	

	First-Aid Hose Reels.	6	0.1	
-		01	/	1
	Total numbers on each floor		Provided	MI
	Length of hose reel hose	30m	Provided	MI
	Nozzle diameter	5mm	Provided	M
	Automatic fire detection and alarmin			1 27
	 Type of detectors 	NA	Provided	NA NA
	 Location of Main Panel 	NA	Provided	NA NA
	 Location of Repeater Panel 	NA	Provided	NA NA
- 1	 Alternate source of power 	NA	Provided	NA NA
	Hooters' Location	NA	Provided	NA
	MOEFA	Required	Provided	MR
	Public Address System.	NA	NA	NA
0	Automatic Sprinkler System.			
	Basement	NA	Provided	l NA
	Upper Floor	NA NA	Provided	NA
	 Opper Floor Sprinkler above false ceiling 	NA	Provided	NA
1	Internal Hydrants	I NA I		500000
1		100mm	Provided	MR
	Size of riser/down-comer	01	Provided	MR
	Number of hydrants per floor	01	Provided	MR
	Hose Box	or .	71011404	31270
2	Yard Hydrants.	I NA I	NA	l NA
	 Total number of hydrants 	NA	NA NA	NA NA
	Hose Box	NA	NA	INA
3	Pumping Arrangements.			
	Ground Level	· · ·		T
-	> Discharge of main Pump	NA	NA	NA NA
	> Head of Main pump	NA	NA	NA NA
	> Number of main pumps	NA	NA NA	NA NA
N.	> Jockey Pump out put	NA	NA NA	NA NA
	Jockey pump headStandby Pump out put	NA	NA NA	NA NA
	 Standby Pump out put Standby Pump Head 	NA	NA NA	NA NA
	> Auto Starting/ Manual stopping	NA	NA NA	NA NA
	> Pump House Access	, NA	NA NA	NA NA
	Terrace level	NA NA	NA	INA
	> Discharge of pump	450 LPM	Provided	MR
	Head of the pump	450 LPM 40 m	Provided	MR
	> Power Supply	Required	Provided	MR
	> Auto Starting of pump	Required	Provided	MR
14	Captive Water Storage for fire fighting	1100-110-110-110-110-110-110-110-110-11		
- constitu	Underground tank capacity	NA I	NA	NA
	> Draw-off connection	NA NA	NA	NA
	> Fire service inlet	NA NA	NA	NA
	> Access to tank	NA	NA	NA
	Overhead Tank capacity	20,000ltr	Provided	MR
15	Exit Signage.	Required	Provided	MR

_			218					
5	Provis	ion of Lifts.	(F)					
		Pressurization of Lift Shaft	NA	NA	NA			
	•	Pressurization of Lift lobby	NA	NA	NA			
		Communication In lift Car	NA	NA	NA			
	a -	Fireman's Grounding Switch	NA	NA	NA			
		Lift Signage	NA	NA	NA			
17	Stand	by power supply	Required	Provided	MR			
18	Refuge Area.							
	> ×	Total Area	NA	NA	NA			
	-	Location	NA	NA	NA			
19	Fire Control Room							
		Detector System Panel	NA	NA	NA			
		Flow Switch Panel	NA	NA	NA			
		PA System Panel	NA	NA	NA			
		Batter backup	NA	NA	NA			
		Building Floor Plans	NA NA	NA	NA			
20	Specia	I Fire Protection Systems for tion of special Risks, if any:	Required	Fire Extinguisher provided near Electric Pannel.	MR			

The fire protection systems provided in the building were checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required under the rules, the NOC vide letter no F6/DFS/MS/EH/WZ/2021/185 dated 16/08/2021 renewal under the rule 35 of the Delhi Fire Service rules 2010 is recommended.

Qy crg/wiv)

13/4

Signature of the Inspecting Officer

Name: Sarabjeet Singh Designation: ADO (MN)

10/04/20