

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2024/ 98

Dated: 23/04./2024

FIRE SAFETY CERTIFICATE

Certified that the Hotel Ashiana Guest House located at 50, Arakashan Road, Pahar Ganj, New Delhi comprised of G+ 4 & 5th floor (sealed), Ground floor (Reception + 06 guest rooms), 1st floor to 3rd floor (07 guest rooms at each floor) and 4th floor & above not in use as per affidavit dated 30.12.2019, total 27 guest rooms up to third floor, was earlier granted FSC by this department vide letter No.F6/DFS/MS/GH/2021/NDZ/138 dated 16/03/21. Now, the premises was re-inspected by the officer concerned of this department on 12/04/24 in the presence of Manager and found that the said guest house building has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as Ground floor (Reception + 06 guest rooms having single beds), 1st floor to 3th floor (07 guest rooms at each floor), Total 27 guest rooms up to third floor only, and valid up to 31.03.2027 from the date of issue in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 23 04 2027 at New Delhi by.

Delhi Fire Service

Copy to:-

1. The Commissioner, MCD, Civic Centre, New Delhi: to kindly ensure the occupancy as detailed above and deviation if any.

2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. ID no.

2024033103908 dated 31/03/24.

3. The Manager, Hotel Ashiana Guest House at 50, Arakashan Road, Pahar Ganj, New Delhi.

Conditions for the validity of Fire Safety Certificate

- All the fire safety arrangements provided therein shall be maintained in good working conditions at all
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned.

5. This fire safety certificate may not be treated in any case for regularization of unauthorized

construction, if any.

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.

8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

9. Any flammable material for interior decoration is prohibited.

N142

INSPECTION REPORT

1. Name & address of the building Ashiana Guest House at 50, Arakashan

Road, Pahar Ganj, New Delhi 2. Type of occupancy:-Residential, Sub Division-A-1 G+4 & 5th floor (sealed)

Ground floor (Reception + 06 guest rooms, 1st floor to 3rdth floor (07 guest rooms at each floor) total 27guest room. 4th floor & above not in use as

per affidavit dated 30.12.2019,

Type of case:-Renewal

4. Details of previous FSC:-No.F6/DFS/MS/GH/2021/NDZ/138

dated 16/03/21

5. Fire safety directives No.-N/A

6. Date of inspection:-12/04/24

Sh. Ravinder Singh(ADO/CC) 7. Name of the inspecting officer:-

8. Name & designation of officer from the building side:-Manager

9. Year of construction:-1991

31/03/24. Online id: 2024033103908 dated 10. Applicant's letter No:-Old Case

Remarks Provided at site Requirement/ Minimum Standards on fire S.N MR/NMR Existing fire safety Prevention and fire safety 0. arrangements U/R 33 Access to Building 1. N/A 04 mtr. N/A 1) Road width N/A N/A N/A 2) Gate width N/A N/A N/A 3)Width of internal road Number, Width Type & Arrangement of Exits 2. A. Number of staircases MR 01 Nos. 01 Nos. 1. Upper floors N/A N/A N/A 2. Basements B. Width of staircase MR 1.25 mtr. / 0.80 mtr. 1. Upper floors N/A N/A N/A 2. Basements C. Protection of exits MR Provided Required 1. Fire check door N/A N/A N/A 2. Pressurization MR 01 01 D. No. of continuous staircase to terrace MR 1.0 mtr. 1.0 mtr. E. Width of corridor 1.0 mtr. MR 1.0 mtr. F. Door size Compartmentation 3. N/A N/A 1) Fire check door N/A N/A N/A N/A 2) Sealing of electrical shafts 3) Fire rating of shaft door N/A N/A N/A 4) Water curtain N/A N/A N/A 5) Fire Dampers N/A N/A N/A Smoke Management System 4. 1) Basements N/A N/A N/A 2) Upper floors 12 ACPH Natural MR Fire Extinguishers 5. 1) Total numbers 30 Nos. 34 Nos. MR 2) Types ABC & CO2 ABC & CO2 MR

-	20
L	

	3) ISI marking	Required	Provided	MR
6.	First-Aid Hose Reel		1	_
	1) Total number of eachfloor	01	01	MR
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR
	3) Nozzle diameter	05 mm	UJ IIIII	MR
7.	Automatic Fire Detection & A	Marming System	1	1
	1) Type of detectors CO type	Required	Provided	MR
	2) Location of main panel	Required	Provided	MR
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	Required	Provided	MR
	5) Hooter's Location	at each floor		MR
8.	MOEFA	Required	Provided	MR
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System			27/4
10.	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A N/A
	3) Sprinkler above false ceiling	N/A	N/A	INA
11.	Internal Hydrants		1.00	N/A
11.	1) Size of riser/down-comer	N/A	100 mm	N/A
	2) Number of hydrants per floor	N/A	01	N/A
	3) Hose box	N/A	01	10.1
12.	Vard Hydrants	15771	N/A	N/A
	Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	1071	
13.	Pumping Arrangement	N/A	N/A	N/A
13.	Ground level	N/A N/A	N/A	N/A
	a) Discharge of main	N/A		
	pump	N/A	N/A	N/A
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pump	N/A	N/A	N/A
	d) Jockey pump out put e) Jockey pump head	N/A	N/A	N/A N/A
	11	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual	N/A	N/A	1071
	stopping 2) Terrace level	15-2-5	450 I D) (MR
	n: 1 of numn	450 LPM	450 LPM	MR
	b) Head of pump	30 mtr.	30 mtr. /	MR
	a) Power supply	Required	Provided	MR
	d) Auto starting of pump	Required	Plovided	
	Captive Water Storage for Fire	Fighting	NIA	N/A
14.	1) Under ground tank capacity	14/21	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A

	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
u. U. s	d) Over head tank capacity	2500 ltr.	2500 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
,	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
197 A	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Sys Risk, if any: ABC & Co2		ction of special	MR

The fire protection systems provided in the building were randomly tested, checked and

found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if approved, we may renew the FSC issued vide letter no. No.F6/DFS/MS/GH/2021/NDZ/138 dated 16/03/21, under rule 35(6) of the Delhi Fire Service rules 2010 Accordingly, DFA is put up for kind perusal and signature please.

Signature of the Inspecting Officer

Name: - Sh. Ravinder Singh

Designation: ADO (CC)