GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2024/ 9 |

Dated: 1.9./94./2024

FIRE SAFETY CERTIFICATE

Certified that the Nirmal Mahal, 1519, Gali Sangtrashan, Pahar Ganj, New Delhi comprised of Ground + 04 Upper floors, Ground floor – reception + 02 guest rooms, 1st floor to 3rd floor 04 guest rooms at each floor & 4th floor not in use as per affidavit dated 18.03.2021 total 14 guest rooms, was earlier granted by this department vide letter No. F6/DFS/MS/GH/2021/NDZ/160 dated 26/03/2021 for 14 guest rooms up to third floor only. Now, The premises was re-inspected by the officer concerned of this department on 09/04/24 in the presence of Manager and found that the said guest house building has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential (Sub Division-A-1) Ground floor (02 guest rooms) 1st floor to 3rd floor (04 guest rooms at each floor), Total 14 guest rooms up to third floor only, and valid up to 31.03.2027 from the date of issue in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued ... 19. 04 2024 ... at New Delhi by.

DIRECTOR Delhi Fire Service

Copy to:-

- The Commissioner, MCD, Civic Centre, New Delhi: to kindly ensure the occupancy as detailed above and deviation if any.
- The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. ID no. 2024031002817 dated 26/03/24.
- 3. The Manager, Nirmal Mahal, at 1519, Gali Sangtrashan, Pahar Ganj, New Delhi.

Conditions for the validity of Fire Safety Certificate

- All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- Any flammable material for interior decoration is prohibited.

INSPECTION REPORT

1. Name & address of the building Nirmal Mahal, 1519, Gali Sangtrashan, Pahar Ganj, New Delhi.

2. Type of occupancy:-

Residential Group A-1 Ground + 4 upper floor (14 guest rooms) ground floor reception + 02 guest rooms, 1st floor to 3rd floor (04 guest rooms at each floor),4th floor not in use as per affidavit

dated 18.03.2021.

3. Type of case:-

Renewal

4. Details of previous FSC:-

No.F6/DFS/MS/GH/2021/NDZ/160 dated

26/03/2021

5. Fire safety directives No.-

N/A

6. Date of inspection:-

09/04/24

7. Name of the inspecting officer:-

Sh. Ravinder Singh (ADO/CC)

8. Name & designation of officer

From the building side:-

Minimum Standards on fire

Manager

2013

Requirement/

9. Year of construction:-10. Applicant's letter No:-

5) Fire Dampers

1) Basements

2) Upper floors

Fire Extinguishers

4.

5.

Smoke Management System

S.No.

ID no. 2024031002817 dated 26/03/24.

Provided at site

Old Case Remarks

N/A

MR

MR/NMR Existing fire Prevention and fire safety safety U/R 33 arrangements Access to Building 1. MR 06 mtr. N/A 1) Road width N/A N/A N/A 2) Gate width N/A N/A N/A 3)Width of internal road Number, Width Type & Arrangement of Exits 2. A. Number of staircases MR 01 Nos. 01 Nos. 1. Upper floors N/A N/A N/A 2. Basements B. Width of staircase MR 1.17to 1.30 mtr. 80cms. 1. Upper floors N/A N/A N/A 2. Basements C. Protection of exits N/A N/A N/A 1. Fire check door N/A N/A N/A 2. Pressurization N/A N/A N/A D. No. of continuous staircase to terrace N/A N/A E. Width of corridor N/A MR 1.0 mtr. 1.0 mtr. F. Door size Compartmentation 3. N/A N/A N/A 1) Fire check door N/A N/A 2) Sealing of electrical shafts N/A N/A N/A 3) Fire rating of shaft door N/A N/A N/A N/A 4) Water curtain N/A N/A

N/A

30 ACPH

Required

N/A

Provided

4/22

	1) Total numbers	08 Nos.	10 Nos.	MR
	2) Types	ABC & CO	2 ABC & CO2	MR
	3) ISI marking	Required	Provided	MR
	3) 151 marking		l l	
	First-Aid Hose Reel			
6	1) Total number of eachfloor	01	01	MR
		30 mtr.	Provided	MR
	2) Length of hose reel hose	Jo ma.	//	
	20.50 1 11 4-4-	05 mm	Provided	MR
	3) Nozzle diameter	US IIIII	Tiovided	IVIIC
_	Automatic Fire Detection &	Alarming Sys	tem	
	1) Type of detectors CO type	Required	Provided	MR
	2) Location of main panel	Required	Provided	MR
		N/A	N/A	N/A
	3) Location of repeater panel	5/3/3/00 D	Provided	MR
	4) Alternate source of power	Required		MR
	5) Hooter's Location	at each floor	Provided	
3.	MOEFA	Required	Provided	MR
).	Public Address System	Required	Provided	MR
0.	Automatic Sprinkler System			
	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling			
1.	Internal Hydrants			
	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per	N/A	N/A	N/A
	floor		14	
	3) Hose box	N/A	N/A	N/A
12.	Yard Hydrants			
	1) Total number of hydrants	N/A	N/A	N/A
_	2) Hose box	N/A	N/A	N/A
3.	Pumping Arrangement	0		
	1) Ground level	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	N/A
	pump			
	b) Head of main pumpc) Number of main pump	N/A	N/A	N/A
	(a) Number of main pump	N/A	N/A	N/A
				The second secon
	d) Jockey pump out put	N/A	N/A	N/A
	d) Jockey pump out put e) Jockey pump head	N/A N/A	N/A N/A	The second secon
	d) Jockey pump out put e) Jockey pump head f) Stand by pump output	N/A N/A N/A	N/A N/A N/A	N/A N/A N/A
	d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head	N/A N/A N/A N/A	N/A N/A N/A N/A	N/A N/A N/A N/A
	d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual	N/A N/A N/A	N/A N/A N/A	N/A N/A N/A
	d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping	N/A N/A N/A N/A	N/A N/A N/A N/A	N/A N/A N/A N/A
	d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level	N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A
	d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump	N/A N/A N/A N/A N/A 450 LPM	N/A N/A N/A N/A N/A 450 LPM	N/A N/A N/A N/A N/A
	d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply	N/A N/A N/A N/A N/A 450 LPM 30 mtr.	N/A N/A N/A N/A N/A 450 LPM 30 mtr.	N/A N/A N/A N/A N/A MR
-	d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump	N/A N/A N/A N/A N/A N/A A N/A A A A A A	N/A N/A N/A N/A N/A N/A 30 mtr. Provided	N/A N/A N/A N/A N/A N/A MR MR
4.	d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for Fi	N/A N/A N/A N/A N/A N/A A N/A A A A A A	N/A N/A N/A N/A N/A 450 LPM 30 mtr.	N/A N/A N/A N/A N/A MR
4.	d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for Fi 1) Under ground tank	N/A N/A N/A N/A N/A N/A A Solution N/A N/A A N/A A Solution A Solu	N/A N/A N/A N/A N/A N/A A So LPM 30 mtr. Provided Provided	N/A N/A N/A N/A N/A MR MR MR MR
4.	d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for Fi 1) Under ground tank capacity	N/A N/A N/A N/A N/A N/A A Solution N/A N/A A N/A A Solution A Solu	N/A N/A N/A N/A N/A N/A 30 mtr. Provided	N/A N/A N/A N/A N/A N/A MR MR
4.	d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for Fi 1) Under ground tank capacity	N/A N/A N/A N/A N/A N/A A N/A A A A A A	N/A N/A N/A N/A N/A N/A A So LPM 30 mtr. Provided Provided	N/A N/A N/A N/A N/A MR MR MR MR



		11100		_
	c) Access to tank	Required	Provided	MR
	d) Over head tank capacity	5,000 ltr.	5,000 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			/
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for Protection of special Risk,			N/A

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

if any: ABC & CO2

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if approved, we may renew the FSC issued vide letter no. No.F6/DFS/MS/GH/2021/NDZ/160 dated 26/03/2021 under rule 35(6) of the Delhi Fire Service rules 2010 Accordingly, DFA is put up for kind perusal and signature please.

Signature of the Inspecting Officer

Name: Ravinder Singh

Designation: ADO (CC)