

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/NDZ/2024/ 104

Dated :30./94./2024

FIRE SAFETY CERTIFICATE

Certified that the Tushar Continental Guest House located at 2677, Gali no. 8, Chuna Mnadi, Pahar Ganj, New Delhi comprised of Ground + 03 Upper floors, Ground floor (02 guest rooms), 1st floor to 3rd floor (04 guest rooms at each floor), total 14 guest rooms owned/occupied by Guest was earlier House granted FSC by this department No.F6/DFS/MS/GH/NDZ/2021/186 dated 22/04/21. Now, the premises was re-inspected by the officer concerned of this department on 22/04/24 in the presence of Manager and found that the said guest house building has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 Ground floor (02 guest rooms), 1st floor to 3rd floor (04 guest rooms at each floor), total 14 guest rooms only and valid up to 31.03.2027 from the date of issue in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued ... 30/04/2024 at New Delhi by.

Delhi Fire Serv

Copy to:-

- 1. The Commissioner, MCD, Civic Centre, New Delhi: to kindly ensure the occupancy as detailed above and deviation in construction if any.
- 2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. ID no. 2024040804406 dated 10/04/24.
- 3. The Manager, Tushar Guest House at 2677 Gali no. 8, Chuna Mnadi, Pahar Ganj, New Delhi. Conditions for the validity of Fire Safety Certificate
 - 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all
 - 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of
 - 3. The trained fire fighting staff should be available round the clock.
 - 4. The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned.
 - 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
 - 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
 - 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an
 - 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.

9. Any flammable material for interior decoration is prohibited.

MIP INSPECTION REPORT

1. Name & address of the building Tushar Guest House at 2677/8, Gali no. 8,

Chuna Mnadi, Pahar Ganj, New Delhi.

2. Type of occupancy:-Residential, Sub Division-A-1

Gr. + 03 Upper floors (total 14 Guest rooms) Ground floor (02 guest rooms), 1st floor to 3rd floor

(04 guest rooms at each floor)

3. Type of case:-Renewal

4. Details of previous FSC:-No. F6/DFS/MS/GH/NDZ/2021/186 dated

5. Fire safety directives No .-N/A

22/04/24 6. Date of inspection:-7. Name of the inspecting officer:-Sh. Ravinder Singh(ADO/CC)

8. Name & designation of officer

From the building side:-

Manager

9. Year of construction:-

OLD

	1.0. 2		In	Old Case		
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR		
1.	Access to Building		ž.			
	1) Road width	N/A	06 mtr.	MR		
	2) Gate width	N/A	N/A	N/A		
	3)Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Arrangement of Exits					
	A. Number of staircases					
	1. Upper floors	01	01	MR		
	2. Basements	N/A	N/A	N/A		
	B. Width of staircase					
	1. Upper floors	1.25 mtr.	1.25 mtr.	MR		
	2. Basements	N/A	N/A	N/A		
	C. Protection of exits					
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous staircase to terrace	01	01	MR		
	E. Width of corridor	N/A	N/A	N/A		
	F. Door size	1 mtr.	1 mtr.	MR		
3.	Compartmentation					
4.	1) Fire check door	N/A	N/A	N/A		
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain	N/A	N/A	N/A		
	5) Fire Dampers	N/A	N/A	N/A		
	Smoke Management System					
	1) Basements	30 ACPH	N/A	N/A		
	2) Upper floors	12 ACPH	Required exhaust fan	Provided		
5.	Fire Extinguishers		- Printed Idii			

N 125

	1) Total numbers	20 Nos.	20 Nos. / ABC & CO2	MR MR
	2) Types	ABC & CO2		MR
	3) ISI marking	Required	Provided	IVIK
,	First-Aid Hose Reel		-	MR
5	1) Total number of each	01	01	MIC
	floor	15	100 100	MR
9	2) Length of hose reel hose	30 mtr.	30 mtr.	MR
	a) ar _la diameter	05 mm	05 mm	14117
	Antomotic Fire Detection & A	Llarming Syst	em	MR
7	1) Type of detectors Co Type	Required	110,10	MR
	2) Location of main panel	Required	Provided (1411
	Gr. Floor			N/A
	3) Location of repeater panel	N/A	N/A	MR
	4) Alternate source of power	Required	Provided	MR
	5) Hooter's Location	Required	Provided	
	9.37	Required	Provided /	MR
8.	MOEFA Public Address System	Required	Provided '	MR
9.	Automatic Sprinkler System	Design of the Control		NT/A
10	Automatic Sprinkler System	N/A	N/A	N/A
	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	1.354.5565.02		
	ceiling			NI/A
11	Internal Hydrants 1) Size of riser/down-comer	N/A	N/A	N/A
	Number of hydrants per	N/A	N/A	N/A
		COCHONIA PORCE		NI/A
	floor	N/A	N/A	N/A
7.0	3) Hose box			TN/A
12.	Yard Hydrants 1) Total number of hydrants	N/A	N/A	N/A
	1) Total number of nyurus	N/A	N/A	N/A
	2) Hose box			
13.	Pumping Arrangement	N/A	N/A	N/A
	1) Ground level	N/A	N/A	N/A
	a) Discharge of main			
	pump	N/A	N/A	N/A
	b) Head of main pump		N/A	N/A
	c) Number of main pump	N/A	N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A N/A	N/A	N/A
	h) Auto starting/Manual	IV/A		
	stopping			
	2) Terrace level	225 LPM	225 LPM	MR
14	a) Discharge of pump		30 mtr.	MR
	b) Head of pump	30 mtr.	Provided	MR
	a) Power supply	Required	Provided	MR
	d) Auto starting of pump Captive Water Storage for F	Required	Hovided	
	C T	ing Highfing		

	Under ground tank capacity	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2500 ltr.	2500 ltr.	N/A
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided /	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	20. Special Fire Protection System for Protection of spe Risk, if any:			N/A

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if agreed, we may renew the FSC issued vide letter no. F6/DFS/MS/GH/NDZ/2021/186 dated 22/04/21 under rule 35(6) of the Delhi Fire Service rules 2010 Accordingly, DFA is put up for kind perusal and signature please.

Signature of the Inspecting Officer

Name: - Sh. Ravinder Singh

Designation: ADO (CC)