GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F.6/DFS/MS/SZ/2024/280

Dated: 06 05 3024

FIRE SAFETY CERTIFICATE

Certified that the building at Plot No. 12-B, Bazar Marg, Old Rajinder Nagar, New Delhi110060, having Basement, Stilt, Ground plus three upper floors. The building owned/occupied by M/s
Bahl Paper Mills Ltd. have complied with the fire prevention and fire safety requirements in
accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of
Fire Service on 02.05.2024 in presence of Sh. Devinder Kumar, J. E. (Bldg), MCD and Sh. Naresh Arya
and the building/premises is fit for Mix occupancy (Class Mercantile, Lusiness & Residential) with
effect from 06 05 2024 for a period of three years in accordance with Rule 36 unless renewed
under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under
Rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on 06 05 2524 at New Delhi by.

Derhi Fire Service

Copy to:-

1. The Executive Engineer-I(Bldg.)HQ, SDMC, 9th floor, Civic Centre, Minto Road, New Delhi110002.

2. The Owner/Occupier, Plot No. 12-B, Bazar Marg. Old Rajinder Nagar, New Delhi- 110060.

Following Fire Safety Directives Must Be Adhered To:-

- Providing of fire safety measures does not give any guarantee that there will be No fire. These
 equipments/installation can minimize the losses if maintained in good working condition and
 handled efficiently in case of fire.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 3. The means of escape arrangements shall be kept unlocked & unobstructed for speedy evacuation of occupants in case of an emergency.
- Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 5. The trained staff should be available round the clock.
- 6. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 7. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dis.delhigovt.nic.in.
- 9. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

11/4

Name & address of the building : Plot No. 12B, Ba

: Plot No. 12B, Bazar Marg, Old Rajinder Nagar, New Delhi- 110060.

2. Type of Occupancy

: Mix Occupancy (Mercantile+Business+Residential)

3. Building Composition

: Said building is comprised of basement, stilt,

4. Type of Case

ground plus three upper floors.

: New Case

5. Details of previous NOC

: N/A

6. Fire Safety directives letter No

: F6/DFS/MS/BP/2022/476 dated 30.11.2022

7. Date of inspection

: 31.08.2023

8. Name of the Inspecting Officers

: Vedpal Chhikara, DO(SW) & Devinder Kumar, JE

(Building) (MCD)

9. Name and designation of officers from the building side

: Sh. Naresh Arya

9. Year of Construction

: 2023-24

10. Applicant's letter No.

: MCD Online ID No. 10107534, dated 27.04.2024.

Sr. No.	Minimum Standards on fire prevention and fire safety U/R 33	Requirement as per NBC-IV	Provided at site	Remark MR/NM				
	Access to building							
	Road width	24 mts	Provided	MR MR				
	Gate width	05 mts	Provided					
	Width of internal road	N/A	N/A	N/A				
,	Number, Width, Type & Arrangement	of Exits	I am be		_			
2	a. Number of staircases	= 8.1	ng sa ili agail		-			
		02 Nos.	02 Nos.		MR_			
	Upper Floors	02 Nos.	02 Nos. - 1.6 mts. each		MR			
	Basements				-			
	b. Width of staircases	1.5 mts each			MR			
	Upper Floors	1.5 mts each	1.6 mts. ea	ch	MR			
	Basements	V y III			-			
	c. Protection of exits	Required	Provided	I.	MR			
	Fire check door	Required	Provided		MR			
	Pressurization	1	02		MR			
	e. No. of continuous staircases to	02	02	8				
	terrace	N/A	N/A		N/A			
	g. Width of Corridor	1.50 mts	1.50 mts		MR			
	h Door Size	1.30 ms		1.0				
3	Compartmentation.	Required	Provided	i	MR			
	Fire check door		Sealed		MR			
	Sealing of electrical shafts	Required	N/A		N/A			
	Fire Rating of shaft door	N/A	N/A		N/A			
	Water Curtain	N/A			N/A			
	Fire Dampers	N/A	IVA					
	Smoke Management System.							
4	Decements	30 a/c per hour	Provide		MR			
	II floore	12 a/c per hour	Provided		MR			
	• Upper Hoors Fire Extinguishers		T 6 91 1		MR			
5	m 1 mbore	15	Provided					
		ABC & CO ₂ type	ABC & CO ₂	71	MR			
	• Types	ISI marked	Provided		MR			
	IS marking	1						

6	First-Aid Hose Reels.				
	Total numbers on each floor	02 no. 02 Nos Prov		10	
	Length of hose reel hose	30 mts.	02 Nos. Provided	M	
	Nozzle diameter		Provided	MI	
7		5 mm	Provided	MI	
	Automatic fire detection and alarming system. • Type of detectors				
	Location of Main Panel	N/A	Provided	N/A	
		N/A	Provided	N/A	
	Escation of Repeater Panel	N/A	N/A	N/A	
	Alternate source of power	N/A	Provided	N/A	
8	Hooters' Location	N/A	Provided	N/A	
	MOEFA	Required	Provided	MI	
9	Public Address System.	N/A	N/A		
10	Automatic Sprinkler System.	119		N/A	
	Basement	Required	Provided		
	Upper Floor / Ground Floor	N/A	Provided	MF	
	Sprinkler above false ceiling	N/A		N/A	
11	Internal Hydrants	Maril II.	N/A	N/A	
	Size of ricor/down				
	Number of hydrants per floor	02	Provided	MF	
	Hose Box	02	02	MR	
12	Yard Hydrants.				
	Total much Cl. 1				
	Hose Box	N/A	N/A	N/A	
13	17.5/e	N/A	N/A	N/A	
	Pumping Arrangements. • Ground Level				
	Discharge of main Pump	2280 LPM	7		
	Head of Main pump	70 mts	Provided Provided	MF	
	Number of main pumps	01 No.	Provided	MR	
	> Jockey Pump out put	180 LPM	Provided	MR	
	Jockey pump head	40 mts	Provided	MR	
	Standby Pump out put	2280 LPM	Provided	MR	
	Standby Pump Head	70 mts	Provided		
	> Auto Starting/ Manual stopping	Required		MR	
	> Pump House Access		Provided	MR	
	Terrace level	Required	Provided	MR	
	Discharge of pump	000 % 450 L DM			
	Head of the pump	900 & 450 LPM	Provided	MR	
	Power Supply	40 mts	Provided	MR	
	- wet suppry	Required -	Provided	MR	
14	Auto Starting of pump Captive Water Storage for fire fighting.	Required	Provided	MR	
	II. 1				
	Underground tank capacity	1,50,000	Provided	MR	
	➤ Draw-off connection ➤ Fire service inlet	Required	Provided	MR	
	Access to tank	Required	Provided	MR	
	Overhead Tank capacity	Required	Provided	MR	
15		30,000 Its	30,000 Its	MR	
	Exit Signage.	Required	Provided	MR	

			1/16						
V	Provis	ion of Lifts.	(Lifts not installed yet)						
1	•	Pressurization of Lift Shaft	N/A	N/A	N/A				
	•	Pressurization of Lift lobby	N/A	N/A	N/A				
	•	Communication In lift Car	N/A	N/A	N/A				
	•	Fireman's Grounding Switch	N/A	N/A	N/A				
	•	Lift Signage	N/A	N/A	N/A				
17	Stan	dby power supply	N/A	N/A	N/A				
18	1	Refuge Area.							
1	1	Total Area	N/A	N/A	N/A				
	,	Location	N/A	N/A	N/A				
19	Fire	Fire Control Room							
		Detector System Panel	N/A	N/A	N/A				
		Flow Switch Panel	N/A	N/A	N/A				
		PA System Panel	N/A	N/A	N/A				
			N/A	N/A	N/A				
	-	Batter backup Batter backup Batter backup	N/A	N/A	N/A				
20	Spe	Building Floor Plans cial Fire Protection Systems for	Required	Fire Extinguishers are provided near electric panel.	MR				

The fire protection systems provided in the building were test/checked at random and found functional at the time of inspection.

In view the substantial compliance of the minimum standards on fire prevention and fire safety required under the Rules, it is recommended to grant fire safety certificate under Delhi Fire Service Act-2007 & Rules- 2010 if agreed.

Accordingly, DFA is put up for approval & signature please.

Protection of special Risks, if any:

Signature of the inspecting officer Name- Vedpal Chhikara

Divisional Officer (SW)