## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/WZ/2024/ 286

## FIRE SAFETY CERTIFICATE

Dated: 07/05/2024

Certified that the Plot No.358, B-Block, Mangol Puri, Industrial Area, Phase-I, New Delhi110083, comprised of Basement, stilt, Ground + 02 upper floors was inspected by the officer
concerned of this department on 26.04.224 in the presence of Mr. Ashok Kumar (Guard) and found
that the said premises have complied with the fire prevention and fire safety requirements in
accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premise is fit for occupancy
G, 'Industrial' with effect from Delhi Fire Service Rules 37 or sooner cancelled under Rule 40 and subject
to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 07 05 2024 at New Delhi by

Aful Garg)
DIRECTOR
Ph; 011-23414000

Copy to:

 Mr. Satish Garg, (Treasurer), BJP- Delhi State Office, 14 Pandit Pant Marg Area, Sansad Marg, Area Delhi-110001.

Conditions for validity of Fire Safety Certificate;

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on
- 8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.
- 9. Mechanical ventilation shall be provided in basement wherever car lift is installed in the building, failing which FSC shall be null & void.

http://www.delhi.gov.in/wps/wcm/connect/doit\_fire/FIRE/Home/Fire+Safety+Acts+and+Rules/http://www.delhi.gov.in/wps/wcm/connect/doit\_fire/FIRE/Home/Forms

			INCDE	CONTO				
1.	Name & ac	dress of the building	THOPE	CTION REPORT				
			Plot N	lo.358, B-Block, Ma	ngol Puri, Industrial Area	a, Phase-I, Ne		
2.	Type of Occupant			hi-110083.				
1	Type of Case Indust			strial building				
4.	Details of l	revious NOC	-NA-	Case (Basement, stil	t, Ground + 02 upper f	loors)		
٥.	rire Safety	directives law xx	71.00	EC/MC/DD/2021/410	1 - 100 00 0001			
v.	Date of ins	Dection		F.6/DFS/MS/BP/2021/418 dated 20.09.2021. 26.04.2024				
0	Name of Inspecting Officer Sh. Aj							
٥.			n. Ajay Kumar Sharma (ADO Rohini) r. Ashok Kumar (Guard)					
	Year of Co	wilding side		(Cuaru)				
10	). Applicant's	Istruction	2021					
S.	Minimum	Standard Standard	OD No	o.14628 dated 27.03.	2024.			
No	and fire so	Standards on fire prevented U/R 33	ention	BBL/NBC	Provided at site	Remarks		
	Access to l	nety U/R 33				MR/NMR		
		d width		18mtr	18mtr	MR		
		e width		4.5m	Directly accessible	MR		
_	• Wid	th of internal road		-NA-	-NA-	-NA-		
_	Number, \	Vidth, Type & Arrange	ment of	Exits				
	d. Number	of staircases						
	• [	pper Floors		02	02 (01metal staircase)	MR		
		asements		02	02	MR		
	e. Width o	f staircases				MIK		
	• [	pper Floor		1.5m	2 x 1.5m	MR		
	• F	asements		1.5	(01metal staircase)	1000		
		ection of exits		1.5m	2 x 1.5m	MR		
		Fire check door		Danie 1				
		Pressurization		Required	Provided .	MR		
		o. of continuous staircases to terrace		Natural ventilation	Provid <b>ed</b>	MR		
		2,020 8	еггасе	02nos.	<b>0</b> 2nos.	MR		
	f. Door Siz	Width of Corridor		-NA-	-NA-	-NA-		
	Jan State of Louisian			1.5m	Provid <b>ed</b>	MR		
-	Compartm	SEATS CORES						
	f) Fire check door			-NA-	-NA-	-NA-		
	g) Sealing of electrical shafts		-NA-	-NA-	-NA-			
	h) Fire Rating of shaft door		-NA-	-NA-	-NA-			
	i) Water Curtain		-NA-	-N.A-	-NA-			
	(4.57)	Dampers		-NA-	-NA	-NA-		
		nagement System						
	c) Basements			12 a/c per hour	Natural ventilation	MR		
		er floors		12 a/c per hour	Natural ventilated	MR		
	Fire Extinguishers							
	d) Total numbers			10nos.	12nos.	MR		
	e) Types		ABC/CO2	ABC-10nos.	MR			
	1.00	arking		ISI marked	Yes	MR		
1	First-Aid Hose Reels					IVIK		
	d) Total numbers on each floor			01	Provided	MR		
	u) Tota	e) Length of hose reel hose			Lines of the New VIII	IVIK		
	200	th of hose reel hose		30mm	Provided	MR		

ナ

net

П	Automatic fire detection and alarming system  NA Provided				
	Type of detectors	-1874-	Provided .	MR	
ł	g) Location of Main Panel	Required	Provided	MR	
	h) Location of Repeater Panel	Required	Provided	MR	
	i) Alternate source of power	Required	Provided	MR	
	The state of the s	Required	Provided	MR	
0	j) Hooters' Location  MOEFA	Required	-NA-	-NA-	
8.	Public Address System	-NA-	-N/\-		
9.	Automatic Sprinkler System		n 1.4	MR	
10.	d) Basement	Required	Provided	MR	
	La II - Floore	Required	Provided	MR	
	t feloa gailing	Required	Provided	IVIIX	
				MR	
11.	Internal Hydrants d) Size of riser/down-comer	100mm	Provided	MR	
	C1 - leasts per floor	01nos.	Provided	MR	
		Required	Provided	IVIK	
	f) Hose Box			NIA	
12.	Yard Hydrants	-NA-	-NA-	-NA-	
	c) Total number of hydrants	-NA-	-NA-	-NA-	
	d) Hose Box	-4000000		374	
13.	Pumping Arrangements	-NA-	-NA-	-NA-	
	Ground Level     Figure of main Pump	-NA-	-NA-	-NA-	
	Discharge of main Pump	-NA-	-NA-	-NA-	
	> Head of Main pump	-NA-	-NA-	-NA-	
	Number of main pumps	-NA-	\\.\-	-NA-	
	<ul> <li>Jockey Pump out put</li> <li>Jockey pump head</li> </ul>	-NA-	-NA-	-NA-	
	<ul> <li>Jockey pump nead</li> <li>Standby Pump out put</li> </ul>	-ΝΛ-	-NA-	-NA-	
	Standby Pump Head	-ΝΛ-	-NA-	-NA-	
	> Standby Fullip Flead > Auto Starting/Manual Stopping	-NA-	-NA-:	-NA-	
	> Pump House Access	-ΝΛ-	-N.V-:	-NA-	
	Fump House 1.				
	Terrace level	900lpm	9001pm	MR	
	> Discharge of pump	40m	40m	MR	
	➤ Head of the pump	Required	Provided	MR	
	> Power Supply	Required	Provided	MR	
	> Auto Starting of pump				
14.		-NA-	->- \-	-NA-	
	Underground tank capacity	-NA-	-7/2-	-NA-	
	> Draw-off connection		-No.	-NA-	
	➤ Fire service inlet	-NA-		-NA-	
	> Access to tank	-NA-	-N. (-		
	Overhead Tank capacity	20,000ltr	4 x 00ltr	MR MR	
15		Required	Provided	IVIK	
16	Provision of Lifts.				
	f) Pressurization of Lift Shaft	Required	Provided	MR	
	g) Pressurization of Lift lobby	-NA-	-NA-	-NA-	
	h) Communication In lift Car	Required	Provided	MR	
	i) Fireman's Grounding Switch	Required	Provided	MR	
	j) Lift Signage	Required	P. Seled	MR	
1	Standby power supply	Required	Provided	MR	

1	Refuge Area.						
0.	c) Total Area	-NA-	-NA-	-NA-			
+	d) Location	-NA-	-NA-	-NA-			
9.	Fire Control Room		NA	-NA-			
	f) Detector System Panel	-NA-	-NA-	-NA-			
t	g) Flow Switch Panel	-NA-	-NA-				
	h) PA System Panel	-NA-	-NA-	-NA-			
	i) Battery backup	-NA-	-NA-	-NA-			
	j) Building Floor Plans	-NA-	-NA-	-NA-			
20		-NA-	-NA-	-NA-			

The fire protection systems provided in the building were test checked and found functional at

the time of inspection.

Keeping in view the satisfactory compliance of the minimum standards on fire prevention and fire safety required as stipulated in NBC Part-4, and removal of shortcomings issued vide letter no. 202 dated 07.02.2024, under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rule 2010.

Signature of the Inspecting Office Name: - M. K. Chartopadhyay Designation:- Dy. Chief Fire Officer

Signature of the Inspecting Officer Name: - Ajay Kumar Sharma Designation:- ADO/Rohini

उपरोक्त का स्पन्धीकारत दें