ولا

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE : CONNAUGHT PLACE NEW DELHI

No. F6/DFS/MS/Hospital/2024/SZ/ 289

Dated: 08/05/2024

FIRE SAFETY CERTIFICATE

Certified that the Gandhi Hospital situated at C-42, Om Vihar, Uttam Nagar, New Delhi- 110059, comprised of stilt, ground, plus three upper floors, owned/occupied by A unit of Pawan Gandhi Health Care Pvt. Ltd.. The hospital building was inspected by the officer concerned of this department on 10.04.2024 in the presence of Dr. Alisha and found that hospital have complied with the Fire Prevention and Fire Safety requirements in accordance with Rule 33 of Delhi Fire Service Rules, 2010 and that the building/premises is fit for occupancy Group-C "Institutional Building" sub. Div. C-1 w.e.f the date of issue of this certificate for a period of Three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010 printed below.

Issued 08 05 2024 at New Delhi by.

DIRECTOR
DELHI FIRE SERVICE

Copy to: -

- 1. Authorised Signatory, M/s. Gandhi Hospital situated at C-42, Om Vihar, Uttam Nagar, New Delhi-110059.
- 2. The Directorate of Health Services, M.O.I/C Nursing Home Cell, S-1, School Block, Shakarpur, New Delhi- 110092.

Condition for the validity of fire safety certificate

- All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. All passage shall be kept free from obstructions.
- This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 9. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.

INSPECTION REPORT

1. Name & address of the building: M/s Gandhi Hospital, situated at C-42, Om Vihar, Uttam Nagar, New Delhi-110059.

2. Building is comprised of : Stilt, ground plus three upper floors. 3. Type of Occupancy : Institutional (Hospital Building)

4. Type of Case : New 5. Details of Previous NOC : N/A

6. Fire Safety directives letter No : F6/DFS/MS/ BP/2024/10 dated 08.01.2024

7. Date of inspection : 10.04.2024

8. Name of Inspecting Officer : A.D.O. R.K.Yadav (JKP)

9. Name and designation of officers

From the building side : Dr. Alisha 10. Year of Construction : 2020-21

11. Applicant's letter No. : Nil dated 06.03.2024

| S. No. | Minimum Standards on fire prevention and fire safety U/R 33 | Requirement | Provided at site | Remarks |
|--------|---|---------------------------|--------------------|------------|
| 1. | Access to building | | | MR/NMR |
| | Road width Gate width Width of internal road | Accessible N/A N/A | 06 m N/A N/A | M/R N/A |
| 2. | Number, Width, Type & Arrangement of | Frita | IV/A | N/A |
| | | LAILS | | |
| | a. Number of staircases | | 1 | |
| | • Upper Floors | 02 nos. | 02 no.'s | |
| | Basements | N/A | N/A | M/R |
| | b. Width of staircases | | N/A | N/A |
| | • Upper Floor | 2 m & 1.5 m | Provided | |
| | Basements | N/A | N/A | MR |
| | c. Protection of exits | | IV/A | N/A |
| | Fire check door Pressurization | Required | Provided | |
| | 1 1033ul 12ation | N/A | N/A | M/R |
| | d. No. of continuous staircases to terrace | 02 | | N/A |
| | e. Width of Corridor | 02 | 02 | M/R |
| | f. Door Size | Required | Provided | M/R |
| 3. | Compartmentation | 1.25 m | 1.25 m | MR MR |
| 34 | Fire check door | | | IVIK |
| | Sealing of electrical shafts | Required | Provided | 1470 |
| | Fire Rating of shaft door | Required | Sealed | M/R |
| | Water Curtain | N/A | N/A | M/R |
| | • Fire Dampers | Required | | N/A |
| 4. | | N/A | Provided | M/R |
| | Smoke Management System | | N/A | N/A |
| | Basements | | 4 | |
| | Upper floors | Required | Provided | M/R |
| | 11. | Required | Provided | |
| 5. | Fire Extinguishers | and the second | 1988 | M/R |
| | Banana | | | |
| | Total numbers | | | |
| | • Types | 20 no.'s | Provided | 145 |
| | IS marking | ABC/ CO ₂ type | Provided | M/R |
| | | ISI marked | Provided | M/R |
| | 0 _C | | -1071464 | M/R |

| | | 437 | Provided | M/R |
|----|--|-----------------|----------------------|------------|
| | Total numbers on each floor | 1 No. | Provided Provided | M/R |
| | Length of hose reel hose | 30 m | | |
| | Nozzle diameter | 5 mm | Provided | M/R |
| | Automatic fire detection and alarming system Type of detectors | Required | Provided | M/R |
| | Location of Main Panel | N/A | Ground floor | M/R |
| | Location of Repeater Panel | 10.23/05 | Ground floor | 1504545 |
| | Alternate source of power | N/A Required | Provided | M/R M/R |
| | Hooters' Location | Required | Provided | M/R |
| | MOEFA | Required | Provided | M/R |
| 5 | Public Address System | Required | Provided | M/R |
| 0. | Automatic Sprinkler System | • | | |
| | Basement | Required | Provided | M/D |
| | Upper Floor | | | M/R |
| | X | Required | Provided | M/R |
| | Sprinkler above false ceiling | N/A | N/A | N/A |
| 1. | Internal Hydrants | | | 111 |
| | Size of riser/down-comer | 100 mm | Provided | M/R |
| | Number of hydrants per floor | one | Provided | M/R |
| | Hose Box | one | Provided | M/R |
| 2. | Yard Hydrants | | | |
| | Total number of hydrants | N/A | N/A | N/A |
| | Hose Box | N/A | 37 03352 | N/A |
| 3. | Pumping Arrangements | IVA | N/A | N/A |
| | Ground Level | | | |
| | Discharge of main Pump | 1620 1 70 6 | | |
| | > Head of Main pump | 1620 LPM | Provided | M/R |
| | Number of main pumps | 60 m | Provided | M/R |
| | ➢ Jockey Pump out put | one | Provided | M/R |
| | Jockey pump head | 180 LPM | Provided | M/R |
| | Standby Pump out put | 60 m | Provided | M/R |
| | Standby Pump Head | 1620 LPM | Provided | M/R |
| | ➤ Auto Starting/Manual Stopping | 60 m | Provided | M/R |
| | N D | Required | Provided | M/R |
| | Pump House Access Terrace level | Required | Provided | MR |
| | Discharge of pump | 4 | | 200000 |
| | > Head of the pump | N/A | 450 LPM | N/A |
| | Power Supply | N/A | 40 m | N/A |
| | Auto Starting of pump | N/A | Provided | N/A |
| 4. | Captive Water Storage for fire fighting | N/A | Provided | N/A |
| | Underground tank capacity | 75.000 | | |
| | > Draw-off connection | 75,000 ltrs. | 1,06,000 ltrs | M/R |
| | Fire service inlet | Required | Provided | M/R |
| | Access to tank | Required | Provided | M/R |
| _ | Overhead Tank capacity | Required | Provided | M/R |
| 5. | Exit Signage. | 10,000 Ltrs | 10,000 Ltrs | M/R |
| | | Required | Provided | 11411 |

1



| 16. | Provision of Lifts. | 7: | | | | |
|--------|---|----------|-----------|-----|--|--|
| | Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply | Required | Provided | 100 | | |
| | | Required | Provided | MR | | |
| | | Required | Provided | MR | | |
| | | Required | Provided | MR | | |
| 17. | | Required | Provided | MR | | |
| 18. | | Required | Provided | MR | | |
| 10. | Refuge Area. | | | M/R | | |
| | > Total Area | | | | | |
| | ➤ Location | N/A | N/A | N/A | | |
| 19. | Fire Control Room | N/A | N/A | N/A | | |
| | | | | | | |
| | Detector System Panel Flow Switch Panel | N/A | N/A | | | |
| | PA System Panel Battery backup | N/A | N/A | N/A | | |
| | | N/A | N/A | N/A | | |
| | Building Flore Pt | N/A | | N/A | | |
|). | Building Floor Plans Special Bi | N/A | N/A | N/A | | |
| | Special Fire Protection System for | Required | N/A | N/A | | |
| | " " VIVUUUI OI engoial D! 1 | required | Provided | | | |
| oto. T | Protection of special Risks, if any: Electrical meter board found outside of the | 22 | 2 TOVIDEU | MR | | |

The fire protection systems provided in the building were tested, checked and found functional at time of inspection.

Keeping in view of the above compliance of the minimum standards of fire prevention and fire safety measures under Rule 35 of the Delhi Fire Service Rules 2010 it is recommended to grant Fire Safety Certificate.

CFO (South Zone)

Dineta

Signature of Inspecting Officer 2

Name: - R.K. Yadav Designation: - ADO (JKP)