

No.F6/DFS/MS/EH/NDZ/2024/ 125

Dated: 93/95/2024

FIRE SAFETY CERTIFICATE

Certified that the M/S Haldiram Product Pvt. Ltd located at 70, Janpath Connaught Place, New Delhi comprises of Ground, mezzanine & 02 upper floors, and Restaurant at Ground department this by granted FSC earlier The **FSC** was No.F6/DFS/MS/EH/NDZ/2021/77 dated 30/03/21 for the ground floor only and storage at mezzanine. Now, the premises was re-inspected by the officers concerned of this department on 24/04/24 in the presence of Manager and found that the restaurant running at ground and mezzanine closed as per undertaking dated 25.04.24, has deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of Delhi Fire Service Rules, 2010 and that the said restaurant is fit for occupancy class Assembly Building Group D, Restaurant at ground floor only and valid up to 31.03.2027 from the date of issue in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued . 03 05 2024. at New Delhi by.

Delhi Fire Service

Copy to:-

1. The Chief Architect, NDMC, Palika Kendra, New Delhi.

2. The Dy. Commissioner of Police (Lic.), Ist floor, PS Defence Colony, New Delhi, ID No. 2024041304956 dated 13.04.2024.

3. The Manager, M/s Haldiram at 70, Janpath Connaught Place, New Delhi.

Conditions for the validity of Fire Safety Certificate

1. This FSC is valid only for restaurant at ground floor.

- 2. All the fire safety arrangements provided therein shall be maintained in good working conditions at all
- 3. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

4. The trained fire fighting staff should be available round the clock.

- 5. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority. Mezzanine floor shall be used only for storage purpose no seating shall be allowed.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 9. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

10. Any flammable material for interior decoration is strictly prohibited.

119

INSPECTION REPORT

1. Name & address of the building Haldiram Product Pvt. ltd. located at 70,

Janpath Connaught Place, New Delhi

2. Type of occupancy:- Assembly Building Group-D, Ground + Mez.

and 02 upper floors and Restaurant is running on Ground floor only.

3. Type of case:- Renewal

4. Details of previous FSC:- F6/DFS/MS/EH/NDZ/2021/77 dated

30/03/21.

5. Fire safety directives No.-

N/A

6. Date of inspection:-

24.04.2024

7. Name of the inspecting officer:-

Sh. Rajinder Atwal (DO/CD) &

Sh. Ravinder Singh (ADO/CC)

8. Name & designation of officer

From the building side:-

Manager

9. Year of construction:-

1960

10	. Applicant's letter No:-	online id no.	2024041304956 date	d 13.04.2024.	
.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing	Provided at site	Remarks MR/NMR	
1.	Access to Building				
	1) Road width	06 mtr	06 mtr.	MR	
	2) Gate width	N/A	N/A	N/A	
	3)Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Arra				
	A. Number of staircases				
	1. Upper floors (mezzanine floor closed & not in use)	N/A	02 nos /	N/A	
	2. Basements	N/A	N/A	N/A	
-	B. Width of staircase		_		
1	1. Upper floors (mezzanine)	N/A	02 of 1.5m& .50 m	N/A	
	2. Basements	N/A	N/A	N/A	
1	C. Protection of exits			* *	
	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous staircase to terrace	N/A	N/A	N/A	
	E. Width of corridor	N/A	N/A	N/A	
	F. Door size	1.5 mtr	1.5 mtr	MR	
3.	Compartmentation				
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System				
	1) Basements	30 ACPH	N/A	N/A	
	2) Upper floors	12 a/c per hour	Natural	MR	

		NIO		. 10	
	Lhom		2631	100	1
5.	Fire Extinguishers	06 Nos.	06 Nos.	MR	-
	1) Total numbers	ABC & CO2	ABC & CO2	MR	
	2) Types	Required	Provided	MR	
	2) ISI marking	Rogani			
6.	WALL A A LA PLOGO ICCCI	01	01	MR	
0.	1) Total number of eachitoor	30 mtr.	30 mtr.	MR	
	2) Length of hose reel nose	Control of the last of the las	05 mm	MR	
	3) Nozzle diameter	05 mm			
7	3) Nozzle diameter Automatic Fire Detection &	Alarming Syst	N/A	N/A	
7.	1) Type of detectors		N/A	N/A	
	2) Location of main panel	N/A		N/A	
	3) Location of repeater panel	N/A	N/A	N/A	
	4) Alternate source of power	N/A	N/A	N/A	
	5) Hooter's Location	N/A	N/A	MR	
		Required	Provided	AND DESCRIPTION OF THE PERSON NAMED IN	
8.	MOEFA	Required	Provided	MR	_
9.	Public Address System				
10.	Automatic Sprinkler System	N/A	N/A	N/A	
	1) Basement	N/A	Provided	N/A	
	2) Upper floors	N/A	N/A	N/A	
	3) Sprinkler above false	IV/A			
	ceiling		· · · · · · · · · · · · · · · · · · ·		
11.	Internal Hydrants	1100	100mm	MR	
	1) Size of riser/down-comer	100mm	01	MR	
	2) Number of hydrants per	01	01		
	floor	01	01	MR	
	3) Hose box	01	01	11223	
12.	Yard Hydrants	157/4	NT/A	N/A	
	1) Total number of hydrants	N/A	N/A	N/A	
	2) Hose box	N/A	N/A	IVA	
13.	Pumping Arrangement		3.77	NI/A	
	1) Ground level	N/A	N/A	N/A	
	a) Discharge of main	N/A	N/A	N/A	
	pump			27/4	
	b) Head of main pump	N/A	N/A	N/A	
	c) Number of main	N/A	N/A	N/A	
	pump				
	d) Jockey pump out put	N/A	N/A	N/A	
	e) Jockey pump head	N/A	N/A	N/A	
	f) Stand by pump	N/A	N/A	N/A	
	output	100 (1990) TV (1991)			
		N/A	N/A	N/A	
	g) Stand by pump headh) Auto starting/Manual	N/A	N/A	N/A	
		11/74			
	stopping		1		
	2) Terrace level	450 LPM	Provided	MR	
	a) Discharge of pump		Provided	MR	
	b) Head of pump	30 mtr.		MR	
	c) Power supply	Required	Provided	MR	
	d) Auto starting of	Required	Provided	IVIK	
	pump				



N/11

	Captive Water Storage for Fire Fighting				
	Under ground tank capacity	N/A	N/A	N/A	
4	a) Draw-off connection	N/A	N/A	N/A	
	b) Fire service inlet	N/A	N/A	N/A	
	c) Access to tank	N/A	N/A	N/A	
	d) Over head tank capacity	20,000 lit.	20,000 lit.	MR	
5	Exit Signage.	Required	Provided .	MR	
5.	Provision of Lifts.	The state of the s			
	a) Pressurization of lift shaft	N/A	N/A	N/A	
	b) Pressurization of lift	N/A	N/A	N/A	
	c) Communication in lift	N/A	N/A	N/A	
	d) Fireman's switch	N/A	N/A	N/A	
	The state of the s	N/A	N/A	N/A	
17.	e) Lift signage Stand by Power Supply	Required	Provided	MR	
	Refuge Area	N/A	N/A	. N/A	
19.	Total area location	N/A	N/A	N/A	
	Fire Control Room	N/A	N/A	N/A	
	a) Detector system panel	N/A	N/A	N/A	
	b) Flow switch panel	N/A	N/A	N/A	
	c) PA system panel	N/A	N/A	N/A	
	d) Battery backup	N/A	N/A	N/A	
	e) Building floor plan	N/A	N/A	N/A	
20.	Special Fire Protection Syste Risk, if any:	em for Prote	ction of special	N/A	

The fire protection systems provided in the said building were randomly tested, checked and found functional at the time of inspection. An undertaking dated 25.04.2024 regarding not to use mezzanine floor for any purpose has been submitted by applicant and same is placed on file.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if approved, we may renew the FSC issued vide letter no. F6/DFS/MS/EH/NDZ/2021/77 dated 30/03/21, under rule 35 of the Delhi Fire Service rules 2010. Accordingly, reply letter is prepared and put up for kind perusal and signature please.

Signature of the Inspecting Officer

Name - Sh. Rajinder Attwal Designation: - DO (CD) Signature of the Inspecting Officer

Name: - Ravinder Singh

Designation: - ADO (CC)

Jugo 26/04)

1 Jugo

tal My 2014

Andr