



GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F.6/DFS/MS/EH/2024/SZ/ 135

Dated: 09/05/2024

FIRE SAFETY CERTIFICATE

Certified that M/s Liv Bar (A unit of Delhi Lounge & Bar Pvt. Ltd) at Shop No. R3, Lower Ground Floor, Worldmark-1, Aerocity, New Delhi-110037, comprised of Three Tier Basement, Ground, Mezzanine & 06 Upper Floors, but the restaurant running at lower ground floor only was issued Fire Safety Certificate by this department vide letter No. F.6/DFS/MS/EH/SZ/2021/186 dated 16/08/2021. The premise was re-inspected by the officers concerned of this department on 06/05/2024 in the presence of Mr. Shri Dama and observed that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the said premise is fit for occupancy class "Group-D Assembly" for a period up to 31/03/2027 in accordance with rule 36 unless renewal under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 09 05 2024 at New Delhi by

DIRECTOR
DELHI FIRE SERVICE

Copy to: -

- 1. The Joint Commissioner of Police, Licensing Unit, First Floor, Police Station Defence Colony, New Delhi-110049 (w.r.t. MHA ID No. 2024041204944 dated 12/04/2024)
- Authorized Signatory M/s Liv Bar (A Unit of Delhi Lounge & Bar Pvt. Ltd), Shop No. R3, Lower Ground Floor, Worldmark-1, Aerocity, New Delhi-110037

Conditions for the validity of Fire Safety Certificate:

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangement provided therein shall be maintained in good working conditions at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of fire-fighting system.
- 4. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.
- 5. The owner/occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule37] along with a copy of this Certificate, six months prior to its expiry.

	Name & Address of the Building	ION REPORT M/s Liv Bar (A Unit of Delhi Lounge & Bar				
	or the building	Det LIV Ba	ır (A l	Init of Delhi Lou	nge & Bar	
		Pvt. Ltd), Shop No. R3, Lower Ground Fl			und Floor	
2	Type of Occupancy	Worldmark	-1, Ae	rocity, New Delh	i–110037	
3	Building comprised of	Assembly 'Group-D' (Restt. at LG Floor)				
-	Building comprised of	Three Basement, Ground, Mezzanir Upper Floors.				
4	Type of Case	Renewal	rs.			
5	Details of Previous NOC		S/EH/	2021/SZ/186 dt. 1	6/08/2021	
6	Fire Safety Directives Letter No	Nil	O' DI U	2021/02/100 dt. 1	0/00/2021	
7	Date of Inspection	06/05/2024				
8	Name of the Inspecting Officers	Santosh Kumar (ADO/SJ)				
9	Name & Designation of Officers	Mr. Shri Dama				
	from the building side	CARA DE WARAN				
10	Year of construction	2014				
11	Applicant letter No.	MHA ID No. 2024041204944 dated 12/04/2024				
S.	Minimum standards on Fire	Old FSC	7	Provided at	Remark	
No.	Prevention and Fire Safety U/R 33	Requireme	ents	Site	MR/NMI	
1	[25][[하는 옷이 맛이 되었다.] [[12] [12] [12] [12] [12] [12] [12] [1	DFS/MS/Mixe	d/202	4/SZ/HTL/12 dated	ł	
	12/03/2024	n			1 vm	
	Road width	Restt with	_	As above	MR	
	Gate width	Worldmarl		As above	N/A	
	Width of internal road	Aerocity		As above	N/A	
2	Number, width, type & arrangement of exits					
	a. Number of Staircase		& Mai	ntained by Buildin		
	Upper floors	-NA-		As above	-NA-	
	Basement floor	NA		As above	-NA-	
	b. Width of Staircase	Provided & Maintained by Building Mgmt.				
	 Upper floors 	N/A		As above	-NA-	
	Basement floor	NA		As above	-NA-	
	c. Protection of exits			ntained by Buildir		
	Fire check door	1000000		As above	The second second second	
	Pressurization	-NA-		As above As above	-NA- MR	
	d. No. of continuous staircase to terrace	Required			IVIK	
	- Width of countdox	_NI A _		_N A _	-NA-	
	e. Width of corridor	-NA-	-	-NA- 1 40m & 2 80m	-NA-	
3	f. Door size	2 exits	& Mai	1.40m & 2.80m	MR	
3	f. Door size Compartmentation.	2 exits Provided &	& Mai	1.40m & 2.80m ntained by Buildir	MR ng Mgmt.	
3	f. Door size Compartmentation. • Fire check door.	2 exits Provided 8 -NA-	& Mai	1.40m & 2.80m ntained by Buildir As above	MR ng MgmtNA-	
3	f. Door size Compartmentation. • Fire check door. • Sealing of electrical shafts.	2 exits Provided & -NANA-	& Mai	1.40m & 2.80m ntained by Buildin As above As above	MR ng MgmtNA-	
3	f. Door size Compartmentation. • Fire check door. • Sealing of electrical shafts. • Fire rating of shaft door.	2 exits Provided & -NANANA-	& Mai	1.40m & 2.80m ntained by Buildin As above As above As above	MR ng MgmtNANANA-	
3	f. Door size Compartmentation. Fire check door. Sealing of electrical shafts. Fire rating of shaft door. Water curtain	2 exits Provided & -NANANANA-	& Mai	1.40m & 2.80m Intained by Buildir As above As above As above As above As above	MR ng MgmtNANANANA-	
	f. Door size Compartmentation. Fire check door. Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers.	2 exits Provided & -NANANANANA-		1.40m & 2.80m Intained by Buildin As above As above As above As above As above As above	MR ng MgmtNANANANANA-	
3	f. Door size Compartmentation. Fire check door. Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system.	2 exits Provided & -NANANANANA- Provided &		1.40m & 2.80m ntained by Buildir As above	MR ng MgmtNANANANANA- g Mgmt.	
	f. Door size Compartmentation. Fire check door. Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement	2 exits Provided & -NANANANANANANANA	& Mai	1.40m & 2.80m Intained by Buildin As above	MR ng MgmtNANANANANANANANA	
4	f. Door size Compartmentation. Fire check door. Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement Upper floors / Restt. Area	2 exits Provided & -NANANANANA- Provided &	& Mai	1.40m & 2.80m ntained by Buildir As above	MR ng MgmtNANANANANA- g Mgmt.	
	f. Door size Compartmentation. Fire check door. Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement Upper floors / Restt. Area Fire Extinguishers.	2 exits Provided & -NANANANANANA- Required	& Mai	1.40m & 2.80m Intained by Buildir As above As above As above As above As above As above Intained by Buildir As above Intained by Buildir As above Intained by Buildir As above	MR ng MgmtNANANANANA- Mg MgmtNANA- Mg MgmtNA- MR	
4	f. Door size Compartmentation. Fire check door. Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement Upper floors / Restt. Area Fire Extinguishers. Total numbers	2 exits Provided & -NANANANA- Provided & -NA- Required	& Mai	1.40m & 2.80m ntained by Buildir As above As above As above As above As above ntained by Buildir As above ntained by Buildir As above nust Fan Provided	MR ng MgmtNANANANANA- Mg MgmtNA- Mg MgmtNA- MR	
4	f. Door size Compartmentation. Fire check door. Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement Upper floors / Restt. Area Fire Extinguishers.	2 exits Provided & -NANANANANA- Provided & -NA- Required 06 Nos ABC / CO	& Mai	1.40m & 2.80m Intained by Building As above As above As above As above As above Intained by Building As above	MR ng MgmtNANANANANA- Mg MgmtNANA- Mg MgmtNA- MR	
4	f. Door size Compartmentation. Fire check door. Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement Upper floors / Restt. Area Fire Extinguishers. Total numbers	2 exits Provided & -NANANANA- Provided & -NA- Required 06 Nos ABC / CO ISI marke	& Mai	1.40m & 2.80m Intained by Buildir As above As above As above As above As above Intained by Buildir As As above Intained by Buildir As above	MR ng MgmtNANANANA- Mg MgmtNA- Mg MgmtNA- MR MR	
4	f. Door size Compartmentation. Fire check door. Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement Upper floors / Restt. Area Fire Extinguishers. Total numbers Types	2 exits Provided & -NANANANA- Provided & -NA- Required 06 Nos ABC / CO ISI marke	& Mai	1.40m & 2.80m Intained by Building As above As above As above As above As above Intained by Building As above	MR ng MgmtNANANANA- Mg MgmtNA- Mg MgmtNA- MR MR	
5	f. Door size Compartmentation. Fire check door. Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement Upper floors / Restt. Area Fire Extinguishers. Total numbers Types ISI Marking	2 exits Provided & -NANANANA- Provided & -NA- Required 06 Nos ABC / CO ISI marke	& Mai	1.40m & 2.80m Intained by Buildir As above As above As above As above As above Intained by Buildir As As above Intained by Buildir As above	MR ng MgmtNANANANA- Mg MgmtNA- MR MR MR MR MR MR MR MR Mg Mgmt.	
5	f. Door size Compartmentation. Fire check door. Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement Upper floors / Restt. Area Fire Extinguishers. Total numbers Types ISI Marking First Aid Hose Reels.	2 exits Provided & -NANANANA- Provided & -NA- Required 06 Nos ABC / CO ISI market Provided &	& Mai	1.40m & 2.80m Intained by Buildir As above As above As above As above As above Intained by Buildir	MR ng MgmtNANANANA- Mg MgmtNA- MR MR MR MR MR MR MR Mg Mgmt.	

	Automatic fire detection & alarming s	vstem. (Provide	ed & Maintained by Build	ing Mgmt.
1	Automatic fire detection & alarming s	-NA-	Smoke & Heat	
	Type of detectors	-NA-	Mezzanine floor	-NA-
	 Location of Main Panel 	-NA-	FCR at GF	-NA-
	 Location of Repeater Panel 		Provided	-NA-
1	 Alternate source of power 	-NA-		-NA-
	 Hooter's location 	-NA-	All area	1
8	MOEFA	Required	Provided	MR
9	Public Address System	-NA-	-NA-	-NA-
10	Automatic Sprinkler System	Provided &	Maintained by Building	
	Basement floor.	-NA-	As above	-NA-
	Upper floors	-NA-	As above	-NA-
	Sprinkler above false ceiling	-NA-	As above	-NA-
11	Internal Hydrants.		Maintained by Building	Mgmt.
Services.	Size of Riser/Down-comer	-NA-	As above	-NA-
	Number of Hydrant per floor	-NA-	As above	-NA-
	Hose box.	-NA-	As above	-NA-
12	Yard Hydrants.	3/25/27/77 ETV	100000000000000000000000000000000000000	3,000,000
-			Maintained by Building	
	 Total number of hydrants. Hose box. 	-NA-	As above	-NA-
13		-NA-	As above	-NA-
10	Pumping arrangements. • Ground Level	P		
			Maintained by Building	250
	Discharge of main pump.Head of main pump.	-NA-	2280 LPM	-NA-
	Number of main pumps.	-NA-	105m	-NA-
	> Jockey Pump output.	-NA-	Two 2 x 180 LPM	-NA-
	Jockey Pump head.	-NA-	105m	-NA-
	Standby Pump output.	-NA-	2280 LPM	-NA-
	Standby Pump head. Auto Starting / Manual Stanning	-NA-	105m	-NA-
	 Auto Starting / Manual Stopping. Pump House Access 	-NA-	Provided	-NA-
	Terrace Level	-NA-	Provided	-NA-
	Discharge of pump.	450 LPM	Maintained by Building	
	➤ Head of pump.	430 LPM	As above	MR
	➤ Power supply.	Required	As above	MR
	Auto starting of pump.	Required	As above	MR
14	Captive water storage for Fire Fightin	ng (Provided &	As above	MR
	onderground tank capacity.	-NA-	1 50 000 T	
	Draw-off connection.	-NA-	1,50,000 Ltr Provided	-NA-
	Fire Service Inlet.	-NA-	Provided	-NA-
	Access to tank.	-NA-	Provided	-NA-
15	Overhead tank capacity. Exit Signage.	5,000 Ltr	20,000 Ltr	MR
16	Provision of Lifts.	Required	Provided	MR
	Pressurization of lift shaft.	Provided &	Maintained by Building I	
	Pressurization of lift lobby.	-NA-	As above	-NA-
	Communication in lift car.	-NA-	As above As above	-NA-
	Fireman's switch.	-NA-	As above As above	-NA-
-	Lift signage.	-NA-	As above	-NA-
17	Standby Power Supply	Required	As above	-NA- MR
18	Refuge Area		Maintained by Building	Momt
	Total area	-NA-	-NA-	-NA-
	Location	-NA-		35555

B

w

19	Fire Control Room.	Provided & Maintained by Building Mgmt.		
	 Detector System Panel. 	-NA-	As above	-NA-
	 Flow Switch Panel. 	-NA-	As above	-NA-
	 PA system Panel. 	-NA-	As above	-NA-
	Battery backup	-NA-	As above	-NA-
	 Building floor plan 	-NA-	As above	-NA-
20	Special Fire Protection System for the Protection of special Risk, if any:	-NA-	As above	N/A

The fire protection systems provided in the building/premises were checked, tested at random and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the fire safety certificate issued vide letter No. F.6/DFS/MS/EH/SZ/2021/186 dated 16/08/2021, renewal under rule 37 of Delhi Fire Service Rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name: Santosh Kumar Designation: ADO (S.J.)

Jols / Mult