FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F6/DFS/MS/2024/44 137

Dated: 13 /05/2024

FIRE SAFETY CERTIFICATE

Certified that the M/s Shhaurya Guest House, located at Plot no-16, Pocket-B, Sector -13 Dwarka New Delhi, running at G.F = Reception, open hall, 1st & 2nd floor = 7 rooms each floor & 3rd floor = 6 rooms (Total 20 rooms) in a building comprised of Basement + Ground + 3 Upper Floors was issued FSC vide Letter No F6/DFS/MS/SWZ/2021/GH/485 dated 28/10/2021. The premises was re inspected by the officer concerned of this department on 02/05/2024 in the presence of Dr. D. N. Mishra (Manager) and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Lodging or rooming building" Group A-1 {At G.F = Reception, open hall, 1st & 2nd floor = 7 rooms each floor & 3rd floor = 6 rooms Total 20 rooms} with effect from 13 2024 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2019.

Issued on ...13/05/2029.... at New Delhi by.

Delhi Fire Serv

Copy to:

1. The Joint. Commissioner of Police (Lic), 1st Floor, Licensing Unit, Police Station, Defence Colony,

2. The Manager, M/s Shhaurya Guest House, plot no-16, Pocket-B, Sector -13 Dwarka New Delhi.

Following fire safety directives must be adhered to:-

1. The Exits /passage to stair shall be kept free from any obstruction/ lock and key.

2. All the fire safety arrangements provided therein shall be maintained in good working condition at

3. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

4. The trained staff should be available round the clock.

- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 6. The certificate may not be treated in any case for the regularization of the unauthorized construction,

7. Basement strictly shall be kept vacant as seen during inspection.

The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.

9. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

 Name & address of the building: M/s Shhaurya Guest House, located at Plot no-16, Pocket-B, Sector -13 Dwarka New Delhi.

2. Type of Occupancy: Lodging or rooming;- Lodging or rooming "A-1"

3. Type of Case : Renewal Running at 1st, 2nd &3rd floor building comprise of (Basement + Ground + 3 Upper Floor)

 Details of previous NOC : F6/DFS/MS/SWZ/2021/GH/485 dated 28/10/2021

5. Fire Safety directives Letter No.: Old Case

6. Date of inspection :02/05/2024

7. Name of the Inspecting Officer: ADO (DWK)

8. Name and designation of Officer

from the building side : Dr. . D. N. Mishra (Manager

9. Year of Construction : 2014

10. Applicant's letter No. : 2024032603584 dated 18/04/2024

S	Minimum standards on fire prevention and fire safety U/R	33	As per N/6 N/8	,]	N/7 &	Provided site	aı	Remarks MR/NMR	
No	- of building						MR		
1.	- 1 14la	06 t)6 mtr		NA	N		NA	
8 2	Gate width Width of internal road		NA ·		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		NA		
			ŅA.		NA				
_	Number, width, Type & Arrang	geme	nts of exits						
2.	a. Number of staircases				2Nos		MR		
3	Upper floors	2 N		0.000		100	MR		
	Basements	2 N	os	2	Nos ·				
	1.1 - f atoircases			_				MR	
		1.5m &1.25m		Provided			IN	IR old case	
3	• Upper floors	1.5m &1.25m 1.5m &1.2m			2m	1			
	Basements The second								
	c. Protection of exits	Required P		Prov	rovided				
	• Fire check door	NA				IA		NA	
	 Pressurization 	01			P	rovided		MR	
	d. No of continuous	01		1 25 7		25 mtr	IV	⁄IR	
	staircase to terrace		1.25 mtr			1.25 III		MR	
655	e. Width Of Corridor	1m		1	1m				
- 59	f. Door Size		CV2						
3.	Compartmentation .					Provided		MR	
<u>J.</u>	• Fire check door	Required		Provided		rovided		MR	
	Sealing of electrical	Re	quired						
7 6 77	shafts			_	- I	NA .		NA	
	• Fire Rating of shaft	NA	1		- 1	11.5			
	door	· 140				NA		NA	
528	Water Curtain	NA		NA NA			NA		
		NA			I	N/A	4		
. 3	• Fire Dampers							MR	
4.	Smoke managements System		30 a/c per hour Pro		Provide	Provided		MR	
	Basements	a/c per hour					IVIIC		
	 Upper floors 	12	12 arc per nour						



•		(9)	^,	1/99	2					
5.	Fire E	xtinguishers		1						
	•	Total numbers	10Nos.		12 N			_	/IR	
	•	Types	ABC		CO ₂	& AE	SC .	N	/IR	
	. •	IS marking	Required	,	Prov	rided		N	⁄IR	t
5.	First -	Aid Hose Reels								
	•	Total numbers on	01	٠	Prov	rided		N	/IR	1
		each floor						- 1		Ļ
•	•	Length of hose reel	30 mtr	:::	30 n	ntr :		N	/IR	ı
		hose				•		-	(D)	Ł
	•	Nozzle diameter	5 MM		5 M	M		ļ	/IR	H
7.	Auton	natic fire detection and al				1 5	11-1		MR	┞
	•	Type of detectors	CO Detect			Prov	ided			L
	•	Location of Main Panel	Required	Prov	rided		7 - 7-		MR	
	. •	Location of Repeater Panel	NA	NA	197				NA	
		Alternate source of	Required	Prov	rided				MR	
		power								
	•	Hooters' Location	Required	Prov	rided				MR	
8.	MOE	FA	Required	Prov	rided		April 1		MR	
9.		Address System	NA	Prov					NA	
10.		natic Sprinkler System					12			
	•	Basements	Required	×			Provided-		IR.	
	٠.	Upper Floor	NA				NA	_	A	•
	•	Sprinkler above false ceiling	NA			7	NA	N	A	
11.	Intern	al Hydrants:								_
11.	intern	Size of riser/down-	100mm				Provided	M	R	Т
		comer	100111111				110.100			
7		Number of hydrants	01 no				01 no	M	R	
	-	per floor			•				٧	
	•	Hose Box	Required	٠.	•		Provided	M	IR	
12.	Yard l	Hydrants			-					Ξ
		Total number of	NA .	:			NA	N	A	
		hydrants	•						-	_
	. •	Hose Box	NA				NA	N	A	
13.	Pump	ing Arrangements:								
	•	Ground Level			بل			1		
je i	•	Discharge of main pump	NA				NA	8	A	
	4	Head of main pump	NA				NA	1000	Α	
	· >	Number of main	NA				NA	N	A	
		pumps						-		_
	200	Jockey pump out put	NA				NA	-	A	_
	>	Jockey pump head	NA			8 00	NA	_	A	_
	· >		NA ·	Fi.			NA	-	A	
		Standby Pump Head	NA	4	•		NA	_	A	_
	. >	Auto Staring/Manual stopping	NA ·				NA ·		Α	
	. >		NA.				NA .	N	Α	
	•	Terrace level	100	•						
	. >	Discharge of pump	900 LPM,	180 lpi	m i	Provid	led .	_	1R	
	. >	Head of the pump	35 mtrs			35mtr	S		1R	
1	>	Power supply	Required			DG se	t 125 KVA	N	1R	,
		Auto starting of pump	Required			Provid		Ņ	1R	
- 1		- · · · · · · · · · · · · · · · · · · ·					e	1		

. C	aptive water Storage for fire fi	ghting:	30)	Ca San kan	
Under ground tank capacity		NA	NA	NA	
	Draw off connection	NA ·	NA	NA	
	> Fire service inlet	NA	NA	NA	
	Access to tank	NA	NA	NA	
	Overhead Tank capacity	10000 ltrs	Provided	MR	
5 - 1	Exit Signage	Required	Provided	MR	
	Provision of Lifts		A DUTTE		
	 Pressurization of Lift Shaft 	NA	NA	NA	
	Pressurization of lift lobby	NA .	NA	NA	
	 Communication in lift Car 	Required	Provided	MR	
	 Fireman's Grounding Switch 	Required	Provided	MR	
	➤ Lift Signage	Required	Provided	MR	
17.	Standby power supply	Required	Provided	MR	
18.	Refuge Area		371	NA	
	> Total area	NA	NA	NA NA	
	> Location	NA	NA	IVA	
19.	Fire control room		NA	NA	
	> Detector system panel	NA	NA NA	NA	
	➤ Flow Switch Panel	NA	NA NA	NA	
	> PA System Panel	NA ·	NA .	NA	
	➤ Battery backup	NA .	NA .	NA 4	
	> Building Floor Plans	NA			
Ĭ.		ns for NA Co2	fire extinguisher	MR	
20	Special Fire Protection System Protection of special Risks, if	15 101	ded near electric	panel	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter no. F6/DFS/MS/SWZ/2021/GH/485 dated 28/10/2021 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Name: Udai vir Singh Designation: ADO (DWK)

CGO (57)

151 2014 M

Burlant