

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE **NEW DELHI-110001**

No.F.6/DFS/MS/EH/2024/SZ/ /4/S

Dated.13..105./2024

FIRE SAFETY CERTIFICATE

Certified that the Eating House in the Name & Style of M/s The Clay Oven located at Ground floor, D-1, Green Park, Ashirwad Building, New Delhi 110016 in the building comprised of Basement, Ground plus three upper floor owned/occupied by Alliance Enterprises was issued Fire Safety Certificate by this department vide letter no. F6/DFS/MS/EH/SZ/2021/243 dated 22/09/2021. The restaurant premise was reinspected by the officer concerned of this department on 08/05/2024 in the presence of Mr. Sree Kumar (Manager) and found that the said premise have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy Class D "Assembly Building" (Restaurant) and validity upto 31/03/2027 in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on <u>13</u> / <u>05</u> / 2024 at New Delhi by

DELHI FIRE SERVICE

Copy to: -

010 The Addl. C.P (Lic/Branch) First Floor, PS Defence Colony, New Delhi - 110049. (Ref. MHA Portal ID 2024041204888 dated 12-04-2024)

Conditions for the validity of Fire Safety Certificate: -

1. All the means of escape/entry/exit shall be kept free from any obstruction.

2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to nonfunctional fire safety measures shall be at the responsibility of the management.

3. All the staff members must know the correct method of operation of fire fighting

system.

4. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-

2016), if any.

6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six





2			N REPORT	THE PERSON OF		
1	Naı	ne & Address of the Building	M/s The Clay Oven Restaurant at D-1, Green Park, Ashirwad Building, New Delhi 110016			
2	Туг	e of Occupancy	Assembly 'Group-D' (Restaurant running at Ground floor only)			
3	Bui	ding comprised of	Basement, Ground plus three upper floors			
4	Ty	e of Case	Renewal			
5	De	ails of Previous NOC	F6/DFS/MS/EH/SZ/2021/243 dated 22/09/2021			
6	Fir	Safety Directives Letter No	Nil			
		e of Inspection	08.05.2024 assissed #			
7			DO (South) & ADO (BCP)			
8		me of the Inspecting Officers				
9	fro	me & Designation of Officers m the building side	Mr. Sree Kumar (Manager)			
10	Ye	ar of construction/ date of conversion	2006			
11	An	plicant letter No.	MHA Portal ID 2024041204888 dated 12-04-2024			
S. No.	Mi	nimum standards on Fire Prevention d Fire Safety U/R 33	As per old NOC	Provided at Site	Remarks	
1		cess to Building.				
•	-		Required	09 mtr	MR	
		Road width Gate width	NA NA	NA	-NA-	
		Width of internal road	NA	NA	-NA-	
2	N	umber, width, type & arrangement of e	xits	Jayy I Januari 3 +		
	8.	Number of Staircase		197	-NA-	
- 1 A	-	Upper floors	NA	NA NA	MR	
		Basement floor	02	Provided	IVIIX	
	b.	Width of Staircase	NA	NA NA	-NA-	
		Upper floors Resement floor		1.25 m & 0.93 m	MR	
		Basement floor	1.25·m	1.25 m & 0.95 Hr	(old case)	
	c.	Protection of exits		hosti grusikan landak sa	-NA-	
		Fire check door	NA-W Lee	NA NA	-NA-	
		Pressurization	-NA- 01	01	MR	
	d.	No. of continuous staircase to terrace	N/A	N/A	N/A	
	e.	Width of corridor	02 exits	1.10 m & 1.25 m	MR	
	f.	Door size		nearly health a	(old case	
3	C	mpartmentation.		Victor in the second		
- ED	H	Fire check door.	N/A	N/A	N/A	
		 Sealing of electrical shafts. 	N/A	N/A	N/A N/A	
		Fire rating of shaft door.	N/A	N/A N/A	N/A	
	1	Water curtain	N/A N/A	N/A N/A	N/A	
_ 5-1		Fire dampers.	IV/A		1	
4	Sn	oke Management system.		And a south w		
o Til		Promot pri/108,7	30 ACPH	Exhaust fan provided	MR	
	3	Basement Upper floors	12 ACPH	Exhaust fan provided	MR	
On!	T/E	re Extinguishers.		A/ (-k		
5	FI	Total numbers	08 Nos	08 Provided	MR	
	į	• Types	ABC / CO2	ABC & Co2	MR	
	. 7	ISI Marking	ISI marked	Provided	MR	
6	Hir	et Aid Hose Reels.	10.4			
U	1	 Total numbers on each floor. 	One	Provided	MR	
198	3	 Length of hose-reel hose. 	30m	Provided	MR	
	Ĵ.	Noggle Diameter	5mm	Provided	MR	
7	Au	tomatic fire detection & alarming system.				
	-	Type of detectors	N/A	N/A	N/A	
		• Type of detectors	02502020	STOREGE A	IVA	

Λ

	10/10			13.00
	Location of Main Panel	N/A	N/A	N/A
	Location of Repeater Panel	N/A	N/A	N/A
	Alternate source of power	N/A	N/A	N/A
	Hoofer's location	N/A	N/A	N/A
8	MOEFA	IVA		
9		Required	Provided	MR
	Public Address System	-NA-	NA	-NA-
10	Automatic Sprinkler System		_A	
	Basement	Required	ST I I I I I I I I I I I I I I I I I I I) (D
	Upper floors	Required	Provided	M/R
	Sprinkler above false ceiling		Provided	M/R
11	Internal Hydrants.	N/A	N/A	N/A
	Size of Riser/Down-comer		and the second second	
	Number of It	100mm	Provided	MR
	Number of Hydrant per floor Hose box.	-NA-	01 provided	-NA-
12	Yard Hydrants.	-NA-	01 provided	-NA-
			12 W 1 7215 278 1	
	Total number of hydrants.	-NA-	-NA-	NA.
13	Hose box.	-NA-	-NA-	-NA-
13	Pumping arrangements.		-NA-	-NA-
	Ground Level	o to recompany		
	S 200	N/A	secular ex-	
	Discharge of main pump.	-NA-	-NA-	-NA-
	Head of main pump.	-NA-	-NA-	-NA-
	Number of main pumps. Jockey Pump output.	-NA-	-NA-	-NA-
973	> Jockey Pump head.	-NA-	-NA-	-NA-
	Standby Pump output.	-NA-	-NA-	-NA-
	Standby Pump head.	N/A	-NA-	-NA-
	Auto Starting / Manual Stopping	N/A	-NA-	-NA-
	➤ Pump House Access	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
	Terrace Level		vibration to district	1421
	Discharge of pump.	900 LPM	900 & 180 LPM	MR
	Head of pump. Power supply	40m	35mtr	MR
	a supply.	Required	Provided	M/R
4	the state of the pump.	Required	Provided	M/R
· ·	Captive water storage for Fire Fighting.	2 1 1012	SorteMile politica e	
	Underground tank capacity.	-NA-	-NA-	-NA-
	Draw-off connection.	-NA-	-NA-	-NA-
	Fire Camina Tala	- n · ·	THE PART OF THE PA	
	Fire Service Inlet.	Required	Provided	M/K
	Access to tank.	-NA-	Provided -NA-	M/R -NA-
A 10	 Access to tank. Overhead tank capacity. 			
	Access to tank. Overhead tank capacity. Exit Signage.	-NA-	-NA-	-NA-
	 Access to tank. Overhead tank capacity. 	-NA- 5,000 ltrs	-NA- 5,000 ltrs	-NA- MR
	Access to tank. Overhead tank capacity. Exit Signage.	-NA- 5,000 ltrs	-NA- 5,000 ltrs Provided	-NA- MR MR
	Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft.	-NA- 5,000 ltrs Required	-NA- 5,000 ltrs Provided	-NA- MR MR
5	Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby.	-NA- 5,000 ltrs Required -NA- -NA-	-NA- 5,000 ltrs Provided -NANA-	-NA- MR MR -NA-
	 Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. 	-NA- 5,000 ltrs Required -NA- -NA- -NA-	-NA- 5,000 ltrs Provided -NA- -NA- -NA-	-NA- MR MR -NA- -NA-
	Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch.	-NA- 5,000 ltrs Required -NA- -NA- -NA-	-NA- 5,000 ltrs Provided -NANANANA-	-NA- MR MR -NA- -NA- -NA-
	 Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. 	-NA- 5,000 ltrs Required -NA- -NA- -NA-	-NA- 5,000 ltrs Provided -NA- -NA- -NA-	-NA- MR MR -NA- -NA-



		-NA-	-NA-	-NA-
19	Total area Location Fire Control Room.	-NA-	-NA-	-NA-
				l NA
	D. J Denal	-NA-	-NA-	-NA-
	 Detector System Panel. Flow Switch Panel. PA system Panel. Battery backup Building floor plan 	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
20	Special Fire Protection System for the Protection of special Risk, if any:	-NA-	-NA-	-NA-

The Fire protection systems provided in the premises were test checked at random and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standard on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no F6/DFS/MS/EH/SZ/2021/243 dated 22/09/2021, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

mus

Signature of the Inspection Officer

Name: Sh. Manoj Kumar Sharma

Design: DO (South)

Signature of the Inspecting Officer

Name: Sh. Rajesh Kumar

Design: ADO (BCP)

СГО (НО)

10/3/200g

Dineta M)

13/5/24