Dated: 10 /05/2024

O/Delhi4Fire S

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No. F6/DFS/MS/GH/2024/ 128

FIRE SAFETY CERTIFICATE

Certified that the building of M/s Anila Hotels (A unit of Maison stays pvt. Ltd.), Located at Ground, 1st, 2nd & 3rd floorA-15, Naraina Vihar, New Delhi-110028, in a building comprised of Basement + Stilt + Ground + 3 Upper Floors using basement = (storage) stilt= (parking), Ground floor = (reception, office & 09 guest rooms), 1st floor to 3rd floor=(09 guest rooms each floor), and a pantry for staff in tin shed on terrace (Now sealed) (Total = 36 rooms) was issued FSC vide Letter No. F6/DFS/MS/GH/SZ/2022/85, dated 07/02/2022. The premises was re inspected by the officer concerned of this department on 30/04/2024 in the presence of Sh. Vijay Chauhan (Account officer) and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential" (guest house) at Ground floor = (reception, office & 09 guest rooms), (1st floor to 3rd floor=09 guest rooms each floor), (Total=36 rooms) with effect from 10 0 2022 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 10 05 2024. at New Delhi by.

Copy to:

 The Joint. Commissioner of Police (Lic), 1st Floor, Licensing Unit, Police Station, Defence Colony, New Delhi.

 The Manager, M/s Anila Hotels (A unit of Maison stays pvt. Ltd.), Located at Ground, 1st, 2nd & 3rd floorA-15, Naraina Vihar, New Delhi-110028.

Following fire safety directives must be adhered to:-

1. 4th floor shall not be used as per undertaking given by owner/management

All the fire safety arrangements provided therein shall be maintained in good working condition at all times.

Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

4. The trained staff should be available round the clock.

5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.

6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

7. Basement strictly shall be kept vacant as seen during inspection.

8. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.

9. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building: M/s Anila Hotels (A unit of Maison stays pvt. Ltd.), Located at Ground, 1st, 2nd & 3rd floorA-15, Naraina Vihar, New Delhi-110028.

2. Type of Occupancy

:Lodging or rooming "A-1"

: Renewal (Running at Ground, 1st, 2nd & 3rd floor in a 3. Type of Case building comprised of Basement, Stilt, Ground + 3 Upper Floor)

4. Details of previous NOC: F6/DFS/MS/GH/SZ/2022/85, dated 07/02/2022

5. Fire Safety directives Letter No.: Nil

6. Date of inspection

:30/04/2024

7. Name of the Inspecting Officer: ADO (DWK)

8. Name and designation of Officer

from the building side

: Sh. Vijay Chauhan (Account officer)

9. Year of Construction

: Before 2010

S No	Minimum standards on fire prevention and fire safety U/R 33		As per ruse,			Provio site	1,000		Remai MR/N		
1.	Access of building			1	I D-	vided				MR	
	Road width	O mu				oogih	acible from road			MR	
	Gate width		THE COLUMN TWO IS NOT THE PARTY OF THE PARTY			accessible from road				NA	
	 Width of internal road 		Α.								
2.	Number, width, Type & Arrang	gem	ents of e	xits	100						
2.	a. Number of staircases) M (Daing (eing ol	old case)			
-	Upper floors Basements		1 No.		01		MR (Being old ea			u case)	
			02 Nos. 02 Nos			os.					
	b. Width of staircases	•					T	ID /	Reing	old case)	
3	 Upper floors 	Old case 1.32 m		16	1	VIII.	Reing	g old case)			
~ /	Basements	Old case 1.50 & 1.15m				1	MIC (Doing out 122)				
	c. Protection of exits							154		MR	
	Fire check door	R	Required Provided				374			NA	
	 Pressurization 		NA			_	NA		MR		
	d. No of continuous staircase to terrace e. Width Of Corridor		01			0	01		IVAC		
			old case 1.80m & 1		1.47	1.47m MR (Bein		g old case)			
٠.,			old case	0.88m			MR (Being old c		g old case)		
	f. Door Size	+	· ·	0.0	OZZZ			XI.			
3.	Compartmentation	+	Required . Provided			ed			MR		
	Fire check door Sealing of electrical		NA NA			. 1	NA NA		NA		
	shafts		NA.			1			NA		
	Fire Rating of shaft	L	N/A								
	door	1	NA NA			1	NA NA			NA	
(*)	Water Curtain Fire Dampers					1				NA	

W

N/41.

ě

4.	Smoke	e managements Syste	em			Prov	iided	MR
	•	Dasement		per ho		Prov		MR
	. •	Upper floors	12 a/c	per ho	ur	Plov	lucu	
5.	Fire E	xtinguishers			*		Provided	MR
	•	Total numbers		20 Nos. ABC & CO ₂			CO ₂ & ABC	MR
	•	Types				2		MR
	•	IS marking		Require	;a 		Provided	IVIX
6.	First -	- Aid Hose Reels	7					MR
0.	•	Total numbers on		01			Provided	IVIIX
		each floor	L			n¥'	Didad	MR
		Length of hose ree	1	30 mtr			Provided	,,,,,
		hose	L	* * * * *			Provided	MR
	•	Nozzle diameter		J IVALVA			Provided	1,122
7.	Autor	natic fire detection a	nd ala	rming s	yste	m	n .:1.1	MR
	•	Type of detectors		CO de	tecto)rs	Provided	
	•	Location of Main		Require	ed ,		Provided	MR
		Panel	*					17.
×	•	Location of Repeat	ter	NA		NA		NA
		Panel						1.00
	•	Alternațe source of	f	Require	ed .	DG s	et 72 KVA	MR
		power					In	MI
9.	. •	Hooters' Location		Require			Provided	240000
8.	MOE	FA		Require		Provi		MR
9.		c Address System		Require	ed	Provi	ded	MR
10.	Autor	matic Sprinkler Syste			10	·		1.0
	•	Basements		Require	ed		Provided	MR
	•	Upper Floor		NA			NA	NA
	•	Sprinkler above fa	lse	NA	21 1 - J		. NA	NA
	2	ceiling	- 114	_				
11.	Intern	nal Hydrants:	4.0			**		150
	•	Size of riser/down		entry .	NA	Ļ	100mm	NA
	. •	Number of hydran	ts per	tloor	NA		01 No.	NA
	•	Hose Box		NA :			01 No.	NA
12.	Yard	Hydrants		- 1				-
		Total number of		NA			01 No.	NA
		hydrants						
	•	Hose Box	9	NA	NA ·		01 No.	NA
13.	Pump	oing Arrangements:						
	•		•					Se
	•	Discharge of main			_		NA	NA
	>	or man pan		NA			NA	NA
		Number of main p		N/			NA NA	NA
	>	The second second		NA			. NA	NA
	>	really paring mean		NA			NA	NA
		Standby Pump out		· NA		2002	· NA	NA
	>			N/		•	NA .	NA
	, >		ual	N	A ·		NA ·	NA
		stopping			2	⁴ Dku	Professional Control	
	1	Pump House Acce	SS	NA NA 450 lpm Provided 30 mtrs Provided			NA	NA
		Terrace level					Karalani.	
	1 2	Discharge of pump					Provided	MR
,		Lload at the					D	
	. >	Head of the pump	95	. 30	mti	·S .	Provided	MR
	. A	Head of the pump Power supply Auto starting of pu			mtr		Provided	MR MR

To	aptive water Storage for fire fig • Under ground tank	nung NA			NA	NA	
T	• Officer P.	*			374	NA	
1	> Draw off connection	NA			NA	NA	
1	> Fire service inlet	NA NA 15,000 ltr			NA	NA	
1	> Access to tank				NA	MR	
1	Overhead Tank				Provided	MAL	
1					5 11.1	MR	
1	capacity	Requ	ired		Provided	1	
_	Exit Signage				Tare	NA	
5.	Provision of Lifts > Pressurization of Lift SI	Shaft NA			NA .	NA	
	> Pressurization of lift lot	oby	NA		NA	MR	
١	 Pressurization of interest Communication in lift (Car Required		ed	Provided	MR	
.	 Communication in interest Fireman's Grounding 		Required		Provided	MIK	
-	Switch		-	1	Provided	MR	
	> Lift Signage	Required		eu	Provided	MR	
_			Requi	red	Horas		
7.	Refuge Area				NA .	NA	
8.	> Total area	*	NA		NA NA	NA	
	> Location		NA		INA		
	the free land		2		NA	NA	
19.	> Detector system pane				NA NA	NA	
36	> Flow Switch Panel	NA ·			NA NA	NA	
	> PA System Panel > Battery backup > Building Floor Plans		\		Provided	MR	
			quired		NA	NA	
			A		NA	MR	
20	Destaction	Kedinen 02.2			C fire extinguisher ed near electric pan	el	

The fire protection systems provided in the building were test checked and found

In view of the deemed compliance of minimum standards on fire prevention and fire functional at the time of inspection. safety as required under the rules the NOC issued vide letter No. F6/DFS/MS/GH/SZ/2022/85, dated 07/02/2022 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended. If approved FSC may be issued.

ADOPOWIE