

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/School/WZ/2024/callege 26

Dated: 07/05/2021

FIRE SAFETY CERTIFICATE

Rohini, Delhi-110086, comprised of Ground + 03 upper floors owned/occupied by Maharaja Agrasen Technical Education Society have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of fire service on dated 29.04.2024 in the presence of Mr. Arun Ray (Civil Engineer) and that the building/ premise is fit for occupancy Group B Educational with effect from ___67 | 05 | 2024 ____ for a period of three years, in accordance with the Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 07 05 2024 at New Delhi by

(Atul Garg)
DIRECTOR
Ph; 011-23414000

Copy to:

1. The Principal, Maharaja Agrasen Global School 1, Lakhi ram Park, Sector-22, Rohini, Delki-110086.

The Director of Education, GNCT of Delhi Old Secretariat, Delhi-110054
 Conditions for validity of Fire Safety Certificate;

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.

3. The regimed fire fighting staff should be available round the clock.

- 4. Any deviation with regard to the construction etc shall be verified by the concerned business sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its espiry".

7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schule of Delhi Fire Service Rules 2010. The form is available on

8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.

hup://www.delhi.gov.in/wps/wcm/connect/doit_fire/FIRE/Home/Fire+Safety+Acts+and+R_ules/_http://www.delhi.gov.in/wps/wcm/connect/doit_fire/FIRE/Home/Forms

| | | | Thiomas c | TTION DEPORT | | | | |
|---|----------------------|---|-------------------------------|--|---------------------|---------------|--|--|
| / | | | INSPEC | CTION REPORT | Gabasi 1 Tabbi | | | |
| 1. | Name & a | ddress of the building | Rohini, | Delhi-110086. | School 1, Lakhi ram | Park, Sector- | | |
| 2. | Type of O | ccupancy | Educati | ional | upper floors) | | | |
| 3. Type of Case New C 4. Details of Previous NOC -NA- 5. Fire Safety directives letter No NBC P 6. Date of inspection 29.04.2 | | | | v Case (Ground + 03 upper floors) | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| 8. | Name and From the | designation of officers building side | Mr. Arun Ray (Civil Engineer) | | | | | |
| 9. | Year of C | of Construction | | -NA- OD No. 14027 dated 11.03.2024 Remark Rem | | | | |
| 10. | Applicant | s letter No. | | . 14027 dated 11.0. | Provided at site | Remarks | | |
| | Minimu | n Standards on fire prev | ention | | | MR/NMR | | |
| lo | | safety U/R 33 | | Requirement | | | | |
| | Access to | building | | 6.0m | 6.0m | MR | | |
| | • R | oad width | | | 4.5m | MR | | |
| | • G | ate width | | 4.5m | -NA- | -NA- | | |
| | • V | idth of internal road | | -NA- | -NA- | -INA- | | |
| 2. | Number | Number, Width, Type & Arrangement of Exits | | | | | | |
| _ | a. Numb | nber of staircases | | | 1 00 | l Mm | | |
| | | Upper Floors | | 02nos. | 03nos. | MR | | |
| | | Basements | | -NA- | -NA- | -NA- | | |
| | | th of staircases | | 2.5 | | | | |
| | | | | 1.5m | 3 x 1.7m | MR | | |
| | 100 | Upper Floor | | -NA- | -NA- | -NA- | | |
| | D 4 | Basements | | | | * | | |
| | c. Prote | ection of exits Fire check door | | -NA- | -NA- | -NA- | | |
| | | Pressurization | | -NA- | -NA- | -NA- | | |
| | • | I ME THE CALL THE STREET THE CONTROL OF THE STREET THE | torrace | 02nos. | 03nos. | MR | | |
| | | f continuous staircases to terrace | | 1.5m | 2.10m | MR | | |
| | | th of Corridor | | -NA- | -NA- | -NA- | | |
| | 14.15.41.21.4 | or Size | | -11/1- | | | | |
| • | | artmentation | | -NA- | -NA- | -NA- | | |
| | 200 | Fire check door | | -NA- | -NA- | -NA- | | |
| | | Sealing of electrical shafts | | -NA- -NA- | -NA- | -NA- | | |
| | 130 | re Rating of shaft door Vater Curtain | | -NA- | -NA- | -NA- | | |
| | | Children Children Children | | 2012(2) | -NA- | -NA- | | |
| 4. | | Fire Dampers ke Management System | | -NA- | -11/7- | | | |
| ** | | Basements | | NT A | -NA- | -NA- | | |
| | | Upper floors | | -NA- | Natural ventilated | MR | | |
| 5. | | | | 12 a/c per hour | ivaturai ventilated | IVIX | | |
| | | Fire Extinguishers a) Total numbers | | | 17 | MR | | |
| | | Types | | 12nos. | 16nos. | MR | | |
| | | | | ABC/CO2 | ABC/CO2 | MR | | |
| 6. | First-A: | c) IS marking rst-Aid Hose Reels | | ISI marked | Yes | IVIX | | |
| 24-5 | | | | | | MR | | |
| | b) I | I cach moor | | 02nos. | Provided | MR | | |
| | c) 1 | ength of hose reel hose lozzle diameter | _ | 30mm | Provided | MR | | |
| | | o-zae diameter | | 5m | Provided | MIK | | |

John John

4/4

Refug

| | de de la coming system | | | | | |
|-------|--|-----------------------|-----------|------|--|--|
| A | Automatic fire detection and alarming system -NANA- | | | | | |
| | a) Type of detectors | -NA- | -NA- | -NA- | | |
| | b) Location of Main Panel | A. 100 CO | -NA- | -NA- | | |
| | c) Location of Repeater Panel | -NA- | -NA- | -NA- | | |
| | d) Alternate source of power | -NA- | -NA- | -NA- | | |
| | e) Hooters' Location | -NA- | -NA- | -NA- | | |
| . 1 | MOEFA | -NA- | 72.770.00 | -NA- | | |
| . 1 | Public Address System | -NA- | -NA- | -NA- | | |
| 0. | Automatic Sprinkler System | 0 | | NA. | | |
| | a) Basement | -NA- | -NA- | -NA- | | |
| | b) Ground & Upper Floors | -NA- | -NA- | -NA- | | |
| | c) Sprinkler above false ceiling | -NA- | -NA- | -NA- | | |
| 11. | Internal Hydrants | | | | | |
| 324 | a) Size of riser/down-comer | -NA- | -NA- | -NA- | | |
| | b) Number of hydrants per floor | -NA- | -NA- | -NA- | | |
| Ì | c) Hose Box | -NA- | -NA- | -NA- | | |
| 12. | Yard Hydrants | | | | | |
| DAME. | a) Total number of hydrants | -NA- | -NA- | -NA- | | |
| | b) Hose Box | -NA- | -NA- | -NA- | | |
| 13. | Pumping Arrangements | | | | | |
| | Ground Level | -NA- | -NA- | -NA- | | |
| | Discharge of main Pump | -NA- | -NA- | -NA- | | |
| | Head of Main pump | -NA- | -NA- | -NA- | | |
| | Number of main pumps | -NA- | -NA- | -NA- | | |
| | > Jockey Pump out put | -NA- | -NA- | -NA- | | |
| | > Jockey pump head | -NA- | -NA- | -NA- | | |
| | Standby Pump out putStandby Pump Head | -NA- | -NA- | -NA- | | |
| | > Auto Starting/Manual Stopping | -NA- | -NA- | -NA- | | |
| | > Pump House Access | -NA- | -NA- | -NA- | | |
| _ | Terrace level | -NA- | -NA- | -NA- | | |
| | > Discharge of pump | 4501 | | | | |
| | > Head of the pump | 450lpm 40m | 450lpm | MR | | |
| | > Power Supply | Required | 40m | MR | | |
| | > Auto Starting of pump | Required | Provided | MR | | |
| 14. | Captive Water Storage for fire fighting | required | Provided | MR | | |
| | The state of the s | | | | | |
| | > Draw-off connection | -NA- | -NA- | -NA- | | |
| | > Fire service inlet | -NA- | -NA- | -NA- | | |
| | > Access to tank | | -NA- | -NA- | | |
| | Overhead Tank capacity | -NA- | -NA- | -NA- | | |
| 15. | Exit Signage. | 10,000ltr Required | 10,000ltr | MR | | |
| 16. | Provision of Lifts. | Required | Provided | MR | | |
| 10. | a) Pressurization of Lift Shaft | NIA I | | | | |
| | b) Pressurization of Lift Shart b) Pressurization of Lift lobby | -NA- | -NA- | -NA- | | |
| | c) Communication In lift Car | -NA- | -NA- | -NA- | | |
| | d) Fireman's Grounding Switch | -NA- | -NA- | -NA- | | |
| | e) Lift Signage | -NA- | -NA- | -NA- | | |
| 17. | Standby power supply | -NA- | -NA- | -NA- | | |
| 1/. | Standay po | Chy | * 36.47 | -NA- | | |

| | Refuge Area. a) Total Area | | 3 | | |
|-----|-----------------------------|----------------------|-------|------|------|
| y | b) Location | | -NA- | -NA- | 1 |
| 19. | | | -NA- | | -NA- |
| | Fire Control Room -NA | | | -NA- | -NA- |
| | a) Detector Sy | etector System Panel | NIA T | | |
| | b) Flow Swite | h Panel | -NA- | -NA- | -NA- |
| | c) PA System | Panel | -NA- | -NA- | -NA- |
| | d) Battery bac | attery backup | -NA- | -NA- | -NA- |
| | e) Building Fl | oor Plans | -NA- | -NA- | |
| 0. | Special Fire Prote | oot i idiis | -NA- | -NA- | -NA- |
| | Protection of spec | ial Risks, if any | -NA- | -NA- | -NA- |

The fire protection systems provided in the building were test checked and found functional at the time

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rule 2010.

No Such Case

Signature of the Inspecting Officer
Name Ajay Kumar Sharma
Designation ADO(Rohini)

Dy. CFO(WZ)

01 00

2 5 2024 Enceted W 5 M

May Phyler.

FT cletter to fort up for kind perisal and Agnature Bear.

Director

myr 2/5/24