GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, NEW DELHI - 110001

No. F6/DFS/MS/EH/MN/2024/ |41

Dated: 13/05 /2024

FIRE SAFETY CERTIFICATE

Certified that the M/s. Hira Sweets & Confectionary Private Limited located at A-2, Ground Floor, Najafgarh Road, Kirti Nagar, New Delhi 110015 in a building comprised of Basement, Ground & three upper floors Owned/Occupied by M/s. Hira Sweets & Confectionary Private Limited was issued Fire Safety Certificate vide Letter No. F6/DFS/MS/EH/MN/2021/105 dated 20/04/2021, The premises was re-inspected by officer concerned of this department on 01/05/2024 in the presence of Sh. Ratna Prakash Kar and found that the said building/Premises have deemed complied with the fire prevention & fire safety requirements in accordance with Rule 33 of Delhi Fire Service Rule 2010 & the said premises is fit for occupancy class "Assembly" Group - D (Ground Floor Only) and valid upto 31/03/2027 in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010 condition mentioned below.

Issued on ... 13 05 2024. at New Delhi by.

Copy to:

- 1. M/s. Hira Sweets & Confectionary Private Limited located at H. N. A-2, Ground Floor, Upper basement, Kirti Nagar New Delhi - 110015.
- 2. Dy. Health Officer, MCD, West Zone, Vishal Enclave, Rajouri Garden, New Delhi -110027. (dhowest zone@gmail.com)
- 3. The Joint Commissioner of Police, Licensing Unit, 1st floor, Police Station, Defence Colony, New Delhi. (addlcp.lic-dl@nic.in.)

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning
- 5. The certificate may not be treated in any case for the regularization of the unauthorized
- 6. Basement shall be used as per building bye laws.
- 7. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on
- 9. This NOC is valid for Ground floor only.

111

			NSPE	CTION REPORT		
1	. Nam	e & address of the building	onary Pvt. Ltd. located Road, Kirti Nagar, Ne			
2	. Type	of Occupancy	Ass	embly/ Restaurant (Ea	ating House)	
3. Type of Case				ewal		
			ECO	DEGA/G/EUA DI/202	1/105 dated 20/04/202	1
				DF8/M8/EH/MN/202	1/105 dated 20/04/202	1
	4	Safety directives letter No	Nil			
- 6	. Date	of inspection	01/0	05/2024		
				abjeet Singh ADO (M	N)	
8	. Nam offic	e and designation of ers from the building side	Sh.	Ratna Prakash Kar		
9	. Year	of Construction	201	0 (As per MHA Porta		W T W
10	0. Appli	cant's letter No.	Onl	ine Application ID No	o. 2024041505191 dat	ed 15/04/2024
The	Said R	estaurant is running at Gro	ound	Floor in a building	comprised of Basem	ent + Ground
S.	C2585 Re-	inimum Standards on fire		Required as per Rule 35(6) of DFS Rule 2010	Provided at site	Remarks MR/NMR
No.		ention and fire safety U/R 3	3 3	55(6) 01 DF5 Rule 2010		IVII U I VII I
1	Acces	ss to building Road width		06 m	Provided	MR
	•	Gate width		5 m	Provided	MR
		Width of internal road		NA NA	NA	NA
	N7	Contracts parameter	×0770		TI SKET I	
2		ber, Width, Type & Arrang mber of staircases	geme	III OI EXICS	7	
	a. Ivu	Upper Floors		NA	NA (GF)	NA
	·	Basements		N/A	N/A	MR
	b. Wi	dth of staircases		I Sinv Li	Lagran of the	
		Upper Floors		NA	NA (GF)	NA
		Basements		NA	NA	NA
	c. Pro	tection of exits			RE 120	NA
	- ₹ •	Fire check door		NA	NA NA	NA NA
	•	Pressurization		NA	NA NA	NA NA
	N53.5	of continuous staircases to ter	rrace	NA	NA NA	NA NA
		th of Corridor	100	NA 2 V 1 5 m	Provided 2 & 1.6 m	MR
	g. Do	or Size		2 X 1.5 m	Flovided 2 & 1.0 iii	11124
	Comp	artmentation.			NA	NA
	•	Fire check door		NA NA	NA NA	NA
		Sealing of electrical shafts		NA NA	NA NA	NA
	•	Fire Rating of shaft door		NA NA	NA NA	NA
		Water Curtain		NA NA	NA NA	NA NA
	•	Fire Dampers		NA	IIA	
	Smok	e Management System.		1 111	NA	NA
	•	Basements		NA		MR
\		Upper floors		Required	Provided	, IVIK
	Fire F	extinguishers		-,		
	FIICE	Total numbers		05 Nos.	Provided	MR
, ="		Types		CO ₂ , ABC type	Provided	MR
	•	IS marking		ISI marked	Provided	MR

84/

- 1	12	
~ 1	11/	
	, ,	

8 9 10 11 II II 2 Y	First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarmin Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location MOEFA Public Address System. Automatic Sprinkler System. Basement Upper Floor Sprinkler above false ceiling Internal Hydrants Size of riser/down-comer Number of hydrants per floor	01 30 m 5mm 5mm Respectively NA NA NA NA NA Required NA Required NA	Provided Provided Provided NA NA NA NA NA NA Provided Provided Provided Provided Provided	MR MR MR MR NA
8 9 110 12 11	Length of hose reel hose Nozzle diameter Automatic fire detection and alarmin Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location MOEFA Public Address System. Automatic Sprinkler System. Basement Upper Floor Sprinkler above false ceiling Internal Hydrants Size of riser/down-comer Number of hydrants per floor	Smm g system. NA NA NA NA NA NA Required NA Required NA NA NA NA NA NA	Provided NA NA NA NA NA NA Provided NA Provided Provided	MR NA NA NA NA NA NA MR NA NA
8 9 110 12 11	Nozzle diameter Automatic fire detection and alarmin Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location MOEFA Public Address System. Automatic Sprinkler System. Basement Upper Floor Sprinkler above false ceiling Internal Hydrants Size of riser/down-comer Number of hydrants per floor	NA NA NA NA NA Required NA Required NA NA NA	NA NA NA NA NA Provided NA Provided Provided	NA NA NA NA NA NA MR NA MR NA
8 9 110 12 11	 Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location MOEFA Public Address System. Automatic Sprinkler System. Basement Upper Floor Sprinkler above false ceiling Internal Hydrants Size of riser/down-comer Number of hydrants per floor 	NA NA NA NA NA Required NA Required NA NA NA	NA NA NA NA Provided NA Provided Provided	NA NA NA NA MR NA MR NA
8 9 10 11 II II 2 Y	 Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location MOEFA Public Address System. Automatic Sprinkler System. Basement Upper Floor Sprinkler above false ceiling Internal Hydrants Size of riser/down-comer Number of hydrants per floor 	NA NA NA NA NA Required NA Required NA NA NA	NA NA NA NA Provided NA Provided Provided	NA NA NA NA MR NA MR NA
9 1 10 2 11 I	Location of Repeater Panel Alternate source of power Hooters' Location MOEFA Public Address System. Automatic Sprinkler System. Basement Upper Floor Sprinkler above false ceiling Internal Hydrants Size of riser/down-comer Number of hydrants per floor	NA NA NA Required NA Required NA NA NA	NA NA NA Provided NA Provided Provided	NA NA NA MR NA MR NA
9 1 10 1 1 1 2 Y	Alternate source of power Hooters' Location MOEFA Public Address System. Automatic Sprinkler System. Basement Upper Floor Sprinkler above false ceiling Internal Hydrants Size of riser/down-comer Number of hydrants per floor	NA NA Required NA Required NA NA NA	NA NA Provided NA Provided Provided	NA NA MR NA MR
9 1 10 1 1 1 2 Y	Hooters' Location MOEFA Public Address System. Automatic Sprinkler System. Basement Upper Floor Sprinkler above false ceiling Internal Hydrants Size of riser/down-comer Number of hydrants per floor	NA Required NA Required NA NA NA	NA Provided NA Provided Provided	NA MR NA MR NA
9 1 10 1 1 1 2 Y	MOEFA Public Address System. Automatic Sprinkler System. Basement Upper Floor Sprinkler above false ceiling Internal Hydrants Size of riser/down-comer Number of hydrants per floor	Required NA NA NA	Provided NA Provided Provided	MR NA MR NA
9 1 10 1 1 1 2 Y	Public Address System. Automatic Sprinkler System. Basement Upper Floor Sprinkler above false ceiling Internal Hydrants Size of riser/down-comer Number of hydrants per floor	Required NA NA	NA Provided Provided	MR NA
10 I	Automatic Sprinkler System. Basement Upper Floor Sprinkler above false ceiling Internal Hydrants Size of riser/down-comer Number of hydrants per floor	Required NA NA	Provided Provided	MR NA
11 I	Basement Upper Floor Sprinkler above false ceiling Internal Hydrants Size of riser/down-comer Number of hydrants per floor	NA NA	Provided	NA
2 Y	Upper Floor Sprinkler above false ceiling Internal Hydrants Size of riser/down-comer Number of hydrants per floor	NA NA	Provided	NA
2 Y	Sprinkler above false ceiling Internal Hydrants Size of riser/down-comer Number of hydrants per floor	NA NA		50 5 0
2 Y	Size of riser/down-comer Number of hydrants per floor		Provided	NA
2 Y	 Size of riser/down-comer Number of hydrants per floor 	100 mm		
	 Number of hydrants per floor 	100 mm		- 7
			Provided	MR
		1 Nos.	Provided	MR
	Hose Box	1 Nos.	Provided	MR
B Pt	Yard Hydrants.	. 3)		
P	Total number of hydrants	NA	NA	NA.
P	Hose Box	NA	NA	NA
	umping Arrangements.			
	Ground Level		Allow and the	
	Discharge of main Pump	NR		
1	➤ Head of Main pump	NR NR	NR	NR
	Number of main pumps	NR NR	NR NR	NR
	Jockey Pump out put	NR NR	NR NR	NR
	Jockey pump head	NR	NR NR	NR
	Standby Pump out put	NR	NR NR	NR
	➢ Standby Pump Head	NR	NR NR	NR
	➤ Auto Starting/ Manual stopping	NR	NR NR	NR
	Pump House Access	NR		NR
. •	Terrace level	INC	NR	NR
	Discharge of pump	450 lpm		1
	➤ Head of the pump	40 m	Provided	MR
	Power Supply		Provided	MR
	Auto Starting of pump	Required	Provided	MR
Car		Required	Provided	MR
1	ptive Water Storage for fire fighting	441	and a	
'	Underground tank capacity	NA	NA	NA
	> Draw-off connection	NA	Provided	NA
1 .	Fire service inlet	NA	Provided	NA
'	> Access to tank	NA	Provided	NA
•	Overhead Tank capacity	20,000 ltrs	Provided	MR
Exit	Signage.	Required	Provided	
	The second second	quiiou	- 1011000	MR

		MIN				
16	Provision of Lifts.			1		
	Pressurization of Lift Shaft	NA	NA	NA		
	Pressurization of Lift lobby	NA NA	NA	NA		
	Communication In lift Car	NA NA	NA	NA		
	Fireman's Grounding Switch	NA	NA	NA		
	Lift Signage	NA NA	NA	NA		
17	Standby power supply	Required	Provided	MR		
18	Refuge Area.					
	> Total Area	NA	NA	NA		
	> Location	NA NA	NA	NA		
19	Fire Control Room					
	Detector System Panel	NA	NA	NA		
	Flow Switch Panel	NA NA	NA	NA		
	PA System Panel	NA NA	NA	NA		
	Batter backup		NA	NA		
	Building Floor Plans	NA NA	· NA	NA		
		NA	NA	NA		
20	Special Fire Protection Systems for Protection of special Risks, if any:	NA	PE 14			

The fire fighting arrangements provided in the building/restaurant were checked & found functional at the time of inspection.

Keeping in view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required under the rules, the NOC vide letter no F6/DFS/MS/EH/MN/2021/105 dated 20/04/2021 renewal under the rule 35 of the Delhi Fire Service rules 2010 is recommended.

18 ADO MN 06/5 2024 for no pudney

Q4000 V612)

06/05/2024

Signature of the Inspecting Officer

Name: Sarabjeet Singh Designation: ADO (MN)

253/10M

8 5) John

eneutary My of 20

any at

Sir, F. T is put up

for your

Kind persuel