

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F6/DFS/MS/2024/School/WZ/ 459

Dated: 22/05/2023

## FIRE SAFETY CERTIFICATE

Certified that the Malik Public School, B-130, Vijay Vihar, Phase-II, Rohini, Delhi-110085, comprised of Ground + 03 upper floors has already been issued FSC by this department vide letter No. F.6/DFS/MS/2018/WZ/1759 dated 27.07.2018. The premises was re-inspected by the officer concerned of this department on 14.05.2024 in the presence of Mr. Subhash Malik and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises fit for occupancy class Group B Educational with effect from 22 05 2024 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subjected to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 22 05 2024 at New Delhi by

DIRECTOR Ph; 011-23414000

## Copy to: -

1. The Director, Education, Government of N.C.T of Delhi. Old Sect. Delhi - 54.

2. The Principal, Malik Public School, B-130, Vijay Vihar, Phase-II, Rohini, Delhi-110085. Conditions for the validity of Fire Safety Certificate:

1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.

- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on
- 8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.

http://www.delhi.gov.in/wps/wcm/connect/doit fire/FIRE/Home/Fire+Safety+Acts+an d+Rules/ http://www.delhi.gov.in/wps/wcm/connect/doit fire/FIRE/Home/Forms

n/n

						æ.	
1.	Name &	ddress of the building	INSPEC	CTION REPORT			
<u> </u>		ddress of the building	dress of the building Malik Public Sabari P. 100 YEL THE TO Delki				
	I VDO - C -		110085	Public School, B-130, Vijay Vihar, Phase-II, Rohini, Delhi-			
3.	Type of C	ase	Educat				
		Safety directives letter No NBC I		Renewal (Ground + 03 upper floors) F.6/DFS/MS/2018/WZ/1759 dated 27.07.2018. NBC Part-IV.			
$\frac{3}{6}$	Fire Safet						
$-\frac{0}{7}$	Date of in						
	" 'euric Ot I	1 11001					
٠,				Ajay Kumar Sharma (ADO Rohini) Subhash Malik			
9.	Venn of C	uesignation of officers uilding side	IVII. Bu	Uliasii ivialik			
10	Year of Co	nstruction	-NA-				
S.	Applicant's letter N		e e-mail dated 07.05.2024.				
No	Millimum Standards on C		ention	NBC	Provided at site	Remarks	
1.		ire safety U/R 33		Requirement		MR/NMR	
	• Ro	Duilding					
		ad width		Accessible	Accessible	MR	
		e width		Directly accessible	Directly accessible	MR	
2.	N W	Width of internal road		374	-NA-	-NA-	
۷.	Number,	Width, Type & Arrangement of		Exits		L	
		of staircases					
		Upper Floors		02nos.	02nos.	MR	
		Basements		-NA-	-NA-	-NA-	
	b. Width	of staircases			.51	-1121	
	•	Upper Floor		1.5m & 1.0m	1.5m & 1.0m	MR	
		Basements		-NA-	NY ALEXANDER	XXX 0.5	
		tion of exits		-NA-	-NA-	-NA-	
		Fire check door		-NA-	374		
	•	Pressurization			-NA-	-NA-	
	d. No. of	continuous staircases to terrace		-NA-	-NA-	-NA-	
	e. Width	of Corridor		01nos.	01nos.	MR	
	f. Door S	A MAN TO CONTRACT CON		-NA-	-NA-	-NA-	
3.		E-89		1.0m	1.0m	MR	
-		Compartmentation		- 200m			
	2004	ire check door		-NA-	-NA-	-NA-	
		ling of electrical shafts		-NA-	-NA-	-NA-	
		Rating of shaft door		-NA-	-NA-	-NA-	
		ater Curtain		-NA-	-NA-	-NA-	
		re Dampers		-NA-	-NA-	-NA-	
1.	Smoke Management System						
	,	asements		-NA-	-NA-	-NA-	
		b) Upper floors		12 a/c per hour	Natural ventilated	- 2 25.00	
5.	Fire Extinguishers			1 Tonulaied	MR		
	a) Tot	Total numbers		08nos.	08nos.		
	b) Ty	vpes		ABC/CO2		MR	
	0.85.77.	S marking		ISI marked	ABC-08nos.	MR	
5.		Hose Reels		AUG	Yes	MR	
•				Olnos.			
	/	Length of hose reel hose		30mm	01nos.	MR	
- 1		Nozzle diameter		5m	Provided	MR	
					Provided		

TH



		$H _{\Gamma}$		6	
7.	Automatic fire detection and alarming system				
	a) Type of detectors	-NA-	-NA-	-NA-	
	b) Location of Main Panel	- SAMONE -	-NA-	-NA-	
		-NA-	-NA-	-NA-	
	, the of responder failer	-NA-	-NA-	-NA-	
	, and source of power	-NA-	-NA-	-NA-	
0	e) Hooters' Location	-NA-	-NA-	-NA-	
8.	MOEFA	-NA-	-NA-	-NA-	
9.	Public Address System	-NA-	-NA		
10.	Automatic Sprinkler System	- X*A	-NA-	-NA-	
	a) Basement	-NA-	-NA-	-NA-	
	b) Ground & Upper Floors	-NA-	-NA-	-NA-	
	c) Sprinkler above false ceiling	-NA-	-1//		
11.	Internal Hydrants	271	-NA-	-NA-	
	a) Size of riser/down-comer	-NA-	-NA-	-NA-	
	b) Number of hydrants per floor	-NA-	-NA-	-NA-	
	c) Hose Box -NA-				
12.	Yard Hydrants	N/A	-NA-	-NA-	
-	a) Total number of hydrants	-NA-	-NA-	-NA-	
	b) Hose Box	-NA-			
13.	Pumping Arrangements	-NA-	-NA-	-NA-	
	Ground Level	-NA-	-NA-	-NA-	
	Discharge of main Pump	-NA-	-NA-	-NA-	
	> Head of Main pump	-NA-	-NA-	-NA-	
	> Number of main pumps	-NA-	-NA-	-NA-	
	> Jockey Pump out put	-NA-	-NA-	-NA-	
	> Jockey pump head	-NA-	-NA-	-NA-	
	> Standby Pump out put	-NA-	-NA-	-NA-	
	<ul> <li>Standby Pump Head</li> <li>Auto Starting/Manual Stopping</li> </ul>	-NA-	-NA-	-NA-	
	- TT - A 00000	-NA-	-NA-	-NA-	
	Pump House Access				
	Terrace level	450lpm	450lpm	MR	
	➤ Discharge of pump	40m	40m	MR	
	➤ Head of the pump	-NA-	-NA-	-NA-	
	> Power Supply	-NA-	-NA-	-NA-	
/	> Auto Starting of pump			1	
14.	Captive Water Storage for fire fighting	-NA-	-NA-	-NA-	
	Underground tank capacity	-NA-	-NA-	-NA-	
	> Draw-off connection		-NA-	-NA-	
	> Fire service inlet	-NA-	-NA-	-NA-	
	> Access to tank	-NA-		MR	
	Overhead Tank capacity	10,000ltr	10,000ltr	MR	
15.	Exit Signage.	Required	Provided	IVIIC	
16.	Provision of Lifts.		T	NIA	
10.	a) Pressurization of Lift Shaft	-NA-	-NA-	-NA-	
.	b) Pressurization of Lift lobby	-NA-	-NA-	-NA-	
	c) Communication In lift Car	-NA-	-NA-	-NA-	
}	d) Fireman's Grounding Switch	-NA-	-NA-	-NA-	
-	e) Lift Signage	-NA-	-NA-	-NA-	
	Standby power supply	-NA-	-NA-	-NA-	

Cut

18.	Refuge Area.						
	a) Total Area	-NA-	-NA-	-NA-			
	b) Location	-NA-	-NA-	-NA-			
19.	Fire Control Room						
	a) Detector System Panel	-NA-	-NA-	-NA-			
	b) Flow Switch Panel	-NA-	-NA-	-NA-			
	c) PA System Panel	-NA-	-NA-	-NA-			
	d) Battery backup	-NA-	-NA-	-NA-			
	e) Building Floor Plans	-NA-	-NA-	-NA-			
20.	Special Fire Protection System for Protection of special Risks, if any:	-NA-	-NA-	-NA-			

Accordingly, the fire protection systems provided in the building were tested/ checked randomly and found in working condition at the time of inspection.

Keeping in view the satisfactory compliance of the minimum standards on fire prevention and fire safety required as stipulated in NBC Part-4, and removal of shortcomings issued vide letter no. 230 dated 08 05.2024, the FSC issued vide letter no. F.6/DFS/MS/2018/WZ/1759 dated 27.07.2018, renewal under rule 37 of the Delhi Fire Service Rules, 2010 is recommended.

Signature of the Inspecting Officer
Name Ajay Kumar Sharma

Designation ADO(Rohini)

Dy. CFO (WZ)

16/5

Director

Director My 11 05 M

most the

Fi letter to port up for kind perual and Rights

Director M/4/m

2/15/24