

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADOUARTERS : DELHI FIRE SERVICE, NEW DELHI – 110001

No.F6/DFS/MS/GH/NDZ/2024/ 151

Dated: 16 /05 /2024

FIRE SAFETY CERTIFICATE

Certified that the M/s Malhotra Guest House situated at 2911, Sir Seyed Ahmed Road, Darya Ganj, Delhi, comprised of Ground + 04 upper floors, ground floor- (commercial use), 1st floor - (reception + 09 guest rooms), 2nd floor - (11 guest rooms), 3rd floor & 4th floor - (owner's personal use), total 20 guest rooms owned/ occupied by Malhotra Guest House was granted FSC by this department vide letter no. F6/DFS/MS/GH/NDZ/2020/104 dated 18.03.2020. The building/ premises was re-inspected by the officer concerned of this department on dated 07.05.2024 in presence of Mohd. Qamar Ali Khan (Owner) and found that the building is comprised of ground + 04 upper floors and now the floor wise occupancy is ground floor- (commercial use), 1st floor -(reception + 09 guest rooms), 2nd floor- (11 guest rooms), 3rd floor- (owner personal use) & 4th floor - (not in use as per affidavit dated 08.05.2024). The building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of Delhi Fire Service Rules, 2010. Accordingly, the premises is fit for occupancy of "Residential (Sub Division-A-1), 1st floor -(09 guest rooms) & 2nd floor - (11 guest rooms), total 20 guest rooms upto 2nd floor only, with renewed under Rule 37 or sooner cancelled under Rule 40 and subject to conditions under Rule 38, of Delhi Fire Service Rules, 2010 printed below.

Delhi Fire Service of C

Copy to:-

1. The Commissioner, MCD:- to kindly ensure the occupancy as detailed above & deviation, if any.

- The Joint Commissioner of Police (Licensing), 1st Floor, Police Station Defence Colony, New Delhi. w.r.to ID No. 2023050908472 dated 22.04.2024.
- 3. The Licensee, M/S Malhotra Guest House at 2911, Sir Seyed Ahmed Road, Darya Ganj, Delhi.

Conditions for the validity of Fire Safety Certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.

7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.

- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub Rule (I) of Rule 37] along with a copy of this Certificate, six month prior to its expiry. Any change in the occupancy shall be intimated to this Deptt. and approval shall be obtained thereto before occupancy of the same.
- 9. The occupancy of above 3rd floor not allowed as per clause 7.31 in UBBL-2016.

| 1 | Nar | ne & address of the building | M/s Malhotra Guest House at 2911, Sir Seyed Ahmed Road, Darya Ganj, Delhi. | | | |
|--------|----------------------------|----------------------------------|---|---------------------------------------|--------------|--|
| 2 | Bui | lding is comprised of | (Ground + 04 up | | | |
| | | | Ground floor - | | | |
| - | | | 1st floor - (recent | tion + 09 guest room | \ | |
| | | | 2 nd floor - (11 m) | nest rooms) | ns) | |
| | 1 | | 2 nd floor – (11 guest rooms) 3 rd floor – (owner's personal use) | | | |
| | | | 4th floor - (not in use as per affidavit dated | | | |
| | | | | in use as per an | idavit dated | |
| 3 | Tvr | pe of occupancy | 08.05.2024) | | | |
| 4 | | be of case | Residential Group | | | |
| 5 | 100/100 | The second second | Renewal (old case | | | |
| | | ails of previous FSC | F6/DFS/MS/GH/I 18.03.2020 | NDZ/2020/104 date | ed | |
| 6 | | e safety direction letter no. | Nil | | | |
| 7 | | te of inspection | 07.05.2024 | | | |
| 8 | | me of the inspecting officers | Sumit Kumar, AD | OO (SPM) | | |
| 9 | | me of the designation of officer | | | | |
| | | m the building side | | · · · · · · · · · · · · · · · · · · · | | |
| 10 | _ | ar of construction | 1982 | | | |
| 11 | _ | plicant's letter no. | United the second | on ID No 201 | 23050000477 | |
| AL ALL | TP | | Online application I.D. No. 2023050908472 dated on 22.04.2024 | | | |
| S.N | Mi | nimum Standards on fire | Requirement/ | Provided at | Remarks | |
| 0 | Prevention and fire safety | | Existing fire | Site | MR/ | |
| | requirements U/R 33 | | safety | Site | NMR | |
| | | | arrangements | | MALK | |
| 1 | | cess To Building: | 3 6 11 - | | | |
| | Road width | | NA · | 05 mtr | NA | |
| | Gate width | | NA | NA | NA | |
| 2 | _ | dth of internal road | NA | NA | NA | |
| | | mber, Width, Type and Arran | gement of Exits: | and the | | |
| | A | Number of staircases | | 7 | | |
| | ١. | a Upper floor b Basement | 01 no. | 01 no. | MR | |
| | В | Width of staircases | NA | NA | NA | |
| | | | 00 | New Year | | |
| | | a Upper floor b Basement | 90 cms. | 90 cms. | MR | |
| | C | Protection of exits | NA | NA | NA | |
| | | a Fire check door | Paguiro J | | | |
| | | b Pressurization | Required NA | Provided | MR | |
| | D | No. of continuous staircases | 01 no. | NA 01 no | NA | |
| | 32.00 | to terrace | J. 110. | 01 no. | MR | |
| | E | Width of corridor | NA | NA | NA | |
| | F | Door size | 1.0 mtr. | 1.0 mtr. | 5.970 | |
| 3 | | mpartmentation: | | 1.0 mu. | MR | |
| | A | Fire check door | NA | NA | NIA | |
| | В | Sealing of electrical shafts | NA | NA NA | NA NA | |
| | C | Fire rating of shaft door | NA | NA NA | | |
| | D | Water curtain | NA | NA NA | NA | |
| 1 | E | Fire dampers | NA | NA NA | NA | |
| 4 | | oke Management System: | | 11/1 | NA | |
| | A | Basement | NA | NA | NYA : | |
| | В | Upper floor | NA | NA NA | NA | |
| | | | | - 14 % | NA | |

| 5. | | Extinguisher: | 07 nos. | 07 nos. | MR | | |
|-----|---|---------------------------------|-----------------------|--|----------|--|--|
| | A | Total numbers | | NO CASE STATE OF THE SECOND SE | MR | | |
| | В | Types | CO ₂ & ABC | CO ₂ & ABC | MR | | |
| | C | ISI marking | Required | Provided | MIK | | |
| 6 | First-Aid-Hose Reels: | | | | | | |
| | A | Total numbers of each floor | 1 no. | 01 no. (| MR | | |
| - 1 | В | Length of hose reel hose | 30 mtrs. | 30 mtrs. | MR | | |
| | C | Nozzle diameter | 05 mm | 05 mm ℓ | MR | | |
| 7 | Automatic Fire Detection And Alarming System: | | | | | | |
| | A | Type of detectors (CO type) | Required | Provided | MR | | |
| | В | Location of main panel | Required | Provided at / 1st floor | MR | | |
| | C | Location of repeater panel | NA | NA | NA | | |
| | D | Alternate source of power | Required | Provided | MR | | |
| | E | Hooters | Required | Provided | MR | | |
| 8 | 250000000 | EFA: | NA | NA | NA | | |
| 9 | Pub | lic Address System: | NA | NA | NA | | |
| 10 | | | | | | | |
| | A | Basement | NA | NA | NA | | |
| | В | Upper floor | NA | NA | NA | | |
| | C | Sprinkler above false ceiling | NA | NA | NA | | |
| 11 | | | | | | | |
| | A | size of riser/down-comer | NA | NA | NA | | |
| | В | Number of hydrants per floor | NA | NA | NA | | |
| | C | Hose box | NA | NA | NA | | |
| 12 | C Mose sea | | | | | | |
| 12 | A | Total number of hydrants | NA | NA | NA | | |
| | Charter | Hose box | NA | NA | NA | | |
| | В | | IWA | 3 3 3 3 3 | 1 | | |
| 13 | | | | | | | |
| | A | Ground level | INTA | NA | NA | | |
| | a) | Discharge of main pump | NA NA | | NA NA | | |
| | b) | Head of main pump | NA | NA | | | |
| | c) | Number of main pumps | NA | NA | NA | | |
| | d) | Jockey pump out put | NA | NA | NA | | |
| | e) | Jockey pump head | NA | NA | NA | | |
| | f) | Standby pump out put | NA | NA | NA | | |
| | g) | Standby pump head | NA | NA | NA | | |
| | h)_ | Auto starting /manual stopping | NA | NA | NA | | |
| | i) | Pump house access | NA | NA | NA | | |
| | В | Terrace level | | | <i>I</i> | | |
| | a) | Discharge of pump | 225 LPM | 225 LPM | MR | | |
| | b) | Head of the pump | 30 mtrs. | 30 mtrs. | / MR | | |
| | c) | Power supply | Required | Provided | MR | | |
| | d) | Auto starting of pump | Required | Provided | MR | | |

801 p

| _ | 1/2 | 32 - |
|---|-----|------|
| | | |

| 14 | Captive Water Storage For Fire Fighting: | | | | | | |
|-----|--|---|------------|------------|----|--|--|
| | A | Underground tank capacity | NA | NA | NA | | |
| - 1 | В | Draw-off connection | NA | NA | NA | | |
| - 1 | C | Fire service inlet | NA | NA | NA | | |
| 1 | D | Access to tank | NA | NA | NA | | |
| | E | Overhead tank capacity | 5000 ltrs. | 5000 ltrs. | MR | | |
| 15 | Exi | it Signage: | Required | Provided | MR | | |
| 16 | Provision of Lifts: | | | | | | |
| | A | Pressurization of lift shaft | NA | NA | NA | | |
| | В | Pressurization of lift lobby | NA | NA | NA | | |
| | C | Communication in lift car | NA | NA | NA | | |
| | D | Firemen's grounding switch | NA | NA | NA | | |
| | E | Lift signage | NA | NA | NA | | |
| 17 | Sta | andby Power Supply: | Required | Provided | MR | | |
| 18 | Refuge Area: | | | | | | |
| | A | Total area | NA | NA | NA | | |
| | В | Location | NA | NA | NA | | |
| 19 | Fire Control Room: | | | | | | |
| | A | Detector system panel | NA | NA | NA | | |
| | B | Flow switch panel | NA | NA | NA | | |
| | C | Pa system panel | NA | NA | NA | | |
| | D | Battery backup | ŇA | NA | NA | | |
| 1 | E | Building floor plans | NA | NA | NA | | |
| 20 | Sp | pecial Fire Protection Systems F pecial Risks, If Any: | NA | NA | | | |

The fire protection systems provided in the building were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required under the Rules, the FSC issued vide letter no. F6/DFS/MS/GH/NDZ/2020/104 dated 18.03.2020 is recommended to be renewed upto 2nd floor only, under Rule 35 of the Delhi Fire Service Rules, 2010.

Signature of the Inspecting Officer
Name Sumit Kumar

Designation ADO (SPM)

ANISON