

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2024/171

Dated: 91./05/2024

Certified that the Centra Inn Guest House located at 2503-A, Nalwa Gali, Chuna Mandi, Pahar Ganj, New Delhi comprised of Ground + 04 Upper floors, Ground floor (Reception + office) 1st floor + ord G + office), 1st floor to 3rd floor (08 guest rooms at each floor), 4th floor not in use as per affidavit dated 05.12.2019 total 24 guest rooms owned/occupied by Centra Inn Guest House Guest House was earlier granted FSC by this department vide letter No.F6/DFS/MS/GH/NDZ/2021/244 dated 22/07/21. Now, the premises was re-inspected by the officer concerned of this department on 14/05/24 in the presence of Manager and found that the said guest house building has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1, 1st floor to 3rd floor (08 guest rooms at each floor) total 24 guest rooms up to third floor only, and valid up to 31.03.2027 from the date of issue in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued _21105/2024 New Delhi by.

elhi Fire Service

Copy to:-

1. The Commissioner, North MCD, Civic Centre, and New Delhi: to ensure not to use any floor above third floor for any purpose and deviation if any.

2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.

Online id no.2024042005667 dated: 30-04-2024.

3. The Manager, Centra Inn Guest House 2503-A, Nalwa Gali, Chuna Mandi, Pahar Ganj, New Delhi

Conditions for the validity of Fire Safety Certificate

1. All the fire safety arrangements provided therein shall be maintained in good working conditions at

2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned.

5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.

8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

9. Any flammable material for interior decoration is prohibited.

N/29

INSPECTION REPORT 1. Name & address of the building

Centra Inn Guest House at 2503-A, Nalwa Street, Chuna Mandi, Pahar Ganj, New Delhi 2. Type of occupancy:-

Residential, Sub Division-A-1

Ground + 04 Upper floors (total 24 guest rooms)

Ground floor (Reception + office), 1st floor to 3rd floor

(08 guest rooms at each floor) and 4th floor

(staff rooms + open terrace) building having affidavit dated 05.12.2019 not to use any floor above third floor

Type of case:-Renewal

4. Details of previous FSC:-No.F6/DFS/MS/GH/NDZ/2021/244 dated

22/07/21.

5. Fire safety directives No.-

N/A 6. Date of inspection:-14/05/24

7. Name of the inspecting officer: -Sh. Ravinder Singh (ADO/CC)

8. Name & designation of officer From the building side:-

Manager 9. Year of construction:-

Old

ID no. 2024042005667 dated: 30/04/2024

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR			
l.	Access to Building			MR			
	1) Road width	06 mtr.	06 mtr. /	N/A			
	2) Gate width	N/A	N/A	05/2005/S			
	3)Width of internal road	N/A	N/A	N/A			
•	Number, Width Type & Arr	its					
2.	A. Number of staircases			- m			
	The state of the s	01 Nos.	01 Nos.	MR			
3.	Upper floors Basements	N/A	N/A	N/A			
	B. Width of staircase						
	1. Upper floors	1.25 mtr.	1.25 mtr.	MR			
	2. Basements	N/A	N/A	N/A			
	C. Protection of exits	TABLE OF					
	1. Fire check door	Required	Provided	MR			
	2. Pressurization	N/A	N/A	N/A			
	D. No. of continuous staircase to terrace	01	01	MR			
	E. Width of corridor	N/A	N/A	N/A			
	F. Door size	01 mtr.	01 mtr. /	MR			
	Compartmentation		Richard Control				
J.	1) Fire check door	N/A	N/A	N/A			
	2) Sealing of electrical shafts	N/A	N/A	N/A			
	3) Fire rating of shaft door	N/A	N/A	N/A			
	4) Water curtain	N/A	N/A	N/A			
	5) Fire Dampers	N/A	N/A	N/A			
4.	Smoke Management System						
	1) Basements	30 ACPH	N/A	N/A			
	2) Upper floors	Required	Natural /exhaust fan	MR			
5.	Fire Extinguishers		AWII				
	1) Total numbers	10 Nos.	10 Nos.	M			
	2) Types	ABC & CO2		MR			
	3) ISI marking	Required	ABC & CO2	MR			
6.	First-Aid Hose Reel	required	Provided	MR			

	JVI	1987				
	1) Total number of eachfloor	01	01	+) A CT	
	2) Length of hose reel hose	30 mtr.	30 mtr.	-	M	
	3) Nozzle diameter	05 mm	05 mm	-	MI	
7.	Automatic Fire Detection &	Alarming Sv	stem	-	MF	
	1) Type of detectors CO Type	Required	Provided	1	MR	
L I	2) Location of main panel	Ground floo	r Provided	1	MR	
	3) Location of repeater panel	N/A	N/A		N/A	
	4) Alternate source of power	Required	Provided		MR	
	5) Hooter's Location	Ground floo	r Provided	1	MR	
8.	MOEFA	Required	Provided	1	MR	
9.	Public Address System	Required	Provided		MR	
10.	Automatic Sprinkler System					
	1) Basement	N/A	N/A	_	N/A	
	2) Upper floors	N/A	N/A	\top	N/A	
45.	3) Sprinkler above false ceiling	N/A	N/A		N/A	
11.	Internal Hydrants					
	1) Size of riser/down-comer	N/A	N/A		N/A	
	Number of hydrants per floor	N/A	N/A		N/A	
	3) Hose box	N/A	N/A	1	N/A	
12.	Yard Hydrants					
	1) Total number of hydrants	N/A	N/A	1	N/A	
	2) Hose box	N/A	N/A	1	N/A	
13.	Pumping Arrangement					
	1) Ground level	N/A	N/A	U	N/A	
	a) Discharge of main pump	N/A	N/A		N/A	
	b) Head of main pump	N/A	N/A		N/A	
	c) Number of main pump	N/A	N/A		N/A	
	d) Jockey pump out put	N/A	N/A		N/A	
	e) Jockey pump head	N/A	N/A		N/A	
	f) Stand by pump output	N/A				
			N/A		N/A	
	g) Stand by pump head	N/A	N/A N/A		N/A	
	g) Stand by pump head h) Auto starting/Manual stopping					
	g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level	N/A N/A	N/A N/A	<i>V</i>	N/A	
	g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump	N/A N/A 180 LPM	N/A N/A 180 LPM		N/A	
	g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump	N/A N/A 180 LPM 30 mtr.	N/A N/A 180 LPM 30 mtr.	<i>Y</i>	N/A N/A MR MR	
	g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply	N/A N/A 180 LPM 30 mtr. Required	N/A N/A 180 LPM 30 mtr. Provided	<i>(</i>	N/A N/A MR MR	
14.	g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump	N/A N/A 180 LPM 30 mtr. Required Required	N/A N/A 180 LPM 30 mtr.	<i>V</i>	N/A N/A MR MR	
14.	g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for Fire 1) Under ground tank	N/A N/A 180 LPM 30 mtr. Required Required e Fighting	N/A N/A 180 LPM 30 mtr. Provided	/	N/A N/A MR MR	
14.	g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for Fire 1) Under ground tank capacity	N/A N/A 180 LPM 30 mtr. Required Required e Fighting	N/A N/A 180 LPM 30 mtr. Provided Provided		N/A N/A MR MR MR MR	
14.	g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for Fire 1) Under ground tank capacity a) Draw-off connection	N/A N/A 180 LPM 30 mtr. Required Required e Fighting N/A	N/A N/A 180 LPM 30 mtr. Provided Provided N/A		N/A N/A MR MR MR MR	
14.	g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for Fire 1) Under ground tank capacity a) Draw-off connection b) Fire service inlet c) Access to tank	N/A N/A 180 LPM 30 mtr. Required Required e Fighting N/A N/A	N/A N/A 180 LPM 30 mtr. Provided Provided N/A N/A		N/A N/A MR MR MR MR N/A N/A	
14.	g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for Fire 1) Under ground tank capacity a) Draw-off connection b) Fire service inlet c) Access to tank	N/A N/A 180 LPM 30 mtr. Required Required e Fighting N/A N/A N/A	N/A N/A 180 LPM 30 mtr. Provided Provided N/A	,	N/A N/A MR MR MR MR	

6.	Provision of Lifts.			
7.5	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
		N/A	N/A	N/A
18		Required	Provided	MR
17.	Stand by Power Supply	N/A	N/A	N/A
18.	Total area location	N/A	N/A	N/A
		N/A	N/A	N/A
19.	Fire Control Room		N/A	N/A
	a) Detector system	N/A	IWA	
	panel	N/A	N/A	N/A
/	b) Flow switch panel	1,000	N/A	N/A
	c) PA system panel	N/A N/A	N/A	N/A
1	d) Battery backup			N/A
	n Ulina floor plan	N/A	N/A	
N.	e) Building floor plan	for Protection of special		N/A
20.	Special Fire Protection Syst Risk, if any:	e randomly te		

The fire protection systems provided in the building were randomly tested,

checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if agreed, we may renew the FSC issued vide letter no. F6/DFS/MS/GH/NDZ/2021/244 dated 22/07/21, under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - Ravinder Singh Designation: - ADO (CC)