

Dated: 05 06 2024

# FIRE SAFETY CERTIFICATE

Certified that the CNG Station (CNG Storage & Dispensing unit) located at Madanpur khadar, New Delhi comprised of ground floor only, was granted Fire Safety Certificate by this department vide letter No. F6/DFS/MS/2021/CNG/290 dated 29.06.2021. The Premises was reinspected by the officer concerned of this department on 03.06.2024 in the presence of Sh. Gaurav, GET F&S (IGL) & Sh. Rakesh Bhardwaj, Sr. Engineer (F&S) and found that the CNG station has deemed complied with the fire prevention and fire safety requirements in accordance with the Rule 33 of the Delhi Fire Service Rules, 2010. Accordingly, the premises/building is fit for occupancy of Group J "Hazardous" (CNG Storage & Dispensing unit) with effect from O.J. O.G. (2014). for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rule, 2010 printed below.

Issued on .. 0 5 06 2024 .... at New Delhi by.

Director elhi Fire Service

#### Copy to:-.

Sh. Ajay Khatri, GM (Fire & Safety), IGL Bhawan, Plot No. 4, Community Centre, Sector
-9, R. K. Puram, New Delhi-22.

### Conditions for the validity of Fire Safety Certificate

- No trade susceptible to cause ignition to CNG by generating heat, mechanical/electrical spark should be allowed within the licensed premises.
- Overhead electrical cable and loose/naked wiring shall not be allowed across the licensed premises. The electrical equipments, electrical gadgets and fitting in the premises shall conform to hazardous area classification for that purpose and be of a type approved by the CCE.
- In premises "No Smoking" signs board both in Hindi and English shall be displayed in such a manner as to be easily readable by all people.
- 4. All fire protection arrangements shall be maintained.
- Nothing contravention of the explosive Act. 1884 and Rules their under 1983, and static and mobile pressure vessels (unfired) Rules 1981 as modified from time to time.
- All comments/directions of the Chief Inspector of Explosives should always be permitted and followed.
- All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- This Fire Safety Certificate cannot be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 10. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.

	Name	and address of the building:	CTION REPORT  CNG Station locat	ted at Madanpur l	chadar, Nev	
			Delhi.			
	Build	ing is comprised of	Ground floor only			
	Type of occupancy		Group J- Hazardous (CNG Storage & Dispensing unit)			
	Type of case:		Renewal			
	Details of previous FSC:		F6/DFS/MS/2021/CNG/290 dated 29.06.2021			
407	Fire safety directives no.:		F.5 (3A)/DFS/CNG/2000/111 dated 29.03.2000			
	Date of inspection:  Name of the inspecting officer:  Name and designation of the officer		03.06.2024 ADO Rajesh Kumar Shukla (M. Road) Sh. Gauray, GET F&S (IGL) & Sh. Rakesh			
		the building side:	Bhardwaj, Sr. Engineer (F&S)			
0	Year of construction:		2001-01			
1	Reference letter no.:		Outdoor diary No. 1600 dated 13.05.2024			
	200000000000000000000000000000000000000	and the same of th	Requirements as	Provide at site	Kemarkz	
S.No	Minimum Standards on fire Prevention and fire safety		per Rule 35 (6)		MR/NMF	
				d marrie		
		uirements U/R 33			Tv.m	
1	1	ess to Building Road width	Required	Provided	MR	
	A	Gate width	NA	NA	NA	
	В	Width of internal roads	NA	NA	NA	
	C	Width of Internal loads	ent of Exits	Ty Table 1		
2	Nu	mber, Width, Type & Arrangem				
	A	No. of staircase:	NA	NA	NA	
		a) Upper floor	NA NA	NA	NA	
	b) Basements					
	В	Width of the staircase:	NA	NA	NA	
		a) Upper floor	NA ·	NA	NA	
		b) Basements	1		1	
	C	Protection of exits	NA	NA	NA	
		a) Fire check door	NA	NA	NA	
		b) Pressurization	NA	NA	NA	
	D	No. of continuous staircase to		film vg re	NA	
		terrace:	NA	NA	NA NA	
	F	Width of the corridor	NA	NA	IMA	
	E	Door size		To a w	NA	
3	Co	mpartmentation:	NA	NA	NA NA	
	A	Fire check doors	NA	NA	NA NA	
	В	Sealing of electrical shafts	NA	NA	NA NA	
	C	Fire rating of shaft doors	NA	NA	NA NA	
	D	Water curtain	NA	NA		
	E	Fire dampers		-	NA	
4	Sn	noke Management System:	NA	NA	NA NA	
	A	Upper floors	NA	NA	434.6	
	В	Basements		و د د الاستاد د د	MR	
	5 Fi	re Extinguishers	Required	44 nos.	IVIK	
	A	T hord			MR	
	В	Types	Required	21 nos.	MR	
		a DCP 10 Kg	Required	13 nos.	MR	
1		b DCP 75 Kg Trolley	Required	10 nos.	MR MR	
		c CO <sub>2</sub> 4.5 Kg		Provided		

# N/21

	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	rst Aid Hose reel		1	374		
	A	Total no. at each floor	NA	NA	NA		
	B	Length of hose reel	NA	NA	NA		
7	C	Nozzle diameter	NA	NA	NA		
	Automatic Fire Detection and Alarm System (ADAS)						
	A	Type of detectors	Gas & Flame	Provided in compressor	MR		
	В	Location of main panel	At Ground	Provided	MR		
	C	Location of repeater panel	NA	NA	NA		
	D	Alternate power source	NA	NA	NA		
_	E	Hooter's location	Required	Provided	MR		
8		OEFA	NA	NA	NA		
9		blic Address System	NA	NA	NA		
10	oprimier System						
	A	Basement	NA	NA	NA		
		Upper floor	NA	NA	NA		
1-	C	Sprinklers above false ceiling	NA	NA	NA		
11		ternal Hydrants		En Sun and			
	A	Size of the riser/down comer	NA	NA	NA		
	B	No. Of hydrants per floor	NA	NA	NA		
12	C	Hose box	NA	NA	NA		
12		rd Hydrants	prin in the				
	A	Total no. of hydrants	NA	NA	NA		
12	B	Hose box	NA	NA	NA		
13		mping Arrangements	1.78	77 1			
	A	Ground Level		K			
		a) Discharge of main pump	NA	NA	NA		
		b) Head of main pump	NA	NA	NA		
	100	c) Number of main pump	NA	NA	NA		
		d) Discharge of jockey pump	NA	NA	NA		
	123	e) Head of jockey pump	NA	NA	NA		
		f) Discharge of standby pump	NA	NA	NA		
	N.	g) Head of standby pump	NA	NA	NA		
	5-	h) Auto starting/ manual stopping	NA	NA	NA		
	В	Terrace Level	7.31				
		a) Discharge of terrace pump	NA	NA	NA		
	YU	b) Head of terrace pump	NA	NA	NA		
	75	c) Alternate power supply	NA	NA	NA		
		d) Auto starting of pump	NA	NA	NA		
4		ptive Water Storage for Fire Fight	ting				
	A	Underground tank capacity	NA	NA	NA		
	В	Draw off connection	NA	NA	NA		
	C	Fire service inlet	NA	NA	NA		
	E	Access to tank	NA	NA	NA		
-	D	Overhead tank capacity	NA	NA	NA		
15	No	Smoking Signage	Required	Provided in	MR		
6	D=-	vision of lift		Hindi & English			
U				Marine .			
	A	Pressurization of lift shaft	NA	NA	NA		
	В	Pressurization of lift lobby	NA	NA	NA.		
	C	Communication in lift car	NA	NA	NA		
		Fireman switch	NA	NA	NA		
		Lift signage	NA	NA	NA		
7	Star	ndby Power Supply	NA	Provided (DG Set)	NA		

-	A	Tuge Area location	NA	1374	1		
-		Total area		NA	NA		
	В		NA	NA	NA		
19	Fire Control Room						
	A	Fire detection system panel	NA	NA	NA		
	В	Flow switch panel	NA	NA	NA		
	C	P A system panel	NA	NA	NA		
	D	Battery backup	NA	NA	NA		
	E	Building floor plan	NA	NA	NA		
20			Required	CO <sub>2</sub> flooding     system connected     through detectors     provided in each     compressor unit     DCP flooding     system for     overhead Cascades	MR		

# LEGENDS:- Meeting Requirement (MR), Not Meeting Requirement (NMR), Not Applicable (NA), Provided But Not Functional (PNF).

The fire protection systems provided in the building were tested checked and found properly functional at the time of inspection.

In view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required in Rules, the FSC issued vide letter no. F6/DFS/MS/2021/CNG/290 dated 29.06.2021 renewal under rule 37 of the Delhi Fire Service rules 2010 is recommended.

Signature of the Inspecting Officer

Name Rajesh Kumar Shukla Designation ADO (M. Road)