GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2024/ 187

Dated: 28/9.5./2024

FIRE SAFETY CERTIFICATE

Certified that the Delhi Guest House located at 1016, Mantola, Pahar Ganj, New Delhi comprised of Ground + 05 Upper floors, Ground floor (Reception + Shops), 1st floor to 2nd floor (03 guest rooms at each floor & 01 room locked) and 3rd floor (02 guest rooms & 02 room locked) 4th & 5th not in use as per affidavit dated 03.08.21 total 08 guest rooms was earlier granted FSC by this department vide letter No.F6/DFS/MS/GH/2021/363 dated 07/09/21. Now, the premises was re-inspected by the officers concerned of this department on 14/05/24 in the presence of (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 Ground floor (Reception), 1st floor to 2nd floor (03 guest rooms at each floor & 01 room locked) and 3rd floor (02 guest rooms & 02 room locked) total - 08 guest rooms only up to third floor and valid up to 31.03.2027 from the date of issue in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 28/05/2024 at New Delhi by.

Defhi Fire Service

Copy to:-

1. The Commissioner, North MCD, Civic Centre, and New Delhi: to ensure not to use any floor above third floor for any purpose and deviation if any.

2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. Online id no.2024041004708 dated: 20/04/24

3. The Manager, Delhi Guest House located, 1016, Mantola, Pahar Ganj, New Delhi.

Condition for the validity of Fire Safety Certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 9. Any flammable material for interior decoration is prohibited.

N/25

INSPECTION REPORT

1. Name & address of the building

Delhi Guest House located at 1016,

2. Type of occupancy

Mantola, Pahar Ganj, New Delhi Gr. +05 Upper floors (total 08 Guest rooms) Ground floor (Reception + Shops), 1st floor to 2nd floor (03 guest rooms at each floor &01 room locked) and 3rd floor (02 guest rooms) 4th & 5th floor sealed as per Affidavit dated 03.08.21 given by owner.

3. Type of case:-

Renewal

4. Details of previous FSC:-

No. F6/DFS/MS/GH/2021/363 dated

07/09/21

5. Fire safety directives No.-

N/A

6. Date of inspection:-

14/05/24.

7. Name of the inspecting officer:-

- Sh. Ravinder Singh, ADO (CC)

8. Name & designation of officer

From the building side:-

Manager

9. Year of construction:-

10. Applicant's letter No:-

ID no 2024041004708 dated: 20/04/24.

	Minimum Standards on fire	D	502.0	d Case
	Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remark MR/NM R
•	Access to Building		.,.	
	1) Road width	N/A	04 mtr.	N/A
	2) Gate width	N/A	N/A	N/A
	3)Width of internal road	N/A	N/A	N/A
	Number, Width Type & Arra	DOS CONTROL	2.5.00 (CAPE)	1
	A. Number of staircases	8		
	1. Upper floors	01 Nos.	01 Nos.	MR
	2. Basements	N/A	N/A	N/A
	B. Width of staircase			
	1. Upper floors	0.80 mtr.	1.10 Mtr.	MR
	2. Basements	N/A	N/A	N/A
	C. Protection of exits			1
	1. Fire check door	N/A	N/A	N/A
	2. Pressurization	N/A	N/A	N/A
	D. No. of continuous staircase to terrace	01	01	MR
	E. Width of corridor	01 mtr.	01 mtr.	MR
	F. Door size	01 mtr.	01 mtr.	MR
3.	Compartmentation	(4)		
	1) Fire check door	N/A	N/A	N/A
	2) Sealing of electrical shafts	N/A	N/A	N/A
	3) Fire rating of shaft door	N/A	N/A	N/A
	4) Water curtain	N/A	N/A	N/A
	5) Fire Dampers	N/A	N/A	N/A
4.	Smoke Management System		To the second se	
	1) Basements	30 ACPH	N/A	N/A
	2) Upper floors	12 ACPH	Natural/exhaust fan	MR
5.	Fire Extinguishers			
	1) Total numbers	08	10	MR

	2) Types	200	ABC & CO	2	1
		ABC & CO2	ADC & CO	2	MR
6.	3) ISI marking	Required	Provided		
0.	THE AID HOSE Reel	quired	Flovided		MR
	1) Total number of eachfloor	01	01	/	
	2) Length of hose reel hose	30 mtr.	30 mtr.		MR
7.	3) NOZZIe diameter	A			MR
7.	Automatic Fire Detection & A	larming System	OJ IIIII		MR
		Required	Provided		
	2) Location of main nanel	Ground floor	Provided		MR
	2) Ecouloli di lepeater nanel	N/A	N/A		MR
	4) Alternate source of power	Required			N/A
_	3) Hooter's Location	Ground floor	Provided		MR
8.	MOEFA	Required	Provided		MR
9.	1 dulic Address System		Provided		MR
10.	Automatic Sprinkler System	Required	Provided		MR
	I I Dacement	NIA			1
	2) Upper floors	N/A	N/A		N/A
	3) Sprinkler ob C.	N/A	N/A		N/A
	ceiling	N/A	N/A		N/A
11.	Internal Hydrants				
	11 \$170 06 = 11				
	2) Number of hydrants per	N/A	N/A		N/A
	floor	N/A	N/A		N/A
	3) Hose box				and the work
12.	Yard Hydrants	N/A	N/A		N/A
180	1) Total number of hydrants	N//			
	2) Hose box	N/A	N/A		N/A
13.		N/A	N/A	_	N/A
20.	Pumping Arrangement			_	5,024-7,1-8
	1) Ground level	N/A	N/A	T-E-	N/A
	a) Discharge of main	N/A	N/A		N/A
	pump		and additional mails		1 1/2
	b) Head of main pump	N/A	N/A		N/A
	c) Number of main pump		N/A		N/A
	d) Jockey pump out put	N/A	N/A		N/A
	e) Jockey pump head	N/A	N/A		N/A
	f) Stand by pump output	N/A	N/A		N/A
	g) Stand by pump head	N/A	N/A		N/A
	h) Auto starting/Manual	N/A	N/A		N/A
	stopping	il	The section of		""
	2) Terrace level	(21 · 6		1	
	a) Discharge of pump	450 LPM	450 LPM	-	MR
	b) Head of pump	30 mtr.	30 mtr.	/	MR
	c) Power supply	Required	Provided	-	MR
	d) Auto starting of pump		Provided		MR
14.	Captive Water Storage for F		Tiovided		TATE
14.		N/A	N/A	1	N/A
	1) Under ground tank	IVA	IVA		INI
	capacity	NI/A	N/A	-	N/A
	a) Draw-off connection	N/A		-	_
	the state of the s	N/A	N/A	1	N/A
	b) Fire service inlet		DT/4		
	c) Access to tank d) Over head tank	N/A 2500 ltr.	N/A 2500 ltr.	1/	N/A

5.	Exit Signage.	Required	Provided	MR	
6.	Provision of Lifts.		1	MK	
	Pressurization of lift shaft	N/A	N/A	N/A	
	b) Pressurization of lift lobby	N/A	N/A	N/A	
	c) Communication in lift car	N/A	N/A	N/A	
	d) Fireman's switch	N/A	N/A	N/A	
	e) Lift signage	N/A	N/A	N/A	
	Stand by Power Supply	Required	Provided /	MR	
17.		N/A	N/A	N/A	
18.	Refuge Area		N/A	N/A	
11	Total area location	N/A	N/A	100000000000000000000000000000000000000	
		N/A	N/A	N/A	
19.	Fire Control Room		N/A	N/A	
	a) Detector system	N/A	IVA		
	panel	N/A	N/A	N/A	
	b) Flow switch panel	N/A	N/A	N/A	
	c) PA system panel	N/A	N/A	N/A	
	d) Battery backup		Te-s	N/A	
	e) Building floor plan	N/A	N/A		
175	e) Building noor plan			NA	
20.	Special Fire Protection Systems, if any:	tem for 1 force			

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if agreed, we may renew the FSC issued vide letter no. F6/DFS/MS/GH/2021/363 dated 07/09/21, under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - Ravinder Singh Designation: - ADO (CC)

gno