## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No. F6/DFS/MS/assembly hall /2024/ 35/

Dated !! / 06/2024

## FIRE SAFETY CERTIFICATE

Certified that the Assembly hall at Delhi Parsi Anjuman Premises located at Bahadurshah Zafar Marg, Delhi Gate, New Delhi, comprised of basement and ground floor having hall for religious prayer at ground floor and basement for storage, was earlier granted FSC by this department vide letter No.F6/DFS/MS/assembly hall/2021/505 dated 14/10/2021. Now, the premises was re-inspected by the officers concerned of this department on 04/06/24 in the presence of Mr. Jai bhagwan and found that the said hall has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class – Assembly occupancy, Assembly Hall at Ground floor with effect from ...// .....for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued .// 06/2024 ... at New Delhi by.

DIRECTOR
Delhi Fire Service

## Copy to:-

1) The Commissioner, Municipal Corp. of New Delhi.

2) Sh. Cyrus Engineer, The Joint Secretory, The Delhi Parsi Anjuman, Bahadurshah Zafar Marg, Delhi Gate, New Delhi.

## Conditions for the validity of Fire Safety Certificate:

- All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned. Basement shall not be used for any purpose.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.
- 9. The flammable material use for interior decoration, if any, shall strictly be prohibited.

I	Name & address of the building	TION REPORT  Delhi Parsi Anjuman, Assembly Hall located at Bahadurshah Zafar Marg, Delhi Gate, New Delhi, building is comprised of		
-	Type of occupancy:-		l ground floor. ccupancy –Hall for a	assembly at
			·	
	Type of case:-	Renewal		
	Details of previous FSC:-	F6/DFS/MS/ 14/10/2021.	assembly hall/2021	/505 dated
	Fire safety directives No	N/A		
Fire safety directives No Date of inspection:-		04.06.2024		
7	Name of the inspecting officer:-	Sh. Rayinder Sh. Rajinder	r Singh (ADO/CC) : Atwal (DO/CD)	> 6
8	Name & designation of officer From the building side:-	Mr. Jai bhagwan		
9	Year of construction:-	NA	wilder of	
10 Applicant's letter No:-		Letter No nil dated 22.05.24		
	Applicant's letter No:- be basement is using for storage purped seat, using for prayer.		ly hall at ground flo	1 6 600
The	basement is using for storage purped seat, using for prayer.	Requirement/ Existing fire safety	ly hall at ground flo	1 6 600
The fixe	basement is using for storage purpled seat, using for prayer.  D. Minimum Standards on fire Prevention and fire safety U/R  33	Requirement/ Existing fire	ly hall at ground flo Ren	ewal old ca
The	basement is using for storage purpled seat, using for prayer.  D. Minimum Standards on fire Prevention and fire safety U/R 33  Access to Building	Requirement/ Existing fire safety arrangements	ly hall at ground flo  Ren  Provided at site	Remarks MR/NMR
The fixe	basement is using for storage purpled seat, using for prayer.  Minimum Standards on fire Prevention and fire safety U/R 33  Access to Building  1) Road width	Requirement/ Existing fire safety arrangements  06mtr	Provided at site  06mtr.	Remarks MR/NMR
The fixe	basement is using for storage purpled seat, using for prayer.  D. Minimum Standards on fire Prevention and fire safety U/R 33  Access to Building  1) Road width 2) Gate width	Requirement/ Existing fire safety arrangements  06mtr 05 mtrs	Provided at site  06mtr.  05 mtrs	Remarks MR/NMR
S.No	basement is using for storage purpled seat, using for prayer.  Minimum Standards on fire Prevention and fire safety U/R 33  Access to Building  1) Road width 2) Gate width 3) Width of internal road	Requirement/ Existing fire safety arrangements  06mtr 05 mtrs N/A	Provided at site  06mtr.	Remarks MR/NMR
The fixe	basement is using for storage purpled seat, using for prayer.  D. Minimum Standards on fire Prevention and fire safety U/R 33  Access to Building  1) Road width 2) Gate width	Requirement/ Existing fire safety arrangements  06mtr 05 mtrs N/A	Provided at site  06mtr.  05 mtrs	Remarks MR/NMR  MR  MR
The fixe	basement is using for storage purped seat, using for prayer.  Minimum Standards on fire Prevention and fire safety U/R 33  Access to Building  1) Road width 2) Gate width 3)Width of internal road Number, Width Type & Arran	Requirement/ Existing fire safety arrangements  06mtr 05 mtrs N/A	Provided at site  06mtr.  05 mtrs	Remarks MR/NMR  MR  MR  N/A
S.No	basement is using for storage purped seat, using for prayer.  Minimum Standards on fire Prevention and fire safety U/R 33  Access to Building  1) Road width 2) Gate width 3)Width of internal road  Number, Width Type & Arran A. Number of staircases 1. Upper floors 2. Basements	Requirement/ Existing fire safety arrangements  06mtr  05 mtrs  N/A gement of Exits	Provided at site  06mtr.  05 mtrs  N/A	Remarks MR/NMR
The fixe	basement is using for storage purped seat, using for prayer.  Minimum Standards on fire Prevention and fire safety U/R 33  Access to Building  1) Road width 2) Gate width 3)Width of internal road  Number, Width Type & Arran A. Number of staircases 1. Upper floors 2. Basements B. Width of staircase	Requirement/ Existing fire safety arrangements  06mtr  05 mtrs  N/A  gement of Exits  N/A  02	Provided at site  06mtr. 05 mtrs  N/A  . N/A  02	Remarks MR/NMR  MR MR N/A
S.No	basement is using for storage purped seat, using for prayer.  Minimum Standards on fire Prevention and fire safety U/R 33  Access to Building  1) Road width 2) Gate width 3)Width of internal road  Number, Width Type & Arran  A. Number of staircases 1. Upper floors 2. Basements B. Width of staircase 1. Upper floors	Requirement/ Existing fire safety arrangements  06mtr 05 mtrs N/A gement of Exits  N/A 02	Provided at site  06mtr. 05 mtrs N/A  N/A  N/A  N/A	Remarks MR/NMR  MR MR N/A N/A N/A
The fixe	basement is using for storage purped seat, using for prayer.  Minimum Standards on fire Prevention and fire safety U/R 33  Access to Building  1) Road width 2) Gate width 3)Width of internal road  Number, Width Type & Arran  A. Number of staircases 1. Upper floors 2. Basements B. Width of staircase 1. Upper floors 2. Basements 2. Basements	Requirement/ Existing fire safety arrangements  06mtr  05 mtrs  N/A  gement of Exits  N/A  02	Provided at site  06mtr. 05 mtrs  N/A  . N/A  02	Remarks MR/NMR  MR MR N/A N/A N/A
The fixe	basement is using for storage purped seat, using for prayer.  D. Minimum Standards on fire Prevention and fire safety U/R 33  Access to Building  1) Road width 2) Gate width 3)Width of internal road  Number, Width Type & Arran A. Number of staircases 1. Upper floors 2. Basements B. Width of staircase 1. Upper floors 2. Basements C. Protection of exits	Requirement/ Existing fire safety arrangements  06mtr 05 mtrs N/A gement of Exits  N/A 1.10 mtr & 0.75 mtr	Provided at site  O6mtr.  05 mtrs  N/A  N/A  1.10 mtr & 0.75 mtr	Remarks MR/NMR  MR MR N/A  N/A  N/A  MR Old case )
The fixe	basement is using for storage purped seat, using for prayer.  Minimum Standards on fire Prevention and fire safety U/R 33  Access to Building  1) Road width 2) Gate width 3)Width of internal road  Number, Width Type & Arran  A. Number of staircases 1. Upper floors 2. Basements B. Width of staircase 1. Upper floors 2. Basements 2. Basements	Requirement/ Existing fire safety arrangements  06mtr 05 mtrs N/A gement of Exits  N/A 1.10 mtr & 0.75 mtr	Provided at site  O6mtr.  05 mtrs  N/A  N/A  1.10 mtr & 0.75 mtr  N/A	Remarks MR/NMR  MR  MR  N/A  N/A  N/A  N/A  N/A  N/A  N/A  N/
The fixe	basement is using for storage purped seat, using for prayer.  Minimum Standards on fire Prevention and fire safety U/R 33  Access to Building  1) Road width 2) Gate width 3) Width of internal road  Number, Width Type & Arran  A. Number of staircases 1. Upper floors 2. Basements B. Width of staircase 1. Upper floors 2. Basements C. Protection of exits 1. Fire check door 2. Pressurization D. No. of continuous staircase to terrace	Requirement/ Existing fire safety arrangements  06mtr 05 mtrs N/A gement of Exits  N/A 1.10 mtr & 0.75 mtr	Provided at site  O6mtr.  05 mtrs  N/A  N/A  1.10 mtr & 0.75 mtr	Remarks MR/NMR  MR MR N/A  N/A  N/A  MR Old case )
The fixe	basement is using for storage purped seat, using for prayer.  Minimum Standards on fire Prevention and fire safety U/R 33  Access to Building  1) Road width 2) Gate width 3) Width of internal road  Number, Width Type & Arran  A. Number of staircases 1. Upper floors 2. Basements B. Width of staircase 1. Upper floors 2. Basements  C. Protection of exits 1. Fire check door 2. Pressurization D. No. of continuous	Requirement/ Existing fire safety arrangements  06mtr 05 mtrs N/A gement of Exits  N/A 1.10 mtr & 0.75 mtr  N/A N/A N/A	Provided at site  O6mtr.  05 mtrs  N/A  1.10 mtr & 0.75 mtr  N/A  N/A  N/A  N/A	Remarks MR/NMR  MR MR N/A  N/A  N/A  N/A  N/A  N/A  N/A  N/A

	1) Fire check door	N/A	N/A	N/A
	2) Sealing of electrical shafts	N/A	N/A	N/A
	3) Fire rating of shaft door	N/A	N/A	N/A
	4) Water curtain	N/A	N/A	N/A
	5) Fire Dampers	N/A	N/A	N/A
4.	Smoke Management System			_
	1) Basements	12 ACPH	Exhaust	MR
	·/			
	2) Upper floors	12 ACPH	Natural	MR
5.	Fire Extinguishers		/	
	1) Total numbers	06 Nos.	06 Nos.	MR
-	2) Types	ABC & CO2	ABC & CO2 /	MR
	3) ISI marking	Required	Provided	MR
6.	First-Aid Hose Reel			
	1) Total number	02	02	MR
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR
	3) Nozzle diameter	05 mm	05 mm	MR
7.	Automatic Fire Detection & A	104-11 10000-1111	OJ IIIII	MAIX
	1) Type of detectors	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	N/A	N/A	N/A
8.	MOEFA		53.757.25	I SAMPLE AND STREET
9.		Required	Provided	MR
10.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System  1) Basement	In	×	
	2) Upper floors	Required	Provided	MR
	3) Sprinkler above false ceiling	Required N/A	Provided	MR
11.	Internal Hydrants	IN/A	N/A	N/A
	1) Size of riser/down-comer	100mm	D	
	2) Number of hydrants	02Nos	Provided	MR
	3) Hose box	02Nos	Provided	MR
12.	Yard Hydrants	UZINOS	Provided	MR
	Total number of hydrants	02nos	D	
	2) Hose box	02nos	Provided	MR
13.	Pumping Arrangement	UZIIOS	Provided	MR
	1) Ground level	NI/A	10.000	
	a) Discharge of main	N/A	N/A	N/A
	pump	450 LPM	900 LPM /	MR
	b) Head of main pump	40mtr	40 mtr	) (D
	c) Number of main pump	01 nos	Provided	MR
	d) Jockey pump out put	N/A	N/A	MR
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual	Required	Provided	N/A
	stopping	Janou	Tiovided	MR
	2) Terrace level	N/A	N/A	NU
	a) Discharge of pump	N/A	N/A	N/A
			WA	N/A



	b) Head of pump	N/A	N/A	N/A
		N/A	N/A	N/A
3		N/A	N/A	N/A
	d) Auto starting of pump  Captive Water Storage for Fire	Fighting		
4.	<ol> <li>Under ground tank</li> </ol>	10,000 ltr.	10,000 ltr.	MR
	capacity	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	Required	Provided	MR
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity		Provided	MR
15.	Exit Signage.	Required	Hovides	
16.	Provision of Lifts.			N/A
**. JI		t N/A	N/A	N/A
	b) Pressurization of lift	N/A	N/A	727726
	lobby	r N/A	N/A	N/A
	c) Communication in lift ca	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	Required	Provided /	MR
17.	Stand by Power Supply (DG	Required	7	
- Olivina	Set)	N/A	N/A	N/A
18.	Refuge Area	N/A	F).078.55	N/A
55.841	Total area location	N/A	N/A	(
19.	Fire Control Room	N/A	N/A	N/A
17.	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	Service and the service and th	N/A	N/A	N/A
	c) PA system panel	On Miles	N/A	N/A
	d) Battery backup	N/A	IV/A	A35-55-195-195
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System		n of special Risk, if	N/A building W

The fire protection systems provided in the building were

randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if approved, we may renew the FSC issued vide letter no. F6/DFS/MS/assembly hall/2021/505 dated 14/10/2021, under rule 35(6) of the Delhi Fire Service rules 2010. Accordingly, DFA is put up for kind perusal and signature please.

Signature of the Inspecting Officer

Name: - Rajinder Atwal Designation:-DO (CD)

Name: - Ravinder Singh Designation: - ADO (CC)

Signature of the Inspecting Officer