



## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F.6/DFS/MS/2021/SZ/ 353

Dated: 1/ /06 /2024

## **FIRE SAFETY CERTIFICATE**

Certified that the Commercial Building at F-43, NDSE-1, New Delhi-110049, comprised of Basement, Ground & Three upper floors, have complied with fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officers concerned of this department on 06/06/2024 in the presence of Sh. Aashish Kumar (Owner) and that the said premises is fit for occupancy class "Mercantile" with effect from the date of issuance for a period of three years in accordance with rule 36 unless renewal under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 11/06/2024 at New Delhi by

DIRECTOR DELHI FIRE SERVICE

Copy to: -

- 1. The Executive Engineer (Bldg.), Municipal Corporation of Delhi, Central Zone, Lajpat Nagar, New Delhi-110024
- 2. Authorized Signatory M/s Nalli Silk Sarees Pvt. Ltd., F-43, NDSE-1, New Delhi-110049

## Conditions for the validity of Fire Safety Certificate:

All the means of escape/entry/exit shall be kept free from any obstruction.

- All the fire safety arrangement provided therein shall be maintained in good working conditions at all time as seen during inspection.
- 2. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of fire-fighting system.
- 4. The Basement shall be used strictly in accordance with the Building Bye-Laws.
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. The owner/occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule37] along with a copy of this Certificate, six months prior to its expiry.

| - 4 | 1     |  |
|-----|-------|--|
| 100 | 43555 |  |
|     |       |  |

| 1.     | INSPECTION Name & address of the building                   | Commercial                            | Building at F-43, N   | DSE-1,    |
|--------|---|---------------------------------------|-----------------------|-----------|
| 1.     | Traine & address of the building                            | New Delhi–110049                      |                       |           |
| 2.     | Type of Occupancy   | Mercantile (C                         |                       |           |
| 3.     | Building Comprised of                                       | Basement, Ground & Three upper Floors |                       |           |
|        |   | New                                   |                       |           |
| 4.     | Type of Case  | Nil                                   |                       |           |
| 5.     | Details of previous NOC                                     | F.6/DFS/MS/                           | 2022/BP/507 dt. 30    | /12/2022  |
| 6.     | Fire Safety Directives Letter No.                           | 06/06/2024                            |                       |           |
| 7.     | Date of inspection  | DO (SD) & ADO (SJ)                    |                       |           |
| 8.     | Name of Inspecting Officer                                  | Sh. Aashish Kumar (Owner)             |                       |           |
| 9.     | Name and designation of Officer from building side          | 2000                                  |                       |           |
| 10.    | Year of Construction  | Request ID: 1                         | 0111476 dated 01/0    | )2/2023   |
| 11.    | Applicant letter/ MHA ID No.                                | NBC/UBBL                              | Provided at site      | Kelliaiks |
| S. No. | Minimum standards on fire                                   | Requirement                           |                       | MR/NMR    |
| 4      | prevention and fire safety U/R 33                           |                                       |                       | MR        |
| 1.     | Access of building  | 6 mtr.                                | Provided              | NA<br>NA  |
|        | Road width  | NA                                    | Abuts on road         | NA<br>NA  |
|        | <ul><li>Gate width</li><li>Width of internal road</li></ul> | NA                                    | NA                    | IVA       |
|        | Number, width, Type & Arrangements                          | of exits                              |                       |           |
| -2.    | a. Number of staircases                                     | manager 1                             | = _ Ll =              | 1 vm      |
|        |   | Two                                   | Provided              | MR<br>MR  |
|        | Upper floors  | Two                                   | Provided              | MK        |
|        | Basements     Available of stoircoses                       | 144.5                                 | MAT WIND B            | I .m      |
|        | b. Width of staircases                                      | 1.50m                                 | 1.50m each            | MR        |
|        | Upper floors  | 1.50m                                 | 1.50m each            | MR        |
|        | Basement     Carrita  | - 3                                   |                       |           |
|        | c. Protection of exits                                      | Required                              | Provided              | MR        |
|        | Fire check door   | NA                                    | NA                    | NA        |
|        | Pressurization  d. No of continuous staircase to terrace    | Required                              | 02 Nos                | MR        |
|        |   | NA                                    | NA                    | NA        |
|        | e. Width of Corridor  | 1.5m                                  | Provided              | MR        |
|        | f. Door Size  |                                       |                       |           |
| 3.     | Compartmentation  | Required                              | Provided              | MR        |
|        | Fire check door     Calcatrical shafts                      | Required                              | Provided              | MR        |
|        | Sealing of electrical shafts                                | NA                                    | NA                    | NA        |
|        | Fire Rating of shaft door                                   | NA                                    | NA                    | NA        |
|        | Water Curtain   | NA                                    | NA                    | NA        |
|        | Fire Dampers  |                                       |                       |           |
| 4.     | Smoke managements System                                    | 12 ACPH                               | Exhaust Fans          | MR        |
|        | Basements   | 12 ACPH                               | Natural Ventilation   | MR        |
|        | Upper floors  | 12710111                              |                       |           |
| 5.     | Fire Extinguishers  | 10 nos.                               | Provided              | MR        |
|        | Total numbers   | ABC/CO <sub>2</sub>                   | ABC & CO <sub>2</sub> | MR        |
|        | • Types   | Required                              | Provided Provided     | MR        |
|        | ISI marking   | Required                              |                       |           |
| 6.     | First-Aid Hose Reels  |                                       | D 11.1                | MR        |
|        | <ul> <li>Total numbers on each floor</li> </ul>             | Two                                   | Provided              | MR        |
|        | <ul> <li>Length of hose reel hose</li> </ul>                | 30m                                   | Provided              | 552       |
|        | Nozzle diameter   | 5mm                                   | Provided              | MR        |

|   | • | _ |   |
|---|---|---|---|
| _ | _ | _ | _ |
|   |   |   |   |

| 7. Automatic fire detection and alarming   | g system  |  |   |
|--|---|--|---|
| Type of detector   | NA  | NA   | NA  |
| Location of Main Panel   | NA  | NA   | NA  |
|  | NA  | NA   | NA  |
| Location of Repeater Panel   | NA  | NA   | NA  |
| Alternate source of power  | NA  | NA   | NA  |
| Hooters' Location  | Required  | Provided   | MR  |
| B. MOEFA   | NA  | NA   | NA  |
| Public Address System  | INA   | 1,1,1  |   |
| 0 Automatic Sprinkler System   | NA  | NA   | NA  |
| Basements  | NA<br>NA  | NA NA  | NA  |
| Upper floors     Section above folso cailing   | NA  | NA   | NA  |
| Sprinkler above false ceiling     Internal Hydrants  | 1,112   |  |   |
| Size of riser/down-comer   | 100 mm  | 100 mm   | MR  |
| Number of hydrants per floor   | Required  | Two  | MR  |
| Hose Box   | Required  | Two  | MR  |
| 2 Yard Hydrants  |   | and Ware Road  |   |
| Total number of hydrants   | NA  | NA   | NA  |
| Hose Box   | NA  | NA   | NA  |
| Pumping Arrangements   | E I Jumesur   | Dangalah k   |   |
| Ground Level   | ture = Areau  | April 18 March   |   |
| > Discharge of main pump   | NA  | NA   | NA  |
| ➤ Head of main pump  | NA  | NA   | NA  |
| > Number of main pumps   | NA  | NA   | NA  |
| ➤ Jockey pump out put  | NA  | NA   | NA  |
| ➢ Jockey pump head   | NA  | NA   | NA  |
| ➤ Standby Pump out put   | NA  | NA   | NA  |
| > Standby Pump Head  | NA  | NA   | NA  |
| ➤ Auto Staring/Manual stopping   | NA  | NA   | NA  |
| ➤ Pump House Access  | NA  | NA   | NA  |
| Terrace level  |   | AVA  | - Children  |
| ➤ Discharge of pump  | 900 LPM   | 900 LPM  | MR  |
| > Head of the pump   | 40m   | 40m  | MR  |
| > Power supply   | Required  | Provided   | MR  |
| ➤ Auto starting of pump  | Required  | Provided   | MR  |
| Captive water Storage for fire fighting  |   | r jun 💝 🚾  |   |
| Underground tank capacity  | NA  | NA   | NA  |
| > Draw of connection   | NA  | NA   | NA  |
| Fire service inlet   | NA<br>NA  | NA<br>NA   | NA<br>NA  |
| <ul> <li>Access to tank</li> <li>Overhead Tank capacity</li> </ul>   | NA<br>25,000 Ltrs   | NA<br>25,000 Ltrs  | NA<br>MR  |
| Exit Signage   | Required  | Provided   | MR  |
| Provision of Lifts   | required  | 11011404   | 14116   |
| > Pressurization of Lift Shaft   | NA  | NA   | NA  |
| > Pressurization of lift lobby   | NA NA   | NA NA  | NA  |
| Communication in lift Car  | NA NA   | NA<br>NA   | NA<br>NA  |
|  | - Cecar   | Excess Street  | NA<br>NA  |
| and the same of th | W.1952.   | 2.000,000  | Access to the second  |
|  | 25)9/635  | 200 March 200  | NA<br>MB  |
| Control of the Contro | Required  | Provided   | MR  |
| Refuge Area  | NTA T   | The same of the sa | - I   |
|  | 755560VC  | 250 250 250 250 250 250 250 250 250 250  | NA<br>NA  |
| Refuge   | Fireman's Grounding Switch Lift Signage y power supply Area Total area Location | Fireman's Grounding Switch Lift Signage NA y power supply Area Total area NA   | Fireman's Grounding Switch Lift Signage NA NA NA NA y power supply Required Provided Area Total area NA NA NA |

| 19. | Fire control room  |   |    |    |
|-----|--|---|----|----|
|     | Detector system panel  | NA  | NA | NA |
|     | Flow Switch Panel  | NA  | NA | NA |
|     | PA System Panel  | NA  | NA | NA |
|     | ➤ Battery backup   | NA  | NA | NA |
|     | Building Floor Plans   | NA  | NA | NA |
| 20. | Special Fire Protection Systems for Protection of special Risks, if any; | ABC & CO <sub>2</sub> fire extinguishers provided near electrical panel |    | MR |

The fire protection system provided in the building/premises were checked, tested at random and found functional at the time of inspection.

Keeping in view of the substantial compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, issuance of Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer Name: Manoj Kumar Sharma

Designation: DO (SD)

Signature of the Inspecting Officer

Name: Santosh Kumar Designation: ADO (SJ)

CFO (HQ)

Denoctor

Mayso

Sir,

putup for your Sing

11/06/14

Co