GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2024/ 2 14

Dated: 0.5/06/2024

FIRE SAFETY CERTIFICATE

Certified that the M/s Hari Piorko Inn Guest House located at 4778-A&B, 4781 (Part), Main Bazar, Pahar Ganj, New Delhi comprised of Ground floor to 3rd floor (07 guest rooms at each floor) 4th floor not in use as per affidavit dated 01.02.2020 total 28 guest rooms up to third floor only. was earlier granted FSC by this department No.F6/DFS/MS/GH/2021/NDZ/139 dated 16/03/21 for 30 guest rooms up to third floor only. Now, the premises was re-inspected by the officer concerned of this department on 28/05/24 in the presence of Manager and found that the said guest house building has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as Ground floor to 3rd floor (07 guest rooms at each floor) Total 28 guest rooms up to third floor only, and valid up to 31.03.2027 from the date of issue in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

05 06 2024 New Delhi by.

Fire Service

Copy to:-

The Commissioner, North MCD, Civic Centre, New Delhi: to ensure not to use 1. any floor above third floor.

The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New

Delhi. Online id no. 2024051507582 dated 15/05/24.

The Manager, Hari Piorko Inn Guest House located at 4778-A&B, 4781 (Part), Main Bazar, Pahar Ganj, New Delhi.

Conditions for the validity of Fire Safety Certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility

3. The trained fire fighting staff should be available round the clock.

4. The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned.

5. This fire safety certificate may not be treated in any case for regularization of unauthorized

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an

8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

9. The owner shall not use any floor above third floor for any purpose and same shall remain

INSPECTION REPORT

1. Name & address of the building Hari Piorko Inn Guest House located at

4778-A&B, 4779, 4781 (Part), Main Bazar,

Pahar Ganj, New Delhi

2. Type of occupancy:-

Residential, Sub Division-A-1
Ground +4th upper floor (30 guest rooms)
ground to 2nd floor(07 room at each floor), 3rd
floor 09 guest room, 4th floor not to use as per

affidavit dated 01.02 20.

3. Type of case:-

No.F6/DFS/MS/GH/2021/NDZ/139 dated 16/03/21

4. Details of previous FSC:-5. Fire safety directives No.-

N/A

Renewal

6. Date of inspection:-

28/05/24

7. Name of the inspecting officer:-

Sh. Ravinder Singh(ADO/CC)

8. Name & designation of officer

from the building side:-

Manager

9. Year of construction:-

1991

10. Applicant's letter No:-

online id 2024051507582 dated 15/05/24.

.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR
1.	Access to Building			
	1) Road width	N/A	09 mtr.	N/A
	2) Gate width	N/A	N/A	N/A
	3)Width of internal road	N/A	N/A	N/A
•	Number, Width Type & Arra		its	
2.	A. Number of staircases			
	1. Upper floors	01 Nos.	01 Nos.	MR
3.	2. Basements	N/A	N/A	N/A
	B. Width of staircase			
	1. Upper floors	150 mtr.	160 mtr.	MR /
	2. Basements	N/A	N/A	N/A
	C. Protection of exits			
	1. Fire check door	Required	Provided	MR <
	2. Pressurization	N/A	N/A	N/A
	D. No. of continuous staircase to terrace	N/A	N/A	N/A
	E. Width of corridor	N/A	N/A	N/A
	F. Door size	1.0 mtr.	1.0 mtr.	MR
	Compartmentation			
	1) Fire check door	N/A	N/A	N/A
	2) Sealing of electrical shafts		N/A	N/A
	3) Fire rating of shaft door	N/A	N/A	N/A
	4) Water curtain	N/A	N/A	N/A
	5) Fire Dampers	N/A	N/A	N/A
4.	Smoke Management System			
	1) Basements	N/A	N/A	N/A
	2) Upper floors	12 ACPH	Natural/exhaust	MR
5.	Fire Extinguishers			N/D
	1) Total numbers	08 Nos.	10 Nos.	MR
	2) Types	ABC & CO2	ABC & CO2	MR

سادح

		Required	Provided	MR	-
	3) ISI marking	Roquires			
	First-Aid Hose Reel	01	01	MR	
	1) Total number of eachfloor	30 mtr.	Provided	MR	
	2) Length of hose reel hose	W. O. S. G. S. S. S.	Provided	MR	
	3) Nozzle diameter	05 mm			
	Automatic Fire Detection &	Alarming Syste	Provided	MR	
	1) Type of detectors CO type	Required	Provided	MR	
	2) Location of main panel	Ground floor	N/A	NA	
	3) Location of repeater panel	N/A	Provided /	MR	
	4) Alternate source of power	Required	Provided	MR	
	5) Hooter's Location	At each floor		MR	
8.	MOEFA	Required	Provided /	MR	
9.	Public Address System	Required	Provided	MIK	
10.	Automatic Sprinkler System			NIA	_
	1) Basement	N/A	N/A	NA	
	2) Upper floors	N/A	N/A	NA	
	3) Sprinkler above false	N/A	N/A	NA	
	ceiling				
11.	Internal Hydrants	-			
	1) Size of riser/down-comer	N/A	N/A	N/A	
	2) Number of hydrants per	N/A	N/A	NA	
	floor		555		
	3) Hose box	N/A	N/A	NA	
12.	Yard Hydrants				
	1) Total number of hydrants	N/A	N/A	NA	
	2) Hose box	N/A	N/A	NA	
13.	Pumping Arrangement				
	1) Ground level	N/A	N/A	NA	
	 a) Discharge of main pump 	N/A	N/A	NA	
	b) Head of main pump	N/A	N/A	NA	
ing.	c) Number of main	N/A	N/A	NA	
	d) Jockey pump out put	N/A	1		
	e) Jockey pump head	N/A	N/A	NA	
	f) Stand by pump	N/A	N/A	NA	
	output	IVA	N/A	NA	
	g) Stand by pump head	N/A	N/A	NIA	
	h) Auto starting/Manual	N/A	N/A N/A	NA	
	stopping		WA	NA	
	2) Terrace level	1111			
	a) Discharge of pump	450 LPM	450 LPM	MD	
	b) Head of pump	30 mtr.	30 mtr.	MR MR	
	c) Power supply	Required	Provided	MR	
	d) Auto starting of pump	Required	Provided	MR	
14.	Captive Water Storage for 1	Pi- TO:			
	Under ground tank capacity	Fire Fighting	I a		
	a) Draw-off connection	N/A	N/A	NA	
	, and our connection	N/A	N/A	NA	

	b) Fire service inlet	N/A	N/A	Tree
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	5,000 ltr.	5,000 ltr.	N/A MR
5.	Exit Signage.	Don't	(
6.	Provision of Lifts.	Required	Provided	MR
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syste Risk, if any: ABC & Co2	em for Protec	ction of special	N/A

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if agreed, we may renew the FSC issued vide letter no. F6/DFS/MS/GH/2021/NDZ/139 dated 16/03/21, under rule 35(6) of the Delhi Fire Service Rules 2010. Accordingly, DFA is put up for kind perusal and signature please.

Signature of the Inspecting Officer

Name: - Rayinder Singh Designation: - ADO (CC)

Dinecter