



GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001

गाजादी » अमृत महोत्सव

No. F6/DFS/MS/School/WZ/2024/ 478

Dated:-

29/05/2024

FIRE SAFETY CERTIFICATE

Certified that the New Saraswati Public Secondary School Located at Ext. No. 2, Nangloi, Delhi-110041, comprised of 02 Blocks – 1st block (Ground + 02 Upper Floors) & 2nd block (Ground + 01 Upper Floor) only owned/occupied by the New Saraswati Public School, was issued Fire Safety Certificate by this department Vide Letter No. F6/DFS/MS/School/2021/WZ/383 dated 27/05/2021. The said premises was re-inspected by the officer concerned of this department on 17/05/2024 in the presence of Sh. Lalit Kumar Yadav (Owner) and found that the premises/building have deemed complied with the fire prevention and fire safety requirements in accordance D.O.E. Cr. No. 3298-3398 dated 01/03/2011 and that the premises/building is fit for occupancy class "Educational Building" Group B with effect from 29 05 2024 for a period of three years in accordance with Rule 36 unless renewal under Rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under Rule 38 of the DFS Rules, 2010, printed below.

Issued on .. 29 05 2024, at New Delhi by.

Tel No. 011-23414000

Copy to: -

1. The Director, Directorate of Education, GNCT of Delhi, Old Secretariat Delhi – 110054.

2. The Principal, New Saraswati Public School, Ext. No. 2, Nangloi, Delhi-110041.

Following fire safety directives must be adhered to:-

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

 All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.

5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.

6. All comments / directions of licensing Department shall always be permitted and followed.

7. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

INSPECTION REPORT

1. Name and address of the building: New Saraswati Public Secondary School located at Ext. No. 2, Nangloi, Delhi-110041

2. Type of Occupancy : Educational, 1st Block- G+2 & 2nd Block- G+1 (02 Blocks)

3. Type of Case : Renewal

4. Details of previous NOC : F6/DFS/MS/School/2021/WZ/383 Dated 27/05/2021

5. Fire Safety directives Letter No. : D.O.E Circular no.3298-3398 dated 01-03-2011

6. Date of inspection : 17/05/2024

7. Name of the Inspecting Officer : Aman Kumar Lathar, ADO (JWP)

8. Name and designation of Officer

from the building side : Sh. Lalit Kumar Yadav (Owner)

9. Year of Construction : 1993, 2009, 2010 & 2016

10 Applicant's letter No. : email dated 08/05/2024 & letter no. 272 dated 07/05/2024

S No	Minimum standards on fire prevention and fire safety U/R 33	D.O.E. Cr. No. 3298- 3398 dated 01.03.2011/as per FSC dated 27/05/2021		Provided at site	Remarks MR/NMR	
1.	Access of building			-1k %	(10)	
	Road width	06		Provided	MR	
	Gate width	4.5 m		Provided	MR	
	 Width of internal road 	N/	1	NA	NA	
2.	Number, width, Type & Arrangen	nents of exi	ts			
	a. Number of staircases	00:	l. l. l. ale T	Provided	MR	
	Upper floors	02 in eac		NA NA	NA	
	Basements	INA	1	NA	117.	
	b. Width of staircasesUpper floors	1.5 m		.30 m & 1.22 n k- 1.27 m x 2	n MR	
	Basements	N/	A les pul de	NA	NA	
	c. Protection of exits	il.	AND THE WAY			
	Fire check door	N.	Α	NA	NA	
	Pressurization	N.		NA	NA	
	d. No of continuous staircase to terrace	0		Provided	MR	
	e. Width Of Corridor	N.	A	NA	NA	
	f. Door Size	1.1	m i	Provided	MR	
3.	Compartmentation			NA		
٥.	Fire check door	N.	A	NA	NA	
	Sealing of electrical shafts	N	A	NA	NA	
	Fire Rating of shaft door	N	A	NA	NA	
	Water Curtain	. N	A	NA	NA	
	Fire Dampers	N	A	NA	NA	
4.	Smoke managements System					
22.9	Basements	N		NA	NA	
	Upper floors	N	A	NA	NA	
5.	Fire Extinguishers					
	Total numbers	08 1		25 nos.	MR	
	Types		& CO ₂	Provided	MR	
	ISI marking	ISI M	arked	Provided	MR	

N-13	-	- 1	ح
------	---	-----	---

5. I	First – Aid Hose Reel	01 (C+2)	Provided	MR	
	Total numbers on each floor	01 (G+2) 30 m	Provided	MR	
4	Length of hose reel hose	05 mm	Provided	MR	
	Nozzle diameter	572	Tiovided		
7.	Automatic fire detection and alarming sy		NA	NA	
	Type of detectors	NA NA	NA	NA	
	Location of Main Panel	NA NA	NA	NA	
	Location of Repeater Panel	NA NA	NA	NA	
	Alternate source of power	NA NA	NA	NA	
_	Hooters' Location		NA	- NA	
8.	MOEFA	NA NA	NA NA	NA	
9.	Public Address System	NA	INA	INA	
10.	Automatic Sprinkler System	NA	NA	NA	
	Basements	NA NA	NA NA	NA	
-	• Upper Floor	NA NA	NA NA	NA	
11	Sprinkler above false ceiling Internal Management Internal Manage	IVA	1471		
11.	Internal Hydrants:	NA	NA	NA	
	Size of riser/down- comer Number of hydronia per floor	NA NA	NA NA	NA	
11	 Number of hydrants per floor Hose Box 	NA NA	NA NA	NA	
12.		INA	17/1	1 1 1 1	
12.	Yard Hydrants	NA	NA	NA	
	Total number of hydrants Hose Box	NA NA	NA NA	NA	
13.	Pumping Arrangements:	IVA			
13.	Ground Level				
		NA	NA	NA	
	 Discharge of main pump Head of main pump 	NA NA	NA	NA	
ж	> Number of main pumps	NA	NA NA	NA	
	> Jockey pump out put	NA	NA	NA	
	> Jockey pump head	NA	NA	NA	
	Standby Pump out put	NA	NA	NA	
	➤ Standby Pump Head	NA	NA	NA	
	> Auto Staring/Manual stopping	NA	NA	NA	
1	➤ Pump House Access	NA	NA	NA	
	Terrace level	2 0 to 0.1			
-	Discharge of pump	450 LPM	Provided	MR	
	> Head of the pump	40 m	Provided	MR	
	> Power supply	Required	Provided	MR	
	> Auto starting of pump	Required	Provided	MR	
14.			Mary III a		
	Under ground tank capacity	NA -	NA	NA	
	> Draw off connection	NA	NA	NA	
	Fire service inlet	NA	NA	NA	
	Access to tank	NA 10 000 h	NA	NA	
15	Overhead Tank capacity Evit Signage	10,000 ltrs.	Provided	MF	
15 16.	Exit Signage	Required	Provided	MF	
10.					
	 Pressurization of Lift Shaft Pressurization of lift lobby 	NA NA	NA NA	NA NA	
	Communication in lift Car	NA NA	NA NA	NA NA	
1	> Fireman's Grounding Switch		NA NA	N/	
- 1	> Lift Signage	NA NA	. NA	N/	
	- DiPimpo	INA	NA	N/	
17.		NA	NA	N/	
17. 18.	Refuge Area			N/	
-		NA NA NA	NA NA NA	N/	

	> Detector system	NA	NA	NA
	panel	NA	NA	NA
	> Flow Switch Panel	NA	NA	NA
	PA System Panel	NA	NA	NA
	Battery backupBuilding Floor Plans	NA	NA	NA
20.	Special Fire Protection Systems for Protection of special Risks, if any; Fire protection systems	NA	NA	NA

Fire protection systems provided in the building functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety requirements as per D.O.E. Circular no. 3298-3398 dated 01.03.2011, vide letter issued Certificate Safety of Fire renewal F6/DFS/MS/School/2021/WZ/383 Dated 27/05/2021 is recommended.

Accordingly DFA is prepared for approval & signature please.

Sir, F.F. letter is had-up In your signature 1013

1/11th 1/2

27/05/24

A 100 (TWP)

ADO (JWP)