

## FORM 'H' FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35] GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

**NEW DELHI** 

No.F6/DFS/MS/2024/SZ/ 340

Dated: 05 /06 /2024

## FIRE SAFETY CERTIFICATE

Certified that the M/s Reliance ambit trade pvt. Ltd. Located at Commercial plot no. 1, City Centre, Sector-13, Dwarka, New Delhi - 110045, comprised of 3 basement, Ground + 03 Upper Floors was issued FSC vide Letter No. F6/DFS/MS/2021/SZ/302 dated 07/07/2021. The premises was re inspected by the officers concerned of this department on 29/05/2024 in the presence of Sh. Sunil Kumar Sharma (EGM) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Mercantile Building" with effect from 0506 2029 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 05 06 2029... at New Delhi by.

Copy to:

1. Sh. Sunil Sharma, Reliance ambit trade pvt. Ltd. Located at Commercial plot no. 1, City Centre, sector-13, Dwarka, New Delhi - 110045.

2. The Vice Chairman (Bldg.), DDA, INA Vikas Sadan New Delhi-110023.

## Following fire safety directives must be adhered to:-

1 All the fire safety arrangements provided therein shall be maintained in good working condition at all times.

2 Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

3 The trained staff should be available round the clock.

4 Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.

5 The certificate may not be treated in any case for the regularization of the unauthorized

construction, if any.

6 The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.

7 Basement shall be used strictly as per building bye laws.

8 The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

## INSPECTION REPORT

1. Name & address of the building: M/s Reliance ambit trade pvt. Ltd. Located at Commercial plot no. 1, city centre, sector-13, Dwarka, new deli – 110045.

2. Type of Occupancy : Mercantile

3. Type of Case : Renewal (3 Basement + Ground + 03 Upper Floors)

4. Details of previous NOC: F6/DFS/MS/2021/SZ/302 dated 07/07/2021

5. Fire Safety directives L. No: F6/DFS/MS /BP/2008/613 Dated 29/02/2008

& F6/DFS/MS/BP/2012/2955 Dated 13/08/2012

6. Date of inspection : 29/05/2024

7. Name of the Inspecting Officer: DO (SW) & ADO (DWK)

8. Name and designation of Officer

from the building side : Sh. Sunil Kumar Sharma (EGM)

9. Year of Construction : 2014

10. Applicant's letter No. : Nil dated 21/05/2024

S No	Minimum standards on fire prevention and fire safety U/	R 33	As per N/1	Provided at site	Remark MR/NN				
1.	Access of building MR								
	Road width	06 m		06 m	MR				
	<ul><li>Gate width</li><li>Width of internal roa</li></ul>	d 06	m	As per controlled I	Orawing	MR			
2.	Number, width, Type & Arra	angeme	ents of exits						
	a. Number of staircases  • Upper floors	03 No	s.	03 Nos.		MR MR			
	Basements	09 Nos. 9 Nos. + 01 Ramp							
-	<ul><li>b. Width of staircases</li><li>Upper floors</li></ul>	1.5 mtr 02 mtr MR							
	Basements	1.5 mtr - 02 mtr   2.00/1.8/1.50 mtr + 1 ramp 7.5 mtr (Two way)							
	c. Protection of exits			Dided		MR			
	<ul> <li>Fire check door</li> <li>Pressurization</li> <li>d. No of continuous staircase to terrace</li> <li>e. Width Of Corridor</li> <li>f. Door Size</li> </ul>	Requi		Provided Provided		MR MR			
		Requi 03 No		Provided	707				
		2.40 n	ntr	02 to 5 mtr		MR			
		1.5 m		1.5 mtr		MR			
3.	Compartmentation			n ided		MR			
	Sealing of     electrical shafts	Requi Requi		Provided Provided	7 1	MR			
		Requi	red	Provided		MR			
	shaft door	Daniel	and '	Provided	2	MR			
	<ul><li>Water Curtain</li><li>Fire Dampers</li></ul>	Requi Requi		Provided		MR			

No h

N/23

	Smoke managements							-		1.00	
	System		quired		Provided					MR	
	<ul> <li>Basements</li> </ul>	Requi	red		Pro	vided				MR	
	<ul> <li>Upper floors</li> </ul>	Requi	ica							Ø	
5.	Fire Extinguishers		A T	200	12	Nos.				MR	
•	Total numbers				ABC, CO2, DCP & WCO2 Provided		CO2	MR			
	<ul> <li>Types</li> </ul>	CO2						MR			
	IS marking	ISI ma	arked	1 4		Provided					
	First – Aid Hose Reels					Neg ) GF 06 Provided		MR			
<b>5.</b>	First - Ald Hose Reeds	Basen	ament 7 & [ [ NOS.] OI					- Assemble			
	Total numbers on	Nos. &	& 1 <sup>st</sup>	to 3 <sup>rd</sup> flo	Provided					MR	
	each floor	30 m								MR	
	<ul> <li>Length of hose reel</li> </ul>	5 mm			Provided					1,11	
	hose	5 1111	Jimi								
	Nozzle diameter	1 -lown	ing s	vstem						T v m	
7.	Nozzle diameter  Automatic fire detection and	d alariii	Heat & Smoke Provided						MR		
	<ul> <li>Type of detectors</li> </ul>	1.1	Ground floor Required		Ground floor		or			MR	
	<ul> <li>Location of Main</li> </ul>				Ti	Provided	at ground floor		MR		
	Panel	R				1107165					
	Location of Repeate	r	Required  Appropriate p		Battery bac		ackup	ckup		MR	
	Panel	R									
	Alternate source of	-			000	Provided				MR	
	power	A	ppro	priate pi	ace	110,1	5				
	Hooters' Location	4	1			111				MR	
		R	Lequi	red		Provided				MR	
8.	MOEFA System	R	Required Provided					7			
9.	Public Address System								MR		
10	. Automatic Sprinkler System	R				Provided	N/D				
	Basements	R	Required		Provided			MR			
	• Upper Floor		Required		Provided			IVIIC			
	Sprinkler above fall	se									
	ceiling					Pers		rovid	ad	MR	
11	. Internal Hydrants:	aamar		150 mn	n					MR	
	Size of riser/down-	comer	1101			each floor Provided				MR	
	Number of hydrant	s per me	Required				Provided			1411	
	Hose Box									MR	
12	2. Yard Hydrants	• Signatur	12 Nos.				2 Nos		MR		
-	<ul> <li>Total number of hy</li> </ul>	drants	Required				F	Provided M			
	Hose Box										
13	Pumping Arrangements:									) (D	
1.	Ground Level		2850 lpm					ovided		MR	
	<ul> <li>Discharge of main</li> </ul>	pump					Provided		V	MR	
	► Head of main pum	)	70 111		Prov			ovided		MR	
	Number of main pu	ımps	2 Nos.		m Pro		Provided			MR	
	> lockey pump out put		ZATO				rovided		MR		
	► lockey nump head		70 m					rovided		MR	
	Standby Pump out	put	1X2850 lp		/111		million of the same	ovided		MR	
	Standby Pump Head		70 m Required					ovided		MR	
	> Auto Staring/Manual					AAM.175.		) 8 (1)			
	stopping				Prox		rovid	ovided		MR	
	> Pump House Acces	SS	Required			Tiovided			3		
	Terrace level		The state of		NA			NA			
	Discharge of pump				NA					NA	
	- 1 Cabo numn		N			NA				NA	
	> Head of the pump				A T A						
	> Power supply > Auto starting of pu			* *	NA NA			-		NA	

X0/11/

1	L. B. J. J.			140	`\				
14.	Captive water Storage for fire	fightir	ng:	14.	17	- 1			
	<ul> <li>Under ground tank capacity</li> </ul>		ground level	1,00,000 ltr  Provided  Provided  Provided			MR		
	Draw off connection	Re	quired				-	MR	
	Fire service inlet		quired				_	MR	
	Access to tank		quired				_	MR	
	Overhead Tank capacity		KL .	20 KL			_	MR	
5	Exit Signage F		quired	Provided	d.		1	MR	
6.	Provision of Lifts								
	Pressurization of Lift S		Required	Required		Provided		MR	
	<ul><li>Pressurization of lift lo</li></ul>		Required	Provided		MR			
		Communication in lift Car			Provided		I	ИR	
	<ul><li>Fireman's Grounding</li></ul>		Required	Provided		1	МR		
	Switch ➤ Lift Signage	Required	Provided		I	ИR			
17.	Standby power supply		Required		D.G Set		N	ИR	
18	Refuge Area								
+	> Total area		NA	NA			N	A	
	> Location		NA		NA			NA	
19.	Fire control room								
-	> Detector system panel		quired	Provided			MR		
	Flow Switch Panel	21.1	quired Provid		200 A 100 A		_		
	> Battery backup		quired	Provided MR					
			quired	Provided MR Provided MR					
	Building Floor Plans		quired	Tiovided				MR	
20.	Special Fire Protection Systems for Protection of special Risks, if any;		2 trolley near , LT panels	Provided				IVIIX	

The fire protection systems provided in the building were test checked and

functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire and fire safety as required under the rules the FSC issued vide letter No. F6/DFS/MS/2021/SZ/302 dated 07/07/2021 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended. If approved, the FSC may be issued.

Sign of Inspecting Officer

Name: Sh. Vedpal Designation: DO/SW

Sign of Inspecting Officer Name: Udai vir Singh Designation: ADO/DWK