

FORM 'H' FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]
GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI
HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F6/DFS/MS/CGHS/SZ/2024/ 357

Dated: 12 /06/2024

FIRE SAFETY CERTIFICATE

Certified that the building of Manchahat CGHS Ltd. Located at Plot No-42, Sector-10, Dwarka, New Delhi-110075, having 04 blocks comprised of stilt/ground + 07 Upper Floors was issued NOC by this department vide letter No. F6/DFS/MS/CGHS/2002/2002/1913 dated 09/10/2002. The premise was re inspected by the officer concerned of this department on 29/05/2024 in the presence of Sh. S.B Soni and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Residential Building" Group A-4 with effect from 12 06 2014 for a period of five years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 2 06 2014 at New Delhi by.

(Atul Garg)
Director

Director,

Delhi Fire Service

Copy to:

1. The President, Manchahat CGHS Ltd. Located at Plot No-42, Sector-10, Dwarka, New Delhi-110075.

2. The Joint Director (Building) DDA, Vikas Sadan, INA, Delhi-110023.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

3. The trained staff should be available round the clock.

- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

6. Basement shall be used as per building bye laws.

7. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. www.dfs.delhigovt.nic.in.

8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT



Name & address of the building: Manchahat CGHS Ltd. Located at Plot No-1. A2 Sector-10, Dwarka, New Delhi-110075. Name 2, Sector-10, Dwarka, New Delhi-110075.

Type of Occupancy

: Residential Building "A" (Apartment)

Type of Case: Renewal 04block= stilt/ground+07 upper floors

Details of previous NOC

F6/DFS/MS/CGHS/2002/2002/1913dated

09/10/2002

5. Fire Safety directives Letter No.: F6//DFS/MS/CGHS/98/1146, dated 22/06/1998

6. Date of inspection

: 29/05/2024

7. Name of the Inspecting Officer: Sh. Udai vir Singh ADO (DWK)

8. Name and designation of Officer

from the building side

: Sh. S.B Soni

9. Year of Construction

: 1998

10. Applicant's letter No. : Manchahat/CGHS/Fire/23-24/20, dated-06/05/2024

- 11	Minimum standards on fire prevention and fire safety U/R 33	As	As Per NBC/BBL			vided at	Remarks MR/NMR			
	Access of building									
	Road width	09 mtrs	.5 mtrs		ed ed		MR MR d case)			
	Gate widthWidth of internal road	6 mtrs			050500	eing old c				
2.	Number, width, Type & Arrangements of exits									
	 a. Number of staircases Upper floors Basements b. Width of staircases 	1 no. ea	ch block	Provided			MR			
		NA	NA		NA		NA			
		1.25 m	1,2m			MD/ Rei	ng old case)			
	Upper floors	NA	755.50 255.00	NA NA			IX(Dellig old case)			
	 Basements c. Protection of exits Fire check door Pressurization d. No of continuous staircase to terrace e. Width Of Corridor 	NA - IVA								
		N/A	N/A			N/A I				
		N/A	N/A			N/A 1				
		Require	ed		Provided		MR			
		N/A	ECONOMIC			N/A				
	f. Door Size	N/A		N/A	4	N/A				
3.	Compartmentation		Table 1		N/A		***			
	 Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain 	N/A	5 7/4				V/A			
			N/A				N/A N/A			
		1174 SATIONS	N/A				N/A			
	Fire Dampers	N/A	N/A N/A				N/A			
4.	Smoke managements System	IN/A	IN/A			1	M04.4			
	Basements	NA	NA			1	NA			
	Upper floors	1 12	per hour	Pı	rovided		MR			





Fi	re Extinguishers		W 'A	XI.				4	MF
-	Total numbers	2	nos. each i	nos. each floor		Provided		0.0	MR
			CO ₂ & ABC			CO ₂ , ABC,	Water	·Coz	MR
1	• Types		SI marked			Provided			IVII
	IS marking	1	JI IIIIIIWU						T. m
F	irst – Aid Hose Reels		101 No. 00	oh fl	oor	Provid	led		MR
	Total numbers on each flo	oor	01 No. each floor			Provided			MR
1	 Length of hose reel hose 		30 m		7	Provided			MR
	 Nozzle diameter 		5 mm						
+	Automatic fire detection and alar	ming	system	-13	T/A			N/A	
	Type of detectors	11/11			N/A	1/4		N/A	
1	 Location of Main Panel 		N/A					N/A	
	 Location of Repeater Pan 	el	N/A		I/A			N/A	-
	Alternate source of power	r	N/A	N	N/A N/A			N/A	
	 Hooters' Location 		N/A		Provided Provided			MR	
			Required					MR	
	MOEFA		Required	P	rov	ided			
\rightarrow	Public Address System							NA	
0.	Automatic Sprinkler System	NA			A			N/A	
	BasementsUpper Floor	N/A			/A		7 - 4	N/A	1
	• Sprinkler above false N/A		N/A		delicate but		y_045_0		
	ceiling					I m			
11.	Internal Hydrants		100 mm	LIII I	P	rovided		MR	
	Size of riser/down- comer	oor	1 each blo	ck	1000	rovided		MR	-
	Number of hydrants per fl	01 No.		Pı	ovided		MR	+	
	Hose Box						y) ju	MR	-
12.	Yard Hydrants • Total number of hydrants	Required Provide				MR	_		
	Total number of flydram Hose Box	Required	Pro	Provided			IVIX	-	
	Pumping Arrangements				_			. 7	1
13.	Ground Level				8	NA	N.	A	
	 Discharge of main pump Head of main pump Number of main pumps Jockey pump out put Jockey pump head 		NA	NA NA			NA		
			NA	NA NA		121			
			NA	-	NA NA		NA		
			NA NA	NA NA		2.40		A	
	Standby Pump out put		NA	NA				A	
	Standby Pump Head		NA ·		1	VΑ	NA		
	Auto Staring/Manual		NA		1	VA.	NA		
	stopping David Access				NA NA				
	Pump House AccessTerrace level					I p. 11 1		MR	+
	 Discharge of pump 		450 lpm each block		Provided		MR		
	> Head of the pump	-	40m		Provided Provided		MR		
	> Power supply	Required Required			Provided		MR		
	> Auto starting of pump		Kequirea			Tiovided			





TC	aptive water Storage for fire figl	2 oo	0001				
. Ci	• Under ground talk	2,00,000 ltrs P		Provided	MD		
	capacity	Required Required		Provided	MR		
	m somice inlet			Provided	MR		
	> Access to tank Overhead Tank capacity		uired		Provided		
			00 ltr each	block Provided	MR	MR	
				Provided	raca		
5	Exit Signage			W.		MR	
16.	Provision of Lifts Pressurization of Lift Sha	ft	N/A	N/A	N/A		
	Description of lift love	y	N/A	N/A			
	Communication in lift Ca	11	Required	Provided			
	> Fireman's Grounding Sw	itch	Required				
1	▶ Lift Signage		Required				
	O. Her maryer supply	Require		DG Set 60 KVA			
17.	Standby power supply						
18.	Refuge Area > Total area	N/A	N/A	N/A			
	> Location		N/A	N/A	N/A		
19.	Fire control room		d.				
17.	> Detector system panel	A	N/A	N/A			
	 Flow Switch Panel PA System Panel Battery backup Building Floor Plans 		A	N/A	N/A		
			quired	Provided			
			quired	Provided			
			quired	Provided			
20.	Special Fire Protection System Protection of special Risks, if	ns for Required			CO2 fire extinguisher provided near electric panel		

The fire protection systems provided in the building were test checked and found functional

at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter No. F6/DFS/MS/CGHS/2002/2002/1913 dated 09/10/2002 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended. If approved FSC may be issued.

Signature of the Inspecting Officer
Name
Designation

Name
Designation

of soh

(S2) | Mugh

Dinecta / 24

And John