

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001

आज़ादी क अमृत महोत्सव

No. F6/DFS/MS/WZ/School/2024/WZ/ 527

Dated:-

14/06/2024

FIRE SAFETY CERTIFICATE

Certified that the Sant Nirankari Public School Located at Avtar Enclave, Paschim Vihar, Delhi-110063, comprised of Basement + Ground + 03 Upper Floors (Old Block – G + 02 & New Block – B + G + 03 Upper Floors both block are interconnected), was issued Fire Safety Certificate by this department vide letter no. F6/DFS/MS/School/2021/WZ/157 dated 25/02/2021. The said premise was re-inspected by the officer concerned of this department on 03/06/2024 in the presence of Sh. Monu (Caretaker) and found that the premises/building have deemed complied with the fire prevention and fire safety requirements in accordance with NBC Part-IV/D.O.E. Cr. No. 3298-3398 dated 01/03/2011 and that the school building is fit for occupancy class "Educational Building" Group B" with effect from 14/06/2024 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010 printed below.

Issued on 14 66 2024 at New Delhi by

Tel No. 011-23414000

Copy to:-

1. The Director, Directorate of Education, GNCT of Delhi, Old Secretariat Delhi - 110054.

2. The Principal, Sant Nirankari Public School, Avtar Enclave, Paschim Vihar, Delhi-110063.

Following fire safety directives must be adhered to:-

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- 5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 6. All comments / directions of licensing Department shall always be permitted and followed.
- 7. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its
- 9. The basement shall be used as per UBBL.

INSPECTION REPORT

Name and address of the building: Sant Nirankari Public School Located at Avtar Enclave, Paschim Vihar, Delhi-110063

Type of Occupancy

: Educational, Basement + Ground + 03 Upper Floor

Old Block - G+2, New Block - B+G+3,both are

interconnected

Type of Case

: Renewal

Details of previous NOC

: F6/DFS/MS/School/2021/SZ/157 dated 25/02/2021

Fire Safety directives Letter No.: D.O.E. Cr. No. 3298-3398 dated 01/03/2011/NBC Part-IV 5

Date of inspection

: 03/06/2024

7. Name of the Inspecting Officer : Aman Kumar Lathar, ADO (JWP)

8. Name and designation of Officer

from the building side

: Sh. Monu (Caretaker)

Year of Construction

: 2009 (G+1), 2012-13 (G+2) & 2016-17 (B+G+3)

· SNPS/AF/2024 dated nil

10.	Applicant's letter No.	: SNPS/A	AE/2024	4 dated ni	ļ	are <u>al</u>	
S No	Minimum standards on fire prevention and fire safety U/R 33	NBC Pa Require FSC dat	ments/a		Provided at site	Remarks MR/NMR	
1.	Access of building				ware w		
	Road width	06	575.71		ovided	MR	
	Gate width	4.5			ovided	MR	
1	Width of internal road	N/	4		NA	NA	
2.	Number, width, Type & Arran	gements of	fexits				
	a. Number of staircases					1/0	
	 Upper floors 			03 & 01 (Iron made)		MR	
	 Basements 	01		01 &	Ramp-01	MR	
4	 b. Width of staircases 		T				
	 Upper floors 	1.5 m) 1.55 m x 1(New Block)		MR (both	
			2) 1.2 m x		A	blocks are	
1					(Old Block)	interconnected)	
1	Basements	1.5 m		5 m x l (e ramp of	New Block) f 3.30 m	MR	
	c. Protection of exits						
	 Fire check door 	1	NA		NA	NA	
	 Pressurization 	1	NA		NA	NA	
	d. No of continuous staircase to terrace	19	01		01	MR	
	e. Width Of Corridor	1.5 m			1.5 m	MR	
	f. Door Size		.0 m		1.0 m	MR	
3.	Compartmentation				NA		
-50	Fire check door	1	NA		NA	NA	
	 Sealing of electrical shafts 	1	NA		NA	NA	
	 Fire Rating of shaft door 	NA		NA		NA	
	Water Curtain	1	NA		NA	NA	
	Fire Dampers		NA		NA	NA	

b

4.	Smoke managements System							
	Basements	NA	NA	NA				
	Upper floors	NA	NA	NA				
5.	Fire Extinguishers							
	Total numbers	15 nos.	34 nos.	MR				
	Types	ABC & CO ₂	Provided	MR				
	IS marking	ISI marked	Provided	MR				
6.	First – Aid Hose Reels							
<u> </u>	Total numbers on each floor	r 02	Provided	MR				
	Length of hose reel hose	30 m	Provided	MR				
	Nozzle diameter	5 mm	Provided	MR				
7.	Automatic fire detection and alarmi	ing system	•					
٠.	Type of detectors	NA	NA	NA				
	Location of Main Panel	NA	NA	NA				
	Location of Repeater Panel	NA	NA NA					
	Alternate source of power	NA	NA	NA				
	Hooters' Location	NA	NA	NA NA				
0	Co. Depart Several Constitution of the Constit	NA	NA					
8.	MOEFA Dublic Address System	NA NA		NA				
9.	Public Address System	1171	110000					
10.	Automatic Sprinkler System	Required	Provided	MR				
	Basements Unner Floor	NA	NA	NA				
	Upper Floor Seriables above false	NA	NA	NA				
	Sprinkler above false seiling	****	55/554-950					
11	ceiling . Internal Hydrants:							
11.	01 01 11	NA	100 mm	NA				
	 Size of riser/down-comer Number of hydrants per 	NA	02	NA				
	floor	NA	02	NA				
	** "	****						
10	Vard Hydrants							
12.	Total number of hydrants	NA	NA	NA				
	2007	NA	NA	NA				
1.2	Hose Box Dumping Arrangements:	1						
13.	Cround Level							
	Discharge of main pump	NA	NA	NA				
	> Head of main pump	NA	NA	NA				
	Number of main pumps	NA	NA	NA				
	> Jockey pump out put	NA	NA	NA				
	> Jockey pump head	NA	NA	NA				
	Standby Pump out put	NA	NA	NA				
	Standby Pump Head	NA	NA	NA				
	Auto Staring/Manual	NA	NA	NA				
	stopping		NIA	NΔ				
	stopping > Pump House Access	NA	NA	NA				
	stopping > Pump House Access • Terrace level							
	stopping > Pump House Access	NA 450 lpm x 2	900 lpm &	NA MR				
	stopping > Pump House Access • Terrace level > Discharge of pump	450 lpm x 2	900 lpm & 180 lpm					
	stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump	450 lpm x 2 40 m	900 lpm & 180 lpm Provided	MR				
	stopping Pump House Access Terrace level Discharge of pump Head of the pump Power supply	450 lpm x 2 40 m Required	900 lpm & 180 lpm Provided Provided	MR MR				
14	stopping Pump House Access Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump	450 lpm x 2 40 m Required Required	900 lpm & 180 lpm Provided	MR MR MR				
14.	stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump > Power supply > Auto starting of pump Captive water Storage for fire fighting	450 lpm x 2 40 m Required Required ng:	900 lpm & 180 lpm Provided Provided	MR MR MR				
14.	stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump > Power supply > Auto starting of pump Captive water Storage for fire fightin • Under ground tank capacity	450 lpm x 2 40 m Required Required	900 lpm & 180 lpm Provided Provided Provided	MR MR MR MR				
14.	stopping Pump House Access Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting Under ground tank capacity Draw off connection	450 lpm x 2 40 m Required Required ng: NA NA	900 lpm & 180 lpm Provided Provided Provided	MR MR MR MR				
14.	stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump > Power supply > Auto starting of pump Captive water Storage for fire fightin • Under ground tank capacity	450 lpm x 2 40 m Required Required ng:	900 lpm & 180 lpm Provided Provided Provided NA NA NA	MR MR MR MR NA				
14.	stopping Pump House Access Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fightin Under ground tank capacity Draw off connection Fire service inlet	450 lpm x 2 40 m Required Required ng: NA NA NA	900 lpm & 180 lpm Provided Provided Provided NA NA NA NA NA Provided	MR MR MR MR NA NA				
14.	stopping Pump House Access Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fightin Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity	450 lpm x 2 40 m Required Required ng: NA NA NA NA	900 lpm & 180 lpm Provided Provided Provided NA NA NA	MR MR MR MR NA NA NA NA				
	stopping Pump House Access Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fightin Under ground tank capacity Draw off connection Fire service inlet Access to tank	450 lpm x 2 40 m Required Required ng: NA NA NA NA 15,000 ltrs.	900 lpm & 180 lpm Provided Provided Provided NA NA NA NA NA Provided	MR MR MR MR NA NA NA NA NA NA				

P	rovision of Lifts	NA	NA	NA
	 Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch 	NA NA	NA	NA
		NA NA	NA	NA
- 11		NA NA	NA	NA
		NA	NA	NA
	➤ Lift Signage	NA	NA	NA
	Standby power supply	103		
18.	Refuge Area	NA	NA	NA
	Total areaLocation	NA NA	NA	NA
19.	Fire control room	NA	T NA	NA
17,	Detector system panel		NA	NA
	> Flow Switch Panel	NA NA	NA	NA
1	> PA System Panel	NA	NA	NA
	Battery backup	NA	NA	NA
i.	> Building Floor Plans	NA	NA NA	NA
20.	Destaction Systems for	NA		aked and 1

Fire protection systems provided in the building were checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety requirements under the rules, renewal of Fire Safety Certificate issued vide letter no. F6/DFS/MS/School/2021/SZ/157 dated 25/02/2021 is recommended under Rule 37 of the Delhi Fire Service Rules, 2010 under the DFS Act 2007.

Accordingly DFA is put up for approval & signature please.

Aman Kumar L ADO (JWP)

F.F. Jetter is added for your nignature 10%.