

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI-,110001

No.F6/DFS/MS/GH/NDZ/2024/ 2 2 2

FIRE SAFETY CERTIFICATE

Certified that the VANDANA GUEST HOUSE located at 47 Arakashan Road, Pahar Ganj, New Delhi comprised of Ground + 04 Upper floors, Ground floor (06 guest rooms + reception), 1s floor to 3rd floor (06 guest rooms at each floor) & 4th floor & above floor not in use as per affidavit dated 06.01.2020, total 24 guest rooms was earlier granted FSC by this department vide letter No.F6/DFS/MS/GH/NDZ/2021/270 dated 30/07/21 for 24 guest rooms up to third floor only. Now, the premise was re-inspected by the officer concerned of this department on 04/06/24 in the presence of Manager and found that the said guest house building has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 Ground floor (06 guest rooms + reception), 1st floor to 3rd floor (06 guest rooms at each floor) total 24 guest rooms up to third floor only and valid up to 31.03.2027 from the date of issue in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 1106 2024 New Delhi by.

elhi Fire Service

Copy to:-

1. The Commissioner, North MCD, Civic Centre, New Delhi. To kindly ensure the occupancy as detailed above and deviation if any.

2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. ID No. 2024051707750 dated 24/05/24.

3. The Manager, Vandana Guest House, 47, Arakansha Road, Pahar Gani, New Delhi.

Conditions for the validity of Fire Safety Certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 9. Any flammable material for interior decoration is prohibited.

INSPECTION REPORT

1. Name & address of the building Vandana Guest House at 47, Arakashan

Road, Pahar Ganj, New Delhi , Gr+4 +

terrace floor

2. Type of occupancy:- Residential, Sub Division-A-1 Gr. +03 floors

Ground floor (Reception + 06 guest rooms), 1st floor to 3rd floor (06 guest rooms at each floor), total 24 guest rooms and 4th & terrace not in use as per affidavit dated 06.01.2020

Renewal

3. Type of case:-

4. Details of previous FSC:-

No. F6/DFS/MS/GH/NDZ/2021/270 dated

30/07/21.

5. Fire safety directives No.-

N/A

6. Date of inspection:-

04/06/24

7. Name of the inspecting officer:-

Sh. Ravinder Singh, ADO (CC)

 Name & designation of officer from the building side:-

9. Year of construction:-

Manager

1991

10. Applicant's letter No:- ID No. 2024051707750 dated 24/05/24.

Old Case

				Old Case
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR
1.	Access to Building			
	1) Road width	N/A	06 mtr.(approx)	N/A
	2) Gate width	N/A	N/A	N/A
	3)Width of internal road	N/A	N/A	N/A
2.	Number, Width Type & Arr	angement of E	exits	
L.	A. Number of staircases			
	1. Upper floors	01 Nos.	01 Nos.	MR
	2. Basements	N/A	N/A	N/A
	B. Width of staircase			
	1. Upper floors	0.80 mtr.	1 mtr.	MR
	2. Basements	N/A	N/A	N/A
	C. Protection of exits			
	1. Fire check door	N/A	N/A	N/A
	2. Pressurization	N/A	N/A	N/A
	D. No. of continuous staircase to terrace	N/A	N/A	N/A
	E. Width of corridor	N/A	N/A	N/A
	F. Door size	1.0 mtr.	1.0 mtr.	MR
3.	Compartmentation	r.		
	1) Fire check door	N/A	N/A	N/A
	2) Sealing of electrical shafts	N/A	N/A	N/A
	3) Fire rating of shaft door	N/A	N/A	N/A
	4) Water curtain	N/A	N/A	N/A
	5) Fire Dampers	N/A	N/A	N/A
4.	Smoke Management System			
	1) Basements	N/A	N/A	N/A

	2) Upper floors	12 ACPH	Natural	MR V
5.	Fire Extinguishers			+
	1) Total numbers	30 Nos.	34 Nos.	MR
	2) Types	ABC & CO2	ABC & CO2	MR
	3) ISI marking	Required	Provided Provided	
6.	First-Aid Hose Reel	Required	riovided	MR
	1) Total number of eachfloor	01	01	100
	2) Length of hose reel hose	30 mtr.		MR
	3) Nozzle diameter	05 mm	30 mtr.	MR
7.	Automatic Fire Detection &	Alamaia - Cart	05 mm /	MR
	1) Type of detectors CO type	Paguined Syste		
	2) Location of main panel	Required	Provided	MR
	3) Location of repeater panel	Gr. floor N/A	Provided	MR
	4) Alternate source of power		N/A	N/A
	5) Hooter's Location	Required	Provided	MR
8.	MOEFA	Gr. floor	Provided	MR
9.		Required	Provided	MR
10.	Public Address System	Required	Provided	MR
	Automatic Sprinkler System 1) Basement			
		N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	Sprinkler above false ceiling	N/A	N/A	N/A
11.	Internal Hydrants	*		1.211.00012104
	1) Size of size //		~	_
	1) Size of riser/down-comer	N/A	100 mm	N/A
	Number of hydrants per floor	N/A	01	N/A
	3) Hose box			PROCESS CONTRACTOR
12.	Yard Hydrants	N/A	01	N/A
1	1) Total number of hydrants	13-77		
	2) Hose box	N/A	N/A	N/A
13.	Pumping Arrangement	N/A	N/A	N/A
	1) Ground level		1.7	_
		N/A	N/A	N/A
	 a) Discharge of main pump 	N/A	N/A	N/A
	b) Head of main pump	NIA		
	c) Number of main	N/A	N/A	N/A
	pump	N/A	N/A	N/A
		NIA		
	d) Jockey pump out pute) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump	N/A	N/A	N/A
	output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual	N/A	N/A	N/A
	stopping		_	IVA
	2) Terrace level		,	_
	a) Discharge of pump	450 LPM	450 LPM	MR
	b) Head of pump	30 mtr.	30 mtr.	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of	Required	Provided	MR
	pump			MIK



~		

4	Captive Water Storage for Fi	re Fighting		
14.	1) Under ground tank capacity	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	70 DOG 47 BU	N/A	N/A	N/A
	d) Over head tank capacity	5000 ltr.	5000 ltr.	MR
15.	Exit Signage.	Required	Provided /	MR
16.	Provision of Lifts.			
10.	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
18.	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System Risk, if any: ABC & Co2	n for Protect	ion of special	MR

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if agreed, we may renew the FSC issued vide letter no. F6/DFS/MS/GH/NDZ/2021/270 dated 30/07/21, under rule 35(6) of the Delhi Fire Service Rules 2010. Accordingly, DFA is put up for kind perusal and signature please.

Signature of the Inspecting Officer

Name: - Ravinder Singh Designation: - ADO (CC)

616/24

Dice (was

Diverto 6 A

Director State In

Anyca