FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No. F6/DFS/MS/SZ/2024/ 566

Dated: 20/06/2024

FIRE SAFETY CERTIFICATE

Certified that the Building Nigam Pratibha Vidyalaya, Located at Old Ranjit Nagar, New Delhi - 110008, comprised of Ground + 01 Upper floor was issued Fire Safety Certificate by this department vide letter No. F6/DFS/MS/School/SZ/2017/539 Dated 12/04/2017. The premise was re inspected by the officer concerned of this department on 06/06/2024 in the presence of Mr. Vinay Tanwar (School Incharge). All the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deem complied with the fire prevention and fire safety requirements in accordance with DOE 3298-3398 dated 1-3-2011 issued by the Director of Education and that the building/ premises is fit for occupancy class B "Educational" with effect from20.06/.2024... for a period of three years, subject to compliance of the condition given below.

Issued on .. 20 06 2024 at New Delhi by.

Director Belhi Fire Service

Copy to: -

The Principal, Nigam Pratibha Vidyalaya, Located at Old Ranjit Nagar, New Delhi - 110008.
 Directorate of Education Old Secretariat Delhi - 110054.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

3. The trained staff should be available round the clock.

- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

6. Basement shall be used strictly as per building bye laws.

7. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its

8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

INSPECTION REPORT

 Name & address of the building: Nigam Pratibha Vidyalaya, Located at Old Ranjit Nagar, New Delhi – 110008.

2. Type of Occupancy : Educational (Ground + 01 Upper Floor)

3. Type of Case : Renewal

4. Details of previous NOC: F6/DFS/MS/School/SZ/2017/539 Dated 12/04/17

5. Fire Safety directives Letter No.: DOE 3298-3398 dated 01-03-2011

6. Date of inspection : 06/06/2024

7. Name of the Inspecting Officer: ADO (DWK)

8. Name and designation of Officer

from the building side :Mr. Vinay Tanwar (School Incharge)

9. Year of Construction

: Before 2009

10. Applicant's letter No.

:nil dated 21/05/2024

| S No | Minimum standards on fire prevention and fire safety U/R 33 | As per N/9, N/10 & N/11 | ris per rus, | | ovided Remarks site MR/NMR | | | |
|---------|---|----------------------------|---|----------------|----------------------------|----|---------------|--|
| 1. | Access of building | | | | | | | |
| | Road width | 06 mtr | 10 mtr · 05 mtr | | MR MR | | | |
| | Gate width | 4.5 mtr | | | | | | |
| | Width of internal road | NA | NA | | NA | | | |
| 2. | Number, width, Type & Arrange | ments of exits | | | | | | |
| | a. Number of staircases | | Ta I | | | | | |
| | Upper floors | 02 Nos. | 04 1 | Nos. | MR | | | |
| | Basements | NA | NA | | NA | | | |
| | b. Width of staircases | | | | | | | |
| | Upper floors | 1.5 mtr additio | .5 mtr if less than .5 mtr additional taircase of 0.75 mtr s required | | 1.20m | | MR | |
| | Basements | NA | NA | NA NA | | | - | |
| | c. Protection of exits | | | | | | | |
| | Fire check door | NA | NA | NA | | NA | | |
| | Pressurization | NA | NA 02Nos. NA 01 mtr | | | NA | | |
| | d. No of continuous | 01 No. | | | | MR | | |
| П | staircase to terrace | NA | | | | NA | | |
| | e. Width Of Corridorf. Door Size | 01 mtr | | | | MR | | |
| 3. | Compartmentation | | | | | | | |
| | Fire check door | NA | NA N | | NA | | NA | |
| | Sealing of electrical | | | NA | | | 0-100-100-100 | |
| | shafts | shafts | | NA | | | NA | |
| | Fire Rating of shaft doorWater Curtain | NA] | | NA | | | NA | |
| | Fire Dampers | NA | 1 | NA | | | NA | |
| | The Dampers | NA | 1 | NA | | NA | | |
| | | | | 1200-120-120-1 | | | 1 12 | |

| 4. | Smoke | managements System | NA | | NA | | N. | |
|-----|---|---|-----------------|------------|---|-----------------------|----------|--|
| | • | Basements | 72 | c per hour | Natural | ventilation | M | |
| | • | Upper floors | | | | | | |
| 5. | Fire Extinguishers • Total numbers | | 06 N | os.ABC & | Provided | | M | |
| | • | Types | CO ₂ | | ABC & | ABC & CO ₂ | | |
| | | IS marking | 22 370 | narked | ISI mark | ked | M | |
| , | Eiret | Aid Hose Reels | | | i i | | | |
| 6. | FIRST - | Total numbers on each flo | or 1 | NΑ | NA | | N. | |
| | | Length of hose reel hose | | NΑ | NA · | | N. | |
| | • | Nozzle diameter | 1 | NA | NA | NA | | |
| 7. | Autom | atic fire detection and alarr | ning s | ystem | | | | |
| - | Type of detectors | | | À | NA | NA | | |
| | • | Location of Main Panel | NA | A | NA | NA | | |
| | • | Location of Repeater | NA | 1 | NA | NA | | |
| | | Panel | | | | | | |
| | • | Alternate source of power | N/ | A` | NA | NA | | |
| | • | Hooters' Location | N/ | | NA | NA | | |
| 8. | MOEF | FA | N/ | | NA | NA | | |
| 9. | 242222 | Address System | N/ | | NA | NA | | |
| 10. | | natic Sprinkler System | 1 | | 1 W 1 V 5 | | | |
| | • | Basements | NA | | NA NA | | | |
| | • | 1 | | | | NA . | | |
| | • | Sprinkler above false | NA | | NA | NA | | |
| | ceiling | | | | 7.00 at | 100 | | |
| 11. | 2 10 10 10 10 10 10 10 10 10 10 10 10 10 | | | | 1 | | | |
| | • | Size of riser/down-comer | | NA | NA | 1200000000 | NA | |
| | Number of hydrants per floHose Box | | loor | NA NA | NA | NA | | |
| 12. | | | | NA | NA | NA | | |
| 12. | raru | 17/1 | N. | A | NIA | Lym | | |
| | | Total number of hydrants Hose Box | N. | (Ma) | NA | NA | | |
| 13. | | | IN. | A | NA NA | | | |
| 15. | Tunp | mig Arrangements | | | | | | |
| | ٠. | Ground Level | N | Δ | NA | NIA | | |
| | Discharge of main pump | | N | | NA NA | NA | | |
| | 400 | Head of main pump | | A | NA NA | NA NA | | |
| | | Number of main pumps | | A | NA NA | | NA NA | |
| | | Jockey pump out put Jockey pump head | NA | | NA | | NA NA | |
| | > | | NA | | NA NA | | NA NA | |
| | > | Standby Pump Head | NA | | NA | | NA NA | |
| | > | Auto Staring/Manual | NA | | NA | | NA NA | |
| | | stopping | | | NA | NA NA | | |
| | Pump House Access Terrace level | | - | 7.)** | 11/1 | NA | | |
| | Discharge of pump | | N | A | NA | NIA | | |
| | | > Head of the pump | | A | 100000000000000000000000000000000000000 | * 14.4 | | |
| | > | Power supply | | mco | | NA NA | | |
| | - > | Auto starting of pump | _ | | Later Agency | | | |
| | | | _ | A A | NA NA NA | | | |

| | capacity | NA | NA NA | | NA | |
|-----|---|----------|----------|---|----|----|
| | Draw off connectionFire service inlet | NA | | | NA | |
| 1 | > Access to tank | NA | | NA | NA | |
| | Overhead Tank NA | | NA | | NA | |
| | capacit'y | NA | | NA | NA | |
| | Exit Signage | NA | | NA | NA | |
| 6. | Provision of Lifts | | _1 | 141 | | |
| | Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch Lift Signage | | NA | NA | NA | |
| 1 | | | NA | NA | NA | |
| | | | NA | NA | NA | |
| | | | NA | NA | NA | |
| | | | NA | NA | NA | |
| 17. | Standby power supply | | NA | NA | NA | |
| 18. | Refuge Area | | | | | |
| | Total areaLocation | | NA | NA | NA | |
| | | | NA | NA | NA | |
| 19. | Fire control room | | | | | |
| | Detector system panel Flow Switch Panel PA System Panel Battery backup Building Floor Plans | | | NA | | NA |
| | | | | NA | | NA |
| 1 | | | | NA | | NA |
| | | | | | | NA |
| | | NA | | NA | | NA |
| 20 | O. Special Fire Protection Systems for Protection of special Risks, if any; | Required | | 01 ABC fire extinguisher provided near electric panel | | MR |

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the FSC issued vide letter F6/DFS/MS/School/SZ/2017/539 Dated 12/04/2017 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended. If approved, the FSC may be issued.

Signature of the Inspecting Officer

Name Designation

Aso Low by

7/6/24

CFO (52)

Dinester My

and on one